

Kahoot

Distributed 4 (Fall26)

Test your understanding of middleware wrappers and brokers, interceptors, connectionless communication, multitiered architectures, and different peer-to-peer system designs and search strategies.

Questions (10)

1 - True or false

True or false

A wrapper enables two software components with incompatible interfaces to communicate with each other.

- True ✓
- False ✗

2 - True or false

True or false

For (N) applications, a wrapper-based integration approach requires (O(N)) wrappers.

- True ✗
- False ✓

3 - True or false

True or false

With a broker, for N applications, (N(N-1)) wrappers are required to enable communication among all applications.

- True ✗
- False ✓

4 - True or false

True or false

Interceptors can be used to adapt middleware behavior to meet the specific requirements of an application.

- True ✓
- False ✗

5 - True or false

True or false

Connectionless communication is more appropriate for unreliable networks.

- True ✗
- False ✓

6 - True or false

True or false

In the multitiered architecture, different hardware levels are distributed across multiple machines.

- True ✗
- False ✓

7 - True or false

True or false

In P2P systems, nodes act as a client and a server at the same time.

- True ✓
- False ✗

8 - True or false

True or false

In structured P2P systems, neighboring nodes are randomly determined.

- True ✗
- False ✓

9 - True or false

True or false

Flooding is a more appropriate data search method for structured P2P systems rather than unstructured P2P systems.

- True ✗
- False ✓

10 - True or false

True or false

In hierarchically organized P2P systems, super nodes are connected based on structured P2P systems.

- True ✓
- False ✗

Details

Max. 100 participants. Upgrade for more

Updated 2 weeks ago • Visibility: Public

Media credits

Cover image: Flavio Coelho/Moment/Getty Images