

# WHEEL LOADERS



## XLHJ Group Limited (China)

Address: Chaoyang District, Wangjing West Road No 48, City One Plaza C-2501, Beijing, China, 100102

Phone: +86-10-64787904 (in English)

Web: <http://en.beijingxlhj.com>

Fax: +86-10-64787322

E-mail: [sales@beijingxlhj.com](mailto:sales@beijingxlhj.com)

### Your reliable partner in China



**XCMG LW300F**



**XCMG LW500F**



**XCMG LW300K**



**XCMG LW500K**



**XCMG ZL50G**



**SDLG LG936**



**SDLG LG938**



**SDLG LG956**

# WHEEL LOADERS



## XLHJ Group Limited (China)

Address: Chaoyang District, Wangjing West Road No 48, City One Plaza C-2501, Beijing, China, 100102

Phone: +86-10-64787904 (in English)

Web: <http://en.beijingxlhj.com>

Fax: +86-10-64787322

E-mail: [sales@beijingxlhj.com](mailto:sales@beijingxlhj.com)

### Your reliable partner in China

Main technical data										
			XCMG LW300F	XCMG LW500F	XCMG LW300K	XCMG LW500K	XCMG ZL50G	SDLG LG936	SDLG LG938	SDLG LG956
Engine	Model		Yuchai YC6B125-T11	Steyr WD615G.220	Yuchai YC6108G	Shangchai C6121ZG50	Steyr WD615G.220	Yuchai YC6108G	Cummins 6BT5.9-C130	Steyr WD615.67G3-36 Cummins 6CTA8.3-C215
	Rated power	kW/hp	92/125	162/220	92/125	162/220	162/220	92/125	97/130	162(160)/220
	Rated speed	r.p.m.	2300	2200	2300	2200	2200	2200	2200	2200
Travelling characteristics	Travel speed forward	km/h	10/16/21/35	13.5/38	8/16/37	6.5/11/24/38	11.5/37	13/38	7/12/27/36	13.5/38
	Travel speed backward	km/h	14/25	17	7/14/35	6.5/11/24	16.5	17	7/12/27	17
	Min. turning radius	mm	5420	6172	5393	5900	6400	5381	5381	6250
	Tyres		17.5-25	23.5-25	17.5 - 25	23.5 - 25	23.5-25	17.5-25	17.5-25	23.5-25
Operating characteristics	Operation type		Manual	Manual	Pilot	Pilot	Pilot	Manual / Pilot	Pilot	Pilot
	Rated loading capacity	kg	3000	5000	3000	5000	5000	3000	3000	5000
	Max. drawbar pull	kN	90	156	90	160	145	105	105	150
	Total hydraulic cycle time	s	10.3	9.9	10.3	11	11	9.2	9.2	9.5
	Boom lift time	s	5.7	5.6	5.68	6	6	5.3	5.3	5.5
	Reach at maximum lift	mm	1104	1231	1000	1130	1130	1050	1050	1120
Dimensions	Total length	mm	6900	7997	7250	8240	8110	7100	7100	8020
	Total width	mm	2470	3000	2580	3010	3000	2510	2460	3050
	Total height	mm	3025	3290	3290	3465	3485	3170	3170	3382
	Weight	kg	10000	16500	10600	16500	17500	10700	10700	16600
Bucket characteristics	Rated capacity	m³	1.8	3.0	1.8	3.0	3.0	1.8	1.8	3.0
	Unloading height	mm	2892	3056	2930	3090	3090	2950	2950	4125
	Max. breakout force	kN	120	158	120	170	170	96	96	160

\* All technical specifications are subject to modification without notice