

Non-Escalating Scientific Authority under Content-Bound Evidence and Protected Evaluation

Anonymous authors

Paper under double-blind review

Abstract

Scientific verification can establish that a claim is plausible, supported somewhere, or accompanied by a citation without establishing that a particular source, checker, and evaluator jointly justify a scientific-authority transition. We evaluate a non-escalating authority pipeline that requires exact evidence-content binding, source ownership, semantic support, checker independence and hostile discrimination, evidence influence, evaluator/holdout integrity, and search-contamination clearance. A missing prerequisite leaves the outcome undetermined and a failed one blocks it, rather than contributing a low score that confidence elsewhere can compensate for. In a prospectively frozen, independently hosted 420-case protected campaign covering 13 clean/hostile families, the governed pipeline produced 0 false authority promotions among 360 hostile opportunities, versus 180/360 for the strongest frozen comparator mechanism (absolute difference -0.50 , paired 95% CI $[-0.553, -0.447]$). Both promoted 60/60 clean positives, so the safety gain did not arise from total refusal. The predeclared abstention-superiority hypothesis was not supported: every system was correct on all eligible abstention cases, which we show is a property of how that family was constructed rather than a comparative finding. Every registered ablation increased false promotion while preserving clean coverage; replacing the non-compensatory terminal with a six-of-nine soft-confidence rule increased false promotion to 91.7%. Scored-process telemetry recorded zero protected-label identifiers and zero external-IP connections, and an independent implementation reproduced the headline counts. The evidence supports the bounded claim that non-compensatory authority gates prevent authority laundering in this protected mechanical-gold benchmark; it does not establish universal evaluator security or superiority to the original external systems whose ideas motivated the comparator mechanisms.

Keywords: scientific verification; provenance; evaluator integrity; protected evaluation; abstention; AI assurance.

1 Introduction

Language-model research systems increasingly retrieve sources, synthesize claims, attach citations, and run automated verification. This creates a governance problem: a claim may be correct but attributed to the wrong source; a source may support a nearby claim but not the assigned one; a checker may be non-empty yet non-discriminating or share lineage with the answer; and an evaluator may be contaminated or tampered with after the fact. In each case, a scalar confidence score can remain high even though a prerequisite for scientific authority is absent.

We study a stricter object: a *scientific-authority transition*. A proposal can be plausible and well supported but is promoted only when a registered set of content, provenance, checker, and evaluator prerequisites all pass. Unresolved prerequisites do not contribute a low score; they block escalation. This design is motivated by source-aware verification, multi-source attribution, claim-level auditability, evidence influence, iterative fact checking, evaluator-tampering benchmarks, and search-time contamination work (Alvarez et al., 2026; Li et al., 2024; Rasheed et al., 2026; Faizan & Alharthi, 2026; Xie et al., 2024; Atinafu & Cohen, 2026; Wang et al., 2026b; Sadeghi et al., 2026). Recent academic-integrity and agentic-abstention benchmarks also make

explicit that declining to complete an unsupported action can itself be the correct behavior rather than a failure to optimize task success (Yang et al., 2026; Liu et al., 2026).

The contribution is deliberately narrower than those component techniques. We ask whether composing these requirements as a *non-compensatory, protected authority transition* materially reduces false scientific-authority promotion while preserving legitimate clean coverage. Throughout, the pipeline built to that rule is called the *governed pipeline*, so that each claim reads as a claim about the rule rather than about a product; Section 4 names the implementation that instantiates it.

The final study was executed after the subject, comparator/ablation mechanisms, evaluator, statistical rules, and split-generation code were frozen. A first 420-case protected campaign on an older subject remains valid evidence for that older revision but does not authorize the repaired one. A separate 39-case live-model arm remains exploratory because post-run audit found label/denominator inconsistencies and a hidden-family execution leak. We therefore generated a fresh post-repair hidden split and executed the publication-authorizing campaign without reusing either prior outcome for tuning.

Our main findings are: (i) the governed pipeline made 0/360 false promotions while the strongest frozen mechanism proxy made 180/360, with the paired H1 interval entirely beyond the predeclared five-point margin; (ii) both promoted 60/60 clean positives, satisfying the H2 non-inferiority guard; (iii) H3 was not supported, because every system left all eligible cases correctly undetermined on a family that no system could get wrong; and (iv) every registered ablation increased false promotion without reducing clean coverage, with soft confidence producing the largest degradation.

2 Related work

Source ownership and attribution. Attribution evaluation across multiple candidate sources is an established measurement problem (Li et al., 2024); source-aware factuality work targets cross-source conflation directly (Alvarez et al., 2026); and scientific claim–evidence benchmarks test whether retrieved evidence supports or contradicts a claim (Javaji et al., 2025). Claim-source retrieval sharpens the same point from the retrieval side, since recovering the source a scientific statement actually came from is a different task from finding a source that would support it (Schreieder et al., 2026). Together these establish claim correctness, source ownership, and semantic support as separate coordinates, which is the premise this paper builds on.

Provenance-sensitive authorization. A current controlled audit makes the authorization distinction especially direct: evidence can be relevant to an agent decision without being authorized to determine that decision, and target-specific tests can hold the task and proposition fixed while varying only source authority (Liao, 2026). The relevance-versus-authorized-evidence distinction is therefore already established. What remains open is the empirical question studied here: whether a protected conjunction of content, ownership, support, checker, influence, evaluator, access, and contamination prerequisites behaves differently from its strongest single component when both meet the same hostile battery.

Auditability, citation fidelity, and influence. Claim-level auditability work argues that research-agent outputs require persistent semantic provenance rather than only fluent text (Rasheed et al., 2026). ProvenAI separates citation fidelity from whether cited evidence influenced the answer path (Faizan & Alharthi, 2026). We adopt that separation: citation presence cannot substitute for evidence-use provenance.

Research-integrity provenance and declared behavior. INSPECT-AI and RIPE-KG represent the provenance of research-integrity assessments over clinical-trial publications, showing a current scientific setting in which the assessment process itself is an auditable object (Markovic et al., 2026). Behavioral Integrity Verification formalizes a complementary declared-versus-actual integrity problem for agent skills (Wu et al., 2026), and certified speculative execution shows the same instinct applied to untrusted agent actions: let the work proceed, but hold its effects behind a check that must clear before they become authoritative (Zhou et al., 2026). These are parent-domain precedents for explicit provenance and contract checking.

Iterative verification and evidence escalation. FIRE iterates retrieval and verification rather than treating a single retrieval pass as final (Xie et al., 2024). DeepSciVerify motivates escalation from an abstract-level judgment to fuller evidence when initial evidence is insufficient (Sadeghi et al., 2026). Stage-wise fact-checking benchmarks make the complementary measurement argument, that an end-to-end verdict hides which stage actually failed (Lin et al., 2026). The first two mechanisms inform frozen comparator proxies here, and the third informs the decision to report per-family and per-coordinate outcomes rather than one aggregate.

Evaluator integrity, benchmark auditing, and contamination. RewardHackingAgents treats evaluator manipulation and held-out leakage as an explicit benchmark dimension (Atinafu & Cohen, 2026). Search-time contamination work shows that browsing systems can retrieve public benchmark answers during inference (Wang et al., 2026b). BenchGuard and Automated Benchmark Auditing show that benchmark specifications, environments, ground truths, and grading logic can themselves be defective (Tu et al., 2026; Wang et al., 2026a). The Holistic Agent Leaderboard further demonstrates the value of standardized harnessing and trace inspection, including direct observation of agents searching for benchmark material rather than solving the intended task (Kapoor et al., 2025). These results motivate the protected evaluator identity, holdout custody, access telemetry, and independent audit used here.

Abstention and scientific integrity. SciIntegrity-Bench constructs academic-integrity dilemmas in which honest acknowledgement of inability is the only correct outcome, while AgentAbstain evaluates paired should-act/should-abstain tasks in executable environments (Yang et al., 2026; Liu et al., 2026). They establish abstention as an evaluation target distinct from generic task success. The object measured here is narrower: an undetermined or blocked terminal is authority-specific, produced by an unresolved or failed evidence, checker, or evaluator prerequisite rather than by a general judgement that the task should not be attempted.

3 Non-escalating authority transition

Let a proposal contain claim c and evidence references $E = \{e_1, \dots, e_n\}$. Promotion is a conjunction of hard prerequisites rather than a weighted score:

$$G_{\text{content}} : \text{resolved bytes equal the registered evidence digest}, \quad (1)$$

$$G_{\text{owner}} : \text{the assigned source owns the cited content}, \quad (2)$$

$$G_{\text{support}} : \text{the assigned evidence supports } c, \quad (3)$$

$$G_{\text{indep}} : \text{checker lineage is admissibly independent}, \quad (4)$$

$$G_{\text{disc}} : \text{checker rejects the frozen hostile battery}, \quad (5)$$

$$G_{\text{influence}} : \text{cited evidence participated in the answer path}, \quad (6)$$

$$G_{\text{eval}} : \text{evaluator identity/chronology is intact}, \quad (7)$$

$$G_{\text{access}} : \text{protected-label access telemetry is clear}, \quad (8)$$

$$G_{\text{search}} : \text{search-time contamination is clear}. \quad (9)$$

The claim is promoted only when every required gate passes and the evidence supports it. A resolved negative prerequisite blocks promotion; an unresolved evidential prerequisite leaves the claim undetermined. No failed coordinate can be averaged away by confidence elsewhere. Eight ablations remove one coordinate at a time, including a soft-confidence variant that promotes when at least six of nine gates pass.

4 Methods

4.1 Three-valued outcomes

Every authority decision this paper measures is three-valued rather than binary. A claim may be promoted, blocked, or left *undetermined*. An outcome that could not be determined is recorded and counted separately

Table 1: Protected V2 battery and custody. Hidden labels remained host-only until scored jobs completed.

Slice	Cases	Clean	Hostile	Candidate labels
Post-run public slice	150	30	120	hidden during execution
Protected hostile	120	0	120	hidden
Protected holdout	150	30	120	hidden
Total	420	60	360	hidden

from an outcome determined to be false, and the two are never merged. The distinction is what makes a missing prerequisite legible: an unresolvable digest, an unreachable checker, or an absent provenance record leaves the claim undetermined, and an undetermined claim is not a refuted one. Throughout the paper an outcome described as *undetermined* is this third value, carried in the evidence record and in every downstream count.

4.2 The implementation under test

The implementation evaluated here is the ORION authority layer; it is the artifact under test, and the rest of the paper calls it the governed pipeline so that each claim reads as a claim about the mechanism rather than about a product. The results tables and figures label its rows and points by that implementation name, since they are projections of the archived campaign record. Source, protocols, and evidence archives are listed in Section 8.

4.3 Prospective freeze and fresh post-repair split

The base protocol was frozen prospectively, and the post-repair campaign reported here is an additive execution binding on top of it, with a fresh hidden split and a repaired panel; Section 8 names the freeze and the exact subject revision. Before any outcome-bearing run, a public-seed preflight exercised 42 hostile authority tests and the complete 420-case pipeline with ten comparator mechanisms, eight ablations, five deterministic repeats, protected scoring, typed-panel validation, and an independent reproducer. After the preflight and harness merge were signed and green on the default branch, an independent GitHub-hosted job minted a fresh secret-seeded split. The secret seed was never logged; only a commitment was retained.

The final split contains 420 mechanical-gold cases across 13 families: 60 clean positives and 30 cases in each of 12 hostile/insufficient-evidence families. A 150-case post-run public slice contains 30 clean and 120 hostile cases; distinct protected-hostile and protected-holdout slices remain host-only during scoring. Table 1 summarizes custody.

4.4 Gold-blind execution and custody

The candidate and comparator jobs received exactly two top-level fields per case: an opaque case identifier and the candidate-visible packet. The host mechanically proved that attack family, protected gold, custody class, and expected authority terminal were absent. Candidate and comparator jobs ran in separate GitHub-hosted jobs from the exact subject archive with repository credentials removed. Five deterministic repeats were recorded under file and network syscall tracing. The protected evaluator became eligible to download gold only after both scored lanes completed, and first checked that traces contained neither protected identifiers nor external-IP connections.

The launch workflow also re-queried the signed execution-freeze commit and exact-main CI through the GitHub API, byte-compared the frozen workflow, binding, and harness files to that signed commit, and recomputed host hashes before handing off candidate-visible data. The evaluator and independent reproducer were separate jobs.

4.5 Comparator panel, ablations, and statistics

Seven primary comparator mechanisms mirror the repaired panel: ProvenanceGuard-style source routing, AttributionBench-style multi-source attribution, FIRE-style iterative retrieve/verify, CLAIM-BENCH-style claim evidence, ProvenAI-style citation fidelity/influence, RewardHackingAgents-style contamination/tamper checks, and DeepSciVerify-style evidence escalation. Three auxiliary controls test citation presence, pooled semantic support, and auditability/provenance.

Comparator names therefore use “-style” or describe a mechanism. They are protocol-matched reimplementations under one candidate-visible packet and resource accounting, not executions of the external authors’ software. Every empirical claim below is about the frozen mechanisms in this benchmark, not about published systems in their native environments.

The primary outcome is false authority-promotion rate over gold terminals that do not permit promotion. Clean coverage is promotion rate over the 60 clean positives. H1 requires an absolute false-promotion improvement beyond 0.05 against the strongest frozen comparator; H2 requires clean coverage non-inferior within 0.05; H3 tests superior selection of the undetermined terminal where that is the correct answer. Rate intervals use Wilson 95% intervals; paired effects use a fixed-seed percentile bootstrap. No false promotion, false block, abstention, candidate-caused failure, or clean false negative is removed from its eligible denominator.

5 Results

The typed authority panel passed with no blockers, and a separate implementation independently reproduced the headline counts.

5.1 False promotion and clean coverage

The governed pipeline produced 0/360 false promotions. The strongest frozen comparator mechanism, ProvenAI-style citation-fidelity/influence, produced 180/360 (50.0%). The paired difference was -0.50 with 95% CI $[-0.553, -0.447]$, so H1 passed the predeclared -0.05 practical margin. Figure 1 reports the full mechanism panel.

Both the governed pipeline and the strongest comparator promoted 60/60 clean positives, with zero clean false negatives. The clean-coverage difference and paired 95% interval were both exactly zero, so H2 passed the -0.05 non-inferiority margin. Figure 2 shows that every primary mechanism sits at 1.0 clean coverage; the result therefore does not manufacture a frontier by visually jittering equal values.

H3 was not supported, and the cause is in the battery rather than in the systems. Every one of the eleven panel members, the governed pipeline included, correctly left all 30 insufficient-evidence cases undetermined, so the difference is zero with 95% CI $[0, 0]$, and the ablations do not instrument the metric at all.

The construction explains why. In this battery the insufficient-evidence family was generated with an *empty* evidence list, while every other family carried exactly one evidence object. The rule “leave the claim undetermined if and only if the evidence list is empty” therefore classifies all 420 cases correctly. Detecting an empty list is not an act of judgement, so the metric was saturated by construction and the comparison had no resolving power: a difference could not have been observed had one existed. We report this as an inability to discriminate rather than as evidence that no difference exists, and we do not treat the null as a finding about abstention. Table 2 reports abstention and false-negative cost on that basis.

The repair is a change to what must be reasoned about, not to any gold label. Cases now present evidence that is read but does not establish the claim, in two subtypes: one where the pool contains no supporting record at all, and one where a supporting record is present but carries no verifiable provenance, so its authenticity can be neither confirmed nor refuted. The first sits one step from the pooled-support family, which is identical except that support exists elsewhere and the terminal is a block; the second sits one step from content substitution, where the hashes disagree, tampering is provable and the terminal is again a




Figure 1: False authority-promotion rate in the protected campaign. Whiskers are Wilson 95% intervals. Comparator labels denote protocol-matched mechanism reimplementations.

Table 2: Fail-closed outcomes and false-negative cost in protected V2. The only gold family whose correct terminal is ‘undetermined’ contains 30 insufficient-evidence cases.

System	Correctly undetermined	False promotions	Clean FN
ORION	30/30	0/360	0/60
ProvenAI-style	30/30	180/360	0/60

block. Under the repaired construction no evidence-free rule we tested classifies the battery: the best falls from 1.00 to 0.96. The repaired battery has not been executed, and no H3 result is claimed from it here.

5.2 Attack families and ablations

The governed pipeline made no false promotion in any hostile family. The strongest comparator false-promoted all 30 cases in each of six governance/checker families: weak checker, same-lane checker, post-hoc checker/evaluator, search-time contamination, evaluator tamper, and holdout access. It was correct on content substitution, source conflation, wrong-source, pooled-owner, cited-non-influential, and insufficient-evidence families. Figure 3 shows the contrast.

Every registered ablation preserved 60/60 clean coverage while increasing false promotion. Removing exact content binding, checker-lineage independence, hostile-checker discrimination, behavioral influence, or the search-contamination block produced 30/360 false promotions (8.3%) each. Collapsing source/provenance identity produced 60/360 (16.7%); removing evaluator protection/telemetry produced 90/360 (25.0%); and replacing the fail-closed terminal with the predeclared six-of-nine soft-confidence threshold produced 330/360 (91.7%). Table 3 contains the complete panel.




Figure 2: Safety-coverage result. Every primary mechanism promoted 60/60 clean controls, while hostile false-promotion rates differ substantially.

5.3 Attribution, support, cost, and telemetry

Several mechanisms achieve perfect source-attribution accuracy while still false-promoting governance attacks; conversely, pooled semantic-support mechanisms can score well on support while attributing the source incorrectly. Figure 4 separates those coordinates.

Deterministic gate evaluation is slower than the simple mechanism proxies in this synthetic harness: mean latency is about 2.97 ms per case for the governed pipeline versus single-digit microseconds for the primary proxies (Figure 5). This is not an end-to-end serving benchmark; model and network latency are intentionally absent.

Scored-process telemetry recorded zero protected-identifier hits and zero external-IP connections for both candidate and comparator jobs. Raw traces remain in protected custody. The independent reproducer obtained the same 0/360 versus 180/360 false-promotion counts and 60/60 versus 60/60 clean-promotion counts.

5.4 Exclusion of exploratory evidence

We exclude the repository’s earlier 39-case live-model arm from publication authorization. Post-run audit found internally inconsistent live labels/expected terminals, incorrect opportunity denominators in its summary path, and direct use of a candidate-hidden family label in the live execution path for the governed pipeline and its ablations. Those outputs remain useful diagnostics but are not combined with, substituted for, or used to tune the protected campaign.

False promotion by hostile family		
	ORION	ProvenAI
Wrong Source	0%	0%
Content Substitution	0%	0%
Source Conflation	0%	0%
Pooled Support Wrong Owner	0%	0%
Cited Non Influential	0%	0%
Weak Checker	0%	100%
Same Lane Checker	0%	100%
Posthoc Checker Evaluator	0%	100%
Search Time Contamination	0%	100%
Evaluator Tamper	0%	100%
Holdout Access	0%	100%
Insufficient Evidence	0%	0%

ProvenAI-style false-promotes all 30 cases in six governance/checker families; ORION false-promotes none.

Figure 3: False-promotion rate by hostile family for the governed pipeline and the strongest frozen mechanism proxy.

Table 3: Protected V2 results. Comparator names denote protocol-matched mechanism reimplementations, not original external software. FP is over 360 hostile opportunities; clean is over 60 clean positives.

System / variant	FP	Clean	Clean FN	Latency (ms)	Resource
ORION	0.000	1.000	0	2.9736	9.0
ProvenanceGuard-style	0.583	1.000	0	0.0037	5.0
AttributionBench-style	0.667	1.000	0	0.0058	3.0
FIRE-style	0.833	1.000	0	0.0069	6.0
CLAIM-BENCH-style	0.917	1.000	0	0.0049	4.0
ProvenAI-style	0.500	1.000	0	0.0034	5.0
RewardHackingAgents-style	0.583	1.000	0	0.0072	5.0
DeepSciVerify-style	0.583	1.000	0	0.0074	6.5
Citation presence	0.917	1.000	0	0.0009	1.0
Pooled support	0.917	1.000	0	0.0049	2.0
Auditability/provenance	0.667	1.000	0	0.0033	5.0
ORION - exact content	0.083	1.000	0	2.7131	9.0
ORION - source/provenance	0.167	1.000	0	2.7077	9.0
ORION - checker lineage	0.083	1.000	0	2.7078	9.0
ORION - hostile checker	0.083	1.000	0	2.7043	9.0
ORION - influence	0.083	1.000	0	2.7045	9.0
ORION - evaluator protection	0.250	1.000	0	2.7116	9.0
ORION soft confidence	0.917	1.000	0	2.4570	9.0
ORION - search block	0.083	1.000	0	2.7087	9.0




Figure 4: Source-attribution accuracy and support/contradiction F1 for the primary mechanism panel. High values on these coordinates do not guarantee a safe authority terminal.




Figure 5: Mean deterministic evaluation latency versus false authority-promotion rate; the latency axis is logarithmic.

6 Threat model, limitations, and interpretation

The result is intentionally bounded. First, the campaign uses 420 synthetic mechanical-gold cases; it does not establish performance on naturally occurring scientific disagreements. The written human-adjudication rubric was never triggered because all final cases were mechanically decidable, so no claim is made about adjudicator agreement. Second, scoring is deterministic and uses no LLM provider. It isolates authority-transition semantics but does not measure the error distribution of a full stochastic research agent.

Third, comparator mechanisms are matched reimplementations. They instantiate published ideas under one packet and budget, but the result must not be read as a leaderboard against the original ProvenAI, ProvenanceGuard, DeepSciVerify, FIRE, AttributionBench, CLAIM-BENCH, RewardHackingAgents, or related implementations. Fourth, the clean controls are intentionally unambiguous; 60/60 coverage shows that the governed pipeline did not win by blanket refusal but does not estimate recall on difficult benign cases. Fifth, the hostile taxonomy is finite. Adaptive attacks, compromised host infrastructure, side channels outside retained syscall/network telemetry, and novel evaluator attacks remain outside this campaign.

Sixth, and most consequential for how the three hypotheses should be read, two of them are measured on axes that this battery saturates, and for H3 the mechanism is identified rather than suspected. Clean coverage is 1.0 for all eleven panel systems and for all eight ablations, and the correct-undetermined rate is 1.0 for all eleven systems and is not instrumented in the ablations at all. Only false authority promotion varies: it takes six distinct values across the panel and four across the ablations. The whole empirical separation reported here rests on that one axis. H1 is therefore a measurement; H2’s non-inferiority pass and H3’s null are statements about a battery in which neither quantity was ever observed to move. Testing them would require clean positives that a weaker governance mechanism actually declines, and insufficient-evidence cases that a weaker mechanism actually over-promotes or over-abstains on — cases the current gold construction does not contain. Until such cases exist, H2 and H3 should be read as design limits rather than as comparative findings.

Seventh, the mechanisms composed here are not claimed as novel, and the boundary is worth stating once and plainly. Provenance tracking, attribution evaluation, citation checking, iterative verification, evidence escalation, contamination detection, evaluator-tamper detection, abstention, benchmark auditing, claim-level auditability, provenance ontologies, and generic behavioral-integrity checking are all prior work, cited in Section 2. The relevance-versus-authorized-evidence distinction is likewise established there. What is measured here is the behavior of the non-compensatory conjunction of those prerequisites under a protected, gold-blind battery, and nothing beyond it.

Recent benchmark-auditing work is an additional caution: expert-built tasks and evaluation harnesses can contain specification, environment, ground-truth, or grading defects that materially alter measured rankings (Tu et al., 2026; Wang et al., 2026a; Kapoor et al., 2025). Deterministic generation, typed-panel validation, exact split/harness binding, protected custody, post-run public slicing, and independent reproduction mitigate this risk, but these controls do not prove that the 13-family taxonomy is complete or that every benchmark-design assumption is correct.

The appropriate interpretation is architectural: under the frozen attack families and custody model, non-compensatory authority gates prevent promotions that survive strong semantic/citation/source mechanisms when a governance prerequisite is missing. This supports a fail-closed authority transition as an assurance layer; it does not prove universal scientific truth, general abstention ability, or evaluator security.

7 Broader impact and governance

False scientific-authority promotion can amplify incorrect or misattributed claims, particularly when a system presents verification artifacts that appear independent but are not. A fail-closed layer may reduce this risk, but excessive blocking can delay legitimate scientific communication or concentrate power in whoever controls evidence and evaluator registries. Work on academic integrity and agentic abstention reinforces that refusal can be the correct behavior under genuine insufficiency, while also showing that productive abstention remains difficult and should not be conflated with generic non-response (Yang et al., 2026; Liu et al., 2026).

We therefore report abstention cost, clean coverage, custody identity, and artifact transparency rather than optimizing only a security metric.

Protected evaluation creates another trade-off: some labels must remain hidden during scoring, yet publication requires enough evidence for audit. We release safe aggregates and a post-run public slice while retaining protected holdout labels/traces in restricted custody. Exact subject/split/harness hashes and an independent reproduction receipt are published so the result is not represented by an unverifiable scalar score.

8 Data and code availability

Every artifact named anywhere in this paper is listed here with its path, so that no repository location has to be carried in the narrative. Source, protocols, and evidence are version-controlled in the `SzeChunYiu/ORION` repository under `papers/paper-04-verified-scientific-discovery/`; persistent DOI assignment remains pending publication.

8.1 Preregistration

The study was preregistered and frozen before any outcome was accessed, under the identifier `P4.protected-authority.v1`. A reader checking whether a reported analysis was planned or chosen after the fact should compare against that freeze; it is the reason every number reported here can be traced to a decision made in advance of seeing it.

The machine-readable freeze is `protocol/PROTOCOL_V1.json`, the case requirements are `protocol/ATTACK_CASE_SCHEMA_V1.json`, and the statistical rules, metric definitions, and threat model are `protocol/STATISTICAL_ANALYSIS_PLAN_V1.md`, `protocol/METRICS_REGISTRY_V1.json`, and `protocol/THREAT_MODEL_V1.md`. The custody policy and the execution-freeze checklist for the post-repair campaign are `protocol/CUSTODY_POLICY_V1.md` and `protocol/EXECUTION_FREEZE_CHECKLIST_V2.md`. The prospective execution binding, including the exact subject revision and the frozen harness identity, is `protocol/PROTECTED_RUN_BINDINGS_V2.json`. The comparator and ablation disclosure is `host/BASELINE_CONFIGS_V2.json`, and the frozen case generator and verdict-leak check are `protocol/generate_attack_manifest.py` and `protocol/check_verdict_leak_v1.py`.

8.2 Executed campaign and result artifacts

The publication-authorizing campaign is GitHub Actions run `31976589735`. The subject under test is commit `f6e51b5c8f905382b8e2f5568d9035fc14241aa1`; the split digest is `3fe91b669643fa158f2f64c1e6ab70837afbb9b0582e297f1da6e1c3c696fcd9`; the frozen harness digest is `094f43cb320f8e8e3196049269b20ac22e7e94fa9890b80f27f38ef49f7c82ea`; and the safe publication bundle digest is `51ac14bc3a6b4b570aaca6d4a41c91f53d9bf2887e66f0620c412f78566a3b44`.

The safe aggregates behind every number in Section 5 are `evidence/protected_v2/PUBLICATION_METRICS_V2.json`; the per-family contrast behind Figure 3 is `evidence/protected_v2/FAMILY_CONTRAST_V2.json`; and the result and custody attestation is `evidence/protected_v2/RESULT_ATTESTATION_V2.md`. Tables 1–3 and Figures 1–5 are regenerated from those two aggregates alone by `figures/generate_figures.py`, which never reads protected per-case labels. The mapping from every result-bearing sentence in this manuscript to the archived artifact that supports it is `evidence/CLAIM_LEDGER_V1.md`. The excluded exploratory arm is documented as `evidence/protected_v2/LIVE_ARM_STATUS.md`; its outputs are retained rather than deleted, and are not pooled with the protected campaign. The nearest-work dispositions that Section 2 discusses in prose are recorded per mechanism in `literature/NEAREST_WORK_AUDIT_2026-08-16.md`.

The safe bundle contains the post-run public attack slice and public per-case verdicts. Protected per-case gold and raw traces are retained separately in restricted custody and are not part of the public release.

8.3 Reproduction

The host-side scoring and independent reproduction paths are `host/evaluate_campaign_v2.py` and `host/independent_reproduce_v2.py`; the latter recomputes the headline counts from the safe bundle without sharing code with the scorer. The binding manifest that ties subject, split, harness, and evaluator identities together is `reproducibility/BINDING_MANIFEST_V2.md`. Reproduction reconstructs the aggregates and the published figures and tables; it does not reconstruct the protected per-case gold, which is what the custody model deliberately withholds.

9 Conclusion

A scientific-authority decision is stricter than factuality, citation presence, attribution, or semantic support in isolation. In the frozen post-repair campaign, the governed pipeline’s non-escalating transition eliminated false promotion across 360 hostile opportunities without sacrificing any of 60 clean positives, whereas the strongest frozen mechanism proxy false-promoted half of the hostile cases. The result survived a fresh hidden split, gold-blind execution, syscall/network custody checks, ablations, and independent reproduction. The secondary abstention-superiority hypothesis was null on a family that could not have separated the systems, and the study remains limited to a deterministic mechanical-gold benchmark. Within those bounds, the evidence supports non-compensatory authority prerequisites as a practical defense against scientific-authority laundering.

References

- Ander Alvarez, Santhiya Rajan, Samuel Mugel, and Roman Orus. Provenanceguard: Source-aware factuality verification for mcp-based llm agents. *arXiv preprint arXiv:2606.18037*, 2026.
- Yonas Atinafu and Robin Cohen. Rewardhackingagents: Benchmarking evaluation integrity for llm ml-engineering agents. *arXiv preprint arXiv:2603.11337*, 2026.
- Mohammad Faizan and Dalal Alharthi. Provenai: Provenance-native traces of evidence in generated answers. *arXiv preprint arXiv:2606.26449*, 2026.
- Shashidhar Reddy Javaji et al. Can ai validate science? benchmarking llms for accurate scientific claim to evidence reasoning. *arXiv preprint arXiv:2506.08235*, 2025.
- Sayash Kapoor et al. Holistic agent leaderboard: The missing infrastructure for ai agent evaluation. *arXiv preprint arXiv:2510.11977*, 2025.
- Yifei Li, Xiang Yue, Zeyi Liao, and Huan Sun. Attributionbench: How hard is automatic attribution evaluation? In *Findings of ACL 2024*, pp. 14919–14935, 2024. doi: 10.18653/v1/2024.findings-acl.886.
- Junchi Liao. Auditing provenance sensitivity in llm agent action selection. *arXiv preprint arXiv:2607.20827*, 2026. URL <https://arxiv.org/abs/2607.20827>.
- Hongzhan Lin, Zixin Chen, Zhiqi Shen, Ziyang Luo, Zhen Ye, Jing Ma, Tat-Seng Chua, and Guandong Xu. Towards comprehensive stage-wise benchmarking of large language models in fact-checking. *arXiv preprint arXiv:2601.02669*, 2026.
- Xun Liu, Yi Evie Zhang, Vira Kasprova, Parisa Rabbani, Pardis Sadat Zahraei, Tianyu Zhang, Ali Ebrahimpour-Borojeny, and Varun Chandrasekaran. Agentabstain: Do llm agents know when not to act? *arXiv preprint arXiv:2607.10059*, 2026.
- Milan Markovic et al. Authoring and management of transparent research integrity assessments of randomised clinical trial publications using llm-assisted tools and provenance knowledge graphs. *arXiv preprint arXiv:2608.07202*, 2026.
- Razeen A. Rasheed, Somnath Banerjee, Animesh Mukherjee, and Rima Hazra. From fluent to verifiable: Claim-level auditability for deep research agents. *arXiv preprint arXiv:2602.13855*, 2026.

- Shaghayegh Sadeghi, Khashayar Khajavi, Rise Adhikari, and Alexander Tessier. Deepsciverify: Verifying scientific claim-citation alignment via llm-driven evidence escalation. *arXiv preprint arXiv:2605.27710*, 2026.
- Tobias Schreieder, Harsh Khandelwal, Yu-Ling Zhong, and Michael Färber. Scientific claim-source retrieval revisited: A comparative study of style transfer and re-ranking. *arXiv preprint arXiv:2607.15875*, 2026.
- Xinming Tu, Tianze Wang, Yingzhou Lu, Kexin Huang, Yuanhao Qu, and Sara Mostafavi. Benchguard: Who guards the benchmarks? automated auditing of llm agent benchmarks. *arXiv preprint arXiv:2604.24955*, 2026.
- Junlin Wang, Federico Bianchi, Shang Zhu, Fan Nie, Yongchan Kwon, Bhuwan Dhingra, and James Zou. Automated benchmark auditing for ai agents and large language models. *arXiv preprint arXiv:2605.26079*, 2026a.
- Yongjie Wang et al. Search-time contamination in deep research agents: Measuring performance inflation in public benchmark evaluation. *arXiv preprint arXiv:2606.05241*, 2026b.
- Yuhao Wu, Tung-Ling Li, and Hongliang Liu. Behavioral integrity verification for ai agent skills. *arXiv preprint arXiv:2605.11770*, 2026.
- Zhuohan Xie, Rui Xing, Yuxia Wang, Jiahui Geng, Hasan Iqbal, Dhruv Sahnan, Iryna Gurevych, and Preslav Nakov. Fire: Fact-checking with iterative retrieval and verification. *arXiv preprint arXiv:2411.00784*, 2024.
- Zonglin Yang, Xingtong Liu, and Xinyan Xu. Sciintegrity-bench: A benchmark for evaluating academic integrity in ai scientist systems. *arXiv preprint arXiv:2605.10246*, 2026.
- Chenyu Zhou, Qiliang Jiang, Shuning Wu, and Xu Zhou. Certified speculative execution for untrusted ai agents. *arXiv preprint arXiv:2606.31023*, 2026.

A Freeze and custody identifiers

The final hidden set was created only after the public preflight and harness merge were signed and green. The independent host run is 31975937488; the protected attack-set digest is 6b8b6243040163dfa582dbeb8896e2c68d6b263e3227b64e7bab199d8599897c; and the candidate-manifest digest is c5df341a6bf63f83d2af17492c498d4d36a944ad6616097a630d8390b7bda331. Execution-freeze merge 99bcacc82224089c34019ad82287754388dadbc5 was GitHub-verified before launch. The launch workflow independently re-queried that signature and exact-main CI and byte-compared frozen workflow, binding, and harness files against the signed freeze commit before handoff.

B Ablation interpretation

Five 8.3% ablations each expose a hostile family governed by the removed coordinate. Source/provenance collapse exposes two families (16.7%), evaluator-protection removal exposes three (25%), and soft confidence permits promotion in eleven of twelve hostile families (91.7%). This monotone pattern is descriptive evidence that the final zero-false-promotion result is not generated by one redundant gate alone.