

Vehicle Routing Problem - VRP

Emma Szigeti, Flaviu Sălnicean

Octombrie 2025

1 Introduction

.....

2 Difference between the Vehicle Routing Problem and the Travelling Salesman Problem

The Travelling Salesman Problem can be considered, at least from my point of view, as a simplified version of the Vehicle Routing Problem.

The Travelling Salesman Problem (TSP) consists in finding the shortest possible route that passes through a given set of points (theoretically, cities), each visited exactly once, with known distances between them, and the route must end at the starting point.

The Vehicle Routing Problem (VRP), in its basic form, consists in finding a set of routes with minimal total cost for a fleet of vehicles (theoretically, delivery trucks) starting from the same depot, such that each customer is visited exactly once. Various additional constraints can be added later.

So, what is the difference? In the Travelling Salesman Problem, there is only one person who must complete the shortest possible tour through all points, while in the Vehicle Routing Problem there are multiple vehicles, each requiring an optimal route that covers a subset of points so that, together, all points are visited.

3 Types of VRP

There are several variations of the Vehicle Routing Problem, including:

- CVRP (Capacitated Vehicle Routing Problem)
- VRPP (Vehicle Routing Problem with Profits)
- VRPTW (Vehicle Routing Problem with Time Windows)
- VRPWT (Vehicle Routing Problem with Transfers)

- VRPMT (Vehicle Routing Problem with Multiple Trips)
- VRPPD (Vehicle Routing Problem with Pickup and Delivery)
- VRPB (Vehicle Routing Problem with Backhauls)
- PVRP (Periodic Vehicle Routing Problem)
- SVRP (Stochastic Vehicle Routing Problem)
- SDVRP (Split Delivery Vehicle Routing Problem)
- MDVRP (Multiple Depot Vehicle Routing Problem)
- IRP (Inventory Routing Problem)
- OVRP (Open Vehicle Routing Problem)
- OP (Orienteering Problem)
- TOP (Team Orienteering Problem)
- CTOP (Capacitated Team Orienteering Problem)
- TOPTW (Capacitated Team Orienteering Problem with Time Windows)
- EVRP (Electric Vehicle Routing Problem)

4 The Meaning of Each Variant

CVRP is the simplest and most common form of VRP. Each vehicle has a limited carrying capacity, and the goal is to find the set of routes with minimal total cost.

VRPP is a variant of VRP in which each customer provides a certain profit, while each trip has an associated cost. The objective is to maximize the total profit.

VRPTW introduces time windows for customers: each must be visited within a specific time interval. The goal remains to minimize the total cost.

VRPWT allows vehicles to leave or pick up goods at transfer points. The objective is to find routes with minimal total cost.

VRPMT allows each vehicle to perform multiple trips per day (for instance, returning to the depot to reload). The goal is again to minimize total travel cost.

VRPPD considers customers who both receive and send deliveries. When a vehicle visits a customer, it delivers a package and picks up another one for delivery elsewhere. The goal is to minimize the total cost.

VRPB distinguishes between two types of customers: those who only receive goods and those who only send them. The objective is to minimize total cost.

PVRP extends VRP over a planning horizon (for example, a week or a month). The goal is to decide on which days and with which vehicles deliveries will be made to each customer.

SVRP introduces randomness: some parameters are uncertain (stochastic), such as traffic conditions, weather, or customer demand. The objective is to minimize expected total cost while accounting for uncertainty.

SDVRP allows customer demands to be split among several vehicles, meaning that deliveries can be divided. The goal is to minimize total cost.

MDVRP involves multiple depots from which deliveries can be made to customers. The goal is to minimize total transportation cost.

IRP integrates inventory management. Each customer has a minimum and maximum stock level, and the objective is to plan routes that maintain proper inventory levels while minimizing total cost.

OVRP assumes that vehicles do not return to the depot at the end of the day. The objective remains to minimize total cost.

OP (Orienteering Problem) associates each customer with a profit, and a single vehicle has a limited distance or time available. The goal is to select which customers to visit to maximize total profit.

TOP (Team Orienteering Problem) generalizes the OP to multiple vehicles. The goal is to select customer visits that maximize total profit.

CTOP adds capacity constraints to the TOP, where each vehicle has limited capacity. The objective remains to maximize total profit.

TOPTW extends CTOP by adding time windows for customers. The goal is to select customer visits that maximize total profit while respecting time constraints.

EVRP models routes for electric vehicles with limited driving range and recharging requirements. The goal is to minimize total cost while considering energy consumption and charging time.

5 Chosen Variant

For this project, we chose to work with the CVRP (Capacitated Vehicle Routing Problem) variant, as it is the easiest to understand and to implement.

6 Formulare matematică pentru Capacitated Vehicle Routing Problem (CVRP)

Date:

- $V = \{0, 1, \dots, n\}$ — mulțimea nodurilor, unde 0 este depozitul și $1, \dots, n$ sunt clienții.
- $c_{ij} \geq 0$ — costul (sau distanța) de la i la j .
- $d_i > 0$ — cererea clientului i , pentru $i = 1, \dots, n$; $d_0 = 0$.

- $Q > 0$ — capacitatea fiecărui vehicul.
- K — numărul maxim de vehicule disponibile.

Variabile de decizie:

$$x_{ij} \in \{0, 1\}, \quad \forall i, j \in V, \quad i \neq j$$

$$f_{ij} \geq 0, \quad \forall i, j \in V, \quad i \neq j$$

Interpretare: $x_{ij} = 1$ dacă arcul (i, j) este utilizat într-o rută; f_{ij} este fluxul de marfă (încărcătura) transportat pe arc-ul $i \rightarrow j$.

Funcția obiectiv:

$$\min \sum_{i \in V} \sum_{\substack{j \in V \\ j \neq i}} c_{ij} x_{ij}$$

Constrângeri:

$$\sum_{\substack{j \in V \\ j \neq i}} x_{ij} = 1, \quad \forall i \in \{1, \dots, n\} \quad (\text{fiecare client este vizitat o dată}) \quad (1)$$

$$\sum_{\substack{i \in V \\ i \neq j}} x_{ij} = 1, \quad \forall j \in \{1, \dots, n\} \quad (\text{fiecare client este părăsit o dată}) \quad (2)$$

$$\sum_{\substack{j \in V \\ j \neq 0}} x_{0j} \leq K, \quad \sum_{\substack{i \in V \\ i \neq 0}} x_{i0} \leq K \quad (\text{maxim } K \text{ vehicule}) \quad (3)$$

$$0 \leq f_{ij} \leq Q x_{ij}, \quad \forall i, j \in V, \quad i \neq j \quad (\text{legătura flux-arc}) \quad (4)$$

$$\sum_{\substack{j \in V \\ j \neq i}} f_{ji} + d_i = \sum_{\substack{j \in V \\ j \neq i}} f_{ij}, \quad \forall i \in \{1, \dots, n\} \quad (\text{conservare flux la clienți}) \quad (5)$$

$$\sum_{\substack{j \in V \\ j \neq 0}} f_{0j} = \sum_{i=1}^n d_i \quad (\text{flux total pornit din depozit}) \quad (6)$$

Domenii:

$$x_{ij} \in \{0, 1\}, \quad f_{ij} \geq 0$$

7 Funcția de fitness și costul penalizat pentru CVRP

În cadrul algoritmilor genetici, funcția de fitness are rolul de a evalua calitatea unei soluții candidate (set de rute). Deoarece nu toate soluțiile generate respectă constrângerile de capacitate sau numărul de vehicule, se utilizează un cost penalizat care integrează aceste abateri în valoarea totală a costului.

Fie pentru o soluție S (set de rute) costul total nepenalizat:

$$C(S) = \sum_{r \in S} \sum_{(i,j) \in r} c_{ij},$$

unde suma internă se face pe arcele succesive ale rutei r (inclusiv arcul de la depozit 0 la primul client și arcul de la ultimul client înapoi la 0).

Definiții pe rută

Pentru fiecare rută $r \in S$ definim:

$$Q_r = \sum_{i \in r} d_i \quad (\text{încărcătura totală pe ruta } r),$$

$$\Delta_r = \max(0, Q_r - Q) \quad (\text{depășirea capacității pentru ruta } r).$$

Dacă există o limită K pe numărul de vehicule, definim și:

$$\Delta_K = \max(0, |S| - K) \quad (\text{numărul de vehicule în exces}).$$

Cost penalizat

Atunci costul penalizat pentru soluția S este:

$$C_{\text{pen}}(S) = C(S) + \alpha \sum_{r \in S} \Delta_r + \beta \Delta_K,$$

unde $\alpha, \beta > 0$ sunt coeficienți de penalizare (de exemplu: α — cost pe unitate de marfă depășită; β — cost fix per vehicul în exces).

Transformare în funcție de fitness

$$\text{fitness}(S) = \frac{1}{1 + C_{\text{pen}}(S)}.$$

Astfel, valorile de fitness mai mari corespund soluțiilor cu cost penalizat mai mic (adică rute mai scurte și mai fezabile).

8 Representation of the Individual for CVRP

In the Genetic Algorithm framework, each individual encodes a possible solution to the Capacitated Vehicle Routing Problem (CVRP). Each solution consists of a set of routes that start and end at the central depot, visiting every customer exactly once.

Array-based sequential representation

In this representation, each gene corresponds to a node: either the depot or a customer. The value 0 represents the depot (start or end of a route), while numbers $1, 2, 3, \dots, n$ represent customers.

For example:

$$R_1 : 0 \rightarrow 2 \rightarrow 5 \rightarrow 7 \rightarrow 0,$$

$$R_2 : 0 \rightarrow 3 \rightarrow 4 \rightarrow 8 \rightarrow 0,$$

$$R_3 : 0 \rightarrow 1 \rightarrow 6 \rightarrow 9 \rightarrow 0.$$

Advantages


- Clear and intuitive structure: The representation directly shows the order of visits for each vehicle.
- Easy to verify route validity and vehicle capacity constraints: You can quickly compute the load of each vehicle.
- Single-array representation: All routes are represented in a single array, simplifying storage and manipulation.
- Flexible for different VRP variants: Works with CVRP, VRPTW, VRPPD, etc., by adjusting constraints or penalties.

Disadvantages

- Sequence interpretation can be less intuitive for very large instances: Long arrays with many vehicles and customers can be harder to read manually.
- Fixed depot representation: If multiple depots are involved, the array format needs modification.
- Limited direct information about route optimization: The representation shows order, but does not encode distance minimization explicitly.

Representation of a CVRP solution using numerical customer IDs

Each number represents a customer, and 0 represents the depot (start and end of each route). The sequence encodes the exact visiting order of customers for each route.



0	5	6	0	1	2	7	0	3	4	0
---	---	---	---	---	---	---	---	---	---	---

(1) Visual grouping of customers by color and route

9 Bibliografie

<https://blog.locus.sh/vehicle-routing-problem/>
https://en.wikipedia.org/wiki/Vehicle_routing_problem
https://tttp-au.com/wp-content/uploads/2024/06/Pages-from-TTTP-Vol-9_No-1_2024-WEB-8.pdf
https://ro.wikipedia.org/wiki/Problema_rut%C4%83rii_vehiculelor
https://ro.wikipedia.org/wiki/Problema_comis-voiajorului
<https://developers.google.com/optimization/routing/cvrp>
<https://www.upperinc.com/glossary/route-optimization/vehicle-routing-problem-with-profit/>
<https://developers.google.com/optimization/routing/vrptw>
<https://www.sciencedirect.com/science/article/abs/pii/S0305054825000085>
<https://www.sciencedirect.com/science/article/abs/pii/S0305054820301040>
<https://www.upperinc.com/glossary/route-optimization/vehicle-routing-problem-with-backhauls/>
<https://www.upperinc.com/glossary/route-optimization/periodic-vehicle-routing-problem-pv/>
<https://www.upperinc.com/glossary/route-optimization/stochastic-vehicle-routing-problem-svrp/>
<https://www.sciencedirect.com/science/article/pii/S0305054814002159>
<https://www.sciencedirect.com/science/article/abs/pii/S0305054813001408>
<https://www.hexaly.com/templates/inventory-routing-problem-irp>
<https://www.upperinc.com/glossary/route-optimization/open-vehicle-routing-problem-ovrp/>
<https://www.sciencedirect.com/topics/mathematics/orienteering-problem>
<https://drops.dagstuhl.de/storage/01oasics/oasics-vol014-atmos2010/OASICS.ATMOS.2010.142/OASICS.ATMOS.2010.142.pdf>
https://www.researchgate.net/publication/256022425_The_Capacitated_Team_Orienteering_Problem_A_Bi-Level_Filter-and-Fan_Method
<https://www.praiseworthyprize.org/jsm/index.php?journal=irecos&page=article&op=view&path%5B%5D=18244>
<https://www.sciencedirect.com/science/article/pii/S2352146516000089>
https://www.researchgate.net/figure/A-CVRP-solution-and-the-individual-encoding-representation-fig2_394965948