The `Column` class has various methods for creating filters... ***Removing a key method or property, such as the `__eq__` method, could break tests*** that compare columns, like `test_column` in `test_types.py`...

<tool: edit> *{remove code hunks from the files...}*

Removal-oriented bug

```
- class SlurmParseException(Exception):
-    pass

- def _expand_id_suffix(suffix_parts: str) -> List[str]:
-    """Parse the a suffix formatted like..."""
-    suffixes = []
-    for suffix_part in suffix_parts.split(","):
-       if "-" in suffix_part:
-          low, high = suffix_part.split("-")
-          for num in range(int(low), int(high) + 1):
-             suffixes.append(str(num))
-       else:
-          suffixes.append(suffix_part)
-    return suffixes
```

Let me investigate the "Speed up `fourier_series` (#2334)" commit, as performance optimizations can sometimes ***introduce bugs or dependencies that might be interesting to revert***. I'll use `git show` to view the changes...

<tool: bash> `git show e2b4ef3`

<tool: edit> *{revert history changes...}*

History-aware bug

```
  def fit(self, stan_init, stan_data, **kwargs):
     if 'inits' not in kwargs and 'init' in kwargs:
-       stan_init = self.sanitize_custom_inits(stan_init, kwargs['init'])
+       kwargs['inits'], _ = self.prepare_data(kwargs['init'], stan_data)
        del kwargs['init']
-    inits_list, data_list = self.prepare_data(stan_init, stan_data)
+    stan_init, stan_data = self.prepare_data(stan_init, stan_data)
     args = dict(
-       data=data_list,
-       inits=inits_list,
-       algorithm='Newton' if data_list['T'] < 100 else 'LBFGS',
+       data=stan_data,
+       inits=stan_init,
+       algorithm='Newton' if stan_data['T'] < 100 else 'LBFGS',
```