

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSTNE12M0GH5L000R0 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=CSTNE12M0GH5L000R0

CSTNE12M0GH5L000R0












Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Consumer equipment,Industrial equipment except for transportation & facility & energy equipment,Medical equipment [GHTF A/B],Mobile Electronics Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.	



Appearance & Shape







Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Embossed Tape	3000



Features

MURATA's frequency adjustment and packaging technology expertise has enabled the development of the chip CERALOCK.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available for a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.
- 5. Stable supply is ensured due to not using precious metal(Palladium).

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of CSTNE12M0GH5L000R0 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=CSTNE12M0GH5L000R0

CSTNE12M0GH5L000R0



Specifications

	Ceramic Resonator	
Product Type		
	(CERALOCK)	
Series	CSTNE_GH5L	
	_	
Frequency	12.000MHz	
Frequency Tolerance	+/-0.07% max.	
Operating Temperature	40% 05%	
Range	-40°C~85°C	
Frequency Shift by	10.440/	
Temperature	+/-0.11% max.	
Frequency Aging	+/-0.07% max.	
Trequency Aging	17-0.07 70 IIIAX.	
Resonant Impedance (R1)	30ohm max.	
Built-in Load Capacitance		
'	33pF	
(CL1/CL2)		
Shape	SMD	
Wash	Not available	
vvasii	INOL available	
L x W (size)	3.2x1.3mm	
,		
Mass	11.73mg	

2 of 2

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

