Charon

Synopsis

Charon does not require any advanced techniques, however there are many subtle tricks needed at almost every step of exploitation

Skills

- Knowledge of linux
- Understanding of SQL injection attacks
- Bypassing filtering to execute SQL injection
- Exploiting PHP image uploads
- Exploiting SUID files
- Shell command injection


Exploitation

As always we start with the nmap to check what services/ports are open

We can see only two ports open 22/SSH and 80/HTTP

Let's then start from web cuz it has much broader attack surface

After opening the browser we can see the following page



A quick reconnaissance shows it's supercms



Let's launch dirb to find hidden directories

```
GENERATED WORDS: 4682
---- Scanning URL: http://10.10.10.31/ ----
==> DIRECTORY: http://10.10.31/cmsdata/
```

After a while we discovered /cmsdata directory

But when trying to access it, we got 403 Forbidden




In that case, let's continue url brute forcing on the /cmsdata directory

```
GENERATED WORDS: 4682


---- Scanning URL: http://10.10.10.31/cmsdata/ ----
+ http://10.10.10.31/cmsdata/forgot.php (CODE:200|SIZE:6322)
+ http://10.10.10.31/cmsdata/login.php (CODE:200|SIZE:6426)
+ http://10.10.10.31/cmsdata/menu.php (CODE:302|SIZE:0)
+ http://10.10.10.31/cmsdata/upload.php (CODE:302|SIZE:0)
```

And we got a few PHP files



The forgot password page allows use to type email address on which the link will be sent; functionality like that makes a perfect opportunity to perform injection attacks

When we type just the email address, we get the following error message "User not found with that email"



Let's check if the application is vulnerable to SQL injection by adding single quotation (') to the email address; after doing this we are provided with a different error message "Error in database"

```
| Post | Raw | Hex | Post | Feety | Raw | Hex | Render | Post | Peety | Raw | Hex | Render | Peety | Raw | Peety | Raw | Hex | Render | Peety | Raw | Peety | Pe
```

This indicates that the application is vulnerable to the SQL injection, indeed

So now we need to establish a number of columns

We can do this by adding null to our union statement until we get a different error message


After a while we determined that we have 4 columns

So now we have to extract information from the database

All attempts to extract them directly proved to be in vain but after a while we managed to succeed by using concat statement


First we extracted a version of the database, next we enumerated the available databases, tables, columns


After enumerating database, we moved to retrieving the users credentials




And we successfully obtained users' credentials

Now, to extract credentials for all the users we will user BurpSuite Intruder with a numeric wordlist





Filter: Shov	ring all items				<u> </u>
Request ^					
0 1 2		200 200 200		3891 6586 6586	
3					
5		200 200 200		6586 6586 6586	
7		200 200 200		6586 6586	
Request					
	Raw Hex				□ In □
2 Host: 1 3 User-Ag 4 Accept 5 Accept 6 Accept 7 Content 8 Content 9 Origin 10 Connect 11 Referen 12 Upgrade	msdataforgot.php HITP/1. 0.10.10.31 ent: Moxilla/5.0 (XII; Lit toxt/html,application/shl language: en-US,en-geb.5 Encoding gutp, deflate Face (Moxilla	nux x86_64; rv tml+xml,applic form-urlencode ata/forgot.php			
වැහි €	→ Search				0 matches



1		9					
1 200 6586 2 2 000 6586 3 200 6586 4 200 6586 5 200 6586 6 6 200 6586 6 6 200 6586 7 200 6586 8 200 6586 9 200 6586 9 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 11 200 6587 2 12 200 6587 2 12 200 6587 2 12 200 6587 2 12 2	Request ^						
2							
3	1	1					
4							
5							
7 200 6586 8 200 6587 10 200 6587 11 200 6587 11 200 6587 12 12 6587 12 12 6587 14 17 200 6587 15 18 200 6587 16 19 19 19 19 17 18 19 19 19 19 18 19 19 19 19 19 19 19 19	5						
Request Response	6						
9 200 6587 1 10 200 6587 1 11 200 6587 2 12 2 12 6587 Request Response Pretty Raw Hex Render **The State of the State of	7	7					
10	8	8					
11	0 1	10					
Request Response Pretty Raw Hex Render	1 1						
Pretty Raw Next Render	2 1						
Pretty Raw Next Render	1						
<pre></pre> <pre><</pre>	Request R	Response					
<pre>33</pre>	Pretty Ray	w Hex R	Render				
4 <form action="forgot.phe" method="post"></form>							
55 <input name="mmail" placeholder="email" required="required" type="text"/> 5			d="post" action="				
Sand <pre></pre>	95		e="text" name="e	email" place	holder=		
<pre></pre>	96	doutton ty Send	/pe="submit" clas	ss="btn btn-		btn-bloc	
98							
99 90 11 12 <nr></nr> Enail sent to: simon@gmail.com:rest4:5f4dcc3b5aa765d61d8327deb882cf99 50 50 50 50 50 50 50 50 50 50 50 50 50 5							
Email sent to: simon@gmail.com::est4:5f4dcc3b5aa765d61d8327deb882cf99 33 =>							
Email sent to: simon@gmail.com: est4:5f4dcc3b5aa765d6ld8327deb882cf99	80						
83 =>	82 < h:						
83 =>				.com:test4:5			
34	83	=> 'body>					
85	U4 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>						
90 列係 4 A Saarch							