
pycast Documentation

Release v0.0.8-prealpha

Christian Schwarz

November 20, 2012

CONTENTS

1	Requirements	3
2	License	5
3	Contributors	7
4	Documentation	9
4.1	pycast.common	9
4.2	pycast.common.timeseries	10
4.3	TimeSeries	10
4.4	Base Methods	15
4.5	Smoothing Methods	18
4.6	Forecasting Methods	19
4.7	Error Measures	21
4.8	Optimization Methods	24
5	Useful Links	27
	Python Module Index	29
	Index	31

pycast aims to provide a python module supporting the basics as well as advanced smoothing and forecasting methods that can be used on time series data.

Examples of pycast can be found in `bin/examples`

REQUIREMENTS

pycast

- nose >= 1.2.1
- coverage >= 3.5.3

Documentation

- sphinx >= 1.1.3

Examples

- itty >= 0.8.1

LICENSE

Copyright (c) 2012 Christian Schwarz

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

CONTRIBUTORS

Christian Schwarz, Felix Leupold

DOCUMENTATION

4.1 pycast.common

`class pycast.common.profileme._ProfileDecorator (filelocation)`
Bases: object

Decorator class that build a wrapper around any function.

Warning The decorator does not take recursive calls into account!

`__call__ (func)`

Returns a wrapped version of the called function.

Parameters `func` (*Function*) – Function that should be wrapped.

Returns Returns a wrapped version of the called function.

Return type Function

`__init__ (filelocation)`

Initializes the ProfileMe decorator.

Parameters

- **func** (*Function*) – Function that will be profiles.
- **filelocation** (*String*) – Location for the profiling results.

`pycast.common.profileme.profileMe`
alias of `_ProfileDecorator`

`pycast.common.helper.linear_interpolation (first, last, steps)`
Interpolates all missing values using linear interpolation.

Parameters

- **first** (*Numeric*) – Start value for the interpolation.
- **last** (*Numeric*) – End Value for the interpolation
- **steps** (*Integer*) – Number of missing values that have to be calculated.

Returns Returns a list of floats containing only the missing values.

Return type List

4.2 pystac.common.timeseries

4.2.1 Normalization Levels

A `TimeSeries` instance can be normalized by different time granularity levels. Valid values for normalization levels required by `pystac.common.TimeSeries.normalize()` are stored in `pystac.common.timeseries.NormalizationLevels`.

Those levels include:

- “second”
- “minute”
- “hour”
- “day”
- “week”
- “2week”
- “4week”

4.2.2 Fusion Methods

Fusion methods that can be used to fusionate multiple data points within the same time bucket. This might sort the list it is used on. Valid values for fusion methods required by `pystac.common.TimeSeries.normalize()` are stored in `pystac.common.timeseries.FusionMethods`.

Valid fusion methods are:

- “sum”: Sums up all valid values stored in the specific time bucket
- “mean”: Calculates the mean value within the time bucket
- “median”: Calculates the median of the given time bucket values. In the case the number of entries within that bucket is even, the larger of the both values will be chosen as median.

4.2.3 Interpolation Methods

Interpolation methods that can be used for interpolation missing time buckets. Valid values for interpolation methods required by `pystac.common.TimeSeries.normalize()` are stored in `pystac.common.timeseries.InterpolationMethods`.

Valid values for interpolation methods are:

- “linear”: Use linear interpolation to calculate the missing values

4.3 TimeSeries

```
class pystac.common.timeseries.TimeSeries(isNormalized=False, isSorted=False)
    Bases: object
```

A `TimeSeries` instance stores all relevant data for a real world time series.

Warning `TimeSeries` instances are NOT threadsafe.

__add__ (*otherTimeSeries*)

Creates a new TimeSeries instance containing the data of `self` and `otherTimeSeries`.

Parameters `otherTimeSeries` (*TimeSeries*) – TimeSeries instance that will be merged with `self`.

Returns Returns a new TimeSeries instance containing the data entries of `self` and `otherTimeSeries`.

Return type TimeSeries

__eq__ (*otherTimeSeries*)

Returns if `self` and the other TimeSeries are equal.

TimeSeries are equal to each other if:

- they contain the same number of entries
- each data entry in one TimeSeries is also member of the other one.

Parameters `otherTimeSeries` (*TimeSeries*) – TimeSeries instance that is compared with `self`.

Returns `True` if the TimeSeries objects are equal, `False` otherwise.

Return type Boolean

__getitem__ (*index*)

Returns the item stored at the TimeSeries index-th position.

Parameters `index` (*Integer*) – Position of the element that should be returned. Starts at 0

Returns Returns a list containing [timestamp, data] lists.

Return type List

Raise Raises an `IndexError` if the index is out of range.

__init__ (*isNormalized=False, isSorted=False*)

Initializes the TimeSeries.

Parameters

- **isNormalized** (*Boolean*) – Within a normalized TimeSeries, all data points have the same temporal distance to each other. When this is `True`, the memory consumption of the TimeSeries might be reduced. Also algorithms will probably run faster on normalized TimeSeries. This should only be set to `True`, if the TimeSeries is really normalized! TimeSeries normalization can be forced by executing `TimeSeries.normalize()`.
- **isSorted** (*Boolean*) – If all data points added to the time series are added in their ascending temporal order, this should set to `True`.

__iter__ ()

Returns an iterator that can be used to iterate over the data stored within the TimeSeries.

Returns Returns an iterator for the TimeSeries.

Return type Iterator

__len__ ()

Returns the number of data entries stored in the TimeSeries.

Returns Returns an Integer representing the number on data entries stored within the TimeSeries.

Return type Integer

__getitem__ (*index, value*)

Sets the item at the index-th position of the TimeSeries.

Parameters

- **index** (*Integer*) – Index of the element that should be set.
- **value** (*List*) – A list of the form [timestamp, data]

Raise Raises an `IndexError` if the index is out of range.

__str__ ()

Returns a string representation of the TimeSeries.

Returns

Returns a string representing the TimeSeries in the format:

“TimeSeries([timestamp, data], [timestamp, data], [timestamp, data])”.

Return type String

add_entry (*timestamp, data, format=None*)

Adds a new data entry to the TimeSeries.

Parameters

- **timestamp** – Time stamp of the data. This has either to be a float representing the UNIX epochs or a string containing a timestamp in the given format.
- **data** (*Numeric*) – Actual data value.
- **format** (*String*) – Format of the given timestamp. This is used to convert the timestamp into UNIX epochs, if set. For valid examples take a look into the `time.strptime()` documentation.

apply (*method*)

Applies the given ForecastingAlgorithm or SmoothingMethod from the `pystac.methods` module to the TimeSeries.

Parameters **method** (*BaseMethod*) – Method that should be used with the TimeSeries. For more information about the methods take a look into their corresponding documentation.

classmethod **convert_epoch_to_timestamp** (*timestamp, format*)

Converts the given float representing UNIX-epochs into an actual timestamp.

Parameters

- **timestamp** (*Float*) – Timestamp as UNIX-epochs.
- **format** (*String*) – Format of the given timestamp. This is used to convert the timestamp from UNIX epochs. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns the timestamp as defined in format.

Return type String

classmethod **convert_timestamp_to_epoch** (*timestamp, format*)

Converts the given timestamp into a float representing UNIX-epochs.

Parameters

- **timestamp** (*String*) – Timestamp in the defined format.

- **format** (*String*) – Format of the given timestamp. This is used to convert the timestamp into UNIX epochs. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns an float, representing the UNIX-epochs for the given timestamp.

Return type Float

classmethod `from_json(json, format=None)`

Creates a new TimeSeries instance from the given json string.

Parameters

- **json** (*String*) – JSON string, containing the time series data. This should be a string created by `TimeSeries.to_json()`.
- **format** (*String*) – Format of the given timestamps. This is used to convert the timestamps into UNIX epochs, if set. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns a TimeSeries instance containing the data.

Return type TimeSeries

Warning This is probably an unsafe version! Only use it with JSON strings created by `TimeSeries.to_json()`. All assumptions regarding normalization and sort order will be ignored and set to default.

classmethod `from_twodim_list(datalist, format=None)`

Creates a new TimeSeries instance from the data stored inside a two dimensional list.

Parameters

- **datalist** (*List*) – List containing multiple iterables with at least two values. The first item will always be used as timestamp in the predefined format, the second represents the value. All other items in those sublists will be ignored.
- **format** (*String*) – Format of the given timestamp. This is used to convert the timestamp into UNIX epochs, if necessary. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns a TimeSeries instance containing the data from datalist.

Return type TimeSeries

initialize_from_sql_cursor(sqlcursor, format=None)

Initializes the TimeSeries's data from the given SQL cursor.

Parameters

- **sqlcursor** (*SQLCursor*) – Cursor that was holds the SQL result for any given “SELECT timestamp, value, ... FROM ...” SQL query. Only the first two attributes of the SQL result will be used.
- **format** (*String*) – Format of the given timestamp. This is used to convert the timestamp into UNIX epochs, if set. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns the number of entries added to the TimeSeries.

Return type Integer

is_normalized()

Returns if the TimeSeries is normalized.

Returns Returns `True` if the `TimeSeries` is normalized, `False` otherwise.

Return type `Boolean`

is_sorted()

Returns if the `TimeSeries` is sorted.

Returns Returns `True` if the `TimeSeries` is sorted ascending, `False` in all other cases.

Return type `Boolean`

normalize (*normalizationLevel*='minute', *fusionMethod*='mean', *interpolationMethod*='linear')

Normalizes the `TimeSeries` data points.

If this function is called, the `TimeSeries` gets ordered ascending automatically. The new timestamps will represent the center of each time bucket. Within a normalized `TimeSeries`, the temporal distance between two consecutive data points is constant.

Parameters

- **normalizationLevel** (*String*) – Level of normalization that has to be applied. The available normalization levels are defined in `timeseries.NormalizationLevels`.
- **fusionMethod** (*String*) – Normalization method that has to be used if multiple data entries exist within the same normalization bucket. The available methods are defined in `timeseries.FusionMethods`.
- **interpolationMethod** (*String*) – Interpolation method that is used if a data entry at a specific time is missing. The available interpolation methods are defined in `timeseries.InterpolationMethods`.

Raise Raises a `ValueError` if a `normalizationLevel`, `fusionMethod` or `interpolationMethod` have an unknown value.

sort_timeseries (*ascending*=`True`)

Sorts the data points within the `TimeSeries` according to their occurrence inline.

Parameters **ascending** (*Boolean*) – Determines if the `TimeSeries` will be ordered ascending or descending. If this is set to descending once, the ordered parameter defined in `TimeSeries.__init__()` will be set to `False` FOREVER.

Returns Returns `self` for convenience.

Return type `TimeSeries`

sorted_timeseries (*ascending*=`True`)

Returns a sorted copy of the `TimeSeries`, preserving the original one.

As an assumption this new `TimeSeries` is not ordered anymore if a new value is added.

Parameters **ascending** (*Boolean*) – Determines if the `TimeSeries` will be ordered ascending or descending.

Returns Returns a new `TimeSeries` instance sorted in the requested order.

Return type `TimeSeries`

to_gnuplot_datafile (*datafilepath*, *format*=`None`)

Dumps the `TimeSeries` into a gnuplot compatible data file.

Parameters

- **datafilepath** (*String*) – Path used to create the file. If that file already exists, it will be overwritten!

- **format** (*String*) – Format of the timestamp. This is used to convert the timestamp from UNIX epochs, if set. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns `True` if the data could be written, `False` otherwise.

Return type Boolean

to_json (*format=None*)

Returns a JSON representation of the TimeSeries data.

Parameters **format** (*String*) – Format of the given timestamp. This is used to convert the timestamp into UNIX epochs, if set. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns a basestring, containing the JSON representation of the current data stored within the TimeSeries.

Return type String

to_twodim_list (*format=None*)

Serializes the TimeSeries data into a two dimensional list of [timestamp, value] pairs.

Parameters **format** (*String*) – Format of the timestamp. This is used to convert the timestamp from UNIX epochs, if set. For valid examples take a look into the `time.strptime()` documentation.

Returns Returns a two dimensional list containing [timestamp, value] pairs.

Return type List

4.4 Base Methods

class `pystac.methods.basemethod.BaseMethod` (*requiredParameters=[]*, *hasToBeSorted=True*, *hasToBeNormalized=True*)

Bases: `object`

Baseclass for all smoothing and forecasting methods.

__init__ (*requiredParameters=[]*, *hasToBeSorted=True*, *hasToBeNormalized=True*)

Initializes the BaseMethod.

Parameters

- **requiredParameters** (*List*) – List of parameter names that have to be defined.
- **hasToBeSorted** (*Boolean*) – Defines if the TimeSeries has to be sorted or not.
- **hasToBeNormalized** (*Boolean*) – Defines if the TimeSeries has to be normalized or not.

__get_parameter_intervals ()

Returns the intervals for the methods parameter.

Only parameters with defined intervals can be used for optimization!

Returns

Returns a dictionary containing the parameter intervals, using the parameter name as key, while the value has the following format: [minValue, maxValue, minIntervalClosed, maxIntervalClosed]

- **minValue** Minimal value for the parameter

- **maxValue** Maximal value for the parameter
- **minIntervalClosed** `True`, if `minValue` represents a valid value for the parameter. `False` otherwise.
- **maxIntervalClosed** `True`, if `maxValue` represents a valid value for the parameter. `False` otherwise.

Return type Dictionary

`_get_value_error_message_for_invalid_parameter` (*parameter*, *value*)
Returns the `ValueError` message for the given parameter.

Parameters

- **parameter** (*String*) – Name of the parameter the message has to be created for.
- **value** (*Numeric*) – Value outside the parameters interval.

Returns Returns a string containing the message.

Return type String

`_in_valid_interval` (*parameter*, *value*)
Returns if the parameter is within its valid interval.

Parameters

- **parameter** (*String*) – Name of the parameter that has to be checked.
- **value** (*Numeric*) – Value of the parameter.

Returns Returns `True` if the value for the given parameter is valid, `False` otherwise.

Return type Boolean

`can_be_executed` ()
Returns if the method can already be executed.

Returns Returns `True` if all required parameters were already set, `False` otherwise.

Return type Boolean

`execute` (*timeSeries*)
Executes the `BaseMethod` on a given `TimeSeries` object.

Parameters **timeSeries** (*TimeSeries*) – `TimeSeries` object that fulfills all requirements (normalization, `sortOrder`).

Returns Returns a `TimeSeries` object containing the smoothed/forecasted values.

Return type `TimeSeries`

Raise Raises a `NotImplementedError` if the child class does not overwrite this function.

`get_interval` (*parameter*)
Returns the interval for a given parameter.

Parameters **parameter** (*String*) – Name of the parameter.

Returns

Returns a list containing with [`minValue`, `maxValue`, `minIntervalClosed`, `maxIntervalClosed`]. If no interval definitions for the given parameter exist, `None` is returned.

- **minValue** Minimal value for the parameter
- **maxValue** Maximal value for the parameter

- **minIntervalClosed** `True`, if `minValue` represents a valid value for the parameter. `False` otherwise.
- **maxIntervalClosed**: `True`, if `maxValue` represents a valid value for the parameter. `False` otherwise.

Return type `List`

get_parameter (*name*)

Returns a forecasting parameter.

Parameters **name** (*String*) – Name of the parameter.

Returns Returns the value stored in parameter.

Return type `Numeric`

Raise Raises a `KeyError` if the parameter is not defined.

get_required_parameters ()

Returns a list with the names of all required parameters.

Returns Returns a list with the names of all required parameters.

Return type `List`

has_to_be_normalized ()

Returns if the `TimeSeries` has to be normalized or not.

Returns Returns `True` if the `TimeSeries` has to be normalized, `False` otherwise.

Return type `Boolean`

has_to_be_sorted ()

Returns if the `TimeSeries` has to be sorted or not.

Returns Returns `True` if the `TimeSeries` has to be sorted, `False` otherwise.

Return type `Boolean`

set_parameter (*name*, *value*)

Sets a parameter for the `BaseMethod`.

Parameters

- **name** (*String*) – Name of the parameter that has to be checked.
- **value** (*Numeric*) – Value of the parameter.

_interval_definitions = {`False`: ['(', ')'], `True`: ['[', ']']}

```
class pystac.methods.basemethod.BaseForecastingMethod(requiredParameters=[],
                                                         valuesToForecast=1,
                                                         hasToBeSorted=True,
                                                         hasToBeNormalized=True)
```

Bases: `pystac.methods.basemethod.BaseMethod`

Basemethod for all forecasting methods.

__init__ (*requiredParameters*=[], *valuesToForecast*=1, *hasToBeSorted*=True, *hasToBeNormalized*=True)

Initializes the `BaseForecastingMethod`.

Parameters

- **requiredParameters** (*List*) – List of parameter names that have to be defined.

- **valuesToForecast** (*Integer*) – Number of entries that will be forecasted. This can be changed by using `forecast_until()`.
- **hasToBeSorted** (*Boolean*) – Defines if the TimeSeries has to be sorted or not.
- **hasToBeNormalized** (*Boolean*) – Defines if the TimeSeries has to be normalized or not.

Raise Raises a `ValueError` when `valuesToForecast` is smaller than zero.

`_calculate_values_to_forecast` (*timeSeries*)

Calculates the number of values, that need to be forecasted to match the goal set in `forecast_until`.

This sets the parameter “`valuesToForecast`” and should be called at the beginning of the `BaseMethod.execute()` implementation.

Parameters **timeSeries** (*TimeSeries*) – Should be a sorted and normalized TimeSeries instance.

Raise Raises a `ValueError` if the TimeSeries is either not normalized or sorted.

`forecast_until` (*timestamp, format=None*)

Sets the forecasting goal (timestamp wise).

This function enables the automatic determination of `valuesToForecast`.

Parameters

- **timestamp** – timestamp containing the end date of the forecast.
- **format** (*String*) – Format of the timestamp. This is used to convert the timestamp from UNIX epochs, if necessary. For valid examples take a look into the `time.strptime()` documentation.

`get_optimizable_parameters` ()

Returns a list with optimizable parameters.

All required parameters of a forecasting method with defined intervals can be used for optimization.

Returns Returns a list with optimizable parameter names.

Return type List

Todo Should we return all parameter names from the `self._parameterIntervals` instead?

`set_parameter` (*name, value*)

Sets a parameter for the `BaseForecastingMethod`.

Parameters

- **name** (*String*) – Name of the parameter.
- **value** (*Numeric*) – Value of the parameter.

4.5 Smoothing Methods

class `pystac.methods.simplemovingaverage.SimpleMovingAverage` (*windowSize=5*)

Bases: `pystac.methods.basemethod.BaseMethod`

Implements the simple moving average.

The SMA algorithm will calculate the average value at time `t` based on the datapoints between `[t - floor(windowSize / 2), t + floor(windowSize / 2)]`.

Explanation: http://en.wikipedia.org/wiki/Moving_average

`__init__ (windowSize=5)`

Initializes the SimpleMovingAverage.

Parameters `windowSize` (*Integer*) – Size of the SimpleMovingAverages window.

Raise Raises a `ValueError` if windowSize is an even or not larger than zero.

`execute (timeSeries)`

Creates a new TimeSeries containing the SMA values for the predefined windowSize.

Parameters `timeSeries` (*TimeSeries*) – The TimeSeries used to calculate the simple moving average values.

Returns TimeSeries object containing the smooth moving average.

Return type TimeSeries

Note This implementation aims to support independent for loop execution.

4.6 Forecasting Methods

`class pystac.methods.exponentialsmoothing.ExponentialSmoothing (smoothingFactor=0.1, valuesToForecast=1)`

Bases: `pystac.methods.basemethod.BaseForecastingMethod`

Implements an exponential smoothing algorithm.

Explanation: <http://www.youtube.com/watch?v=J4iODLa9hYw>

`__init__ (smoothingFactor=0.1, valuesToForecast=1)`

Initializes the ExponentialSmoothing.

Parameters

- **smoothingFactor** (*Float*) – Defines the alpha for the ExponentialSmoothing. Valid values are in (0.0, 1.0).
- **valuesToForecast** (*Integer*) – Number of values that should be forecasted.

Raise Raises a `ValueError` when smoothingFactor has an invalid value.

`_get_parameter_intervals ()`

Returns the intervals for the methods parameter.

Only parameters with defined intervals can be used for optimization!

Returns

Returns a dictionary containing the parameter intervals, using the parameter name as key, while the value has the following format: [minValue, max_value, minIntervalClosed, maxIntervalClosed]

- **minValue** Minimal value for the parameter
- **max_value** Maximal value for the parameter
- **minIntervalClosed** True, if minValue represents a valid value for the parameter. False otherwise.
- **maxIntervalClosed:** True, if max_value represents a valid value for the parameter. False otherwise.

Return type Dictionary

execute (*timeSeries*)

Creates a new TimeSeries containing the smoothed and forecasted values.

Returns TimeSeries object containing the smoothed TimeSeries, including the forecasted values.

Return type TimeSeries

Note The first normalized value is chosen as the starting point.

class `pystac.methods.exponentialsmoothing.HoltMethod` (*smoothingFactor=0.1*,
trendSmoothingFactor=0.5,
valuesToForecast=1)

Bases: `pystac.methods.basemethod.BaseForecastingMethod`

Implements the Holt algorithm.

Explanation: http://en.wikipedia.org/wiki/Exponential_smoothing#Double_exponential_smoothing

__init__ (*smoothingFactor=0.1*, *trendSmoothingFactor=0.5*, *valuesToForecast=1*)

Initializes the HoltMethod.

Parameters

- **smoothingFactor** (*Float*) – Defines the alpha for the ExponentialSmoothing. Valid values are in (0.0, 1.0).
- **trendSmoothingFactor** (*Float*) – Defines the beta for the HoltMethod. Valid values are in (0.0, 1.0).
- **valuesToForecast** (*Integer*) – Defines the number of forecasted values that will be part of the result.

Raise Raises a `ValueError` when `smoothingFactor` or `trendSmoothingFactor` has an invalid value.

_get_parameter_intervals ()

Returns the intervals for the methods parameter.

Only parameters with defined intervals can be used for optimization!

Returns

Returns a dictionary containing the parameter intervals, using the parameter name as key, while the value has the following format: [minValue, maxValue, minIntervalClosed, maxIntervalClosed]

- **minValue** Minimal value for the parameter
- **maxValue** Maximal value for the parameter
- **minIntervalClosed** `True`, if `minValue` represents a valid value for the parameter. `False` otherwise.
- **maxIntervalClosed** `True`, if `maxValue` represents a valid value for the parameter. `False` otherwise.

Return type Dictionary

execute (*timeSeries*)

Creates a new TimeSeries containing the smoothed values.

Returns TimeSeries object containing the smoothed TimeSeries, including the forecasted values.

Return type TimeSeries

Note The first normalized value is chosen as the starting point.

4.7 Error Measures

class `pycast.errors.baseerrormmeasure.BaseErrorMeasure` (*minimalErrorCalculationPercentage=60*)

Bases: object

Baseclass for all error measures.

__init__ (*minimalErrorCalculationPercentage=60*)

Initializes the error measure.

Parameters **minimalErrorCalculationPercentage** (*Integer*) – The number of entries in an original TimeSeries that have to have corresponding partners in the calculated TimeSeries. Corresponding partners have the same time stamp. Valid values are in [0.0, 100.0].

Raise Raises a `ValueError` if `minimalErrorCalculationPercentage` is not in [0.0, 100.0].

_calculate (*startingPercentage, endPercentage*)

This is the error calculation function that gets called by `BaseErrorMeasure.get_error()`.

Both parameters will be correct at this time.

Parameters

- **startingPercentage** (*Float*) – Defines the start of the interval. This has to be a value in [0.0, 100.0]. It represents the value, where the error calculation should be started. 25.0 for example means that the first 25% of all calculated errors will be ignored.
- **endPercentage** (*Float*) – Defines the end of the interval. This has to be a value in [0.0, 100.0]. It represents the vlaue, after which all error values will be ignored. 90.0 for example means that the last 10% of all local errors will be ignored.

Returns Returns a float representing the error.

Return type Float

Raise Raises a `NotImplementedError` if the child class does not overwrite this method.

_get_error_values (*startingPercentage, endPercentage*)

Gets the defined subset of `self._errorValues`.

Both parameters will be correct at this time.

Parameters

- **startingPercentage** (*Float*) – Defines the start of the interval. This has to be a value in [0.0, 100.0]. It represents the value, where the error calculation should be started. 25.0 for example means that the first 25% of all calculated errors will be ignored.
- **endPercentage** (*Float*) – Defines the end of the interval. This has to be a value in [0.0, 100.0]. It represents the vlaue, after which all error values will be ignored. 90.0 for example means that the last 10% of all local errors will be ignored.

Returns Returns a list with the defined error values.

Return type List

get_error (*startingPercentage=0.0, endPercentage=100.0*)

Calculates the error for the given interval (`startingPercentage`, `endPercentage`) between the TimeSeries given during `BaseErrorMeasure.initialize()`.

Parameters

- **startingPercentage** (*Float*) – Defines the start of the interval. This has to be a value in [0.0, 100.0]. It represents the value, where the error calculation should be started. 25.0 for example means that the first 25% of all calculated errors will be ignored.
- **endPercentage** (*Float*) – Defines the end of the interval. This has to be a value in [0.0, 100.0]. It represents the value, after which all error values will be ignored. 90.0 for example means that the last 10% of all local errors will be ignored.

Returns Returns a float representing the error.

Return type Float

Raise Raises a `ValueError` in one of the following cases:

- startingPercentage not in [0.0, 100.0]
- endPercentage not in [0.0, 100.0]
- endPercentage < startingPercentage

Raise Raises a `StandardError` if `BaseErrorMeasure.initialize()` was not successful before.

initialize (*originalTimeSeries, calculatedTimeSeries*)

Initializes the ErrorMeasure.

During initialization, all `BaseErrorMeasure.local_errors()` are calculated.

Parameters

- **originalTimeSeries** (*TimeSeries*) – TimeSeries containing the original data.
- **calculatedTimeSeries** (*TimeSeries*) – TimeSeries containing calculated data. Calculated data is smoothed or forecasted data.

Returns Return `True` if the error could be calculated, `False` otherwise based on the `minimalErrorCalculationPercentage`.

Return type Boolean

Raise Raises a `StandardError` if the error measure is initialized multiple times.

local_error (*originalValue, calculatedValue*)

Calculates the error between the two given values.

Parameters

- **originalValue** (*Numeric*) – Value of the original data.
- **calculatedValue** (*Numeric*) – Value of the calculated TimeSeries that corresponds to originalValue.

Returns Returns the error measure of the two given values.

Return type Numeric

Raise Raises a `NotImplementedError` if the child class does not overwrite this method.

class `pystac.errors.meansquarederror.MeanSquaredError` (*minimalErrorCalculationPercentage=60*)
 Bases: `pystac.errors.baseerrormmeasure.BaseErrorMeasure`

Implements the mean squared error measure.

Explanation: http://en.wikipedia.org/wiki/Mean_squared_error

_calculate (*startingPercentage*, *endPercentage*)

This is the error calculation function that gets called by `BaseErrorMeasure.get_error()`.

Both parameters will be correct at this time.

Parameters

- **startingPercentage** (*Float*) – Defines the start of the interval. This has to be a value in `[0.0, 100.0]`. It represents the value, where the error calculation should be started. 25.0 for example means that the first 25% of all calculated errors will be ignored.
- **endPercentage** (*Float*) – Defines the end of the interval. This has to be a value in `[0.0, 100.0]`. It represents the value, after which all error values will be ignored. 90.0 for example means that the last 10% of all local errors will be ignored.

Returns Returns a float representing the error.

Return type Float

Raise Raises a `NotImplementedError` if the child class does not overwrite this method.

local_error (*originalValue*, *calculatedValue*)

Calculates the error between the two given values.

Parameters

- **originalValue** (*Numeric*) – Value of the original data.
- **calculatedValue** (*Numeric*) – Value of the calculated TimeSeries that corresponds to originalValue.

Returns Returns the error measure of the two given values.

Return type Float

class `pystac.errors.symmetricmeanabsolutepercentageerror.SymmetricMeanAbsolutePercentageError`
Bases: `pystac.errors.baseerrormeasure.BaseErrorMeasure`

Implements the symmetric mean absolute percentage error with a boarder of 200%.

Explanation: <http://monashforecasting.com/index.php?title=SMAPE> (Formula (3))

If the calculated value and the original value are equal, the error is 0.

_calculate (*startingPercentage*, *endPercentage*)

This is the error calculation function that gets called by `BaseErrorMeasure.get_error()`.

Both parameters will be correct at this time.

Parameters

- **startingPercentage** (*Float*) – Defines the start of the interval. This has to be a value in `[0.0, 100.0]`. It represents the value, where the error calculation should be started. 25.0 for example means that the first 25% of all calculated errors will be ignored.
- **endPercentage** (*Float*) – Defines the end of the interval. This has to be a value in `[0.0, 100.0]`. It represents the value, after which all error values will be ignored. 90.0 for example means that the last 10% of all local errors will be ignored.

Returns Returns a float representing the error.

Return type Float

local_error (*originalValue*, *calculatedValue*)

Calculates the error between the two given values.

Parameters

- **originalValue** (*Numeric*) – Value of the original data.
- **calculatedValue** (*Numeric*) – Value of the calculated TimeSeries that corresponds to originalValue.

Returns Returns the error measure of the two given values.

Return type Numeric

4.8 Optimization Methods

```
class pystac.optimization.baseoptimizationmethod.BaseOptimizationMethod (errorMeasureClass,
                                                                    precision=-1)
```

Bases: object

Baseclass for all optimization methods.

__init__ (*errorMeasureClass*, *precision=-1*)
Initializes the optimization method.

Parameters

- **errorMeasureClass** (*BaseErrorMeasure*) – Error measure class from `pystac.errors`
- **precision** (*Integer*) – Defines the accuracy for parameter tuning in $10^{\text{precision}}$. This parameter has to be an integer in $[-7, 0]$.

Raise Raises a `TypeError` if `errorMeasureClass` is not a valid class. Valid classes are derived from `pystac.errors.BaseErrorMeasure`.

Raise Raises a `ValueError` if `precision` is not in $[-7, 0]$.

optimize (*timeSeries*, *forecastingMethods=[]*)
Runs the optimization on the given TimeSeries.

Parameters

- **timeSeries** (*TimeSeries*) – TimeSeries instance that requires an optimized forecast.
- **forecastingMethods** (*List*) – List of forecastingMethods that will be used for optimization.

Returns Returns the optimized forecasting method with the smallest error.

Return type (`BaseForecastingMethod`, `Dictionary`)

Raise Raises a `ValueError` if no forecastingMethods is empty.

```
class pystac.optimization.gridsearch.GridSearch (errorMeasureClass, precision=-1)
Bases: pystac.optimization.baseoptimizationmethod.BaseOptimizationMethod
```

Implements the grid search method for parameter optimization.

GridSearch is the brute force method.

_generate_next_parameter_value (*parameter*, *forecastingMethod*)
Generator for a specific parameter of the given forecasting method.

Parameters

- **parameter** (*String*) – Name of the parameter the generator is used for.
- **forecastingMethod** (*BaseForecastingMethod*) – Instance of a `ForecastingMethod`.

Returns Creates a generator used to iterate over possible parameters.

Return type Generator Function

optimization_loop (*timeSeries*, *forecastingMethod*, *remainingParameters*, *currentParameterValues*={})

The optimization loop.

This function is called recursively, until all parameter values were evaluated.

Parameters

- **timeSeries** (*TimeSeries*) – TimeSeries instance that requires an optimized forecast.
- **forecastingMethod** (*BaseForecastingMethod*) – ForecastingMethod that is used to optimize the parameters.
- **remainingParameters** (*list*) – List containing all parameters with their corresponding values that still need to be evaluated. When this list is empty, the most inner optimization loop is reached.
- **currentParameterValues** (*Dictionary*) – The currently evaluated forecast parameter combination.

Returns Returns a list containing a BaseErrorMeasure instance as defined in BaseOptimizationMethod.__init__() and the forecastingMethods parameter.

Return type List

optimize (*timeSeries*, *forecastingMethods*=[], *startingPercentage*=0.0, *endPercentage*=100.0)

Runs the optimization of the given TimeSeries.

Parameters

- **timeSeries** (*TimeSeries*) – TimeSeries instance that requires an optimized forecast.
- **forecastingMethods** (*List*) – List of forecastingMethods that will be used for optimization.
- **startingPercentage** (*Float*) – Defines the start of the interval. This has to be a value in [0.0, 100.0]. It represents the value, where the error calculation should be started. 25.0 for example means that the first 25% of all calculated errors will be ignored.
- **endPercentage** (*Float*) – Defines the end of the interval. This has to be a value in [0.0, 100.0]. It represents the value, after which all error values will be ignored. 90.0 for example means that the last 10% of all local errors will be ignored.

Returns Returns the optimized forecasting method with the smallest error.

Return type BaseForecastingMethod, Dictionary

Raise Raises a ValueError if no forecastingMethods is empty.

optimize_forecasting_method (*timeSeries*, *forecastingMethod*)

Optimizes the parameters for the given timeSeries and forecastingMethod.

Parameters

- **timeSeries** (*TimeSeries*) – TimeSeries instance, containing the original data.
- **forecastingMethod** (*BaseForecastingMethod*) – ForecastingMethod that is used to optimize the parameters.

Returns Returns a tuple containing only the smallest BaseErrorMeasure instance as defined in BaseOptimizationMethod.__init__() and the forecastingMethods parameter.

Return type Tuple

USEFUL LINKS

- [github Project Page](#)
- *search*

PYTHON MODULE INDEX

p

`pycast.common.helper`, 9

`pycast.common.profileme`, 9

INDEX

Symbols

_ProfileDecorator (class in pycast.common.profileme), 9
 __add__() (pycast.common.timeseries.TimeSeries method), 10
 __call__() (pycast.common.profileme._ProfileDecorator method), 9
 __eq__() (pycast.common.timeseries.TimeSeries method), 11
 __getitem__() (pycast.common.timeseries.TimeSeries method), 11
 __init__() (pycast.common.profileme._ProfileDecorator method), 9
 __init__() (pycast.common.timeseries.TimeSeries method), 11
 __init__() (pycast.errors.baseerrormmeasure.BaseErrorMeasure method), 21
 __init__() (pycast.methods.basemethod.BaseForecastingMethod method), 17
 __init__() (pycast.methods.basemethod.BaseMethod method), 15
 __init__() (pycast.methods.exponentialsMOOTHING.ExponentialSmoothing method), 19
 __init__() (pycast.methods.exponentialsMOOTHING.HoltMethod method), 20
 __init__() (pycast.methods.simplemovingaverage.SimpleMovingAverage method), 18
 __init__() (pycast.optimization.baseoptimizationmethod.BaseOptimizationMethod method), 24
 __iter__() (pycast.common.timeseries.TimeSeries method), 11
 __len__() (pycast.common.timeseries.TimeSeries method), 11
 __setitem__() (pycast.common.timeseries.TimeSeries method), 11
 __str__() (pycast.common.timeseries.TimeSeries method), 12
 _calculate() (pycast.errors.baseerrormmeasure.BaseErrorMeasure method), 21
 _calculate() (pycast.errors.meansquarederror.MeanSquaredError method), 22
 _calculate() (pycast.errors.symmetricmeanabsolutepercentageerror.SymmetricMeanAbsolutePercentageError method), 23
 _calculate_values_to_forecast() (pycast.methods.basemethod.BaseForecastingMethod method), 18
 _generate_next_parameter_value() (pycast.optimization.gridsearch.GridSearch method), 24
 _get_error_values() (pycast.errors.baseerrormmeasure.BaseErrorMeasure method), 21
 _get_parameter_intervals() (pycast.methods.basemethod.BaseMethod method), 15
 _get_parameter_intervals() (pycast.methods.exponentialsMOOTHING.ExponentialSmoothing method), 19
 _get_parameter_intervals() (pycast.methods.exponentialsMOOTHING.HoltMethod method), 20
 _get_value_error_message_for_invalid_parameter() (pycast.methods.basemethod.BaseMethod method), 16
 in_valid_interval() (pycast.methods.basemethod.BaseMethod method), 16
 _interval_definitions (pycast.methods.basemethod.BaseMethod attribute), 17
A
 add_entry() (pycast.common.timeseries.TimeSeries method), 12
 apply() (pycast.common.timeseries.TimeSeries method), 12
B
 BaseErrorMeasure (class in pycast.errors.baseerrormmeasure), 21
 BaseForecastingMethod (class in pycast.methods.basemethod), 17
 BaseMethod (class in pycast.methods.basemethod), 15
 BaseOptimizationMethod (class in pycast.optimization.baseoptimizationmethod), 24

BaseOptimizationMethod (class in py- method), 17
cast.optimization.baseoptimizationmethod), 24

C

can_be_executed() (py- cast.methods.basemethod.BaseMethod method), 16

convert_epoch_to_timestamp() (py- cast.common.timeseries.TimeSeries method), 12

convert_timestamp_to_epoch() (py- cast.common.timeseries.TimeSeries method), 12

E

execute() (pystac.methods.basemethod.BaseMethod method), 16

execute() (pystac.methods.exponentialsMOOTHING.ExponentialSMOOTHING method), 19

execute() (pystac.methods.exponentialsMOOTHING.HoltMethod method), 20

execute() (pystac.methods.simplemovingaverage.SimpleMovingAverage method), 19

ExponentialSmoothing (class in py- cast.methods.exponentialsMOOTHING), 19

F

forecast_until() (pystac.methods.basemethod.BaseForecastingMethod method), 18

from_json() (pystac.common.timeseries.TimeSeries class method), 13

from_twodim_list() (py- cast.common.timeseries.TimeSeries class method), 13

G

get_error() (pystac.errors.baseerrormeasure.BaseErrorMeasure method), 21

get_interval() (pystac.methods.basemethod.BaseMethod method), 16

get_optimizable_parameters() (py- cast.methods.basemethod.BaseForecastingMethod method), 18

get_parameter() (pystac.methods.basemethod.BaseMethod method), 17

get_required_parameters() (py- cast.methods.basemethod.BaseMethod method), 17

GridSearch (class in pystac.optimization.gridsearch), 24

H

has_to_be_normalized() (py- cast.methods.basemethod.BaseMethod method), 17

has_to_be_sorted() (py- cast.methods.basemethod.BaseMethod method), 17

HoltMethod (class in py- cast.methods.exponentialsMOOTHING), 20

I

initialize() (pystac.errors.baseerrormeasure.BaseErrorMeasure method), 22

initialize_from_sql_cursor() (py- cast.common.timeseries.TimeSeries method), 13

is_normalized() (pystac.common.timeseries.TimeSeries method), 13

is_sorted() (pystac.common.timeseries.TimeSeries method), 14

L

linear_interpolation() (in module pystac.common.helper), 9

local_error() (pystac.errors.baseerrormeasure.BaseErrorMeasure method), 22

local_error() (pystac.errors.meansquarederror.MeanSquaredError method), 23

local_error() (pystac.errors.symmetricmeanabsolutepercentageerror.SymmetricMeanAbsolutePercentageError method), 23

M

MeanSquaredError (class in py- cast.errors.meansquarederror), 22

N

normalize() (pystac.common.timeseries.TimeSeries method), 14

O

optimization_loop() (py- cast.optimization.gridsearch.GridSearch method), 25

optimize() (pystac.optimization.baseoptimizationmethod.BaseOptimizationMethod method), 24

optimize() (pystac.optimization.gridsearch.GridSearch method), 25

optimize_forecasting_method() (py- cast.optimization.gridsearch.GridSearch method), 25

P

profileMe (in module pystac.common.profileme), 9

pystac.common.helper (module), 9

pystac.common.profileme (module), 9

S

[set_parameter\(\)](#) (pycast.methods.basemethod.BaseForecastingMethod method), [18](#)
[set_parameter\(\)](#) (pycast.methods.basemethod.BaseMethod method), [17](#)
[SimpleMovingAverage](#) (class in pycast.methods.simplemovingaverage), [18](#)
[sort_timeseries\(\)](#) (pycast.common.timeseries.TimeSeries method), [14](#)
[sorted_timeseries\(\)](#) (pycast.common.timeseries.TimeSeries method), [14](#)
[SymmetricMeanAbsolutePercentageError](#) (class in pycast.errors.symmetricmeanabsolutepercentageerror), [23](#)

T

[TimeSeries](#) (class in pycast.common.timeseries), [10](#)
[to_gnuplot_datafile\(\)](#) (pycast.common.timeseries.TimeSeries method), [14](#)
[to_json\(\)](#) (pycast.common.timeseries.TimeSeries method), [15](#)
[to_twodim_list\(\)](#) (pycast.common.timeseries.TimeSeries method), [15](#)