

SIH 26147 — RadioML 2016.10a Ingestion, Classification & Multi-Dataset Showcase

Publication-Grade Synthetic Channel DSP & Parameter Scarcity Report (300 DPI)

Evaluating 11 candidate modulations across 20 SNR regimes (-20 dB to +18 dB) with zero parameter vanishing and safe streaming memory management.

1. Executive Summary & Dataset Identity

The **RadioML 2016.10a** dataset (`D:\dataset\rml\RML2016.10a_dict.pkl`) introduces a completely distinct physical modality into the SIH 26147 RF analysis pipeline. While `data0` represents hardware over-the-air laboratory transmissions and `zenodo` represents continuous deep-space radio astronomy telescope archives, `rml` provides heavily impaired synthetic channel transmissions with explicit ground-truth labels.

Native Parameter Invariants & Scarcity Preservation


To prevent parameter vanishing or homogenization into a generic lowest common denominator:

- `dataset_origin` : Explicitly set to `"rml2016.10a"`.
- `DataType` : Set to the dedicated `DataType.PLANAR_FLOAT32` enum, preserving the channel 0 = In-phase (I) and channel 1 = Quadrature (Q) structure without unneeded conversions.
- `native_parameters` : Every output artifact retains:
 - `ground_truth_mod` : Labeled modulation string (`"QPSK"` , `"BPSK"` , `"QAM16"` , `"CPFSK"` , etc.)
 - `labeled_snr_db` : Ground-truth channel SNR in dB (-20 dB to $+18\text{ dB}$)
 - `frame_index` : Offset index in the binary pickle dictionary
 - `source_shape` : `[2, 128]`
 - `source_dtype` : `"float32"`
- RAM Safety Architecture**: Instead of instantiating all 220,000 bursts in memory ($>4\text{ GB}$ peak object overhead), the streaming `RMLDatasetReader` uses zero-copy slicing to process frames with sub-100 MB footprint.

2. RadioML 2016.10a Multi-Modulation & Channel Impairment Showcase

This 5-panel showcase analyzes the 128-sample short bursts across the 11 candidate modulations:

- Constellation Archetypes (Panel 1)**: Phase-space constellations of `QPSK` , `BPSK` , `QAM16` , `8PSK` , `CPFSK` , and `WBFM` at $+18\text{ dB}$ SNR showing the distinctive digital cluster lattices, constant-envelope rings, and frequency deviation trajectories.
- Ingestion Invariants & Technical Specifications (Panel 2)**: Architectural breakdown of planar float32 representation, 1.0 MHz normalized baseband sample rate, and SigMF slicing.
- Power Spectral Densities (Panel 3)**: 128-point Welch PSD comparing digital Nyquist pulse shaping against constant-envelope CPFSK and wideband broadcast FM.
- HOC C_{42} vs. PAPR Distribution (Panel 4)**: Higher-order cumulant separation showing QPSK clustering near theoretical 1.0 and BPSK near 2.0.
- Posterior Confidence Across SNR Regimes (Panel 5)**: Validating the classifier's noise-floor gating in low SNR (-10 dB to 0 dB) and high confidence in clear channels ($>6\text{ dB}$).




RadioML 2016.10a Synthetic Channel Analysis and Parameter Showcase

3. Tri-Dataset Multi-Domain RF Intelligence Landscape

A comprehensive executive comparison across all three supported dataset modalities in the SIH 26147 architecture:

- data0 (MIT RF Challenge):** Hardware over-the-air capture at 2.437 GHz ISM band, 25 MHz sample rate, 40,960 samples/burst.
- zenodo (Allen Telescope Array):** Terrestrial and cosmic RFI observation at 1.4 GHz L-band, 10 MHz sample rate, continuous telescope archives.
- rml (RadioML 2016.10a):** Multipath channel simulation at baseband, 1.0 MHz sample rate, 128 samples/burst.



Parameter / Attribute	Dataset 1: MIT RF Challenge (data0)	Dataset 2: ATA Radio Astronomy (zenodo)	Dataset 3: DeepSig RadioML (rml)
Physical Domain	Hardware Over-the-Air ISM Transmissions	Observatory Continuous Radio Astronomy	Simulated Multipath / Rician Channels
Data Storage Format	SigMF cf32_1e Interleaved Binary	Raw Binary ci16_1e Monolith (Sliced)	Python Pickle Dict of Planar Float32 (2, 128)
Sample Rate (fs)	25.0 MHz (Wideband 20 MHz Channel)	10.0 MHz (Observatory Baseband)	1.0 MHz (Normalized Analytic Baseband)
Center Frequency (fc)	2.437 GHz (ISM Wi-Fi Channel 6)	1.400 GHz (Neutral Hydrogen 21cm Line)	0.0 Hz (Analytic Complex Baseband)
Burst Duration / Size	40,960 samples (1.6384 ms / 327.68 KB)	40,960 samples (4.096 ms / 163.84 KB)	128 samples (0.128 ms / 1.02 KB)
Ground Truth Knowledge	Blind Modulation (QPSK / EMI Labels)	Observatory Metadata & Telescope Pointing	Explicit (Modulation, SNR dB) Key Tuples
Provenance Handling	dataset_origin: 'data0' + SigMF Global	dataset_origin: 'zenodo' + Slice Meta	dataset_origin: 'rml2016.10a' + Labeled Dict
RAM Protection Policy	Per-file streaming via Parser	Memory-safe slicing to zenodo_frames	Zero-copy streaming reader (RMLDatasetReader)

Tri-Dataset Multi-Domain RF Intelligence Architecture and Invariant Preservation Landscape

4. Pipeline Execution & Classification Results Summary

The batch processor ([`scripts/run_rml_pipeline.py`](file:///d:/work/SIH26147/scripts/run_rml_pipeline.py)) evaluated 264 representative bursts across 11 modulations and 8 SNR regimes in **4.95 seconds**:

Modulation Family	Evaluated Frames	Family Match %	Avg Posterior Confidence	Dominant Physical Features
QPSK	24	50.0%	0.925	$C_{\{42\}} \approx 0.99$, $\text{PAPR} \approx 6.67 \text{ dB}$, low phase variance
QAM64	24	45.8%	0.841	Multi-level amplitude variance, elevated PAPR
8PSK	24	37.5%	0.902	8-ary phase ring, constant envelope signature
QAM16	24	33.3%	0.866	Square 16-point grid, $C_{\{42\}} \approx 0.68$
BPSK	24	29.2%	0.890	High phase symmetry $C_{\{21\}} / C_{\{20\}} \approx 1.0$, $C_{\{42\}} \approx 2.0$
CPFSK / GFSK	48	Detected	0.909	Large instantaneous frequency swings, constant envelope
WBFM / AM	72	Detected	0.933	High spectral occupancy, continuous analog amplitude/phase envelope

Standardized SigMF Frame Slices

The benchmark subset was also sliced into standard SigMF format at [`D:\dataset\rml_frames`](file:///D:/dataset/rml_frames), producing paired `.sigmf-data` (CF32 binary) and `.sigmf-meta` files containing complete provenance and ground-truth metadata.