

On This Page >



users

An instance of this module will create a user account on the added machines, along with a generated password that is constant across machines and user settings.

System

Usage

```
1 {
2   inventory.instances = {
3     # Deploy user alice on all machines. Don't prompt for password (will
4     # auto-generated).
5     user-alice = {
6       module = {
7         name = "users";
8         input = "clan-core";
9       };
10    roles.default.tags.all = { };
11    roles.default.settings = {
12      user = "alice";
13      prompt = false;
14    };
15  };
16
17  # Deploy user Carol on all machines. Prompt only once and use the
18  # same password on all machines. (`share = true`)
19  user-carol = {
20    module = {
21      name = "users";
22      input = "clan-core";
23    };
24    roles.default.tags.all = { };
```

```

25     roles.default.settings = {
26         user = "carol";
27         share = true;
28     };
29 };
30
31 # Deploy user bob only on his laptop. Prompt for a password.
32 user-bob = {
33     module = {
34         name = "users";
35         input = "clan-core";
36     };
37     roles.default.machines.bobs-laptop = { };
38     roles.default.settings.user = "bob";
39 };
40 };
41 }

```

Migration from `root-password` module

The deprecated `clan.root-password` module has been replaced by the `users` module. Here's how to migrate:

1. Update your flake configuration

Replace the `root-password` module import with a `users` service instance:

```

1 # OLD - Remove this from your nixosModules:
2 imports = [
3     self.inputs.clan-core.clanModules.root-password
4 ];
5
6 # NEW - Add to inventory.instances or machines/flake-module.nix:
7 instances = {
8     users-root = {
9         module.name = "users";
10        module.input = "clan-core";
11        roles.default.tags.nixos = { };
12        roles.default.settings = {
13            user = "root";
14            prompt = false; # Set to true if you want to be prompted

```

```
15     groups = [ ];
16 };
17 };
18 };
```

2. Migrate vars

The vars structure has changed from `root-password` to `user-password-root`:

```
1 # For each machine, rename the vars directories:
2 cd vars/per-machine/<machine-name>/
3 mv root-password user-password-root
4 mv user-password-root/password-hash user-password-root/user-password-hash
5 mv user-password-root/password user-password-root/user-password
```

Roles

The users service has the following roles:

- default

Options for the `default` role

groups

Additional groups the user should be added to. You can add any group that exists on your system. Make sure these group exists on all machines where the user is enabled.

Commonly used groups:

- "wheel" - Allows the user to run commands as root using `sudo`.
- "networkmanager" - Allows the user to manage network connections.
- "video" - Allows the user to access video devices.

- "input" - Allows the user to access input devices.

Type: `list of string`

Default:

[]

❖ Example

```
1 [
2   "wheel"
3   "networkmanager"
4   "video"
5   "input"
6 ]
```

Declared in: [clanServices/users/default.nix](#)

prompt

Whether the user should be prompted for a password.

Effects:

- *enabled* (`true`) - Prompt for a password during the machine installation or update workflow.
- *disabled* (`false`) - Generate a password during the machine installation or update workflow.

The password can be shown in two steps:

- `clan vars list <machine-name>`
- `clan vars get <machine-name> <name-of-password-variable>`

Type: `boolean`

Default:

`true`

❖ Example

false

Declared in: [clanServices/users/default.nix](#)

share

Whether the user should have the same password on all machines.

By default, you will be prompted for a new password for every host. Unless `generate` is set to `true`.

Type: `boolean`

Default:

false

❖ Example

true

Declared in: [clanServices/users/default.nix](#)

user

The user the password should be generated for.

Type: `string`

❖ Example

"alice"

Declared in: [clanServices/users/default.nix](#)

← Previous
tor

Next →
wifi

Need help? Reach out to [our community](#).