

On This Page >



vars

Attribute: `clan.core.vars`

Generated Variables

Define generators that prompt for or generate variables and secrets to store, deploy, and rotate them easily. For example, generators can be used to:

- prompt the user for input, like passwords or host names
- generate secrets like private keys automatically when they are needed
- output multiple values like private and public keys simultaneously

Type: `submodule`

Declared in: [nixosModules/clanCore/vars/secret/password-store.nix](#)

generators

Attribute: `clan.core.vars.generators`

A set of generators that can be used to generate files. Generators are scripts that produce files based on the values of other generators and user input. Each generator is expected to produce a set of files under a directory.

Type: `attribute set of (submodule)`**Default:**

```
{ }
```

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

dependencies

Attribute: `clan.core.vars.generators.<name>.dependencies`

A list of other generators that this generator depends on. The output values of these generators will be available to the generator script as files.

For example:

A file `file1` of a generator named `dep1` will be available via `$in/dep1/file1`

Type: `list of string`

Default:

[]

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

files

Attribute: `clan.core.vars.generators.<name>.files`

A set of files to generate. The generator 'script' is expected to produce exactly these files under \$out.

Type: `attribute set of (submodule)`

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

deploy

Attribute: `clan.core.vars.generators.<name>.files.<name>.deploy`

Whether the file should be deployed to the target machine.

Disable this if the generated file is only used as an input to other generators.

Type: `boolean`

Default:

true

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

exists

Attribute: `clang.core.vars.generators.<name>.files.<name>.exists`

Returns true if the file exists. This is used to guard against reading not set value in evaluation. This currently only works for non secret files.

Type: `boolean`

Default:

"Throws error because the existence of a secret file cannot be determined"



Declared in: [modules/clang/vars/settings-opts.nix](#)

flakePath

Attribute: `clang.core.vars.generators.<name>.files.<name>.flakePath`

The path to the file containing the content of the generated value. This will be set automatically

Type: `null or absolute path`

Default:

null

Declared in: [modules/clang/vars/settings-opts.nix](#)

generatorName

Attribute: `clan.core.vars.generators.<name>.files.<name>.generatorName`

name of the generator

Type: `string`

Default:

"Name of the generator that generates this file"

Declared in: [modules/clang/vars/settings-opts.nix](#)

group

Attribute: `clan.core.vars.generators.<name>.files.<name>.group`

The group name or id that will own the file.

Type: `string`

Default:

`if pkgs.stdenv.hostPlatform.isDarwin then "wheel" else "root"`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

mode

Attribute: `clan.core.vars.generators.<name>.files.<name>.mode`

The unix file mode of the file. Must be a 4-digit octal number.

Type: `string matching the pattern ^[0-7]{4}$`

Default:

"0400"

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

name

Attribute: `clan.core.vars.generators.<name>.files.<name>.name`

Readonly

name of the public fact

Type: `string`

Default:

"Name of the file"

Declared in: [modules/clan/vars/settings-opts.nix](#)

neededFor

Attribute: `clan.core.vars.generators.<name>.files.<name>.neededFor`

This option determines when the secret will be decrypted and deployed to the target machine.

By setting this to `partitioning`, the secret will be deployed prior to running `disko` allowing you to manage filesystem encryption keys. These will only be deployed when installing the system. By setting this to `activation`, the secret will be deployed prior to running `nixos-rebuild` or `nixos-install`. By setting this to `user`, the secret will be deployed prior to users and groups are created, allowing users' passwords to be managed by vars. The secret will be stored in `/run/secrets-for-users` and `owner` and `group` must be `root`.

Type: `one of "partitioning", "activation", "users", "services"`

Default:

"services"

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

owner

Attribute: `clan.core.vars.generators.<name>.files.<name>.owner`

The user name or id that will own the file.

Type: `string`

Default:

`"root"`

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

path

Attribute: `clan.core.vars.generators.<name>.files.<name>.path`

The path to the file containing the content of the generated value. This will be set automatically

Type: `string`

Default:

```
1 ''
2   builtins.path {
3     name = "$'`${file.config.generatorName}_$'`${file.config.name}";
4     path = file.config.flakePath;
5   }
6 ''
```

Declared in: [modules/clan/vars/settings-opts.nix](#)

restartUnits

Attribute: `clan.core.vars.generators.<name>.files.<name>.restartUnits`

A list of systemd units that should be restarted after the file is deployed. This is useful for services that need to reload their configuration after the file is updated.

WARNING: currently only sops-nix implements this option.

NOTE: This option is not supported on Darwin systems.

Type: `list of string`

Default:

`[ ]`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

secret

Attribute: `clangCore.vars.generators.<name>.files.<name>.secret`

Whether the file should be treated as a secret.

Type: `boolean`

Default:

`true`

Declared in: [modules/clang/vars/settings-opts.nix](#)

value

Attribute: `clangCore.vars.generators.<name>.files.<name>.value`

The content of the generated value. Only available if the file is not secret.

Type: `string`

Default:

`"Throws error because the value of a secret file is not accessible"`

Declared in: [modules/clang/vars/settings-opts.nix](#)

name

Attribute: `clan.core.vars.generators.<name>.name`

Readonly

The name of the generator. This name will be used to refer to the generator in other generators.

Type: `string`

Default:

"Name of the generator"

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

prompts

Attribute: `clan.core.vars.generators.<name>.prompts`

A set of prompts to ask the user for values. Prompts are available to the generator script as files. For example, a prompt named 'prompt1' will be available via \$prompts/prompt1

Type: `attribute set of (submodule)`

Default:

`{ }`

Declared in: [nixosModules/clanCore/vars/interface.nix](#)

description

Attribute: `clan.core.vars.generators.<name>.prompts.<name>.description`

The description of the prompted value

Type: `string`

Default:

"Name of the prompt"

❖ Example

"SSH private key"

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

display

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.display`

group

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.display.group`

The group to display the prompt in. This is useful to group prompts together.

Type: `null or string`

Default:

`null`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

helperText

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.display.helperText`

Additional text to display next to the prompt. This can be used to provide additional information about the prompt.

Type: `null or string`

Default:

`null`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

label

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.display.label`

The label to display for the prompt. If not set, the name of the prompt will be used.

Type: `null or string`

Default:

`null`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

required

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.display.required`

Whether the prompt is required. If set to false, the user will be able to continue without providing a value.

Type: `boolean`

Default:

`true`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

name

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.name`

The name of the prompt. This name will be used to refer to the prompt in the generator script.

Type: `string`

Default:

`"Name of the prompt"`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

persist

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.persist`

Whether the prompted value should be stored in a file with the same name as the prompt.

If enabled, the behavior is equivalent to the following configuration:

```
1 {  
2   files.<name>.secret = true;  
3   script = "cp $prompts/<name> $out/<name>";  
4 }
```

Type: `boolean`

Default:

`false`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

type

Attribute: `clang.core.vars.generators.<name>.prompts.<name>.type`

The input type of the prompt. The following types are available:

- `hidden`: A hidden text (e.g. password)
- `line`: A single line of text
- `multiline`: A multiline text
- `multiline-hidden`: A multiline text

Type: one of "hidden", "line", "multiline", "multiline-hidden"

Default:

"line"

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

runtimeInputs

Attribute: clangCore.vars.generators.<name>.runtimeInputs

A list of packages that the generator script requires. These packages will be available in the PATH when the script is run.

Type: list of package

Default:

[]

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

script

Attribute: clangCore.vars.generators.<name>.script

The script to run to generate the files. The script will be run with the following environment variables:

- \$in: The directory containing the output values of all declared dependencies
- \$out: The output directory to put the generated files
- \$prompts: The directory containing the prompted values as files

The script should produce the files specified in the 'files' attribute under \$out.

Type: string or absolute path

Default:

||

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

share

Attribute: `clang.core.vars.generators.<name>.share`

Whether the generated vars should be shared between machines. Shared vars are only generated once, when the first machine using it is deployed. Subsequent machines will re-use the already generated values.

Type: `boolean`

Default:

`false`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

validation

Attribute: `clang.core.vars.generators.<name>.validation`

A set of values that invalidate the generated values. If any of these values change, the generated values will be re-generated. Lists are not allowed as of now due to potential ordering issues

Type: `null or boolean or signed integer or string or attribute set of (boolean or signed integer or string or attribute set of (boolean or signed integer or string))`

Default:

`null`

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

globalSettings

Attribute: `clan.core.vars.globalSettings`

fileModule

Attribute: `clan.core.vars.globalSettings.fileModule`

exists

Attribute: `clan.core.vars.globalSettings.fileModule.exists`

Returns true if the file exists. This is used to guard against reading not set value in evaluation. This currently only works for non secret files.

Type: `boolean`

Default:

"Throws error because the existence of a secret file cannot be determined"

Declared in: [modules/clan/vars/settings-opts.nix](#)

flakePath

Attribute: `clan.core.vars.globalSettings.fileModule.flakePath`

The path to the file containing the content of the generated value. This will be set automatically

Type: `null or absolute path`

Default:

`null`

Declared in: [modules/clan/vars/settings-opts.nix](#)

generatorName

Attribute: `clan.core.vars.globalSettings.fileModule.generatorName`

name of the generator

Type: `string`

Default:

"Name of the generator that generates this file"

Declared in: [modules/clan/vars/settings-opts.nix](#)

name

Attribute: `clan.core.vars.globalSettings.fileModule.name`

Readonly

name of the public fact

Type: `string`

Default:

"Name of the file"

Declared in: [modules/clan/vars/settings-opts.nix](#)

path

Attribute: `clan.core.vars.globalSettings.fileModule.path`

The path to the file containing the content of the generated value. This will be set automatically

Type: `string`

Default:

```
1 ''  
2   builtins.path {  
3     name = "$'`${file.config.generatorName}_$'`${file.config.name}";  
4     path = file.config.flakePath;  
5   }  
6 ''
```

Declared in: [modules/clang/vars/settings-opts.nix](#)

secret

Attribute: `clang.core.vars.globalSettings.fileModule.secret`

Whether the file should be treated as a secret.

Type: `boolean`

Default:

`true`

Declared in: [modules/clang/vars/settings-opts.nix](#)

value

Attribute: `clang.core.vars.globalSettings.fileModule.value`

The content of the generated value. Only available if the file is not secret.

Type: `string`

Default:

`"Throws error because the value of a secret file is not accessible"`

Declared in: [modules/clang/vars/settings-opts.nix](#)

publicStore

Attribute: `clan.core.vars.globalSettings.publicStore`

Method to store public vars. Currently only 'in_repo' is supported, which stores public vars in the clan repository.

Type: `value "in_repo" (singular enum)`

Default:

`"in_repo"`

Declared in: [modules/clan/vars/settings-opts.nix](#)

secretStore

Attribute: `clan.core.vars.globalSettings.secretStore`

method to store secret vars. custom can be used to define a custom secret var store.

Type: `one of "sops", "password-store", "vm", "fs", "custom"`

Default:

`"sops"`

Declared in: [modules/clan/vars/settings-opts.nix](#)

password-store

Attribute: `clan.core.vars.password-store`

passCommand

Attribute: `clan.core.vars.password-store.passCommand`

Password store command to use, must be available in PATH. E.g.

- "pass": GPG-based password store
- "passage": age-based password store

Type: one of "pass", "passage"

Default:

"passage"

Declared in: [nixosModules/clangCore/vars/secret/password-store.nix](#)

secretLocation

Attribute: clan.core.vars.password-store.secretLocation

location where the tarball with the password-store secrets will be uploaded to and the manifest

Type: absolute path

Default:

"/etc/secret-vars"

Declared in: [nixosModules/clangCore/vars/secret/password-store.nix](#)

settings

Attribute: clan.core.vars.settings

Settings for the vars module.

Type: submodule

Default:

{ }

Declared in: [nixosModules/clangCore/vars/interface.nix](#)

fileModule

Attribute: `clan.core.vars.settings.fileModule`

exists

Attribute: `clan.core.vars.settings.fileModule.exists`

Returns true if the file exists. This is used to guard against reading not set value in evaluation. This currently only works for non secret files.

Type: `boolean`

Default:

"Throws error because the existence of a secret file cannot be determined"

Declared in: [modules/clan/vars/settings-opts.nix](#)

flakePath

Attribute: `clan.core.vars.settings.fileModule.flakePath`

The path to the file containing the content of the generated value. This will be set automatically

Type: `null or absolute path`

Default:

`null`

Declared in: [modules/clan/vars/settings-opts.nix](#)

generatorName

Attribute: `clan.core.vars.settings.fileModule.generatorName`

name of the generator

Type: string

Default:

"Name of the generator that generates this file"

Declared in: [modules/clang/vars/settings-opts.nix](#)

name

Attribute: clan.core.vars.settings.fileModule.name

Readonly

name of the public fact

Type: string

Default:

"Name of the file"

Declared in: [modules/clang/vars/settings-opts.nix](#)

path

Attribute: clan.core.vars.settings.fileModule.path

The path to the file containing the content of the generated value. This will be set automatically

Type: string

Default:

```
1 ''
2   builtins.path {
3     name = "${file.config.generatorName}_${file.config.name}";
4     path = file.config.flakePath;
5   }
```

6 ' '

Declared in: [modules/clang/vars/settings-opts.nix](#)

secret

Attribute: `clang.core.vars.settings.fileModule.secret`

Whether the file should be treated as a secret.

Type: `boolean`

Default:

`true`

Declared in: [modules/clang/vars/settings-opts.nix](#)

value

Attribute: `clang.core.vars.settings.fileModule.value`

The content of the generated value. Only available if the file is not secret.

Type: `string`

Default:

`"Throws error because the value of a secret file is not accessible"`

Declared in: [modules/clang/vars/settings-opts.nix](#)

publicStore

Attribute: `clang.core.vars.settings.publicStore`

Method to store public vars. Currently only 'in_repo' is supported, which stores public vars in the clang repository.

Type: value "in_repo" (singular enum)

Default:

"in_repo"

Declared in: [modules/clan/vars/settings-opts.nix](#)

secretStore

Attribute: clan.core.vars.settings.secretStore

method to store secret vars. custom can be used to define a custom secret var store.

Type: one of "sops", "password-store", "vm", "fs", "custom"

Default:

"sops"

Declared in: [modules/clan/vars/settings-opts.nix](#)

sops

Attribute: clan.core.vars.sops

secretUploadDirectory

Attribute: clan.core.vars.sops.secretUploadDirectory

The directory where sops-related files are uploaded to on the target machine. This includes the age private key used for decryption and activation secrets.

Type: absolute path

Default:

`"/var/lib/sops-nix"`

Declared in: [nixosModules/clangCore/vars/secret/sops](#)

← Previous
state

Next →
CLI Overview

Need help? Reach out to [our community](#).