



You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Interface & Plugins

Customize and secure your desktop experience with these commands.

Security & Privacy

Function	Command	Description
Lock Screen	<code>lockScreen lock</code> 	Lock your screen
Idle Inhibit	<code>idleInhibitor toggle</code> 	Toggle idle inhibitor
Enable Inhibit	<code>idleInhibitor enable</code> 	Enable idle inhibitor
Disable Inhibit	<code>idleInhibitor disable</code> 	Disable idle inhibitor
Airplane Mode	<code>airplaneMode toggle</code> 	Toggle airplane mode
Enable Airplane Mode	<code>airplaneMode enable</code> 	Enable airplane mode (disables Wi-Fi & Bluetooth)
Disable Airplane Mode	<code>airplaneMode disable</code> 	Disable airplane mode

Notifications

Function	Command	Description
History	<code>notifications toggleHistory</code> 	View past notifications

Function	Command	Description
----------	---------	-------------

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Do Not Disturb	<code>notifications toggleDND</code> 	Toggle silence mode
Enable DND	<code>notifications enableDND</code> 	Enable silence mode
Disable DND	<code>notifications disableDND</code> 	Disable silence mode
Clear All	<code>notifications clear</code> 	Clear notification history
Remove Oldest	<code>notifications removeOldestHistory</code> 	Remove oldest from history
Remove ID	<code>notifications removeFromHistory \$id</code> 	Remove notification by ID
Dismiss Oldest	<code>notifications dismissOldest</code> 	Dismiss oldest active
Dismiss All	<code>notifications dismissAll</code> 	Dismiss active notifications

Toast Notifications

Function	Command	Description
Send	<code>toast send '\$json'</code> 	Display a toast notification
Dismiss	<code>toast dismiss</code> 	Dismiss active toast notification

The toast send command accepts a JSON object with the following fields:

Field	Type	Required	Description
title	string	Yes	Toast title
body	string	No	Toast body/description
icon	string	No	Icon name (only for notice type)
type	string	No	notice (default), warning, or error

Field	Type	Required	Description
-------	------	----------	-------------

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

error=60000)

Examples:

```
# Simple notice
qs -c noctalia-shell ipc call toast send '{"title": "Recording", "body": "Started (AV1 HDR)", "icon": "media-record"}'

# Warning toast
qs -c noctalia-shell ipc call toast send '{"title": "Low battery", "type": "warning"}'

# Error with custom duration
qs -c noctalia-shell ipc call toast send '{"title": "Connection failed", "body": "Check your network", "type": "error", "duration": 10000}'
```

Appearance

Visibility

Function	Command	Description
Toggle Bar	<code>bar toggle</code>	Toggle bar visibility
Show Bar	<code>bar showBar</code>	Show bar
Hide Bar	<code>bar hideBar</code>	Hide bar
Peek Bar	<code>bar peek</code>	Briefly show bar, then auto-hide
Bar DisplayMode	<code>bar setDisplayMode <mode> <screen></code>	Set bar display mode
Bar Position	<code>bar setPosition <position> <screen></code>	Set bar position

Function	Command	Description
----------	---------	-------------

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Show Widgets	<code>desktopWidgets enable</code> 	Enable desktop widgets
Hide Widgets	<code>desktopWidgets disable</code> 	Disable desktop widgets
Toggle Widgets	<code>desktopWidgets toggle</code> 	Toggle desktop widgets
Edit Widgets	<code>desktopWidgets edit</code> 	Toggle widget editing

Available Bar Display Modes

- `always_visible`
- `non_exclusive`
- `auto_hide`

<screen>: Monitor identifier (e.g., HDMI-A-1), or use an empty string or all to set mode on all monitors.

Available Bar Positions

- `top`
- `bottom`
- `left`
- `right`

<screen>: Monitor identifier (e.g., HDMI-A-1). Use an empty string or all to set position on all monitors.

Theme Controls

Function	Command	Description
Dark Mode	<code>darkMode toggle</code> 	Toggle system theme

Function	Command	Description
----------	---------	-------------

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Set Light	<code>darkMode setLight</code> 	Force light theme
Color Scheme	<code>colorScheme set <theme></code> 	Set scheme by name
Set Method	<code>colorScheme setGenerationMethod <method></code> 	Set color generation method

Available Generation Methods

- tonal-spot
- content
- fruit-salad
- rainbow
- monochrome
- vibrant
- faithful
- dysfunctional
- muted

Wallpaper Management

Function	Command	Description
Selector	<code>wallpaper toggle</code> 	Toggle wallpaper selector
Get Wallpaper	<code>wallpaper get \$monitor</code> 	Get path to wallpaper on monitor
Set Wallpaper	<code>wallpaper set \$path \$monitor</code> 	Set wallpaper on monitor

Function	Command	Description
----------	---------	-------------

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

for all)

Toggle Auto	<code>wallpaper toggleAutomation</code> 	Toggle automation
Enable Auto	<code>wallpaper enableAutomation</code> 	Enable automation
Disable Auto	<code>wallpaper disableAutomation</code> 	Disable automation
Refresh List	<code>wallpaper refresh</code> 	Refresh wallpapers list

Wallpaper variables

- \$path: Full path to your wallpaper image file
- \$monitor: Monitor identifier (e.g., HDMI-A-1). Use an empty string or all to apply to all monitors.

Plugin Controls

Function	Command	Description
Settings	<code>plugin openSettings \$pluginId</code> 	Open plugin settings
Open Panel	<code>plugin openPanel \$pluginId</code> 	Open plugin panel
Close Panel	<code>plugin closePanel \$pluginId</code> 	Close plugin panel
Toggle Panel	<code>plugin togglePanel \$pluginId</code> 	Toggle plugin panel

Plugin ID

Replace \$pluginId with the actual plugin identifier (e.g., todo, pomodoro).

Misc

Function

Command

Description

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Set Location	<code>location set \$name</code> 	Set geographic location
Get Location	<code>location get</code> 	Get geographic location