



You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

NixOS

For NixOS users, a [Nix package](#) for Noctalia is available. You can also get the Git version, NixOS module and Home Manager module via flakes.

Caution

To make Noctalia's wifi, bluetooth, power-profile, and battery feature available, please ensure the following NixOS options are enabled:

- `networking.networkmanager.enable`
- `hardware.bluetooth.enable`
- `services.power-profiles-daemon.enable` or `services.tuned.enable`
- `services.upower.enable`

Nix flakes

To install Noctalia, you need to [add a flake input](#) and [install the package](#).

Note

The Noctalia flake requires **nixpkgs unstable**, since we depend on the latest Quickshell version.

Adding the flake input

Add the required inputs to your flake configuration:

flake.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
inputs = {
  nixpkgs.url = "github:nixos/nixpkgs/nixos-unstable";

  noctalia = {
    url = "github:noctalia-dev/noctalia-shell";
    inputs.nixpkgs.follows = "nixpkgs";
  };
};

outputs = inputs@{ self, nixpkgs, ... }: {
  nixosConfigurations.awesomebox = nixpkgs.lib.nixosSystem {
    specialArgs = { inherit inputs; };
    modules = [
      # ... other modules
      ./noctalia.nix
    ];
  };
};
}
```

With the flake installed, we can access Noctalia packages and modules in our configuration.

Installing the package

If you don't use Noctalia's NixOS or home-manager modules, you need to manually install the default Noctalia package from the new noctalia input:

```
noctalia.nix
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
# install package
environment.systemPackages = with pkgs; [
  inputs.noctalia.packages.${pkgs.stdenv.hostPlatform.system}.default
  # ... maybe other stuff
];
}
```

Rebuild with `sudo nixos-rebuild switch --flake ..`

Binary Cache

Pre-built binaries are available on [Cachix](#), so you can skip compiling locally.

You can add the cache either to your flake, nixos configuration, or `/etc/nix/nix.conf`.

flake.nix configuration.nix nix.conf

```
nixConfig = {
  extra-substituters = [ "https://noctalia.cachix.org" ];
  extra-trusted-public-keys = [ "noctalia.cachix.org-
1:pCOR47nnMEo5thcxNDtzWpOxNFQsBRglJzxWPp3dkU4=" ];
};
```

Config with home-manager

If you have [home manager](#) installed, you can configure your Noctalia shell in Nix.

Noctalia settings

To configure Noctalia settings, you can use the Noctalia home manager module:

noctalia.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
{ pkgs, inputs, ... }:  
{
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
# import the home manager module  
imports = [  
  inputs.noctalia.homeModules.default  
];  
  
# configure options  
programs.noctalia-shell = {  
  enable = true;  
  settings = {  
    # configure noctalia here  
    bar = {  
      density = "compact";  
      position = "right";  
      showCapsule = false;  
      widgets = {  
        left = [  
          {  
            id = "ControlCenter";  
            useDistroLogo = true;  
          }  
          {  
            id = "Network";  
          }  
          {  
            id = "Bluetooth";  
          }  
        ];  
        center = [  
          {  
            hideUnoccupied = false;  
            id = "Workspace";  
            labelMode = "none";  
          }  
        ];  
        right = [  
          {
```

```
alwaysShowPercentage = false;  
id = "Battery";
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
{  
  formatHorizontal = "HH:mm";  
  formatVertical = "HH mm";  
  id = "Clock";  
  useMonospacedFont = true;  
  usePrimaryColor = true;  
}  
];  
};  
};  
colorSchemes.predefinedScheme = "Monochrome";  
general = {  
  avatarImage = "/home/drfoobar/.face";  
  radiusRatio = 0.2;  
};  
location = {  
  monthBeforeDay = true;  
  name = "Marseille, France";  
};  
};  
# this may also be a string or a path to a JSON file.  
};  
};  
}
```

We don't have extensive documentation of Noctalia's configuration options; however, you can see an up-to-date list of [configuration defaults](#).

Additionally, since `~/.config/noctalia/settings.json` is now a read-only symlink, you can get the latest (or GUI-modified) settings via: **Open Settings Panel → General → Copy Settings** or by running `noctalia-shell ipc call state all | jq .settings`, then use them to update your Nix config for a permanent change.

**Tip**

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
nix shell nixpkgs#jq -S . ~/.config/noctalia/settings.json
jq -S . ~/.config/noctalia/settings.json
```

Theme colors

To configure Noctalia settings, you can use the Noctalia home manager module. Be sure to set every Material 3 color, including hover-state values, when overriding the defaults:

noctalia.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
home-manager.users.drfooobar = {
  # import the home manager module
  imports = [
    inputs.noctalia.homeModules.default
  ];

  # configure options
  programs.noctalia-shell = {
    enable = true;
    colors = {
      # you must set ALL of these
      mError = "#ddddd";
      mOnError = "#111111";
      mOnPrimary = "#111111";
      mOnSecondary = "#111111";
      mOnSurface = "#828282";
      mOnSurfaceVariant = "#5d5d5d";
      mOnTertiary = "#111111";
      mOnHover = "#ffffff";
      mOutline = "#3c3c3c";
      mPrimary = "#aaaaaa";
      mSecondary = "#a7a7a7";
      mShadow = "#000000";
      mSurface = "#111111";
      mHover = "#1f1f1f";
      mSurfaceVariant = "#191919";
      mTertiary = "#cccccc";
    };
    # this may also be a string or a path to a JSON file.
  };
};
```

User Templates

The user-templates option allows you to define custom templates. This is useful for theming other applications that are not supported by default.

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

As a string:

noctalia.nix

```
{ pkgs, inputs, ... }:  
{  
  home-manager.users.drfoobar = {  
    # ...  
    programs.noctalia-shell = {  
      enable = true;  
      settings = {  
        templates = {  
          enableUserTemplates = true;  
        };  
      };  
    };  
    user-templates = "  
      [config]  
      # General template settings  
      [templates.myapp]  
      input_path = "~/config/noctalia/templates/myapp.css"  
      output_path = "~/config/myapp/theme.css"  
      post_hook = "myapp --reload-theme"  
    ";  
  };  
};  
}
```

As a path:

noctalia.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
home-manager.users.drfoobar = {  
  # ...  
  programs.noctalia-shell = {  
    enable = true;  
    settings = {  
      templates = {  
        enableUserTemplates = true;  
      };  
    };  
    user-templates = ./path/to/user-templates.toml;  
  };  
};  
}
```

As an attribute set:

noctalia.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
home-manager.users.drfoobar = {  
  # ...  
  programs.noctalia-shell = {  
    enable = true;  
    settings = {  
      templates = {  
        enableUserTemplates = true;  
      };  
    };  
  };  
  user-templates = {  
    config = {  
      # General template settings  
    };  
    templates = {  
      myapp = {  
        input_path = "~/.config/noctalia/templates/myapp.css";  
        output_path = "~/.config/myapp/theme.css";  
        post_hook = "myapp --reload-theme";  
      };  
    };  
  };  
};  
}
```

Plugins

You can configure plugins in a declarative way. If an enabled plugin isn't installed in the plugin directory, Noctalia will automatically install it when starts up.

noctalia.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
{ pkgs, inputs, ... }:  
{
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
# import the home manager module  
imports = [  
  inputs.noctalia.homeModules.default  
];  
  
# configure options  
programs.noctalia-shell = {  
  enable = true;  
  plugins = {  
    sources = [  
      {  
        enabled = true;  
        name = "Official Noctalia Plugins";  
        url = "https://github.com/noctalia-dev/noctalia-plugins";  
      }  
    ];  
  };  
  states = {  
    catwalk = {  
      enabled = true;  
      sourceUrl = "https://github.com/noctalia-dev/noctalia-plugins";  
    };  
  };  
  version = 2;  
};  
  
# this may also be a string or a path to a JSON file.  
  
pluginSettings = {  
  catwalk = {  
    minimumThreshold = 25;  
    hideBackground = true;  
  };  
  # this may also be a string or a path to a JSON file.  
};  
};  
};  
}
```

Wallpapers

Wallpapers are configured in the `noctalia.nix` file in the `noctalia` flake.

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

noctalia.nix

```
{ pkgs, inputs, ... }:  
{  
  home-manager.users.drfoobar = {  
    # ... other config ...  
  
    home.file.".cache/noctalia/wallpapers.json" = {  
      text = builtins.toJSON {  
        defaultWallpaper = "/path/to/default/wallpaper.png";  
        wallpapers = {  
          "DP-1" = "/path/to/monitor/wallpaper.png";  
        };  
      };  
    };  
  };  
};  
};  
}
```

Keybinds

Keybindings are configured in your compositor. You make IPC calls to Noctalia [as explained in the keybinds section](#). The only difference is that you can call `noctalia-shell` instead of `qs -c noctalia-shell`.

To safely configure noctalia keybindings in the Niri flake, be sure to pass a list:

[niri.nix](#)

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
# ...
home-manager.users.drfoobar =
{ config, ... }:
{
  # ...
  programs.niri = {
    settings = {
      # ...
      binds = with config.lib.niri.actions; {
        "Mod+Space".action.spawn = [
          "noctalia-shell" "ipc" "call" "launcher" "toggle" # ✓
        ];
        "Mod+P".action.spawn =
          "noctalia-shell ipc call sessionMenu toggle"; # ✗
      };
    };
  };
};
```

It may be convenient to define a utility function to allow you to use simple strings:

niri.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
let
  noctalia = cmd: [
    "noctalia-shell" "ipc" "call"
  ] ++ (pkgs.lib.splitString " " cmd);
in
{
  # ...
  home-manager.users.drfoobar =
    { config, lib, ... }:
    {
      # ...
      programs = {
        niri = {
          # ...
          settings = {
            binds = with config.lib.niri.actions; {
              # ...
              "Mod+L".action.spawn = noctalia "lockScreen lock";
              "XF86AudioLowerVolume".action.spawn = noctalia "volume decrease";
              "XF86AudioRaiseVolume".action.spawn = noctalia "volume increase";
              "XF86AudioMute".action.spawn = noctalia "volume muteOutput";
            };
            # etc
          };
        };
      };
    };
}
```

Running the shell

⚠ Systemd startup deprecation

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

This approach caused recurring technical issues, including delayed shell startup and unreliable IPC communication.

The old documentation is preserved for existing users [here](#).

Please use the way shown below instead.

To run Noctalia using the flake, run:

```
noctalia-shell
```

With the [Niri flake](#), you can then spawn Noctalia on startup like this:

niri.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
# ...

home-manager.users.drfoobar = {
  # ...
  programs.niri = {
    package = niri;
    settings = {
      # ...
      spawn-at-startup = [
        {
          command = [
            "noctalia-shell"
          ];
        }
      ];
    };
  };
};
```

Calendar events support

To add support for events in the calendar via evolution-data-server.

1. Enable the evolution-data-server:

```
services.gnome.evolution-data-server.enable = true;
```

2. Override the Noctalia package:

```
(pkgs.noctalia-shell.override { calendarSupport = true; })
```

or

```
(inputs.noctalia.packages.${pkgs.stdenv.hostPlatform.system}.default.override {  
  calendarSupport = true; })
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Configuration Defaults

There is no comprehensive documentation of all configuration options, but the default values are autogenerated and placed in a [settings-default.json](#) in the Noctalia shell repository. We retrieve a live Nixified version of these here for your convenience:

noctalia.nix

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
{ pkgs, inputs, ... }:  
{
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
imports = [  
  inputs.noctalia.homeModules.default  
];
```

```
programs.noctalia-shell = {  
  enable = true;  
  settings = {  
    settingsVersion = 0;  
    bar = {  
      barType = "simple";  
      position = "top";  
      monitors = [ ];  
      density = "default";  
      showOutline = false;  
      showCapsule = true;  
      capsuleOpacity = 1;  
      capsuleColorKey = "none";  
      widgetSpacing = 6;  
      contentPadding = 2;  
      fontScale = 1;  
      enableExclusionZoneInset = true;  
      backgroundOpacity = 0.93;  
      useSeparateOpacity = false;  
      marginVertical = 4;  
      marginHorizontal = 4;  
      frameThickness = 8;  
      frameRadius = 12;  
      outerCorners = true;  
      hideOnOverview = false;  
      displayMode = "always_visible";  
      autoHideDelay = 500;  
      autoShowDelay = 150;  
      showOnWorkspaceSwitch = true;  
      widgets = {  
        left = [  
          {
```

```
    id = "Launcher";  
  }  
}
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
  }  
  {  
    id = "SystemMonitor";  
  }  
  {  
    id = "ActiveWindow";  
  }  
  {  
    id = "MediaMini";  
  }  
];  
center = [  
  {  
    id = "Workspace";  
  }  
];  
right = [  
  {  
    id = "Tray";  
  }  
  {  
    id = "NotificationHistory";  
  }  
  {  
    id = "Battery";  
  }  
  {  
    id = "Volume";  
  }  
  {  
    id = "Brightness";  
  }  
  {  
    id = "ControlCenter";  
  }  
];
```

```
};  
mouseWheelAction = "none";
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
middleClickAction = "none";  
middleClickFollowMouse = false;  
middleClickCommand = "";  
rightClickAction = "controlCenter";  
rightClickFollowMouse = true;  
rightClickCommand = "";  
screenOverrides = [ ];  
};  
general = {  
  avatarImage = "";  
  dimmerOpacity = 0.2;  
  showScreenCorners = false;  
  forceBlackScreenCorners = false;  
  scaleRatio = 1;  
  radiusRatio = 1;  
  iRadiusRatio = 1;  
  boxRadiusRatio = 1;  
  screenRadiusRatio = 1;  
  animationSpeed = 1;  
  animationDisabled = false;  
  compactLockScreen = false;  
  lockScreenAnimations = false;  
  lockOnSuspend = true;  
  showSessionButtonsOnLockScreen = true;  
  showHibernateOnLockScreen = false;  
  enableLockScreenMediaControls = false;  
  enableShadows = true;  
  enableBlurBehind = true;  
  shadowDirection = "bottom_right";  
  shadowOffsetX = 2;  
  shadowOffsetY = 3;  
  language = "";  
  allowPanelsOnScreenWithoutBar = true;  
  showChangelogOnStartup = true;  
  telemetryEnabled = false;  
  enableLockScreenCountdown = true;
```

```
lockScreenCountdownDuration = 10000;
```

```
autoStartAuth = false;
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
clockFormat = "hh\nmm";
```

```
passwordChars = false;
```

```
lockScreenMonitors = [ ];
```

```
lockScreenBlur = 0;
```

```
lockScreenTint = 0;
```

```
keybinds = {
```

```
  keyUp = [
```

```
    "Up"
```

```
  ];
```

```
  keyDown = [
```

```
    "Down"
```

```
  ];
```

```
  keyLeft = [
```

```
    "Left"
```

```
  ];
```

```
  keyRight = [
```

```
    "Right"
```

```
  ];
```

```
  keyEnter = [
```

```
    "Return"
```

```
    "Enter"
```

```
  ];
```

```
  keyEscape = [
```

```
    "Esc"
```

```
  ];
```

```
  keyRemove = [
```

```
    "Del"
```

```
  ];
```

```
};
```

```
reverseScroll = false;
```

```
smoothScrollEnabled = true;
```

```
};
```

```
ui = {
```

```
  fontDefault = "";
```

```
  fontFixed = "";
```

```
  fontDefaultScale = 1;
```



```
fontFixedScale = 1;  
tooltipsEnabled = true;
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
panelBackgroundOpacity = 0.93;  
translucentWidgets = false;  
panelsAttachedToBar = true;  
settingsPanelMode = "attached";  
settingsPanelSideBarCardStyle = false;  
};  
location = {  
  name = "";  
  weatherEnabled = true;  
  weatherShowEffects = true;  
  weatherTaliaMascotAlways = false;  
  useFahrenheit = false;  
  use12hourFormat = false;  
  showWeekNumberInCalendar = false;  
  showCalendarEvents = true;  
  showCalendarWeather = true;  
  analogClockInCalendar = false;  
  firstDayOfWeek = -1;  
  hideWeatherTimezone = false;  
  hideWeatherCityName = false;  
  autoLocate = true;  
};  
calendar = {  
  cards = [  
    {  
      enabled = true;  
      id = "calendar-header-card";  
    }  
    {  
      enabled = true;  
      id = "calendar-month-card";  
    }  
    {  
      enabled = true;  
      id = "weather-card";  
    }  
  ]  
};
```

```
];  
};
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
overviewEnabled = false;  
directory = "";  
monitorDirectories = [ ];  
enableMultiMonitorDirectories = false;  
showHiddenFiles = false;  
viewMode = "single";  
setWallpaperOnAllMonitors = true;  
linkLightAndDarkWallpapers = true;  
fillMode = "crop";  
fillColor = "#000000";  
useSolidColor = false;  
solidColor = "#1a1a2e";  
automationEnabled = false;  
wallpaperChangeMode = "random";  
randomIntervalSec = 300;  
transitionDuration = 1500;  
transitionType = [  
    "fade"  
    "disc"  
    "stripes"  
    "wipe"  
    "pixelate"  
    "honeycomb"  
];  
skipStartupTransition = false;  
transitionEdgeSmoothness = 0.05;  
panelPosition = "follow_bar";  
hideWallpaperFilenames = false;  
useOriginalImages = false;  
overviewBlur = 0.4;  
overviewTint = 0.6;  
useWallhaven = false;  
wallhavenQuery = "";  
wallhavenSorting = "relevance";  
wallhavenOrder = "desc";  
wallhavenCategories = "111";
```

```
wallhavenPurity = "100";
```

```
wallhavenRatios = "";
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
wallhavenResolutionWidth = "";
```

```
wallhavenResolutionHeight = "";
```

```
sortOrder = "name";
```

```
favorites = [ ];
```

```
};
```

```
appLauncher = {
```

```
  enableClipboardHistory = false;
```

```
  autoPasteClipboard = false;
```

```
  enableClipPreview = true;
```

```
  clipboardWrapText = true;
```

```
  enableClipboardSmartIcons = true;
```

```
  enableClipboardChips = true;
```

```
  clipboardWatchTextCommand = "wl-paste --type text --watch cliphist store";
```

```
  clipboardWatchImageCommand = "wl-paste --type image --watch cliphist store";
```

```
  position = "center";
```

```
  pinnedApps = [ ];
```

```
  sortByMostUsed = true;
```

```
  terminalCommand = "alacritty -e";
```

```
  customLaunchPrefixEnabled = false;
```

```
  customLaunchPrefix = "";
```

```
  viewMode = "list";
```

```
  showCategories = true;
```

```
  iconMode = "tabler";
```

```
  showIconBackground = false;
```

```
  enableSettingsSearch = true;
```

```
  enableWindowsSearch = true;
```

```
  enableSessionSearch = true;
```

```
  ignoreMouseInput = false;
```

```
  screenshotAnnotationTool = "";
```

```
  overviewLayer = false;
```

```
  density = "default";
```

```
};
```

```
controlCenter = {
```

```
  position = "close_to_bar_button";
```

```
  diskPath = "/";
```

```
  shortcuts = {
```

```
left = [
```

```
{
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
{
```

```
  id = "Bluetooth";
```

```
}
```

```
{
```

```
  id = "WallpaperSelector";
```

```
}
```

```
{
```

```
  id = "NoctaliaPerformance";
```

```
}
```

```
];
```

```
right = [
```

```
{
```

```
  id = "Notifications";
```

```
}
```

```
{
```

```
  id = "PowerProfile";
```

```
}
```

```
{
```

```
  id = "KeepAwake";
```

```
}
```

```
{
```

```
  id = "NightLight";
```

```
}
```

```
];
```

```
};
```

```
cards = [
```

```
{
```

```
  enabled = true;
```

```
  id = "profile-card";
```

```
}
```

```
{
```

```
  enabled = true;
```

```
  id = "shortcuts-card";
```

```
}
```

```
{
```

```
  enabled = true;
```

```
    id = "audio-card";  
  }  
}
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
    id = "brightness-card";  
  }  
  {  
    enabled = true;  
    id = "weather-card";  
  }  
  {  
    enabled = true;  
    id = "media-sysmon-card";  
  }  
];  
};
```

```
systemMonitor = {  
  cpuWarningThreshold = 80;  
  cpuCriticalThreshold = 90;  
  tempWarningThreshold = 80;  
  tempCriticalThreshold = 90;  
  gpuWarningThreshold = 80;  
  gpuCriticalThreshold = 90;  
  memWarningThreshold = 80;  
  memCriticalThreshold = 90;  
  swapWarningThreshold = 80;  
  swapCriticalThreshold = 90;  
  diskWarningThreshold = 80;  
  diskCriticalThreshold = 90;  
  diskAvailWarningThreshold = 20;  
  diskAvailCriticalThreshold = 10;  
  batteryWarningThreshold = 20;  
  batteryCriticalThreshold = 5;  
  enableDgpuMonitoring = false;  
  useCustomColors = false;  
  warningColor = "";  
  criticalColor = "";  
  externalMonitor = "resources || missioncenter || jdsystemmonitor || corestats || system-  
monitoring-center || gnome-system-monitor || plasma-systemmonitor || mate-system-monitor || ukui-  
system-monitor || deepin-system-monitor || pantheon-system-monitor";
```

```
};  
noctaliaPerformance = {
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
};  
dock = {  
  enabled = true;  
  position = "bottom";  
  displayMode = "auto_hide";  
  dockType = "floating";  
  backgroundOpacity = 1;  
  floatingRatio = 1;  
  size = 1;  
  onlySameOutput = true;  
  monitors = [ ];  
  pinnedApps = [ ];  
  colorizeIcons = false;  
  showLauncherIcon = false;  
  launcherPosition = "end";  
  launcherUseDistroLogo = false;  
  launcherIcon = "";  
  launcherIconColor = "none";  
  pinnedStatic = false;  
  inactiveIndicators = false;  
  groupApps = false;  
  groupContextMenuMode = "extended";  
  groupClickAction = "cycle";  
  groupIndicatorStyle = "dots";  
  deadOpacity = 0.6;  
  animationSpeed = 1;  
  sitOnFrame = false;  
  showDockIndicator = false;  
  indicatorThickness = 3;  
  indicatorColor = "primary";  
  indicatorOpacity = 0.6;  
};  
network = {  
  bluetoothRssiPollingEnabled = false;  
  bluetoothRssiPollIntervalMs = 60000;  
  networkPanelView = "wifi";
```

```
wifiDetailsViewMode = "grid";  
bluetoothDetailsViewMode = "grid";
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
bluetoothAutoConnect = true;  
};  
sessionMenu = {  
  enableCountdown = true;  
  countdownDuration = 10000;  
  position = "center";  
  showHeader = true;  
  showKeybinds = true;  
  largeButtonsStyle = true;  
  largeButtonsLayout = "single-row";  
  powerOptions = [  
    {  
      action = "lock";  
      enabled = true;  
      keybind = "1";  
    }  
    {  
      action = "suspend";  
      enabled = true;  
      keybind = "2";  
    }  
    {  
      action = "hibernate";  
      enabled = true;  
      keybind = "3";  
    }  
    {  
      action = "reboot";  
      enabled = true;  
      keybind = "4";  
    }  
    {  
      action = "logout";  
      enabled = true;  
      keybind = "5";  
    }  
  ]  
};
```

```
{  
  action = "shutdown";  
}
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
}  
{  
  action = "rebootToUefi";  
  enabled = true;  
  keybind = "7";  
}  
];  
};  
notifications = {  
  enabled = true;  
  enableMarkdown = false;  
  density = "default";  
  monitors = [ ];  
  location = "top_right";  
  overlayLayer = true;  
  backgroundOpacity = 1;  
  respectExpireTimeout = false;  
  lowUrgencyDuration = 3;  
  normalUrgencyDuration = 8;  
  criticalUrgencyDuration = 15;  
  clearDismissed = true;  
  saveToHistory = {  
    low = true;  
    normal = true;  
    critical = true;  
  };  
sounds = {  
  enabled = false;  
  volume = 0.5;  
  separateSounds = false;  
  criticalSoundFile = "";  
  normalSoundFile = "";  
  lowSoundFile = "";  
  excludedApps = "discord,firefox,chrome,chromium,edge";  
};  
enableMediaToast = false;
```



```
enableKeyboardLayoutToast = true;  
enableBatteryToast = true;
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
enabled = true;  
location = "top_right";  
autoHideMs = 2000;  
overlayLayer = true;  
backgroundOpacity = 1;  
enabledTypes = [  
  0  
  1  
  2  
];  
monitors = [ ];  
};  
audio = {  
  volumeStep = 5;  
  volumeOverdrive = false;  
  spectrumFrameRate = 30;  
  visualizerType = "linear";  
  spectrumMirrored = true;  
  mprisBlacklist = [ ];  
  preferredPlayer = "";  
  volumeFeedback = false;  
  volumeFeedbackSoundFile = "";  
};  
brightness = {  
  brightnessStep = 5;  
  enforceMinimum = true;  
  enableDdcSupport = false;  
  backlightDeviceMappings = [ ];  
};  
colorSchemes = {  
  useWallpaperColors = false;  
  predefinedScheme = "Noctalia (default)";  
  darkMode = true;  
  schedulingMode = "off";  
  manualSunrise = "06:30";  
  manualSunset = "18:30";
```

```
generationMethod = "tonal-spot";  
monitorForColors = "";
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
templates = {  
  activeTemplates = [ ];  
  enableUserTheming = false;  
};  
nightLight = {  
  enabled = false;  
  forced = false;  
  autoSchedule = true;  
  nightTemp = "4000";  
  dayTemp = "6500";  
  manualSunrise = "06:30";  
  manualSunset = "18:30";  
};  
hooks = {  
  enabled = false;  
  wallpaperChange = "";  
  darkModeChange = "";  
  screenLock = "";  
  screenUnlock = "";  
  performanceModeEnabled = "";  
  performanceModeDisabled = "";  
  startup = "";  
  session = "";  
  colorGeneration = "";  
};  
plugins = {  
  autoUpdate = false;  
  notifyUpdates = true;  
};  
idle = {  
  enabled = false;  
  screenOffTimeout = 600;  
  lockTimeout = 660;  
  suspendTimeout = 1800;  
  fadeDuration = 5;  
  screenOffCommand = "";
```

```
lockCommand = "";  
suspendCommand = "";
```

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

```
resumeSuspendCommand = "";  
customCommands = "[]";  
};  
desktopWidgets = {  
  enabled = false;  
  overviewEnabled = true;  
  gridSnap = false;  
  gridSnapScale = false;  
  monitorWidgets = [ ];  
};  
};  
};  
};  
}
```