

On This Page &gt;

# Advanced Example

This guide explains how to set up a [Hetzner Storage Box](#) as a backup destination instead of using an internal Clan backup server. Follow the steps below to configure and verify the setup.

## Step 1: Create a Hetzner Storage Box

Begin by [creating a Hetzner Storage Box account](#).

## Step 2: Create a Sub-Account

Set up a sub-account for your `jon` machine. Save the SSH password for this account in your password manager for future reference.

## Step 3: Configure BorgBackup in `clan.nix`

Add the BorgBackup service to your `clan.nix` configuration. In this example, the `jon` machine will back up to `user-sub1@user-sub1.your-storagebox.de` in the `borgbackup` folder:

```
1 inventory.instances = {
2   borgbackup = {
3     module = {
4       name = "borgbackup";
5       input = "clan-core";
6     };
7     roles.client.machines."jon".settings = {
8       destinations."storagebox" = {
9         repo = "user-sub1@user-sub1.your-storagebox.de:./borgbackup";
```

```
10     rsh = ''ssh -p 23 -oStrictHostKeyChecking=accept-new -i /run/secrets/  
11         };  
12     };  
13 };  
14 };
```

## Step 4: Generate SSH Keys

Run the following command to generate the SSH private keys:

```
clan vars generate
```

## Step 5: Add the Public Key to the Sub-Account

Add the generated SSH public key to the `user-sub1` account by running:

```
clan vars get jon borgbackup/borgbackup.ssh.pub | ssh -p23 user-sub1@user-s
```



## Step 6: Deploy the Configuration

Apply the changes to your Clan setup by executing:

```
clan machines update
```

## Step 7: Verify the Setup

Check if the configuration works by starting the BorgBackup service on the `jon` machine:

```
systemctl start borgbackup-job-storagebox.service &
```

Then, inspect the service logs to ensure everything is functioning correctly:

```
journalctl -u borgbackup-job-storagebox.service
```

← Previous  
Digging Deeper

Next →  
Connecting to Your Machines

Need help? Reach out to [our community](#).