

On This Page &gt;

# syncthing

*Syncthing is a continuous file synchronization program with automatic peer discovery*

Utility

System

Network

This service configures Syncthing to continuously synchronize a folder peer-to-peer across your machines.

Example configuration:

```
1 {
2   instances.syncthing = {
3     roles.peer.tags.all = { };
4     roles.peer.settings.folders = {
5       documents = {
6         path = "/home/youruser/syncthing/documents";
7       };
8     };
9   };
10 }
```

Notes:

- Each key under `folders` is a folder ID (an arbitrary identifier for Syncthing).
- Prefer absolute paths (example shown). `~` may work in some environments but can be ambiguous in service contexts.

## Documentation

See the official Syncthing docs: <https://docs.syncthing.net/>

# Roles

The syncthing service has the following roles:

- peer

## Options for the `peer` role

### extraDevices

External syncthing devices not managed by clan (e.g., mobile phones)

Type: `attribute set of (submodule)`

Default:

```
{ }
```

#### Example

```
1 {  
2   phone = {  
3     id = "P56I0I7-MZJNU2Y-IQGDREY-DM2MGTI-MGL3BXN-PQ6W5BM-TBBZ4TJ-XZW"  
4     name = "My Phone";  
5     addresses = [ "dynamic" ];  
6   };  
7 }  
8
```

Declared in: [clanServices/syncthing/default.nix](#)

### extraDevices.<name>.addresses

List of addresses for the device

Type: `list of string`

Default:

```
[  
  "dynamic"  
]
```

#### Example

```
1 [  
2   "dynamic"  
3   "tcp://192.168.1.100:22000"  
4 ]
```

Declared in: [clanServices/syncthing/default.nix](#)

## extraDevices.<name>.id

Device ID of the external syncthing device

Type: `string`

#### Example

```
"P56I0I7-MZJNU2Y-IQGDREY-DM2MGTI-MGL3BXN-PQ6W5BM-TBBZ4TJ-XZWICQ2"
```

Declared in: [clanServices/syncthing/default.nix](#)

## extraDevices.<name>.name

Human readable name for the device

Type: `string`

Default:



Declared in: [clanServices/syncthing/default.nix](#)

## folders

Folders to synchronize between all peers

**Type:** attribute set of (submodule)

**Default:**

{ }

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.devices

List of device names to share this folder with. Empty list means all peers and extraDevices.

**Type:** list of string

**Default:**

[ ]

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.ignorePerms

Ignore permission changes

**Type:** boolean

**Default:**

false

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.path

Path to the folder to sync

Type: `string`

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.rescanIntervalS

Rescan interval in seconds

Type: `signed integer`

Default:

3600

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.type

Folder type

Type: `one of "sendreceive", "sendonly", "receiveonly"`

Default:

"sendreceive"

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.versioning

Versioning configuration

**Type:** null or (submodule)

**Default:**

`null`

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.versioning.params

Versioning parameters

**Type:** attribute set of string

**Default:**

`{ }`

Declared in: [clanServices/syncthing/default.nix](#)

## folders.<name>.versioning.type

Versioning type

**Type:** one of "external", "simple", "staggered", "trashcan"

Declared in: [clanServices/syncthing/default.nix](#)

## openDefaultPorts

Whether to open the default syncthing ports in the firewall.

**Type:** boolean

**Default:**

`true`

Declared in: [clanServices/syncthing/default.nix](#)

← Previous  
sshd

Next →  
trusted-nix-caches

Need help? Reach out to [our community](#).