

On This Page >

# postgresql

Attribute: `clan.core.postgresql`

## databases

Attribute: `clan.core.postgresql.databases`

Databases to create

Type: `attribute set of (submodule)`

Default:

`{ }`

Declared in: [nixosModules/clanCore/postgresql](#)

## create

Attribute: `clan.core.postgresql.databases.<name>.create`

## enable

Attribute: `clan.core.postgresql.databases.<name>.create.enable`

Create the database if it does not exist.

**Type:** `boolean`

**Default:**

`true`

Declared in: [nixosModules/clangCore/postgresql](#)

## options

**Attribute:** `clang.core.postgresql.databases.<name>.create.options`

Options to pass to the CREATE DATABASE command.

**Type:** `lazy attribute set of string`

**Default:**

`{ }`

### Example

```
1 {  
2   ENCODING = "UTF8";  
3   LC_COLLATE = "C";  
4   LC_CTYPE = "C";  
5   OWNER = "foo";  
6   TEMPLATE = "template0";  
7 }
```

Declared in: [nixosModules/clangCore/postgresql](#)

## name

**Attribute:** `clang.core.postgresql.databases.<name>.name`

Database name.

**Type:** `string`

**Default:**

`" <name> "`

Declared in: [nixosModules/clangCore/postgresql](#)

## restore

**Attribute:** `clang.core.postgresql.databases.<name>.restore`

## stopOnRestore

**Attribute:** `clang.core.postgresql.databases.<name>.restore.stopOnRestore`

List of systemd services to stop before restoring the database.

**Type:** `list of string`

**Default:**

`[ ]`

Declared in: [nixosModules/clangCore/postgresql](#)

## service

**Attribute:** `clang.core.postgresql.databases.<name>.service`

Service name that we associate with the database.

**Type:** `string`

**Default:**

`" <name> "`

Declared in: [nixosModules/clangCore/postgresql](#)

## enable

---

**Attribute:** `clang.core.postgresql.enable`

Whether to enable PostgreSQL Server.

**Type:** `boolean`

**Default:**

`false`

### Example

`true`

Declared in: [nixosModules/clangCore/postgresql](#)

## users

---

**Attribute:** `clang.core.postgresql.users`

Users to create

**Type:** `attribute set of (submodule)`

**Default:**

`{ }`

Declared in: [nixosModules/clangCore/postgresql](#)

## name

**Attribute:** `clan.core.postgresql.users.<name>.name`

User name

**Type:** `string`

**Default:**

`"<name>"`

Declared in: [nixosModules/clanCore/postgresql](#)

← Previous  
networking

Next →  
settings

Need help? Reach out to [our community](#).