

On This Page >

state

Attribute: `clan.core.state`

Define state directories to backup and restore

Type: `attribute set of (submodule)`

Default:

```
{ }
```

Declared in: [nixosModules/clangCore/state.nix](#)

folders

Attribute: `clan.core.state.<name>.folders`

Folder where state resides in

Type: `list of string`

Declared in: [nixosModules/clangCore/state.nix](#)

name

Attribute: `clan.core.state.<name>.name`

Name of the state

Type: `string matching the pattern ^[a-zA-Z0-9_-]+$`

Default:

`"attribute name of the state"`

Declared in: [nixosModules/clangCore/state.nix](#)

postBackupCommand

Attribute: `clang.core.state.<name>.postBackupCommand`

Readonly

Use this command in backup providers. It contains the content of postBackupScript.

Type: `null or string`

Default:

`null` if postBackupScript set, or else `"post-backup-<name>"`

Declared in: [nixosModules/clangCore/state.nix](#)

postBackupScript

Attribute: `clang.core.state.<name>.postBackupScript`

script to run after backing up the state dir This is for example useful to reverse any actions done in the preBackupScript

Type: `null or strings concatenated with "\n"`

Default:

`null`

Declared in: [nixosModules/clangCore/state.nix](#)

postRestoreCommand

Attribute: `clan.core.state.<name>.postRestoreCommand`

Readonly

This command is called after a restore of the state dir from a backup.

It contains the content of postRestoreScript.

Type: `null or string`

Default:

`null`

Declared in: [nixosModules/clangCore/state.nix](#)

postRestoreScript

Attribute: `clan.core.state.<name>.postRestoreScript`

script to restore the service after the state dir was restored from a backup

Utilize this to start services which were previously stopped

Type: `null or strings concatenated with "\n"`

Default:

`null`

Declared in: [nixosModules/clangCore/state.nix](#)

preBackupCommand

Attribute: `clan.core.state.<name>.preBackupCommand`

Readonly

Use this command in backup providers. It contains the content of preBackupScript.

Type: `null or string`

Default:

`null` if preBackupScript set, or else `"pre-backup- <name>"`

Declared in: [nixosModules/clangCore/state.nix](#)

preBackupScript

Attribute: `clang.core.state.<name>.preBackupScript`

script to run before backing up the state dir This is for example useful for services that require an export of their state e.g. a database dump

Type: `null or strings concatenated with "\n"`

Default:

`null`

Declared in: [nixosModules/clangCore/state.nix](#)

preRestoreCommand

Attribute: `clang.core.state.<name>.preRestoreCommand`

Readonly

This command can be called to restore the state dir from a backup. It contains the content of preRestoreScript.

Type: `null or string`

Default:

`null` if `preRestoreScript` set, or else `"pre-restore-<name>"`

Declared in: [nixosModules/clangCore/state.nix](#)

preRestoreScript

Attribute: `clangCore.state.<name>.preRestoreScript`

script to run before restoring the state dir from a backup

Utilize this to stop services which currently access these folders

Type: `null` or strings concatenated with `"\n"`

Default:

`null`

Declared in: [nixosModules/clangCore/state.nix](#)

← Previous
sops

Next →
vars

Need help? Reach out to [our community](#).