

On This Page >

Secrets

Manage secrets

Usage: `clan secrets`

Commands

- [get](#):
- [groups](#):
- [import-sops](#):
- [key](#):
- [list](#):
- [machines](#):
- [remove](#):
- [rename](#):
- [set](#):
- [users](#):

This subcommand provides an interface to secrets.

Examples

```
$ clan secrets list [regex]
```

Will list secrets for all managed machines. It accepts an optional regex, allowing easy filtering of returned secrets.

```
$ clan secrets get [SECRET]
```

Will display the content of the specified secret.

For more detailed information, visit: [secrets](#)

Secrets get

Usage: `clan secrets get`

Positional Arguments

1. **secret:** `<secret-name>` the name of the secret

Options

[>](#)

Secrets groups

Usage: `clan secrets groups`

Commands

- [add-machine](#):
- [add-secret](#):
- [add-user](#):
- [list](#):
- [remove-machine](#):
- [remove-secret](#):
- [remove-user](#):

Secrets groups add-machine

Usage: `clan secrets groups add-machine`

Positional Arguments

1. **group:** the name of the secret

2. **machine**: the name of the machines to add

Options



Secrets groups add-secret

Usage: `clan secrets groups add-secret`

Positional Arguments

1. **group**: the name of the secret
2. **secret**: the name of the secret

Options



Secrets groups add-user

Usage: `clan secrets groups add-user`

Positional Arguments

1. **group**: the name of the secret
2. **user**: the name of the user to add

Options



Secrets groups list

Usage: `clan secrets groups list`

 Options >

Secrets groups remove-machine

Usage: `clan secrets groups remove-machine`

 Positional Arguments

1. **group**: the name of the secret
2. **machine**: the name of the machines to remove

 Options >

Secrets groups remove-secret

Usage: `clan secrets groups remove-secret`

 Positional Arguments

1. **group**: the name of the secret
2. **secret**: the name of the secret

 Options >

Secrets groups remove-user

Usage: `clan secrets groups remove-user`

 Positional Arguments

1. **group**: the name of the secret
2. **user**: the name of the user to remove

Options



Secrets import-sops

Usage: `clan secrets import-sops`

Positional Arguments

1. **sops_file**: the sops file to import (- for stdin)

Options



Secrets key

Usage: `clan secrets key`

Commands

- [generate](#): Generate an age key for the Clan, if you already have an age or PGP key, then use it to create your user, see: ``clan secrets users add --help``
- [show](#):
- [update](#):

Secrets key generate

Generate an age key for the Clan, if you already have an age or PGP key, then use it to create your user, see: ``clan secrets users add --help``

Usage: `clan secrets key generate`

 [Options](#) 

Secrets key show

Usage: `clan secrets key show`

 [Options](#) 

Secrets key update

Usage: `clan secrets key update`

 [Options](#) 

Secrets list

Usage: `clan secrets list`

 [Positional Arguments](#)

1. **pattern**: a pattern to filter the secrets. All secrets containing the pattern will be listed.

 [Options](#) 

Secrets machines

Usage: `clan secrets machines`

Commands

- [add](#):
- [add-secret](#):
- [get](#):
- [list](#):
- [remove](#):
- [remove-secret](#):

Secrets machines add

Usage: `clan secrets machines add`

Positional Arguments

1. **machine**: the name of the machine
2. **key**: public or private age key of the machine

Options



Secrets machines add-secret

Usage: `clan secrets machines add-secret`

Positional Arguments

1. **machine**: the name of the machine
2. **secret**: the name of the secret

Options



Secrets machines get

Usage: `clan secrets machines get`

Positional Arguments

1. **machine**: the name of the machine

Options

Secrets machines list

Usage: `clan secrets machines list`

Options

Secrets machines remove

Usage: `clan secrets machines remove`

Positional Arguments

1. **machine**: the name of the machine

Options

Secrets machines remove-secret

Usage: `clan secrets machines remove-secret`

Positional Arguments

1. **machine**: the name of the machine
2. **secret**: the name of the secret

Options



Secrets remove

Usage: `clan secrets remove`

Positional Arguments

1. **secret**: `<secret-name>` the name of the secret

Options



Secrets rename

Usage: `clan secrets rename`

Positional Arguments

1. **secret**: `<secret-name>` the name of the secret
2. **new_name**: the new name of the secret

Options



Secrets set

Usage: `clan secrets set`

Positional Arguments

1. **secret:** `<secret-name>` the name of the secret

Options

Secrets users

Usage: `clan secrets users`

Commands

- [add](#):
- [add-key](#):
- [add-secret](#):
- [get](#):
- [list](#):
- [remove](#):
- [remove-key](#):
- [remove-secret](#):

Secrets users add

Usage: `clan secrets users add`

Positional Arguments

1. **user:** the name of the user
2. **agekey:** public or private age key for a user. Execute 'clan secrets key --help' on how to retrieve a key. To fetch an age key from an SSH host key: `ssh-keyscan <domain_name> | nix shell nixpkgs#ssh-to-age -c ssh-to-age`

 Options

Secrets users add-key

Usage: `clan secrets users add-key`

 Positional Arguments

1. **user**: the name of the user
2. **agekey**: public or private age key for a user. Execute 'clan secrets key --help' on how to retrieve a key. To fetch an age key from an SSH host key: `ssh-keyscan <domain_name> | nix shell nixpkgs#ssh-to-age -c ssh-to-age`

 Options

Secrets users add-secret

Usage: `clan secrets users add-secret`

 Positional Arguments

1. **user**: the name of the user
2. **secret**: the name of the secret

 Options

Secrets users get

Usage: `clan secrets users get`

Positional Arguments

1. **user**: the name of the user

Options >

Secrets users list

Usage: `clan secrets users list`

Options >

Secrets users remove

Usage: `clan secrets users remove`

Positional Arguments

1. **user**: the name of the user

Options >

Secrets users remove-key

Usage: `clan secrets users remove-key`

Positional Arguments

1. **user**: the name of the user

2. **agekey**: public or private age key for a user. Execute 'clan secrets key --help' on how to retrieve a key. To fetch an age key from an SSH host key: `ssh-keyscan <domain_name> | nix shell nixpkgs#ssh-to-age -c ssh-to-age`

Options

Secrets users remove-secret

Usage: `clan secrets users remove-secret`

Positional Arguments

1. **user**: the name of the group
2. **secret**: the name of the secret

Options

← Previous
Select

Next →
Show

Need help? Reach out to [our community](#).