



You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Core & Navigation

These are the most common commands used for opening basic shell interfaces.

Core Functions

Function	Command	Description
Launcher	<code>launcher toggle</code>	Open/close application launcher
Control Center	<code>controlCenter toggle</code>	Toggle control center visibility
Settings	<code>settings toggle</code>	Toggle settings (General tab)
Settings Tab	<code>settings toggleTab \$tab</code>	Toggle settings on a specific tab
Open Settings	<code>settings open</code>	Open settings (General tab)
Open Settings Tab	<code>settings openTab \$tab</code>	Open settings on a specific tab

Settings tab parameter

\$tab is a tab name (case-insensitive, hyphens/underscores ignored): general, bar, dock, wallpaper, color-scheme, user-interface, control-center, desktop-widgets, launcher, notifications, osd, lock-screen, session-menu, audio, display, network, location, system-monitor, plugins, hooks, about.

Append /\$subtab to navigate to a specific subtab index, e.g. settings openTab bar/2.

Quick Access

You are viewing the **v4 (stable)** documentation. [Switch to v5 \(alpha\) →](#)

Clipboard	<code>launcher clipboard</code> 	Access clipboard history
Emoji	<code>launcher emoji</code> 	Quick emoji selector access
Command	<code>launcher command</code> 	Quick command runner access
Windows	<code>launcher windows</code> 	Window switcher access
Settings Search	<code>launcher settings</code> 	Settings search access
Calendar	<code>calendar toggle</code> 	Open/close Calendar window
Session	<code>sessionMenu toggle</code> 	Logout, reboot, shutdown...
Lock	<code>lockScreen lock</code> 	Launch the lock screen
Lock & Suspend	<code>sessionMenu lockAndSuspend</code> 	Lock screen and suspend system
System Monitor	<code>systemMonitor toggle</code> 	Open/close system monitor