

[On This Page](#) >

Digging Deeper

In this section we go over how to manage your collection of backups with the clan command.

Listing states

To see which files (`states`) will be backed up on a specific machine, use:

```
clan state list jon
```

This will show all configured states for the machine `jon`, for example:

```
1 • service: linkding
2   folders:
3     - /var/backup/linkding
4   preBackupCommand: pre-backup-linkding
5   postRestoreCommand: post-restore-linkding
6
7 • service: zerotier
8   folders:
9     - /var/lib/zerotier-one
```

Creating backups

To create a backup of a machine (e.g., `jon`), run:

```
clan backups create jon
```

This will backup all configured states (`zerotier` and `linkding` in this example) from the machine `jon`.

Listing available backups

To see all available backups, use:

```
clan backups list
```

This will display all backups with their timestamps:

```
1 storagebox::username@username.your-storagebox.de:./borgbackup::jon-jon-2
2 storagebox::username@username.your-storagebox.de:./borgbackup::jon-jon-2
3 storagebox::username@username.your-storagebox.de:./borgbackup::jon-stora
4 storagebox::username@username.your-storagebox.de:./borgbackup::jon-stora
```



Restoring backups

For restoring a backup you have two options.

Full restoration

To restore all services from a backup:

```
clan backups restore jon borgbackup storagebox::u444061@u444061.your-storagebox.de
```



Partial restoration

To restore only a specific service (e.g., `linkding`):

```
clan backups restore --service linkding jon borgbackup storagebox::u444061@u444061.your-storagebox.de
```



← Previous
Minimal Example

Next →
Advanced Example

Need help? Reach out to [our community](#).