

On This Page >



admin

Adds a root user with ssh access

Utility

The admin service aggregates components that allow an administrator to log in to and manage the machine.

The following configuration:

1. Enables OpenSSH with root login and adds an SSH public key named `myusersKey` to the machine's `authorized_keys` via the `allowedKeys` setting.
2. Automatically generates a password for the root user.

```
1 instances = {  
2     admin = {  
3         roles.default.tags = {  
4             all = { };  
5         };  
6         roles.default.settings = {  
7             allowedKeys = {  
8                 myusersKey = "ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAIEFDNnY  
9             };  
10        };  
11    };  
12 };
```



Roles

The admin service has the following roles:

- default

Options for the `default` role

allowedKeys

The allowed public keys for ssh access to the admin user

Type: `attribute set of string`

Default:

```
{ }
```

Example

```
{  
  key_1 = "ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQD...";  
}
```

Declared in: [clanServices/admin/default.nix](#)

certificateSearchDomains

List of domains to include in the certificate. This option will prepend the machine name in front of each domain before adding it to the certificate.

Type: `list of string`

Default:

```
[ ]
```

 Example

```
[  
  "mydomain.com"  
]
```

Declared in: [clanServices/admin/default.nix](#)

rsaHostKey.enable

Whether to enable Generate RSA host key.

Type:

Default:

false

 Example

true

Declared in: [clanServices/admin/default.nix](#)

← Previous
Definition

Next →
borgbackup

Need help? Reach out to [our community](#).