

Secure Network and Communications Architecture

The essential principles and practices of building resilient, protected network systems that safeguard sensitive data from evolving cyber threats.



Course Overview: Building Fortress Networks

What You'll Master

This comprehensive course equips you with the critical skills to design, implement, and maintain secure network infrastructures. You'll learn to establish robust network boundaries, implement precise traffic control mechanisms, and deploy encryption protocols that protect data throughout its journey across your networks.

These capabilities are foundational for any organisation handling sensitive information, particularly those managing payment card data under PCI DSS compliance requirements.

Core Competencies

- Creating effective network segmentation strategies that isolate sensitive systems
- Implementing firewall rules that block unauthorised access whilst enabling legitimate business functions
- Configuring network security devices with defence-in-depth principles
- Deploying strong encryption for all data transmission scenarios



Part 1: Understanding and Organising Your Network

Before you can secure a network, you must thoroughly understand its structure, components, and data flows. This foundational knowledge drives every subsequent security decision.

Network Mapping: Creating Your Security Blueprint

01

Create Comprehensive Network Diagrams

Develop detailed visual representations showing every device connected to your network—servers, workstations, routers, switches, wireless access points, and IoT devices. Document physical and logical connections, IP addressing schemes, and VLAN configurations.

03


Maintain Living Documentation

Update your diagrams immediately whenever you add, remove, or modify network components. Stale documentation is worse than no documentation—it creates false confidence and misdirects security efforts. Establish a formal change management process to ensure accuracy.

02

Map Data Flow Diagrams (DFDs)

Trace exactly how sensitive information moves through your systems. Identify entry points, processing locations, storage repositories, and transmission paths. These diagrams reveal where protection is most critical and where vulnerabilities might lurk.



Network Segmentation: Compartmentalising for Security

Network segmentation divides your infrastructure into isolated zones with controlled communication pathways between them. Think of it as creating separate rooms in a building with locked doors and security checkpoints—if intruders breach one room, they cannot freely roam the entire structure.

Define Your Security Scope

Identify precisely which systems handle sensitive data. Document this formally in a scope definition document. Review and update this documentation annually or whenever significant changes occur to your network or business processes.

Create Network Boundaries

Deploy firewalls and routers to establish security checkpoints between network segments. Configure these devices to permit only necessary traffic flows. Each boundary point becomes a control and monitoring opportunity.



Reduces Compliance Costs

Fewer systems fall within audit scope, dramatically reducing assessment time and expense.



Limits Attacker Movement

Even if one segment is compromised, segmentation prevents lateral movement to other areas.



Enables Targeted Security

Apply appropriate security controls to each segment based on the sensitivity of data it handles.

Testing Security Boundaries: Validation is Essential

For service providers handling payment processing, regular testing of network segmentation is not optional—it's mandatory. You must prove that your security boundaries actually function as designed and prevent unauthorised access between network segments.

Testing Requirements

- Conduct penetration testing of firewalls and routers that create segmentation barriers at least every six months
- Perform additional testing immediately following any significant network changes or new system deployments
- Document all testing procedures, findings, and remediation activities
- Engage qualified security professionals with relevant certifications and experience

This regular validation ensures that configuration drift, human error, or overlooked changes haven't inadvertently weakened your security posture.



Part 2: Controlling Network Traffic with Precision



Block Unwanted Incoming Traffic

Default deny for inbound connections



Block Unwanted Outgoing Traffic

Prevent data exfiltration and malware communication



Protect Public -Facing Systems

DMZ isolation for exposed services

Effective traffic control forms the backbone of network security. By implementing strict, well-designed firewall rules, you minimise your attack surface and create multiple defensive barriers against threats.

Implementing Default Deny: Incoming Traffic Control

Configure your firewalls with a "default deny" rule for all incoming traffic. This fundamental principle means that everything is blocked unless explicitly permitted—the security equivalent of a locked door where only authorised individuals possess keys.

Implementation Strategy



Identify Legitimate Traffic Requirements

Conduct a thorough analysis of which incoming connections your business genuinely requires. Document the business justification, source addresses, destination ports, and protocols for each permitted traffic flow.



Create Specific Allow Rules

Build precise firewall rules that permit only the identified legitimate traffic. Use the principle of least privilege—allow the minimum access necessary, no more.



Set Default Deny Policy

Configure the final catch-all rule to deny all other traffic. Log these denials to identify potential attacks or legitimate traffic you may have overlooked.

❏ **Key Benefit:** This approach dramatically minimises your attack surface by closing unnecessary network ports and services that attackers might otherwise exploit to gain initial access to your environment.

Controlling Outbound Traffic and Protecting Public Systems

Outgoing Traffic Control

Apply the same "default deny" philosophy to outbound traffic. This often-overlooked security measure provides critical protection against two major threats:

- **Data Exfiltration:** Even if attackers compromise a system, outbound controls prevent them from stealing your data by blocking unauthorised outgoing connections
- **Malware Communication:** Many malware variants attempt to communicate with command-and-control servers to receive instructions or transmit stolen information. Outbound filtering disrupts these communications


The DMZ Architecture

Public-facing systems (web servers, email servers, DNS) require Internet accessibility, making them high-risk targets. Deploy these in a Demilitarised Zone (DMZ)—a separate network segment with strict access controls.

Structure: Internet → External Firewall → DMZ (Public Servers) → Internal Firewall → Secure Internal Network

When attackers compromise a DMZ system, they encounter another firewall barrier preventing access to your internal sensitive data—buying you time to detect and respond to the breach.

Defence in Depth: Isolating Data and Protecting Endpoints



Systems storing data must never be directly accessible from untrusted networks. Implement multiple security layers between the Internet and your data repositories. Each layer an attacker must bypass increases the time, skill, and resources required and dramatically increases detection probability.

Individual Device Protection

Install and configure host-based firewalls on individual computers and devices, especially laptops used both inside and outside your network perimeter. Configure these with "default deny" rules, allowing only specific services and ports required for legitimate work functions. Laptops connecting to public WiFi then returning to your network can serve as bridges for attackers—host-based firewalls provide crucial protection against this threat vector.



Part 3: Secure Communications and Protocol Management



Encryption for Data Transmission

Always encrypt sensitive data when transmitting across networks, particularly public networks and wireless connections.



Eliminate Insecure Protocols

Replace outdated, vulnerable protocols with modern, secure alternatives to prevent credential theft and data exposure.



Regular Security Reviews

Conduct systematic reviews of firewall rules and network configurations at least every six months to maintain security effectiveness.

Your Security Foundation

1

Documentation is Your Foundation

You cannot secure what you don't understand. Comprehensive, current documentation of your network architecture and data flows enables every other security measure.

2

Segmentation Limits Damage

Network compartmentalisation contains breaches, reduces audit scope, and enables targeted security controls appropriate to each segment's risk level.

3

Default Deny is Your Friend

Block all traffic except what you explicitly allow. This principle dramatically reduces your attack surface and prevents exploitation of unknown vulnerabilities.

4

Encryption is Non-Negotiable

Always protect data in transit using strong encryption protocols. Use SSH, HTTPS, and TLS/SSL for all sensitive communications. Eliminate insecure protocols like Telnet, FTP, and HTTP.

5

Regular Reviews are Essential

Security configurations require ongoing maintenance. Review firewall rules every six months, removing outdated rules and ensuring business justifications remain valid for all permitted traffic flows.