



**POLITECNICO**  
MILANO 1863



# Stochastic Variance-Reduced Policy Gradient

**Matteo Papini**

Damiano Binaghi   Giuseppe Canonaco  
Matteo Pirotta   Marcello Restelli

35<sup>th</sup> International Conference on Machine Learning, Stockholm, Sweden

## Stochastic **V**ariance-**R**educed (**P**olicy) **G**radient

### ■ **SVRG** for Reinforcement Learning

- Motivation
- Challenges


### ■ **SVRPG**

- Convergence Properties
- Heuristics
- Experiments

An effective **Reinforcement Learning (RL)** solution to **continuous** control problems:




Robotics (Heess et al., 2017)



Video games (OpenAI, 2018)

Mostly based on **Stochastic Gradient Ascent** (Robbins and Monro, 1951)



Can we do something better?

A solution from **finite-sum optimization** (Johnson and Zhang, 2013):

$$\underbrace{\nabla J(\boldsymbol{\theta})}_{\text{SVRG estimator}} = \underbrace{\nabla J(\tilde{\boldsymbol{\theta}})}_{\text{FG in snapshot parameter}} + \underbrace{\nabla J(\boldsymbol{\theta})|_{\tau_i}}_{\text{SG in current parameter}} - \underbrace{\nabla J(\tilde{\boldsymbol{\theta}})|_{\tau_i}}_{\text{Correction term}}$$

- Unbiased
- Linear convergence
- More data-efficient than FG
- Easily applicable to **Supervised Learning (SL)**

Not trivial! There are three **challenges**:

- 1 **Non-concavity** of  $J(\theta)$  (Allen-Zhu and Hazan, 2016; Reddi et al., 2016)
- 2 **Infinite dataset**: we would need *infinite samples* to compute FG (Harikandeh et al., 2015; Bietti and Mairal, 2017)
- 3 **Non-stationarity**:  $\tau \sim p_{\theta}$  (new!)

RL so far: *policy evaluation* (Du et al., 2017) and *off-policy control* (Xu et al., 2017)

Our work: **on-policy control**

$$\underbrace{\nabla J(\boldsymbol{\theta})}_{\text{SVRPG estimator}} = \underbrace{\hat{\nabla}_N J(\tilde{\boldsymbol{\theta}})}_{\substack{\text{Large } N \\ \text{to approximate FG}}} + \underbrace{\hat{\nabla}_B J(\boldsymbol{\theta})}_{B \ll N} - \underbrace{\omega(\boldsymbol{\theta}, \tilde{\boldsymbol{\theta}}) \hat{\nabla}_B J(\tilde{\boldsymbol{\theta}})}_{\substack{\text{Importance weighting} \\ \text{for non-stationarity}}}$$

- Unbiased
- More data-efficient than FG
- **On-policy**: only the correction term is weighted

Convergence to **local** optimum:

$$\mathbb{E} \left[ \|\nabla J(\boldsymbol{\theta})\|^2 \right] \leq \frac{J(\boldsymbol{\theta}^*) - J(\boldsymbol{\theta}_0)}{\psi T} + \underbrace{\frac{\zeta}{N}}_{\text{Infinite dataset}} + \underbrace{\frac{\xi}{B}}_{\text{Nonstationarity}}$$

- Linear convergence + error (similar to Harikandeh et al., 2015)



## Meta-parameter selection


- **Adaptive step size:** two ADAM (Kingma and Ba, 2014) annealing schedules

$$\underbrace{\alpha_{FG}}_{\text{used at the snapshot}} \quad \underbrace{\alpha_{SG}}_{\text{used inside epoch}}$$


- **Adaptive epoch size:** take new snapshot when the effective step size becomes too small

$$\frac{\alpha_{SG}}{B} < \frac{\alpha_{FG}}{N} \implies \text{snapshot}$$


Cart-Pole



Swimmer



Half-Cheetah



- Efficient policy optimization is challenging
- **SVRPG**: on-policy control based on SVRG
- Meta-parameters still crucial to tame different sources of variance
- Future work: adaptive batch size, natural gradient, actor-critic

## Thank you for your attention

- Poster: today 06:15 – 09:00 PM @ **Hall B #65**
- Contact: `matteo.papini@polimi.it`
- Online resources: `t3p.github.io`



- Allen-Zhu, Z. and Hazan, E. (2016). Variance reduction for faster non-convex optimization. In *International Conference on Machine Learning*, pages 699–707.
- Baxter, J. and Bartlett, P. L. (2001). Infinite-horizon policy-gradient estimation. *Journal of Artificial Intelligence Research*, 15:319–350.
- Bietti, A. and Mairal, J. (2017). Stochastic optimization with variance reduction for infinite datasets with finite sum structure. In *Advances in Neural Information Processing Systems*, pages 1622–1632.
- Du, S. S., Chen, J., Li, L., Xiao, L., and Zhou, D. (2017). Stochastic variance reduction methods for policy evaluation. In *ICML*, volume 70 of *Proceedings of Machine Learning Research*, pages 1049–1058. PMLR.
- Duan, Y., Chen, X., Houthooft, R., Schulman, J., and Abbeel, P. (2016). Benchmarking deep reinforcement learning for continuous control. In *International Conference on Machine Learning*, pages 1329–1338.
- Harikandeh, R., Ahmed, M. O., Virani, A., Schmidt, M., Konečný, J., and Sallinen, S. (2015). Stopwasting my gradients: Practical svrg. In *Advances in Neural Information Processing Systems*, pages 2251–2259.
- Heess, N., Sriram, S., Lemmon, J., Merel, J., Wayne, G., Tassa, Y., Erez, T., Wang, Z., Eslami, A., Riedmiller, M., et al. (2017). Emergence of locomotion behaviours in rich environments. *arXiv preprint arXiv:1707.02286*.
- Johnson, R. and Zhang, T. (2013). Accelerating stochastic gradient descent using predictive variance reduction. In *Advances in neural information processing systems*, pages 315–323.
- Kingma, D. P. and Ba, J. (2014). Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.

OpenAI (2018). Openai five.

Peters, J. and Schaal, S. (2008). Reinforcement learning of motor skills with policy gradients. *Neural networks*, 21(4):682–697.

Reddi, S. J., Hefny, A., Sra, S., Póczos, B., and Smola, A. (2016). Stochastic variance reduction for nonconvex optimization. In *International conference on machine learning*, pages 314–323.

Robbins, H. and Monroe, S. (1951). A stochastic approximation method. *The annals of mathematical statistics*, pages 400–407.

Xu, T., Liu, Q., and Peng, J. (2017). Stochastic variance reduction for policy gradient estimation. *CoRR*, abs/1710.06034.

**For**  $s = 1, \dots$

Sample  $N$  trajectories using  $\tilde{\theta}$

Compute FG =  $\hat{\nabla}_N J(\tilde{\theta})$

**For**  $t = 1, \dots, m$

Sample  $B$  trajectories using  $\theta$

Compute SG =  $\hat{\nabla}_B J(\theta)$

Compute correction =  $\omega(\theta, \tilde{\theta}) \hat{\nabla}_B J(\tilde{\theta})$

Update  $\theta \leftarrow \theta + \alpha \nabla J(\theta)$

Update  $\tilde{\theta} \leftarrow \theta$

iteration

epoch

ADAM (Kingma and Ba, 2014):

- adapts to gradient variance
- can manage different batch sizes
- **has memory of past gradients (momentum)**

**Problem:** FG and SG updates have very different variance magnitudes  
 $\implies$  spurious momentum

We use two *separate* annealing schedules:

$$\begin{aligned}\tilde{\boldsymbol{\theta}} &\leftarrow \tilde{\boldsymbol{\theta}} + \alpha_{FG} \widehat{\nabla}_N J(\tilde{\boldsymbol{\theta}}) && \text{at the snapshot} \\ \boldsymbol{\theta} &\leftarrow \boldsymbol{\theta} + \alpha_{SG} \nabla J(\boldsymbol{\theta}) && \text{otherwise}\end{aligned}$$

Note that  $\widehat{\nabla}_N J(\tilde{\boldsymbol{\theta}}) \equiv \nabla J(\boldsymbol{\theta})$  at the snapshot



Epoch size  $m$  trade-off:

- Large  $m \implies$  policy very far from snapshot  $\implies$  importance weighting introduces more variance than it reduces  $\implies$  instability
- Small  $m \implies$  frequent snapshot  $\implies$  data-inefficient

Idea: ADAM already relates gradient variance and efficiency

Our stopping criterion:

$$\frac{\alpha_{SG}}{B} < \frac{\alpha_{FG}}{N} \implies \text{snapshot}$$

When going on with the current snapshot is not *convenient*, take a new one

Regular importance weighting (unbiased):


$$\omega(\boldsymbol{\theta}, \tilde{\boldsymbol{\theta}}) \hat{\nabla}_B J(\tilde{\boldsymbol{\theta}}) = \frac{1}{B} \sum_{i=1}^B \frac{p(\tau_i | \tilde{\boldsymbol{\theta}})}{p(\tau_i | \boldsymbol{\theta})} g(\tau_i | \tilde{\boldsymbol{\theta}})$$

Normalized importance weighting:

$$\omega(\boldsymbol{\theta}, \tilde{\boldsymbol{\theta}}) \hat{\nabla}_B J(\tilde{\boldsymbol{\theta}}) = \frac{\sum_{i=1}^B \frac{p(\tau_i | \tilde{\boldsymbol{\theta}})}{p(\tau_i | \boldsymbol{\theta})} g(\tau_i | \tilde{\boldsymbol{\theta}})}{\sum_{i=1}^B \frac{p(\tau_i | \tilde{\boldsymbol{\theta}})}{p(\tau_i | \boldsymbol{\theta})}}$$

- Reduces variance at the price of introducing a small bias
- Only affects the correction term
- Effectiveness is task-dependent

## Swimmer



**Critic** (or *baseline*): an orthogonal variance-reduction technique

$$g(\tau_i|\boldsymbol{\theta}) = \sum_{t=1}^H \left( \sum_{k=1}^t \nabla \log \pi_{\boldsymbol{\theta}}(a_t|s_t) \right) (\gamma^t r_t - \underbrace{\mathbf{b}}_{\text{baseline}}) \quad (\text{Peters and Schaal, 2008})$$

**Not trivial** to combine SVRG with critic: variance reductions are not additive

We combine SVRG with a simple critic suggested in Duan et al. (2016) on the **Half-Cheetah** task

Ad-hoc critic left for future work

- For Swimmer, we employ normalized weights in our final result
- For Half-Cheetah, we employ both normalized weights and critic in our final result
- We compare SVRPG with GPOMDP (Baxter and Bartlett, 2001) with batch size =  $B$
- This is a natural comparison since we want to evaluate the *convenience* of correcting the SG update
- However, GPOMDP with batch size =  $N$  is even worse

## Half-Cheetah

