

# Functions

Victor Eijkhout, Susan Lindsey

COE 322 Fall 2020

# Function basics

# Why functions?

Functions are an abstraction mechanism.

- Code fragment with clear function:
- Turn into *subprogram*: function *definition*.
- Use by single line: function *call*.
- Abstraction: you have introduced a **name** for a section of code.

# Introducing a function

*program*

```
int main() {  
    x = ...  
  
    // foo computation  
    xtmp = ... x ...  
    ytmp = ... x ... xtmp ....  
    y = .... xtmp .... ytmp ....  
  
    .... y ....  
}
```



```
float foo_compute(float x) {
```

```
    // foo computation  
    xtmp = ... x ...  
    ytmp = ... x ... xtmp ....  
    return .... xtmp .... ytmp ....  
}
```

*function*

```
int main() {
```

```
    x = ...  
    y = foo_compute(x);  
    .... y ....  
}
```

*program*

# Program without functions

Example: zero-finding through bisection.

$$\underset{x}{?}: f(x) = 0, \quad f(x) = x^3 - x^2 - 1$$

Step 1: everything in the main program.

```
int main() {  
    float left{0.},right{2.};  
    while (right-left>.1) {  
        mid = (left+right)/2.,  
        float fmid =  
            mid*mid*mid - mid*mid-1;  
        if (fmid<0)  
            left = mid;  
        else  
            right = mid;  
    }  
    cout << "Zero happens at: " << mid << endl;  
}
```

# Introducing functions, step1

Introduce function for the  
expression  $m*m*m - m*m-1$ :

```
float f(float m) {  
    return m*m*m - m*m-1;  
};
```

```
int main() {  
    float left{0.},right{2.},  
        mid;  
    while (right-left>.1) {  
        mid = (left+right)/2.;  
        float fmid = f(mid);  
        if (fmid<0)  
            left = mid;  
        else  
            right = mid;  
    }  
    cout << "Zero happens at: "  
        << mid << endl;  
}
```

# Introducing functions, step 2

Add function for zero finding:

```
float f(float m) {  
    return m*m*m - m*m-1;  
};  
float find_zero_between  
    (float l,float r) {  
    float mid;  
    while (r-l>.1) {  
        mid = (l+r)/2.;  
        float fmid = f(mid);  
        if (fmid<0)  
            l = mid;  
        else  
            r = mid;  
    }  
    return mid;  
};
```

```
int main() {  
    float left{0.},right{1.};  
    float zero  
        = find_zero_between(left,  
            right);  
    cout << "Zero happens at: "  
        << zero << endl;  
}
```

(note the local variable)

# Why functions?

- Easier to read: use application terminology
- Shorter code: reuse
- Cleaner code: local variables are no longer in the main program.
- Maintenance and debugging



# Code reuse

Suppose you do the same computation twice:

```
double x,y, v,w;  
y = ..... computation from x .....  
w = ..... same computation, but from v .....
```

With a function this can be replaced by:

```
double computation(double in) {  
    return .... computation from 'in' ....  
}
```

```
y = computation(x);  
w = computation(v);
```

# Code reuse

Example: multiple norm calculations:

Repeated code:

```
float s = 0;
for (int i=0; i<x.size(); i++)
    s += abs(x[i]);
cout << "One norm x: " << s <<
    endl;
s = 0;
for (int i=0; i<y.size(); i++)
    s += abs(y[i]);
cout << "One norm y: " << s <<
    endl;
```

becomes:

```
float OneNorm( vector<float> a
    ) {
    float sum = 0;
    for (int i=0; i<a.size(); i
        ++ )
        sum += abs(a[i]);
    return sum;
}
int main() {
    ... // stuff
    cout << "One norm x: "
        << OneNorm(x) << endl;
    cout << "One norm y: "
        << OneNorm(y) << endl;
```

# Review quiz 1

True or false?

- The purpose of functions is to make your code shorter.  
`/poll "Functions are to make your code shorter" "T" "F"`
- Using functions makes your code easier to read and understand.  
`/poll "Functions make your code easier to understand" "T" "F"`
- Functions have to be defined before you can use them.  
`/poll "Functions have to be defined before use" "T" "F"`
- Function definitions can go inside or outside the main program.  
`/poll "Function defitions can go in or out main" "T" "F"`

# Anatomy of a function definition

```
void write_to_file(int i, double x) { /* ... */ }  
float euler_phi(int i, bool tf) { /* ... */ return x; }
```

- Result type: what's computed.

`void` if no result

- Name: make it descriptive.
- Parameters: zero or more.

`int i, double x, double y`

These act like variable declarations.

- Body: any length. This is a scope.
- Return statement: usually at the end, but can be anywhere; the computed result. Not necessary for a `void` function.

# Function call

The function call

1. copies the value of the function argument to the function parameter;
2. causes the function body to be executed, and
3. the function call is replaced by whatever you `return`.
4. (If the function does not return anything, for instance because it only prints output, you declare the return type to be `void`.)

# Void function with input

```
void print_result(int day,float value) {  
    cout << "*****" << endl;  
    cout << "* Output      *" << endl;  
    cout << "*****" << endl;  
    cout << "The results for day " << day << ":" << endl;  
    cout << "      " << value << endl;  
}  
  
int main() {  
    print_result(25,3.456);  
    return 0;  
}
```

# Review quiz 2

True or false?

- A function can have only one input  
`/poll "Function can have only one input" "T" "F"`
- A function can have only one return result  
`/poll "Function can have only one return result" "T" "F"`
- A void function can not have a `return` statement.  
`/poll "Void function can not have return" "T" "F"`

# Exercise 1

Write a function with (float or double) inputs  $x, y$  that returns the distance of point  $(x, y)$  to the origin.

Test the following pairs: 1, 0; 0, 1; 1, 1; 3, 4.



## Project Exercise 2

Write a function `test_if_prime` that has an integer parameter, and returns a boolean corresponding to whether the parameter was prime.

```
int main() {  
    bool isprime;  
    isprime = test_if_prime(13);  
}
```

Read the number in, and print the value of the boolean.

Does your function have one or two return statements? Can you imagine what the other possibility looks like? Do you have an argument for or against it?

## Project Exercise 3

Take your prime number testing function `test_if_prime`, and use it to write a program that prints multiple primes:

- Read an integer `how_many` from the input, indicating how many (successive) prime numbers should be printed.
- Print that many successive primes, each on a separate line.
- (Hint: keep a variable `number_of_primes_found` that is increased whenever a new prime is found.)

# Turn it in!

- If you have compiled your program, do:

```
coe_prime yourprogram.cc
```

where 'yourprogram.cc' stands for the name of your source file.

- Is it reporting that your program is correct? If so, do:

```
coe_prime -s yourprogram.cc
```

where the -s flag stands for 'submit'.

- If you don't manage to get your code working correctly, you can submit as incomplete with

```
coe_prime -i yourprogram.cc
```

# Background Square roots through Newton

Early computers had no hardware for computing a square root. Instead, they used Newton's method. Suppose you have a value  $y$  and you want to compute  $x = \sqrt{y}$ . This is equivalent to finding the zero of

$$f(x) = x^2 - y$$

where  $y$  is fixed. To indicate this dependence on  $y$ , we will write  $f_y(x)$ . Newton's method then finds the zero by evaluating

$$x_{\text{next}} = x - f_y(x)/f'_y(x)$$

until the guess is accurate enough, that is, until  $f_y(x) \approx 0$ .

## Optional exercise 4

- Write functions `f(x,y)` and `deriv(x,y)`, that compute  $f_y(x)$  and  $f'_y(x)$  for the definition of  $f_y$  above.
- Read a value  $y$  and iterate until  $|f(x,y)| < 10^{-5}$ . Print  $x$ .
- Second part: write a function `newton_root` that computes  $\sqrt{y}$ .

# Parameter passing

# Mathematical type function

Pretty good design:

- pass data into a function,
- return result through `return` statement.
- Parameters are copied into the function. (Cost of copying?)
- pass by value
- 'functional programming'

# Pass by value example

Note that the function alters its parameter `x`:

**Code:**

```
double squared( double x ) {  
    x = x*x;  
    return x;  
}  
  
/* ... */  
number = 5.1;  
cout << "Input starts as: "  
    << number << endl;  
other = squared(number);  
cout << "Output var is: "  
    << other << endl;  
cout << "Input var is now: "  
    << number << endl;
```

**Output**

**[func] passvalue:**

Input starts as: 5.1

Output var is: 26.01

Input var is now: 5.1

but the argument in the main program is not affected.



# Reference

A reference is indicated with an ampersand in its definition, and it acts as an alias of the thing it references.

**Code:**

```
int i;  
int &ri = i;  
i = 5;  
cout << i << ", " << ri << endl;  
i *= 2;  
cout << i << ", " << ri << endl;  
ri -= 3;  
cout << i << ", " << ri << endl;
```

**Output**

**[basic] ref:**

5,5  
10,10  
7,7

(You will not use references often this way.)

# Parameter passing by reference

The function parameter `n` becomes a reference to the variable `i` in the main program:

```
void f(int &n) {  
    n = /* some expression */ ;  
};  
int main() {  
    int i;  
    f(i);  
    // i now has the value that was set in the function  
}
```

# Results other than through return

Also good design:

- Return no function result,
- or return return status (0 is success, nonzero various informative statuses), and
- return other information by changing the parameters.
- *pass by reference*
- Parameters are sometimes classified 'input', 'output', 'throughput'.

# Pass by reference example 1

Code:

```
void f( int &i ) {  
    i = 5;  
}  
  
int main() {  
  
    int var = 0;  
    f(var);  
    cout << var << endl;
```

Output

[basic] setbyref:

5

Compare the difference with leaving out the reference.

## Pass by reference example 2

```
bool can_read_value( int &value ) {  
    // this uses functions defined elsewhere  
    int file_status = try_open_file();  
    if (file_status==0)  
        value = read_value_from_file();  
    return file_status==0;  
}  
  
int main() {  
    int n;  
    if (!can_read_value(n)) {  
        // if you can't read the value, set a default  
        n = 10;  
    }  
    ..... do something with 'n' .....
```

## Exercise 5

Write a void function `swapij` of two parameters that exchanges the input values:

```
int i=2,j=3;  
swapij(i,j);  
// now i==3 and j==2
```

## Exercise 6

Write a divisibility function that takes a number and a divisor, and gives:

- a bool return result indicating that the number is divisible, and
- a remainder as output parameter.

```
int number, divisor, remainder;  
// read in the number and divisor  
if ( is_divisible(number, divisor, remainder) )  
    cout << number << " is divisible by " << divisor << endl;  
else  
    cout << number << "/" << divisor <<  
        " has remainder " << remainder << endl;
```

## Exercise 7

Write a function with inputs  $x, y, \theta$  that alters  $x$  and  $y$  corresponding to rotating the point  $(x, y)$  over an angle  $\theta$ .

$$\begin{pmatrix} x' \\ y' \end{pmatrix} = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix}$$

Your code should behave like:

**Code:**

```
const float pi = 2*acos(0.0);  
float x{1.}, y{0.};  
rotate(x,y,pi/4);  
cout << "Rotated halfway: ("  
    << x << ", " << y << ")" << endl;  
rotate(x,y,pi/4);  
cout << "Rotated to the y-axis: ("  
    << x << ", " << y << ")" << endl;
```

**Output**

**[geom] rotate:**

Rotated halfway: (0.707107,0.707107)  
Rotated to the y-axis: (0,1)



# Recursion

# Recursion

A function is allowed to call itself, making it a recursive function.  
For example, factorial:

$$5! = 5 \cdot 4 \cdot \dots \cdot 1 = 5 \times 4!$$

You can define factorial as

$$F(n) = n \times F(n - 1) \quad \text{if } n > 1, \text{ otherwise } 1$$

```
int factorial( int n ) {  
    if (n==1)  
        return 1;  
    else  
        return n*factorial(n-1);  
}
```

## Exercise 8

The sum of squares:

$$S_n = \sum_{n=1}^N n^2$$

can be defined recursively as

$$S_1 = 1, \quad S_n = n^2 + S_{n-1}.$$

Write a recursive function that implements this second definition.  
Test it on numbers that are input interactively.

Then write a program that prints the first 100 sums of squares.

## Exercise 9

Write a recursive function for computing Fibonacci numbers:

$$F_0 = 1, \quad F_1 = 1, \quad F_n = F_{n-1} + F_{n-2}$$

First write a program that computes  $F_n$  for a value  $n$  that is input interactively.

Then write a program that prints out a sequence of Fibonacci numbers; set interactively how many.

## More about functions

# Default arguments

Functions can have default argument(s):

```
double distance( double x, double y=0. ) {  
    return sqrt( (x-y)*(x-y) );  
}  
  
...  
d = distance(x); // distance to origin  
d = distance(x,y); // distance between two points
```

Any default argument(s) should come last in the parameter list.

# Polymorphic functions

You can have multiple functions with the same name:

```
double sum(double a, double b) {  
    return (a+b)/2; }  
double sum(double a, double b, double c) {  
    return (a+b+c)/3; }
```

Distinguished by type or number of input arguments: can not differ only in return type.

# Scope



# Lexical scope

## Visibility of variables

```
int main() {  
    int i;  
    if ( something ) {  
        int j;  
        // code with i and j  
    }  
    int k;  
    // code with i and k  
}
```

# Shadowing

```
int main() {  
    int i = 3;  
    if ( something ) {  
        int i = 5;  
    }  
    cout << i << endl; // gives 3  
    if ( something ) {  
        float i = 1.2;  
    }  
    cout << i << endl; // again 3  
}
```

Variable `i` is shadowed: invisible for a while.

After the lifetime of the shadowing variable, its value is unchanged from before.

## Exercise 10

What is the output of this code?

```
bool something{false};
int i = 3;
if ( something ) {
    int i = 5;
    cout << "Local: " << i << endl;
}
cout << "Global: " << i << endl;
if ( something ) {
    float i = 1.2;
    cout << i << endl;
    cout << "Local again: " << i << endl;
}
cout << "Global again: " << i << endl;
```

# Life time vs reachability

Even without shadowing, a variable can exist but be unreachable.

```
void f() {  
    ...  
}  
int main() {  
    int i;  
    f();  
    cout << i;  
}
```