

Advanced Topics

Victor Eijkhout, Susan Lindsey

COE 322 Fall 2021

Pointers

1 Simple example

Simple class that stores one number:

```
class HasX {  
private:  
    double x;  
public:  
    HasX( double x) : x(x) {};  
    auto value() { return x; };  
    void set(double xx) { x = xx; };  
};
```

2 Reference counting illustrated

We need a class with constructor and destructor tracing:

```
class thing {  
public:  
    thing() { cout << ".. calling constructor\n"; }  
    ~thing() { cout << ".. calling destructor\n"; }  
};
```

3 Pointer overwrite

Let's create a pointer and overwrite it:

Code:

```
cout << "set pointer1"
      << endl;
auto thing_ptr1 =
    make_shared<thing>();
cout << "overwrite pointer"
      << endl;
thing_ptr1 = nullptr;
```

Output

[pointer] ptr1:

```
set pointer1
.. calling constructor
overwrite pointer
.. calling destructor
```

4 Pointer copy

Code:

```
cout << "set pointer2" << endl;
auto thing_ptr2 =
    make_shared<thing>();
cout << "set pointer3 by copy"
    << endl;
auto thing_ptr3 = thing_ptr2;
cout << "overwrite pointer2"
    << endl;
thing_ptr2 = nullptr;
cout << "overwrite pointer3"
    << endl;
thing_ptr3 = nullptr;
```

Output [pointer] ptr2:

```
set pointer2
.. calling constructor
set pointer3 by copy
overwrite pointer2
overwrite pointer3
.. calling destructor
```

5 Linked list code, old style

```
node *node::prepend_or_append(node *other) {  
    if (other->value > this->value) {  
        this->tail = other;  
        return this;  
    } else {  
        other->tail = this;  
        return other;  
    }  
};
```

Can we do this with shared pointers?

6 A problem with shared pointers

```
shared_pointer<node> node::prepend_or_append  
    ( shared_ptr<node> other ) {  
    if (other->value>this->value) {  
        this->tail = other;
```

So far so good. However, `this` is a `node*`, not a `shared_ptr<node>`,
so

```
    return this;
```

returns the wrong type.

7 Solution: shared from this

It is possible to have a 'shared pointer to this' if you define your node class with (warning, major magic alert):

```
class node : public enable_shared_from_this<node> {
```

This allows you to write:

```
    return this->shared_from_this();
```

Namespaces

8 You have already seen namespaces

Safest:

```
#include <vector>
int main() {
    std::vector<stuff> foo;
}
```

Drastic:

```
#include <vector>
using namespace std;
int main() {
    vector<stuff> foo;
}
```

Prudent:

```
#include <vector>
using std::vector;
int main() {
    vector<stuff> foo;
}
```

9 Why not 'using namespace std' ?

This compiles, but should not:

```
#include <iostream>
using namespace std;

def swop(int i,int j) {};

int main() {
    int i=1,j=2;
    swap(i,j);
    cout << i << endl;
    return 0;
}
```

This gives an error:

```
#include <iostream>
using std::cout;
using std::endl;

def swop(int i,int j) {};

int main() {
    int i=1,j=2;
    swap(i,j);
    cout << i << endl;
    return 0;
}
```

10 Defining a namespace

You can make your own namespace by writing

```
namespace a_namespace {  
    // definitions  
    class an_object {  
    };  
|
```

11 Namespace usage

```
a_namespace::an_object myobject();
```

or

```
using namespace a_namespace;  
an_object myobject();
```

or

```
using a_namespace::an_object;  
an_object myobject();
```

or

```
using namespace abc = space_a::space_b::space_c;  
abc::func(x)
```

Templates

12 Templated type name

If you have multiple routines that do 'the same' for multiple types, you want the type name to be a variable. Syntax:

```
template <typename yourtypevariable>  
// ... stuff with yourtypevariable ...
```


13 Example: function

Definition:

```
template<typename T>  
void function(T var) { cout << var << end; }
```

Usage:

```
int i; function(i);  
double x; function(x);
```

and the code will behave as if you had defined function twice, once for int and once for double.

Exercise 1

Machine precision, or 'machine epsilon', is sometimes defined as the smallest number ϵ so that $1 + \epsilon > 1$ in computer arithmetic.

Write a templated function `epsilon` so that the following code prints out the values of the machine precision for the `float` and `double` type respectively:

Code:

```
float float_eps;
epsilon(float_eps);
cout << "Epsilon float: "
    << setw(10) << setprecision
    (4)
    << float_eps << endl;

double double_eps;
epsilon(double_eps);
cout << "Epsilon double: "
    << setw(10) << setprecision
    (4)
    << double_eps << endl;
```

Output [template] eps:

```
Epsilon float: 1.0000e-07
Epsilon double: 1.0000e-15
```

14 Templated vector

The Standard Template Library (STL) contains in effect

```
template<typename T>
class vector {
private:
    T *vectordata; // internal data
public:
    T at(int i) { return vectordata[i] };
    int size() { /* return size of data */ };
    // much more
}
```

Exceptions

15 Exception throwing

Throwing an exception is one way of signalling an error or unexpected behaviour:

```
void do_something() {  
    if ( oops )  
        throw(5);  
}
```

16 Catching an exception

It now becomes possible to detect this unexpected behaviour by *catching* the exception:

```
try {  
    do_something();  
} catch (int i) {  
    cout << "doing something failed: error=" << i << endl;  
}
```

17 Exception classes

```
class MyError {  
public :  
    int error_no; string error_msg;  
    MyError( int i,string msg )  
        : error_no(i),error_msg(msg) {};  
}  
  
throw( MyError(27,"oops");  
  
try {  
    // something  
} catch ( MyError &m ) {  
    cout << "My error with code=" << m.error_no  
        << " msg=" << m.error_msg << endl;  
}
```

You can use exception inheritance!

18 Multiple catches

You can multiple catch statements to catch different types of errors:

```
try {  
    // something  
} catch ( int i ) {  
    // handle int exception  
} catch ( std::string c ) {  
    // handle string exception  
}
```


19 Catch any exception

Catch exceptions without specifying the type:

```
try {  
    // something  
} catch ( ... ) { // literally: three dots  
    cout << "Something went wrong!" << endl;  
}
```

20 More about exceptions

- Functions can define what exceptions they throw:

```
void func() throw( MyError, std::string );  
void funk() throw();
```

- Predefined exceptions: `bad_alloc`, `bad_exception`, etc.
- An exception handler can throw an exception; to rethrow the same exception use `'throw;'` without arguments.
- Exceptions delete all stack data, but not new data. Also, destructors are called; section ??.
- There is an implicit `try/except` block around your `main`. You can replace the handler for that. See the exception header file.
- Keyword `noexcept`:

```
void f() noexcept { ... };
```
- There is no exception thrown when dereferencing a `nullptr`.

21 Destructors and exceptions

The destructor is called when you throw an exception:

Code:

```
class SomeObject {
public:
    SomeObject() {
        cout << "calling the
            constructor"
            << endl; };
    ~SomeObject() {
        cout << "calling the
            destructor"
            << endl; };
};
/* ... */
try {
    SomeObject obj;
    cout << "Inside the nested
        scope" << endl;
    throw(1);
} catch (...) {
```

Output

[object] exceptdestruct:

calling the constructor
Inside the nested scope
calling the destructor
Exception caught

Auto

22 Type deduction

In:

```
std::vector< std::shared_ptr< myclass >>*  
myvar = new std::vector< std::shared_ptr< myclass >>  
        ( 20, new myclass(1.3) );
```

the compiler can figure it out:

```
auto myvar =  
    new std::vector< std::shared_ptr< myclass >>  
        ( 20, new myclass(1.3) );  
auto result = someobject.somemethod();
```

23 Type deduction in functions

Return type can be deduced in C++17:

```
auto equal(int i,int j) {  
    return i==j;  
};
```

24 Auto and references, 1

auto discards references and such:

Code:

```
A my_a(5.7);  
auto get_data = my_a.access();  
get_data += 1;  
my_a.print();
```

Output

[auto] plainget:

data: 5.7

25 Auto and references, 2

Combine auto and references:

Code:

```
A my_a(5.7);  
auto &get_data = my_a.access();  
get_data += 1;  
my_a.print();
```

Output

[auto] refget:

data: 6.7

26 Auto and references, 3

For good measure:

```
A my_a(5.7);  
const auto &get_data = my_a.access();  
get_data += 1; // WRONG does not compile  
my_a.print();
```

27 Auto iterators

```
vector<int> myvector(20);  
for ( auto copy_of_int :  
      myvector )  
    s += copy_of_int;  
for ( auto &ref_to_int :  
      myvector )  
    ref_to_int = s;  
for ( const auto& copy_of_thing  
      : myvector )  
    s += copy_of_thing.f();
```

is actually short for:

```
for ( std::vector<int>  
      iterator it=myvector.begin  
      () ;  
      it!=myvector.end() ; ++it  
      )  
    s += *it ; // note the deref
```

Range iterators can be used with anything that is iterable
(vector, map, your own classes!)

Random

28 Random floats

```
// seed the generator
std::random_device r;
// std::seed_seq ssq{r()};
// and then passing it to the engine does the same

// set the default random number generator
std::default_random_engine generator{r()};

// distribution: real between 0 and 1
std::uniform_real_distribution<float> distribution(0.,1.);

cout << "first rand: " << distribution(generator) << endl;
```

29 Dice throw

```
// set the default generator
std::default_random_engine generator;

// distribution: ints 1..6
std::uniform_int_distribution<int> distribution(1,6);

// apply distribution to generator:
int dice_roll = distribution(generator);
    // generates number in the range 1..6
```

30 Poisson distribution

Another distribution is the Poisson distribution:

```
std::default_random_engine generator;  
float mean = 3.5;  
std::poisson_distribution<int> distribution(mean);  
int number = distribution(generator);
```

31 Global engine

Wrong approach:

Code:

```
int nonrandom_int(int max) {  
    std::default_random_engine  
        engine;  
    std::uniform_int_distribution<>  
        ints(1,max);  
    return ints(engine);  
};
```

Output

[rand] nonrandom:

Three ints: 15, 15, 15.

Good approach:

Code:

```
int realrandom_int(int max) {  
    static std::  
        default_random_engine  
        static_engine;  
    std::uniform_int_distribution<>  
        ints(1,max);
```

Output

[rand] truerandom:

Three ints: 15, 98, 70.