

# Compilation

Victor Eijkhout, Susan Lindsey

Fall 2022

last formatted: August 24, 2022

# 1: Intro to file types

# 1. File types

---

## Text files

---

Source	Program text that you write
Header	also written by you, but not really program text.

---

## Binary files

---

Object file	The compiled result of a single source file
Library	Multiple object files bundled together
Executable	Binary file that can be invoked as a command
Data files	Written and read by a program

---

## 2. Text files

- Source files and headers
- You write them: *make sure you master an editor*
- The computer has no idea what these mean.
- They get compiled into programs.

(Also 'just text' files: READMEs and such)

### 3. Binary files

- Programs. (Also: object and library files.)
- Produced by a compiler.
- Unreadable by you; executable by the computer.

Also binary data files; usually specific to a program.  
(Why don't programs write out their data in readable form?)

## 2: Compilation

## 4. Compilers

Compilers: a major CS success story.

- The first Fortran compiler (Backus, IBM, 1954): multiple man-years.
- These days: semester project for graduate students.  
Many tools available (`lex`, `yacc`, `clang-tidy`)  
Standard textbooks ('Dragon book')
- Compilers are very clever!  
You can be a little more clever in assembly – maybe  
but compiled languages are  $10\times$  more productive.

## 5. Compilation vs interpreted

- Interpreted languages: lines of code are compiled 'just-in-time'.  
Very flexible, sometimes very slow.
- Compiled languages: code is compiled to machine language: less flexible, very fast execution.
- Virtual machine: languages get compiled to an intermediate language  
(Pascal, Python, Java)  
pro: portable; con: does not play nice with other languages.
- Scientific computing languages:
  - Fortran: pretty elegant, great at array manipulation  
Note: Fortran2003 is modern; F77 and F90 are not so great.
  - C: low level, allows great control, tricky to use
  - C++: allows much control, more protection, more tools  
(kinda sucks at arrays)



## 6. Simple compilation

hello.c

```
int main() {  
    printf("Hello world\n");  
    return 0;  
}
```

icc -o hello.exe hello.c

hello.exe

- From source straight to program.
- Use this only for short programs.

```
%% gcc hello.c  
%% ./a.out  
hello world
```

```
%% gcc -o helloworld hello.c  
%% ./helloworld  
hello world
```


## 7. Exercise 1

Create a file with these contents, and make sure you can compile it:

```
#include <iostream>
using std::cout;

int main() {
    cout << "hello world\n";
    return 0;
}
```

## 8. Separate compilation



- Large programs best broken into small files,
- ... and compiled separately (can you guess why?)
- Then 'linked' into a program; linker is usually the same as the compiler.

## 9. Exercise 2

Make the following files:

Main program: fooprogram.cxx

```
#include <iostream>
using std::cout;
#include <string>
using std::string;

extern void bar(string);

int main() {
    bar("hello world\n");
    return 0;
}
```

Subprogram: foosub.cxx

```
#include <iostream>
using std::cout;
#include <string>
using std::string;

void bar( string s ) {
    cout << s << '\n';
}
```

## 10. Exercise 2 continued

- Compile in one:

```
icc -o program fooprogram.c foosub.c
```

- Compile in steps:

```
icc -c fooprogram.c
```

```
icc -c foosub.c
```

```
icc -o program fooprogram.o foosub.o
```

What files are being produced each time?

Can you write a shell script to automate this?

# 11. Header files

- `extern` is not the best way of dealing with 'external references'
- Instead, make a header file `foo.h` that only contains

```
void bar(char*);
```

- Include it in both source files:

```
#include "foo.h"
```

- Do the separate compilation calls again.

Now is a good time to learn about makefiles ...

## 12. Compiler options 101

- You have just seen two compiler options.

- Commandlines look like

`command [ options ] [ argument ]`

where square brackets mean: 'optional'

- Some options have an argument

`icc -o myprogram mysource.c`

- Some options do not.

`icc -g -o myprogram mysource.c`

- Question: does `-c` have an argument? How can you find out?

`icc -g -c mysource.c`

## 13. Object files

- Object files are unreadable. (Try it. How do you normally view files? Which tool sort of works?)
- But you can get some information about them.

```
#include <stdlib.h>
#include <stdio.h>
void bar(char *s) {
    printf("%s",s);
}
```

```
[c:264] nm foosub.o
0000000000000000 T _bar
U _printf
```

Where T: stuff defined in this file  
U: stuff used in this file



## 14. Compiler options 102

- Optimization level: -O0, -O1, -O2, -O3  
(‘I compiled my program with oh-two’)  
Higher levels usually give faster code. Level 3 can be unsafe.  
(Why?)
- -g is needed to run your code in a debugger. Always include this.
- The ultimate source is the ‘man page’ for your compiler.

# 15. Compiler optimizations

Common subexpression  
elimination:

```
x1 = pow(5.2,3.4) * 1;  
x2 = pow(5.2,3.4) * 2;
```

becomes

```
t = pow(5.2,3.4);  
x1 = t * 1;  
x2 = t * 2;
```

Loop invariants lifting

```
for (int i=0; i<1000; i++)  
    s += 4*atan(1.0) / i;
```

becomes

```
t = 4*atan(1.0);  
for (int i=0; i<1000; i++)  
    s += t / i;
```

## 16. Example of optimization

Givens program **missing snippet givensfun** Run with optimization level 0,1,2,3 we get:

Done after 8.649492e-02

Done after 2.650118e-02

Done after 5.869865e-04

Done after 6.787777e-04

## 17. Exercise 3

The file `rotate.c` can be speeded up by compiler transformations. Compile this file with optimization levels 0,1,2,3 (try both the Intel and gcc compilers) observe run time and conjecture what transformations can explain this.

Apply these transformations by hand and see if they indeed lead to improvements.

Write a report of your investigations.