


Smart Pointers

Victor Eijkhout, Susan Lindsey

Fall 2024

last formatted: October 14, 2024

1. Motivating application: linked list



- Used inside operating systems
- Model for complicated structures: trees, DAGs.

2. Recursive data structures

Naive code:

```
class Node {  
private:  
    int value;  
    Node tail;  
    /* ... */  
};
```

This does not work: would take infinite memory.

Indirect inclusion: only 'point' to the tail:

```
class Node {  
private:  
    int value;  
    PointToNode tail;  
    /* ... */  
};
```

3. Pointer types

- Smart pointers. You will see 'shared pointers'.
- There are 'unique pointers'. Those are tricky.
- Please don't use old-style C pointers, unless you become very advanced.

4. Example: step 1, we need a class

Simple class that stores one number:

Definition:

```
1 // pointer/pointx.cpp
2 class HasX {
3 private:
4     double x;
5 public:
6     HasX( double x) : x(x) {};
7     auto value() { return x; };
8     void set(double xx) {
9         x = xx; };
10};
```

Example usage

```
1 // pointer/pointx.cpp
2 HasX xobj(5);
3 cout << xobj.value() << '\n';
4 xobj.set(6);
5 cout << xobj.value() << '\n';
```

5. Example: step 2, creating the pointer

Allocation of object and pointer to it in one:

```
auto X = make_shared<HasX>( /* args */ );
```

```
// or explicitly:
```

```
shared_ptr<HasX> X =  
    make_shared<HasX>( /* constructor args */ );
```

6. Use of a shared pointer

Object vs pointed-object:

Code:

```
1 // pointer/pointx.cpp
2 #include <memory>
3 using std::make_shared;
4
5 /* ... */
6 HasX xobj(5);
7 cout << xobj.value() << '\n';
8 xobj.set(6);
9 cout << xobj.value() << '\n';
10
11 auto xptr =
12     make_shared<HasX>(5);
13 cout << xptr->value() << '\n';
14 xptr->set(6);
15 cout << xptr->value() << '\n';
```

Output:

5
6
5
6

7. Example: step 3: headers to include

Using smart pointers requires at the top of your file:

```
#include <memory>
using std::shared_ptr;
using std::make_shared;

using std::unique_ptr;
using std::make_unique;
```

(unique pointers will not be discussed further here)

8. Example: step 4: in use

Set two pointers to the same object:

Code:

```
1 // pointer/pointx.cpp
2 auto xptr = make_shared<HasX>(5);
3 auto yptr = xptr;
4 cout << xptr->value() << '\n';
5 yptr->set(6);
6 cout << xptr->value() << '\n';
```

Output:

5
6

What is the difference with

```
HasX xptr(5);
HasX yptr = xptr
cout << ...stuff...
```

?

9. Pointer dereferencing

Example: function

```
float distance_to_origin( Point p );
```

How do you apply that to a `shared_ptr<Point>`?

```
shared_ptr<Point> p;  
distance_to_origin( *p );
```

10. Null pointer

Initialize smart pointer to null pointer; test on null value:

```
shared_ptr<Foo> foo_ptr = nullptr;  
// stuff  
if (foo_ptr!=nullptr)  
    foo_ptr->do_something();
```

Exercise 1

With this code given:

Code:

```
1 // pointer/dynrectangle.cpp
2 float dx( Point other ) {
3     return other.x-x; };
4 /* ... */
5 // main, with objects
6 Point
7     oneone(1,1), fivetwo(5,2);
8 float dx = oneone.dx(fivetwo);
9 /* ... */
10 // main, with pointers
11 auto
12     oneonep = make_shared<Point>(1,1),
13     fivetwop = make_shared<Point>(5,2);
```

Output:

dx: 4

dx: 4

compute the dx between the *oneonep* & *fivetwop*.

You can base this off the file *dynrectangle.cpp* in the repository

Exercise 2

Make a *DynRectangle* class, which is constructed from two shared-pointers-to-*Point* objects:

```
1 // pointer/dynrectangle.cpp
2 auto
3   origin  = make_shared<Point>(0,0),
4   fivetwo = make_shared<Point>(5,2);
5 DynRectangle lielow( origin,fivetwo );
```

Exercise 3

Test this design: Calculate the area, scale the top-right point, and recalculate the area:


Code:

```
1 // pointer/dynrectangle.cpp
2 cout << "Area: " <<
    lielow.area() << '\n';
3 /* ... */
4 cout << "Area: " <<
    lielow.area() << '\n';
```

Output:

```
Area: 10
Area: 40
```

11. For the next exercise



Exercise 4

Make two *DynRectangle* objects so that the top-right corner of the first is the bottom-left corner of the other.

Now shift that point. Print out the two areas before and after to check correct behavior.

Automatic memory management

12. Memory leaks

C has a 'memory leak' problem

```
// the variable `array' doesn't exist
for ( /* lots of iterations */ ) {
    // attach memory to `array':
    double *array = new double[N];
    // do something with array;
    // forget to free
}
// the variable `array' does not exist anymore
// but the memory is still reserved.
```

The application 'is leaking memory'.

Java/Python have 'garbage collection': runtime impact

C++ has the best solution: smart pointers with reference counting.

13. Illustration

We need a class with constructor and destructor tracing:

```
1 // pointer/ptr1.cpp
2 class thing {
3 public:
4     thing() { cout << ".. calling constructor\n"; };
5     ~thing() { cout << ".. calling destructor\n"; };
6 };
```

14. Constructor / destructor in action

Code:

```
1 // pointer/ptr0.cpp
2 cout << "Outside\n";
3 {
4     thing x;
5     cout << "create done\n";
6 }
7 cout << "back outside\n";
```

Output:

```
Outside
.. calling
    ↪ constructor
create done
.. calling destructor
back outside
```

15. Illustration 1: pointer overwrite

Let's create a pointer and overwrite it:

Code:

```
1 // pointer/ptr1.cpp
2 cout << "set pointer1"
3     << '\n';
4 auto thing_ptr1 =
5     make_shared<thing>();
6 cout << "overwrite pointer"
7     << '\n';
8 thing_ptr1 = nullptr;
```

Output:

```
set pointer1
.. calling
    ↪ constructor
overwrite pointer
.. calling destructor
```

16. Illustration 2: pointer copy

Code:

```
1 // pointer/ptr2.cpp
2 cout << "set pointer2" << '\n';
3 auto thing_ptr2 =
4     make_shared<thing>();
5 cout << "set pointer3 by copy"
6     << '\n';
7 auto thing_ptr3 = thing_ptr2;
8 cout << "overwrite pointer2"
9     << '\n';
10 thing_ptr2 = nullptr;
11 cout << "overwrite pointer3"
12     << '\n';
13 thing_ptr3 = nullptr;
```

Output:


```
set pointer2
.. calling
    ↪ constructor
set pointer3 by copy
overwrite pointer2
overwrite pointer3
.. calling destructor
```

17. Reference counting

- The object counts how many pointers there are:
- 'reference counting'
- A pointed-to object is deallocated if no one points to it.

Example: linked lists

18. Linked list



You can base this off the file `linkshared.cpp` in the repository

19. Definition of List class

A linked list has as its only member a pointer to a node:

```
1 // tree/linkshared.cpp
2 class List {
3 private:
4     shared_ptr<Node> head{nullptr};
5 public:
6     List() {};
```

Initially null for empty list.

20. Definition of Node class

A node has information fields, and a link to another node:

```
1 // tree/linkshared.cpp
2 class Node {
3 private:
4     int datavalue{0},datacount{0};
5     shared_ptr<Node> next{nullptr};
6 public:
7     Node() {};
```

```
8     Node(int value,shared_ptr<Node> next=nullptr)
9         : datavalue(value),datacount(1),next(next) {};
```

A Null pointer indicates the tail of the list.

21. List methods

List testing and modification.

```
List mylist;  
cout << "Empty list has length: "  
      << mylist.length() << '\n';  
  
mylist.insert(3);  
cout << "After one insertion the length is: "  
      << mylist.length() << '\n';  
if (mylist.contains_value(3))  
    cout << "Indeed: contains 3" << '\n';
```

22. Recursive functions

- List structure is recursive
- Algorithms are naturally formulated recursively.

23. Recursive length computation

For the list:

```
1 // tree/linkshared.cpp
2 int List::length() {
3     int count = 0;
4     if (head==nullptr)
5         return 0;
6     else
7         return head->length();
8 };
```

For a node:

```
1 // tree/linkshared.cpp
2 int Node::length() {
3     if (!has_next())
4         return 1;
5     else
6         return 1+next->length();
7 };
```

24. Iterative functions

- Recursive functions may have performance problems
- Iterative formulation possible

25. Iterative computation of the list length

Use a shared pointer to go down the list:

```
1 // tree/linkshared.cpp
2 int List::length_iterative() {
3     int count = 0;
4     if (head!=nullptr) {
5         auto current_node = head;
6         while (current_node->has_next()) {
7             current_node = current_node->nextnode(); count += 1;
8         }
9     }
10    return count;
11 };
```

(Fun exercise: can do an iterative de-allocate of the list?)

26. Print a list

Auxiliary function so that we can trace what we are doing.


Print the list head:

```
1 // tree/linkshared.cpp
2 void List::print() {
3     cout << "List:";
4     if (head!=nullptr)
5         cout << " => ";
6         head->print();
7     cout << '\n';
8 }
```

Print a node and its tail:

```
1 // tree/linkshared.cpp
2 void Node::print() {
3     cout << datavalue << ":" <<
4         datacount;
5     if (has_next()) {
6         cout << ", "; next->print();
7     }
8 }
```

27. Creating the first list element




Exercise 5

Next write the case of *Node::insert* that handles the empty list. You also need a method *List::contains* that tests if an item is in the list.

```
1 // tree/linkshared.cpp
2 myList.insert(3);
3 cout << "After inserting 3 the length is: "
4     << myList.length() << '\n';
5 if (myList.contains_value(3))
6     cout << "Indeed: contains 3" << '\n';
7 else
8     cout << "Hm. Should contain 3" << '\n';
9 if (myList.contains_value(4))
10    cout << "Hm. Should not contain 4" << '\n';
11 else
12    cout << "Indeed: does not contain 4" << '\n';
13 cout << '\n';
```

28. Elements that are already in the list




Exercise 6

Inserting a value that is already in the list means that the *count* value of a node needs to be increased. Update your *insert* method to make this code work:

```
1 // tree/linkshared.cpp
2 mylist.insert(3);
3 cout << "Inserting the same item gives length: "
4     << mylist.length() << '\n';
5 if (mylist.contains_value(3)) {
6     cout << "Indeed: contains 3" << '\n';
7     auto headnode = mylist.headnode();
8     cout << "head node has value " << headnode->value()
9         << " and count " << headnode->count() << '\n';
10 } else
11     cout << "Hm. Should contain 3" << '\n';
12 cout << '\n';
```

29. Element at the head




Exercise 7

One of the cases for inserting concerns an element that goes at the head. Update your *insert* method to get this to work:

```
1 // tree/linkshared.cpp
2 mylist.insert(2);
3 cout << "Inserting 2 goes at the head;\nnow the length is: "
4     << mylist.length() << '\n';
5 if (mylist.contains_value(2))
6     cout << "Indeed: contains 2" << '\n';
7 else
8     cout << "Hm. Should contain 2" << '\n';
9 if (mylist.contains_value(3))
10    cout << "Indeed: contains 3" << '\n';
11 else
12    cout << "Hm. Should contain 3" << '\n';
13 cout << '\n';
```

30. Element at the tail





Exercise 8

If an item goes at the end of the list:

```
1 // tree/linkshared.cpp
2 mylist.insert(6);
3 cout << "Inserting 6 goes at the tail;\nnow the length is: "
4     << mylist.length()
5     << '\n';
6 if (mylist.contains_value(6))
7     cout << "Indeed: contains 6" << '\n';
8 else
9     cout << "Hm. Should contain 6" << '\n';
10 if (mylist.contains_value(3))
11     cout << "Indeed: contains 3" << '\n';
12 else
13     cout << "Hm. Should contain 3" << '\n';
14 cout << '\n';
```

31. Insertion



Exercise 9

Update your insert routine to deal with elements that need to go somewhere in the middle.

```
1 // tree/linkshared.cpp
2 mylist.insert(4);
3 cout << "Inserting 4 goes in the middle;\nnow the length is: "
4     << mylist.length()
5     << '\n';
6 if (mylist.contains_value(4))
7     cout << "Indeed: contains 4" << '\n';
8 else
9     cout << "Hm. Should contain 4" << '\n';
10 if (mylist.contains_value(3))
11     cout << "Indeed: contains 3" << '\n';
12 else
13     cout << "Hm. Should contain 3" << '\n';
14 cout << '\n';
```

32. Linked list exercise

Write a program that constructs a linked list where the elements are sorted in increasing numerical order.

Your program should accept a sequence of numbers from interactive input, and after each number print the list for as far as it has been constructed. Print the list on a single line, with elements separated by commas.

An input value of zero signals the end of input; this number is not added to the list.