

MATHEMATICS

Fitting and machine learning

Teaching with AI (TAI)

Mirte van der Eyden[1], Andrea López Incera[2]

[1] Institut für Fachdidaktik, Universität Innsbruck
mirte.van-der-eyden@uibk.ac.at

[2] Departament de didàctica de la matemàtica i les ciències experimentals, Universitat Autònoma de Barcelona
andrea.lopez.incera@uab.cat

universität innsbruck

UAB Universitat Autònoma de Barcelona

Co-funded by the European Union

European International School of Barcelona

2ο ΠΕΝΙΚΟ ΛΥΚΕΙΟ ODYSSEAS ELYTIS MORE THAN A HIGH-SCHOOL

next VIBENSHUS GYMNASIUM

Project funded by Erasmus+ Programme of the European Union

Subject: Mathematics

Activity duration: 220 min, split over three sessions of about 75, 65 and 80 minutes.

Steps:

1. Intro and connection to exoplanets (15 min)
2. Linear regression and loss functions (60 min)
3. Fitting functions (50 min)
4. Neural networks presentation (15 min)
5. Working with a neural network (45 min)
6. Discover Kepler's Law (20 min)
7. Application to exoplanet (15 min)

The first session (steps 1–2) takes about 75 minutes, the second (steps 3–4) about 65 minutes and the third (steps 5–7) about 80 minutes.
Learning goals:

- Modelling a relationship in data with a function, and fitting it by tuning parameters
- Loss functions and the mean squared error (MSE)
- Linear regression, and finding the optimal fit by minimising the loss (by reasoning, by calculus, and the idea behind gradient descent)
- Comparing different models (linear, quadratic, power law) and choosing the best one
- Training and testing data, and why a model must generalise
- What machine learning and neural networks are, and how they are trained
- Interpretable models versus flexible "black-box" models, and when to use each type
- Using Python (and, optionally, an AI assistant) to fit models, and checking the results critically
- Rediscovering Kepler's third law from data, and using it to find an exoplanet's orbit

Fitting and machine learning

A mathematics lesson about AI

In this lesson, we follow in the footsteps of Johannes Kepler. Starting with a table of planetary data, we learn how to fit mathematical models, measure how well they describe the data, and explore how machine learning and neural networks find patterns. We also consider when these methods are useful and when a simpler model is preferable. Along the way, we rediscover one of the most famous laws in astronomy and use it to determine the orbit of an exoplanet.

1 Introduction

An exoplanet's orbital period can be determined from its transit light curve. The orbital period is the time the planet takes to complete one orbit around its star. Earth's orbital period is one year, whereas known exoplanets have periods ranging from a few hours to many years.
The orbital period can reveal further information about a planet's orbit. In this lesson, you will learn how to estimate the size of a planetary orbit from its period.
Planets move in elliptical orbits around their host stars (Figure 1). Johannes Kepler discovered this in the early 17th century, before Newton developed his laws of motion and universal gravitation. Kepler analysed Tycho Brahe's precise observations of planetary positions and concluded that the planets follow elliptical rather than circular paths.
Because an orbit is elliptical, the planet's distance from its star changes throughout the orbit. When astronomers describe the size of an orbit, they usually use its *semi-major axis*. This distance is indicated in Figure 1.




Figure 1: An elliptical planetary orbit with the semi-major axis indicated in red.

Initial ideas

Question 1: Why is it interesting to know the distance from an exoplanet to its star?

Question 2: Can a planet orbit its host star at any speed? Explain your reasoning.

Question 3: Do you expect a relationship between an exoplanet's orbital period and the semi-major axis of its orbit? If so, what relationship do you predict, and why?

To test whether such a relationship exists, we need observations of planets for which both the orbital period and the semi-major axis are known. We therefore begin with the planetary system closest to us: the Solar System. Because its planets are relatively nearby, astronomers can determine their positions, orbital periods, and distances using several observational methods. Tycho Brahe made exceptionally precise measurements of planetary positions in the late 16th century. The orbital periods and semi-major axes of the Solar System planets are shown in Figure 2.

Kepler studied Brahe's data and found a mathematical relationship between orbital period and orbital size. He formulated this relationship as what we now call *Kepler's third law*. Kepler lived before Newton and therefore did not know the law of universal gravitation. Although Kepler's physical explanation for planetary motion was incorrect, the mathematical pattern he identified in the data was accurate.

Today, we follow in Kepler's footsteps and try to discover the relationship between orbital period and semi-major axis directly from the data. We also have tools that Kepler did




Figure 2: Orbital periods and semi-major axes of the planets in the Solar System.

not: computers, neural networks, and other machine-learning methods. How can machine learning help us find relationships in data, and what limitations does it have?

The Challenge

Challenge: Discover the relationship between planetary orbital period and semi-major axis, then use it to estimate the distance between your exoplanet and its star.

To complete this challenge, you will work through the following steps:

1. Fit and compare several possible relationships, including linear, quadratic, and power-law models.
2. Explore the basic ideas behind machine learning and neural networks.
3. Rediscover Kepler's third law and apply it to an exoplanet.

Constructing new ideas

2 Linear regression and loss functions

To find a relationship in the data, we describe it with a *model*: a mathematical function that takes an input (here, the orbital period T) and returns a prediction for an output (here, the semi-major axis a). A model has one or more *parameters*: numbers that we are free to choose. *Fitting* a model means adjusting these parameters until the model matches the data as closely as possible.

The simplest relationship we can try is a *linear* one: a straight line. In this section, we fit a straight line to data from the inner planets, define what it means for a fit to be "good", and find the best possible line. Along the way, we encounter two ideas that lie at the heart of machine learning: the *loss function* and the distinction between *training data* and *testing data*.

Assignment 1: Finding the best fit

The graph shows orbital period versus distance for the four planets closest to the Sun.




Figure 3: Orbital period and semi-major axis of the four inner planets in the Solar System.

The exact data values are given in the table below.

Planet	Orbital period (years)	Semi-major axis (AU)
Mercury	0.240847	0.387099
Venus	0.615197	0.723332
Earth	1.000017	1.000000
Mars	1.880816	1.523662

Remember that our goal is to predict a planet's orbital size (its semi-major axis a) from its orbital period T. We therefore treat T as the input and place it on the horizontal axis, while a is the output and appears on the vertical axis.

Question 4: Describe the relationship you see in the data.

Question 5: Could this relationship be linear? What would a linear model look like on the graph?

To learn how fitting works, we start with a linear fit. For the simplest version of a linear fit, we require the line to pass through the origin. We use a model of the form $y = cx$, where x is the orbital period T, y is the semi-major axis a, and c is the single adjustable parameter: the slope.

a) Draw a linear fit through the four data points.

Question 6: How good is this fit? Do you think this captures the relation between the points?

Question 7: How would you quantify how good this fit is?

We define a function, called the *Loss function (L)*, that quantifies how far our model/fit is away from the actual data points. Naively, it comes down to calculating how far the points in your plot are distanced from the line that you drew. As modellers, we have to choose how exactly to define our loss function.
In this lesson, we choose to calculate the loss function with the *mean squared error (MSE)*. This can be calculated with the following steps:

1. For every data point (x_i, y_i) that you have, you draw the point $(x_i, \hat{y}_i)$ that lies on the fitting line.
2. For every data point, measure the difference between y_i and $\hat{y}_i$. This is the difference between where your data point is, and where your model predicts it to be and is called the *error*.
3. Calculate the *square* of this error for every data point.
4. Calculate the *mean* value of these squares, over all data points.

Together this forms the following formula for the *mean square error (MSE)*:

$$MSE = \frac{1}{n}\sum_{i}^{n}(y_i - \hat{y}_i)^2.$$

We define our loss function to be the mean square error.

$$L = MSE.$$

b) Calculate the MSE for your fit. Use the space below for your calculation.

$MSE =$ [ ]

Question 8: How satisfied are you with your fit? Do you think this is the most optimal fit possible?

We want to find the *optimal* fit: the one for which the MSE is as low as possible. There are two different ways to reach it. Choose the route that matches what you have learned so far. You only need to do *one* of them.

Choose your route:

- **Route 1: Optimize by hand.** If you have *not* learned how to differentiate yet, follow Route 1. You will improve your fit by hand and reason about how to find the very best one.
- **Route 2: Optimize with calculus.** If you *do* know how to differentiate, skip Route 1 and go straight to Route 2, where you compute the optimal fit exactly.

Route 1: Optimize by hand

To find a better fit, it helps to compare your fit with another one. On the graph below you can draw a second attempt.

c) Draw another possible fit and again calculate the MSE. Make it really different. If you did not manage to improve on your previous fit, draw any other (possibly worse) option and still calculate the MSE.

Question 9: Which fit was better?




Figure 4: Period and semi major axis of the first four planets in our solar system.

Both fits you drew have the form $\hat{y} = cx$. The value of c completely determines the fit.

d) Determine the slope c of each of your two attempts, and complete the table below with each value of c and its corresponding MSE.

c	MSE

For every value of c we get a different value of MSE. Finding the best fit means finding the c for which the MSE is lowest. You are now going to reason about how to get there step by step, without any advanced mathematics.

Question 10: Look at your table. As you change c, what happens to the MSE? Does it always change in the same direction?

Question 11: Suppose you compute the MSE for your value of c, and then again for a slightly *larger* c. How does comparing these two values tell you whether you should increase or decrease c to lower the MSE?

Question 12: Describe a step-by-step procedure that starts from any guess for c and gets closer and closer to the best value, using only your ability to compute the MSE. How would you decide in which direction to step, how big your steps should be, and when to stop?

e) Using this reasoning, find the best value of c you can by hand, and write down your best model.

$\hat{y} =$

Route 1 is complete. Continue at "Testing the model" below.

Route 2: Optimize with calculus

Instead of guessing, we can find the optimal c exactly. We treat the MSE as a function of c and look for the minimum of that function.
Recall that the MSE is

$$MSE = \frac{1}{n}\sum_{i}^{n}(y_i - \hat{y}_i)^2,$$

and that our linear model predicts $\hat{y}_i = c\,x_i$.

Question 13: Substitute $\hat{y}_i = c\,x_i$ into the formula above, to write the MSE as a function of c. Then draw a circle around every c that appears: this is the variable of your function.

In this formula, the only quantity you are free to change is c; it is the *variable* of the function. The numbers x_i and y_i are the measured planet data, so they are fixed *constants*. When you differentiate, you may treat them exactly like ordinary numbers. Because there are only four inner planets ($n = 4$), you may also write the sum out in full, as four terms, instead of using the $\sum$ sign.

Question 14: How can we find the value of c for which $MSE(c)$ is smallest? Which tool from mathematics do you know for finding the minimum of a function?

Chain-rule reminder. Use the chain rule when one function is placed inside another. If

$$F(c) = f\big(g(c)\big),$$

then

$$F'(c) = f'\big(g(c)\big) \cdot g'(c).$$

In words: identify the inside function, differentiate the outside function while leaving the inside unchanged, and then multiply by the derivative of the inside function. Think: *outside derivative times inside derivative.*

Question 15: Step 1. Take the derivative of $MSE(c)$ with respect to c. Remember that c is the variable, while x_i and y_i are constants.

Question 16: Step 2. A function has a minimum where its derivative equals zero. Write down the equation you obtain by setting your derivative from Step 1 equal to zero.

Question 17: Step 3. Solve this equation for c.

Question 18: Use the data of the four inner planets to compute this optimal value of c and the resulting MSE. Then write down your best model $\hat{y} = c\,x$.

Testing the model

Both routes continue here. Whichever route you took, you now have your own best linear model $\hat{y} = cx$.

So far we have only used the four planets closest to the Sun. We call this the *training data*: the data we used to build, or train, our model. However, a good model should also make correct predictions for data that it has *not* seen before. To check this, we keep some data apart as the *testing data* and see how well the model predicts it.

The graph below shows *all eight* planets of the solar system. The four inner planets, near

the origin, are your training data; the four outer planets are the testing data, which your model has never seen.




Figure 5: Period and semi major axis of all eight planets in our solar system.

f) Draw your best model $\hat{y} = cx$ (the straight line with the slope you found) in Figure 5.

Question 19: Look at your line together with the four outer planets. Judging by eye, does your model describe the outer planets well?

Let us now put a number on this. Table 1 summarises the exact data for all eight planets. The four inner planets are the training data, while the four outer planets are the testing data.

Table 1: Orbital periods and semi-major axes of the eight planets in the Solar System.

Planet	Orbital period (years)	Semi-major axis (AU)	Data use
Mercury	0.240847	0.387099	Training
Venus	0.615197	0.723332	Training
Earth	1.000017	1.000000	Training
Mars	1.880816	1.523662	Training
Jupiter	11.862615	5.203363	Testing
Saturn	29.447498	9.537070	Testing
Uranus	84.016846	19.191264	Testing
Neptune	164.791320	30.068963	Testing

g) Use your own best model $\hat{y} = cx$ (with the value of c that you found) to predict the semi major axis of each outer planet, and compute the MSE on this testing data.

$MSE_{\text{test}} =$

Question 20: Do you think a linear model is suited to describe this data? Why (not)?

Question 21: What are the advantages and disadvantages of using *all* of your data to build the model, versus keeping some data apart to test it at the end?

3 Fitting functions

In the previous section, you found the best possible *straight line* through the data and saw that it fails badly for the outer planets. Perhaps the relationship between period and distance is simply not linear, and a function with a different shape, namely a curve, describes the data better.
To find out, we could try many different models and, for each one, compute the loss (MSE) as we did before. But doing this by hand, over and over, is a lot of work. This is exactly the kind of repetitive calculation that a computer does well. From here on we let Python fit the models and compute the loss for us.
We will compare three types of model:

- a **linear** model, $a = cT$ (a straight line through the origin, as in Section 2);
- a **quadratic** model, $a = \alpha T^2 + \beta T + \gamma$ (a parabola);
- a **power-law** model, $a = CT^p$ (a curve whose steepness is set by the exponent p).

Choose one of the following two ways to complete this part:

- **Option A: Guided notebook.** Open the notebook `Mathematics_Fitting_and_machine_learning.ipynb`. This notebook is ready to run: it loads the data, reproduces the linear fit you made by hand, and fits all three models, printing the loss (MSE) of each. Run the cells one by one and read what happens.
- **Option B: Write it yourself with AI.** Open the notebook `Mathematics_Fitting_and_machine_learning_AI_version.ipynb`. Here, only the data is given. For each model, write the Python code yourself with the help of an AI language model (LLM). Ask it to plot the data and fit the linear, quadratic, and power-law models; then run its code and check that the result makes sense.

Whichever option you choose, answer the questions below.

Question 22: The notebook first reproduces the linear fit through the four inner planets. Which value of c does it find, and does it agree with the value you found by hand in Section 2?

Question 23: Run the fits of the three models on all eight planets, and write the loss (MSE) of each model in the table. Which model has the lowest loss?

Model	MSE
Linear $a = cT$	
Quadratic $a = \alpha T^2 + \beta T + \gamma$	
Power law $a = C\,T^p$	

Question 24: Look at the plots of the fitted models. Which model follows the data points best across the *whole* range, from Mercury to Neptune?

Question 25: The power-law model is $a = C\,T^p$. What values did the fit find for C and for the exponent p? Keep the exponent in mind because we will return to it later.

Question 26: Why is it useful to try several different models, instead of just picking one and hoping it is right?

Question 27: Why can the power law, with only two parameters, beat the

quadratic, which has three?

Question 28: ***(Option B only.)*** **Which instructions, or "prompts", did you give the AI to obtain the code? Did the code work the first time, or did you have to correct it? How did you check that the result was actually right?**

4 Neural networks

In the previous section, you chose a *formula* for your model, such as a line, a parabola, or a power law, and then adjusted its few parameters to make the loss small. *Machine learning* takes a similar approach: instead of choosing a formula, we use a very flexible model with *many* parameters and let the computer adjust all of them automatically to make the loss small.

The best-known model of this type is the *neural network*. A simplified example is shown in Figure 6. It is built from many small units ("neurons") connected by adjustable parameters called *weights*. Each choice of weights produces a different function and therefore different predictions.

Training a neural network is still function fitting. In Section 2, your model was the function $\hat{y} = cx$. You adjusted the parameter c to make the loss as small as possible. A neural network follows exactly the same principle, but its function contains many adjustable weights instead of one parameter. The computer makes predictions, calculates the loss, changes the weights to reduce the loss, and repeats this process. This repeated minimisation of the loss function is called *training*. Gradient descent tells the computer how to adjust the weights at each step.




Figure 6: A simplified neural network that uses the orbital period T to predict the semi-major axis a. During training, the network adjusts the parameters of the connections to reduce the loss function.

Why gradient descent is needed

For the linear model $\hat{y} = cx$, the loss $MSE(c)$ was a simple function of one parameter. In Route 2, you differentiated this function, set the derivative equal to zero, and solved an equation to find the minimum exactly.

The loss of a neural network is also a mathematical function, but it depends on many weights at the same time:

$$L = L(w_1, w_2, \ldots, w_k).$$

This function has derivatives, but it is usually far too complicated to solve all the equations for the global minimum exactly. Instead, the computer calculates the *local gradient*: the derivatives of the loss at the current values of the weights. The gradient shows the direction in which the loss increases most quickly, so moving a small step in the opposite direction should lower the loss.

The computer then calculates the gradient again at the new point and takes another small step. This process combines the derivative information from Route 2 with the repeated improvements from Route 1. Repeating these local steps is called *gradient descent*, as illustrated in Figure 7.




Figure 7: Gradient descent on a one-dimensional slice of a loss landscape. At each point, the local derivative determines the downhill direction. After a small step, the derivative is calculated again. A real neural network has many weights, so its loss landscape has many dimensions.

Question 29: In Section 2 you tuned a single parameter c by hand. A neural network can have thousands of parameters. Why is it impossible to tune these by hand, and what do we need instead?

Question 30: A neural network can fit almost any shape. Can you think of an advantage *and* a possible disadvantage of using such a very flexible model?

5 Working with neural network models

How good would a neural network be in predicting the semi-major axis from the orbital period? Let us now train a neural network on our planet data, and see how it compares with the models you have already tried.

Choose one of the following two ways to complete this part:

- **Option A: Guided notebook.** Open the notebook `Mathematics_Neural_network.ipynb`. This notebook is ready to run: it loads the data, trains a small neural network to predict the semi-major axis from the period, plots the fit, and compares it with the power law from Section 3. At the end, there are extensions to try, such as larger networks and other activation functions.
- **Option B: Write it yourself with AI.** Open the notebook `Mathematics_Neural_network_AI_version.ipynb`. Here, only the data is given. Build and train the network yourself with the help of an AI language model (LLM). Ask it to scale the data, build and train the network, plot the fit, and compare it with the power law; then run its code and check the result.

Whichever option you choose, answer the questions below.

Question 31: Does the neural network manage to follow the data? Write down its loss (MSE), and compare it with the loss of the power-law model from Section 3.

Question 32: How many parameters (weights) does the neural network use, and how many does the power law use? Which model is simpler?

Question 33: In the extensions you tried larger networks and different activation functions. Did a bigger network always give a lower loss? Which activation followed the data best?

Question 34: Both the power law and the neural network fit the eight

planets well. If you had to predict the orbit of a completely new planet, far outside the range of our data, which model would you trust more, and why?

Question 35: Which of the two models provides an interpretable relationship that helps you *understand* nature, and which is a "black box" of numbers?

Question 36: *(Option B only.)* Which prompts did you give the AI to build and train the network? Did its code work the first time? How did you check that the network's result was sensible?

When is a neural network the better choice?

For our planet problem, the interpretable power law beat the neural network: we had only a few data points, and there was a clean underlying law. But this is not always the case. Neural networks work well when there is a *lot* of data and *no* simple formula to be found.

A striking example comes from the search for exoplanets itself. Recall from the introduction that a planet passing in front of its star makes the star's brightness dip a little; the record of the brightness over time is called a *light curve* (Figure 8). Space telescopes such as Kepler and TESS measured the light curves of *hundreds of thousands* of stars.




Figure 8: A transit light curve: each time the planet passes in front of its star, the measured brightness dips a little. Real data are noisy, and most dips are not caused by planets.

The catch is that most dips are *not* planets. Pairs of stars eclipsing each other, dark spots on a star's surface, and instrument noise all produce look-alike signals. There is no neat formula that separates a real planet from a false alarm, and there are far too many candidates to check by hand. This is the opposite of the situation with Kepler's law: an enormous amount of data, and no simple model.

This is exactly where neural networks shine. In 2018, researchers trained a neural network on thousands of labelled Kepler light curves. It learned to recognise real transits and even found a planet that people had missed, Kepler-90 i. This discovery made Kepler-90 the first star besides our Sun known to have *eight* planets.[1] In 2021, NASA's *ExoMiner* network validated 301 new exoplanets at once, more reliably than earlier software or human experts, and its successor now scans data from the TESS telescope.[2]

Question 37: For each of the two tasks below, would you choose an interpretable model or a flexible neural network, and why? (a) estimating a planet's radius from the transit depth when the radius of its star is known; (b) screening thousands of noisy atmospheric spectra to identify which ones may contain signs of water vapour.

[1] C. J. Shallue & A. Vanderburg, *Astronomical Journal* **155**, 94 (2018); the network is known as *AstroNet*.

[2] H. Valizadegan et al., *Astrophysical Journal* **926**, 120 (2022); the open-source *ExoMiner++* (2026) analyses TESS data. See also NASA Science.

Closing the challenge

6 Discover Kepler's Law

In Section 3 you found that the power-law model $a = C\,T^p$ fits the planet data almost perfectly, with

$$C \approx 1 \qquad \text{and} \qquad p \approx 0.667.$$

A neural network could also fit the data, but it hid the relationship inside many weights. The power law, by contrast, is simple enough to *read*. Let us now turn this fitted model into a physical law.

Question 38: The exponent $p \approx 0.667$ is very close to a simple fraction. Which fraction is it? Using $C \approx 1$, write down the resulting relation between a and T.

Question 39: Rewrite the relation $a = T^{2/3}$ without a fractional exponent, by raising both sides to the power 3. What equation do you get?

Congratulations! You have just rediscovered **Kepler's third law**:

$$T^2 = a^3,$$

where T is the orbital period in years and a is the semi major axis in AU. In words: *the square of the orbital period equals the cube of the semi major axis.* It took Johannes Kepler about ten years to extract this law from Tycho Brahe's observations; you found it from the data in a single afternoon.

The clean form $T^2 = a^3$ appears because we measured T in years and a in AU. These units are defined relative to Earth's orbit, for which $T = 1$ and $a = 1$. In other units, the law reads $T^2 \propto a^3$. Newton later showed *why* it holds: it follows from his law of gravity, and the full form is

$$T^2 = \frac{4\pi^2}{G\,M}\,a^3,$$

where M is the mass of the star and G is the gravitational constant. For a star with a different mass from the Sun, the constant changes. We will need this result in the next section.

Question 40: Check the law: use $a = T^{2/3}$ to predict the semi-major axis of Saturn, whose orbital period is $T = 29.45$ years. Compare your answer with the measured value in Table 1.

Question 41: We now have two things that both describe the data well: a neural network, and the simple law $T^2 = a^3$. Which of the two would you call a *law of nature*, and why?

Question 42: Kepler found this law purely from data, long before Newton explained it with gravity. Does finding a pattern in data always mean that we understand *why* it is true?

Now that we have Kepler's law, we can rearrange it. If we measure a planet's orbital period, we can *compute* its distance from the star, represented by its semi-major axis. In the next section, you will do exactly this for your own exoplanet.

7 Applying it to your own exoplanet

At the beginning of the lesson, we set you a challenge: find the distance between your exoplanet and its star. You now have everything you need: a way to measure the period from a transit light curve and Kepler's law to convert that period into a distance.
There is one extra ingredient. The law $T^2 = a^3$ holds for planets orbiting the *Sun*. Your exoplanet orbits a different star, with a different mass M. As we saw in the previous section, Newton's version of the law then becomes, when we measure the period T in years, the semi major axis a in AU, and the star's mass M in solar masses ($M_\odot$):

$$T^2 = \frac{a^3}{M}, \qquad \text{which we can solve for the distance:} \qquad a = \sqrt[3]{M\,T^2}.$$

For a star with the same mass as the Sun ($M = 1$) this is exactly the law you rediscovered.

Worked example. A planet with period $T = 2$ years, orbiting a star of mass $M = 1.2\,M_\odot$, has

$$a = \sqrt[3]{1.2 \times 2^2} = \sqrt[3]{4.8} \approx 1.69 \text{ AU},$$

so it orbits a little farther from its star than the Earth does from the Sun. *(A cube root is the same as raising to the power $\frac{1}{3}$ on your calculator.)*

Step 1: Find the period T. Your data sheet contains a transit light curve of your exoplanet. It shows the brightness of the star over time, with a dip each time the planet passes in front of it. The time between two consecutive dips is one orbital period.
Read the period T of your exoplanet from your transit light curve. To be more accurate, measure the total time across *several* transits and divide by the number of periods in between.
$T =$ ☐ years. (Add the value of T to your planet factsheet.)

Step 2: Write down your star's mass M. You can find the mass of your exoplanet's host star on your data sheet.
$M =$ ☐ solar masses ($M_\odot$)

Step 3: Compute the distance a. Substitute your values of T and M into the formula $a = \sqrt[3]{M\,T^2}$.

$a =$ AU. (Add the value of a to your planet factsheet.)

Step 4: Interpret your result.

Question 43: Is your exoplanet closer to or farther from its star than the Earth is from the Sun? Is there a planet in our solar system that has a similar distance?

Question 44: This week, you are gathering different pieces of information about your mystery planet. Now that you know its distance from its star, what might that tell you about the planet? For example, what could you infer about its temperature or whether it could have liquid water?

Well done! Challenge complete. Starting with only a table of numbers, you have followed in Kepler's footsteps: you fitted models, measured their loss, explored neural networks and machine learning, rediscovered Kepler's third law, and used it to find the distance between your exoplanet and its star.

What have we learned?

Question 45: What have you learned that you didn't know before?

Question 46: How have you used AI in this lesson, and what did you learn from it?

© 2026 “Teaching in AI” (TAI) Consortium.

This educational material was developed within the framework of the Erasmus+ project “Teaching in AI” (TAI) (2025-1-DK01-KA226-SCH-000365972).

Funded by the European Union.

The views and opinions expressed are those of the author(s) only and do not necessarily reflect those of the European Union or the granting authority. Neither the European Union nor the granting authority can be held responsible for them.

This material is licensed under the Creative Commons Attribution 4.0 International Licence (CC BY 4.0), unless otherwise indicated.