The Complexity Status of Graph Isomorphism

From Factorial Brute Force to Quasi-Polynomial Breakthrough

Presented by:

2005068	Suman Hossain
2005074	Dipanta Kumar Roy Nobo
2005090	Tawkir Aziz Rahman
2005091	Waseem Mustak Zisan
2005104	Md Hasin Arafat
2005109	Noushin Tabassum Aoishy

March 28, 2026

Department of Computer Science and Engineering
BUET

Outline

1. Introduction — What is Graph Isomorphism?
2. Complexity — Where Does GI Live?
3. Why Computers Struggle — The Matrix Problem
4. Babai's Breakthrough — 2015
5. The Weisfeiler-Lehman Test — Solving GI in Practice
6. Algorithms — A Progression
7. Special Cases — When GI Is Easy
8. Real-World Applications

Introduction — What is Graph Isomorphism?

Are These the Same Graph?



Graph G

?



Graph H

★ Human Intuition Fails Here

They *look* different — but are they structurally identical?
This is the **Graph Isomorphism Problem**.

The Word Isomorphism

Etymology

- **iso** (Greek) *equal*
- **morphe** (Greek) *shape*

⇒ **"Same shape"**



The Necklace Analogy

Tangle, stretch, or rearrange a necklace — the *connections* never change. The **structure** is what matters, not the picture.

Formal Definition

Definition — Graph Isomorphism

Two graphs $G = (V_G, E_G)$ and $H = (V_H, E_H)$ are **isomorphic** ($G \cong H$) if there exists a bijection:

$$f : V_G \longrightarrow V_H$$

such that for all $u, v \in V_G$:

$$(u, v) \in E_G \iff (f(u), f(v)) \in E_H$$

In plain English:

- If A and B are friends in G, their twins $f(A)$, $f(B)$ must be friends in H.
- No friendship is added or removed.
- It is a *structure-preserving* renaming.



Revealing the Mapping



G

$G \to H$
A $\to$ 1
B $\to$ 2
C $\to$ 5
D $\to$ 4
E $\to$ 3



H

$G \cong H$ — **They are the same graph!**

The mapping f is the proof.

Why is This a Problem?

Brute-Force Approach:

- Try *every possible* mapping f
- For n nodes: $n!$ possibilities

Scale of $n!$

Nodes	$n!$
5	120
10	3,628,800
20	$\approx 2.4 \times 10^{18}$
100	9.33×10^{157}

$\otimes$ Atoms in the observable universe:

$$\approx 10^{80}$$

$100! = 9.33 \times 10^{157}$

Vastly exceeds the number of atoms!

$\Rightarrow$ We need a **clever algorithm**.

Complexity — Where Does GI Live?

The "Map" of Computational Complexity



Why is GI Not Known to be in P?

? Why Not Easy (P)?

- No polynomial algorithm found that works for *every* graph.
- Highly **symmetric** graphs defeat most shortcuts.
- After decades of effort — still open!

? Why Not Hard (NP-Complete)?

- NP-Complete problems have *random* structure.
- GI has rich **mathematical structure** (Group Theory).
- It's more like a Rubik's Cube than a pile of tangled yarn!

⊞ The Rubik's Cube Analogy

NP-Complete: Tangled yarn — no structure to exploit.

GI: A Rubik's Cube — looks messy, but strict mathematical rules allow clever "twists."

Evidence: GI Cannot Be NP-Complete

▷ Schöning's Theorem (1988) [9]

If **Graph Isomorphism** were NP-Complete,
then the **Polynomial Hierarchy** would collapse.

What is the Polynomial Hierarchy?

- A tower of complexity levels above P and NP.
- Each level is "strictly harder" than the one below.
- A *collapse* means many "hard" problems become "easy" — widely believed to be **false**.

$\Rightarrow$ GI is **almost certainly not NP-Complete**.
It lives in the mysterious **NP-Intermediate** zone.

Why Computers Struggle — The Matrix Problem

How a Computer "Sees" a Graph



Graph G

Adjacency Matrix of G:

$$A_G = \begin{pmatrix} 0 & \mathbf{1} & \mathbf{1} & \mathbf{1} \\ \mathbf{1} & 0 & \mathbf{1} & 0 \\ \mathbf{1} & \mathbf{1} & 0 & \mathbf{1} \\ \mathbf{1} & 0 & \mathbf{1} & 0 \end{pmatrix}$$

- Entry $[i, j] = 1$ iff edge (i, j) exists.
- Node **labels** determine the matrix layout.

The Labelling Nightmare

Key insight: The same graph gives *different* matrices for different labellings!

Labelling 1



$$\begin{pmatrix} 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 0 \end{pmatrix}$$

Labelling 2 (same graph!)



$$\begin{pmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \end{pmatrix}$$

The computer must find: can we **permute rows & columns** of A_G to get A_H?
For n nodes $\Rightarrow$ $n!$ row/column permutations to check.

The Factorial Explosion



For $n = 100$: brute force needs $\sim 10^{157}$ steps — utterly infeasible.

The "No Corners" Problem — Regular Graphs

Regular Graph

Every node has the **same degree** (same number of neighbours).

- In a jigsaw puzzle ⇒ look for *corner pieces*.
- In GI with regular graphs ⇒ **all nodes look identical**.
- No unique starting point!
- The computer gets completely lost.



K_4: every node has degree 3

Babai's Breakthrough — 2015

November 2015 — A Bombshell

★ The Announcement

László Babai (University of Chicago) announced a

Quasi-Polynomial

time algorithm for Graph Isomorphism [1].

- Previous best: Luks (1983) [7] — sub-exponential.
- Babai improved it by an *exponential factor*.
- Considered one of the greatest TCS results of the 21st century.

László Babai
Univ. of Chicago
Computer Scientist

What is Quasi-Polynomial Time?

Babai's Algorithm Runs in Time:

$$2^{O((\log n)^c)} \quad \text{for some constant } c$$

Exponential (Old)

2^n

For $n = 100$:

$\approx 10^{30}$ steps

Quasi-Poly (Babai)

$2^{(\log n)^c}$

For $n = 100$:

$\approx 10^7$ steps

Polynomial (Goal)

n^k

For $n = 100$:

$\approx 10^6$ steps

Exponential $\gg$ Quasi-Polynomial $\gg$ Polynomial

Babai's result is the *closest* GI has ever been to the "Easy" bucket.

Explore More: Visualize GI Complexity

Explore More

For an interactive visualization of Graph Isomorphism complexity (including Babai's breakthrough), visit:
https://graph-isomorphism-complexity.netlify.app/

Babai's Strategy: Divide and Conquer

Three Key Ideas:

1. **Symmetry Breaking**
   Hard graphs are too symmetrical.
   Find "weak" spots to break symmetry.

2. **Local Landmarks (Splitter)**
   Identify unique sub-structures within the graph.

3. **Divide & Conquer**
   Split graph into smaller pieces at landmarks.
   If all pieces match $\Rightarrow$ whole graphs match.



Uses deep results from **Group Theory**.

The Drama Behind the Proof

△ The Gap (Jan 2017)

Harald Helfgott found a *gap* (error) in one of Babai's key lemmas [4].

The community held its breath...

✓ The Fix (Feb 2017)

Babai returned to his office, worked for weeks, and **fixed the proof**.

By early 2017: community consensus — *the proof is correct*.

What Babai's Result Means

▲ Impact

- **Algorithmically:** Vastly faster for large graphs.
- **Theoretically:** GI is "almost" polynomial — the closest it has ever been to P.
- **Structurally:** Confirms GI has deep mathematical structure exploitable by algorithms.

"Babai's result didn't just give us a faster tool; it proved that Graph Isomorphism is fundamentally **not that hard**.*"*

Open Question (Still!)

Is GI in **P**?
No one knows. It remains one of the great open problems in TCS.

The Weisfeiler-Lehman Test — Solving GI in Practice

Real-World Solution: The Colour Refinement Trick

Weisfeiler-Lehman (WL) Test [10]

Instead of checking structure directly, we **colour** nodes based on their neighbourhood.

If two graphs produce different colour palettes $\Rightarrow$ **not isomorphic**.



Petersen graph [8]

Two Phases:

1. **Initial Colouring** — by node degree.
2. **Refinement** — update colour based on neighbours' colours.

WL Step 1: Initial Colouring by Degree



Both graphs have **2 blue** (degree-2) and **2 green** (degree-3) nodes.
$\Rightarrow$ Initial colouring does *not* distinguish them. **Refine further!**

WL Step 2: Refinement by Neighbourhood Colours

Rule: Update each node's colour based on *its own colour + sorted colours of neighbours.*

Example Update

Node **Blue** with neighbours
{**Red**, **Red**} ⇒ New color: **Purple**

Node **Blue** with neighbours
{**Red**, **Blue**} ⇒ New color: **Green**

Repeat until colours **stabilise**.



Nodes change shade because their neighbors look different!

WL Algorithm — Full Flow



WL Test: Power and Weakness

(+) Strengths

- Runs in **polynomial time** $O(n \log n)$.
- Works for almost all graphs encountered in practice.
- Used in **Graph Neural Networks** (GNNs) in AI!

(-) Weakness

- Fails on **Cai-Fürer-Immerman (CFI) graphs** [3].
- Highly regular graphs with no distinguishing local structure.
- WL says "same" but they are *different*!

CFI Graph — The WL Adversary

WL cannot tell these apart!

WL Testing Live Demo

- Visit the interactive WL testing demo:
  - **https://wl-testing.netlify.app/**
- This live link shows WL tests in action for graph isomorphism experiments.
- Great for real-time intuition on how WL coloring evolves with graph structure.

Algorithms — A Progression

Evolution of GI Algorithms

Year	Author	Complexity	Key Idea
1970s	Various	$O(n!)$	Brute force / backtracking
1980	Luks	$2^{O(\sqrt{n \log n})}$	Group theory, bounded degree
1983	Luks	Sub-exponential	Divide & conquer on groups
1992	Babai, Luks	$e^{O(\sqrt{n \log n})}$	Canonical form
2015	**Babai**	$\mathbf{2^{O((\log n)^c)}}$	**Group theory + local cert.**

Each step is a *massive* improvement. The 2015 jump was the most dramatic in 30 years.
References: [6], [7], [2], [1]

Growth Rate Comparison



Special Cases — When GI Is Easy

When is GI Provably Easy?

✓ Polynomial Cases

- **Trees** — $O(n \log n)$
- **Planar graphs** — $O(n)$ [5]
- **Bounded degree** — polynomial [6]
- **Interval graphs**
- **Bounded genus graphs**

Tree (Easy!)



The more **structure** a graph family has, the easier GI becomes.
Random, highly-connected graphs are the hardest cases.

Real-World Applications

Why Does This Matter?



Application 1: Chemoinformatics

▷ The Problem

Are two molecular structures the same compound?

Atoms = nodes. Chemical bonds = edges.



Benzene ring as a graph

Why it matters:

- Drug discovery: is a new compound the same as a known drug?
- Toxicology: detecting toxic isomers.
- Patent checking for novel compounds.

Application 2: Circuit Design Verification

The Problem

Does the physical chip layout match the digital blueprint?

Logic gates = nodes. Wires = edges.



Why it matters:

- Modern chips have *billions* of transistors.
- Even one wrong connection $\Rightarrow$ chip failure.
- GI algorithms enable automated verification.

Application 3: Software Piracy Detection

{} The Problem

Is this code a stolen copy, even if variable names were changed?

Functions = nodes. Call relationships = edges.

Original Code (Call Graph):



Stolen Code (Renamed):



GI detects: same call structure ⇒ likely **copied code**!

Application 4: Graph Neural Networks (AI)

⋆ GNNs and WL

Modern AI uses graphs to represent: molecules, social networks, knowledge bases.

- GNNs work by *aggregating* node features from neighbours.
- This is **exactly** the WL colour refinement algorithm!
- The **expressiveness** of a GNN is bounded by the WL test.
- Key result: standard GNNs cannot distinguish non-isomorphic graphs that fool WL.



WL power

= GNN power.

Open Problems and Summary

What Remains Unknown?

1. **Is GI in P?**
   The million-dollar question. We have quasi-polynomial; polynomial is still open.
2. **Can Babai's algorithm be improved to polynomial?**
   Would require fundamentally new group-theoretic machinery.
3. **Does $P \neq NP$?**
   If $P = NP$, then GI $\in$ P trivially.
4. **Is there a graph canonical form computable in polynomial time?**
   A canonical form would solve GI; its complexity remains open.

Graph Isomorphism sits at the **frontier** of complexity theory.
It has driven some of the deepest results in algorithms and group theory.

The Full Journey of GI



Summary — The Big Picture

What is GI?

Determining if two graphs share the same structure via a bijection $f : V_G \to V_H$.

Where does it live?

NP-Intermediate — harder than P, almost certainly easier than NP-Complete.

Best algorithm?

Babai (2015): $2^{O((\log n)^c)}$ — quasi-polynomial.

Practical solution?

Weisfeiler-Lehman colour refinement — polynomial, works on almost all real graphs.

Open question?

Is GI $\in$ P? Nobody knows. Still an active frontier.

Real-world uses?

Chemistry, circuits, code, AI/GNNs, networks.

The Key Takeaway

"In theory, Graph Isomorphism is a monster.

In practice, we tame the monster with colour refinement."



Thank You!

Questions?

References

[1] László Babai. Graph isomorphism in quasipolynomial time. *arXiv preprint arXiv:1512.03547*, 2015. Breakthrough quasi-polynomial time algorithm: $2^{O((\log n)^c)}$; announced November 2015.

[2] László Babai and Eugene M. Luks. Canonical labeling of graphs. In *Proceedings of the 24th Annual ACM Symposium on Theory of Computing*, pages 171–183, 1992. Algorithm achieving $2^{O(\sqrt{n \log n})}$ time complexity.

[3] Jin-Yi Cai, Martin Fürer, and Neil Immerman. An optimal lower bound on the number of variables for graph identifications. *Journal of Computer and System Sciences*, 39(2):267–290, 1989. Introduces CFI graphs that defeat the Weisfeiler-Lehman test.

[4] Harald A. Helfgott. Isomorphismes de graphes en temps quasi-polynomial [graph isomorphisms in quasipolynomial time]. *arXiv preprint arXiv:1701.04372*, 2017. Identifies and helps correct a gap in Babai's original proof.

References ii

[5] John E. Hopcroft and J. K. Wong. Linear time algorithm for isomorphism of planar graphs. In *Proceedings of the Sixth Annual ACM Symposium on Theory of Computing*, pages 172–184, 1974.

[6] Eugene M. Luks. Isomorphism of graphs of bounded valence can be tested in polynomial time. In *Proceedings of the 21st Annual Symposium on Foundations of Computer Science*, pages 42–49, 1980.

[7] Eugene M. Luks. Polynomial-time algorithms for permutation groups. In *Proceedings of the 24th Annual Symposium on Foundations of Computer Science*, pages 36–41, 1983. Presents sub-exponential algorithm for graph isomorphism.

[8] Julius Petersen. Die theorie der regulären graphs. In *Acta Mathematica*, volume 15, pages 193–220, 1891. Introduces the Petersen graph, a classic example of a 3-regular graph.

[9] Uwe Schöning. Graph isomorphism is in the low hierarchy. *Journal of Computer and System Sciences*, 37(3):312–323, 1988. Proves GI cannot be NP-Complete unless the Polynomial Hierarchy collapses.

References iii

[10] Boris M. Weisfeiler and Andrey A. Lehman. A reduction of a graph to a canonical form and an algebra arising during this reduction. *Nauchno-Technicheskaya Informatika*, 2:12–16, 1968. Original Russian work; foundational for the WL test.