

The Feedback Vertex Set Problem: Theory, Algorithms, and Applications

Project Checkpoint Presentation

Your Name

Your University

January 26, 2026

Outline

- 1 Problem Definition
- 2 Polynomial-Time Reductions
- 3 Algorithm Survey
- 4 Implementation Plan
- 5 Experimental Design
- 6 Applications
- 7 Potential Research Directions

Overview

- Define the Feedback Vertex Set (FVS) problem and formal statement.
- Provide visual examples and intuition (cycles vs. forests).
- Highlight key properties: NP-completeness and FPT results.

What is the Feedback Vertex Set Problem?

Definition (Feedback Vertex Set)

Given an undirected graph $G = (V, E)$ and an integer k , find a set $S \subseteq V$ with $|S| \leq k$ such that $G - S$ is **acyclic** (a forest).

Formal Problem:


- **Input:** Graph $G = (V, E)$, integer k
- **Question:** $\exists S \subseteq V, |S| \leq k$ such that $G - S$ has no cycles?
- **Optimization:** Find minimum $|S|$

Intuition:

- Break all cycles by removing vertices
- Every cycle must contain ≥ 1 vertex from S
- Minimize disruption (minimize $|S|$)


Visual Examples

Triangle (3-cycle)




FVS = $\{1\}$, Size = 1

Complete Graph K_4



FVS = $\{1, 2\}$, Size = 2

Tree



FVS = $\emptyset$, Size = 0

Key Property

A set S is a feedback vertex set if and only if removing S leaves no cycles.

Important Properties

- ① **NP-Completeness:** FVS is NP-complete (Karp, 1972)
 - One of the original 21 NP-complete problems
- ② **Parameterized Complexity:** Fixed-Parameter Tractable (FPT)
 - Solvable in $O(f(k) \cdot \text{poly}(n))$ time
 - Current best: $O(3.619^k \cdot n^4)$ [Kociumaka & Pilipczuk, 2010]
- ③ **Bounds:**
 - Lower: $|S| \geq |E| - |V| + c$ (where c = connected components)
 - Upper: $|S| \leq |V| - 1$
- ④ **Special Cases:**
 - Trees/Forests: $|S| = 0$
 - Planar graphs: Better approximation algorithms exist

Polynomial-Time Reductions

Overview

- Explain the role of reductions in proving hardness of FVS.
- Summarize key reductions (Vertex Cover, 3-SAT) and constructions.
- State implications for algorithmic transfer and complexity.

Reductions: Proving Hardness

Why Reductions Matter

- Prove FVS is NP-complete
- Show equivalence to other hard problems
- Transfer algorithmic techniques

Reductions TO FVS:

- Vertex Cover $\rightarrow$ FVS
- 3-SAT $\rightarrow$ FVS

Proves: FVS is NP-hard

Reductions FROM FVS:

- FVS $\rightarrow$ Odd Cycle Transversal
- FVS $\rightarrow$ Independent Set

Shows: Algorithmic connections

Reduction 1: Vertex Cover $\rightarrow$ FVS

Vertex Cover Problem

Given $G = (V, E)$, find minimum $S \subseteq V$ such that every edge has at least one endpoint in S .

Construction: Given Vertex Cover instance (G, k)

- ① For each edge $e = (u, v) \in E$:
 - Create triangle with vertices $\{u, v, w_e\}$
 - Add edges: (u, v) , (u, w_e) , (v, w_e)
- ② Set parameter: $k' = k$


Theorem

G has vertex cover of size $\leq k \Leftrightarrow G'$ has FVS of size $\leq k$

Time: $O(|E|)$ — polynomial! ✓

Vertex Cover $\rightarrow$ FVS: Example


Original Graph G :



Edges: $(1,2), (2,4), (4,3), (3,1)$

Vertex Cover: $\{1, 2\}$, size = 2

Transformed Graph G' :



4 triangles created

FVS: $\{1, 2\}$ breaks all triangles, size = 2

Reduction Summary

From	To	Time	Key Idea
Vertex Cover	FVS	$O(E)$	Replace edges with triangles
3-SAT	FVS	$O(n + m)$	Variable/clause gadgets
FVS	Odd Cycle Trans.	$O(V + E)$	Subdivide edges
FVS	Independent Set	$O(V + E)$	Complement problem

Implications

- FVS is as hard as other canonical NP-complete problems
- Techniques for one problem transfer to others
- Approximation hardness results transfer
- Establishes FVS as fundamental in complexity theory

Overview

- Classify algorithms: Exact, Approximation, Randomized, Heuristic, Metaheuristic.
- Present representative methods and their time/quality trade-offs.
- Highlight algorithms selected for implementation and evaluation.

Five Major Categories of Solution Approaches

1. Exact Exponential

- Naive Brute Force
- DP on Subsets
- Iterative Compression
- Bounded Search Tree
- Current Best FPT
- Inclusion-Exclusion DP

2. Approximation

- 2-Approximation (VC-based)
- Log-Approximation
- LP Rounding
- Primal-Dual
- Local Ratio

4. Heuristic

- Greedy Vertex Selection
- Cycle-Based Greedy
- Maximum Degree Heuristic
- Core-Periphery Decomposition
- Reduction Rules + Greedy

5. Metaheuristic

- Genetic Algorithm
- Simulated Annealing
- Ant Colony Optimization
- Tabu Search
- Particle Swarm Optimization

Category 1: Exact Exponential Algorithms

Algorithm	Description	Complexity	Solution Quality
Naïve Brute Force	Enumerate all 2^n subsets and check if each forms a valid FVS using cycle detection	$O(2^n \cdot n^3)$	Optimal
DP on Subsets	Dynamic programming to avoid recomputing subproblems; for each subset, determine if it's a valid FVS	$O(2^n \cdot n^2)$	Optimal
Iterative Compression	FPT algorithm that assumes solution of size $k+1$ and compresses to size k (Dehne et al., 2004)	$O(5^k \cdot kn^2)$	Optimal
Bounded Search Tree	Use branching rules to create search tree with depth $\leq k$; improved branching factor (Chen et al., 2006)	$O(4^k \cdot n^2)$	Optimal
Current Best FPT	State-of-art using crown decomposition, sunflower lemma, refined branching (Kociumaka & Pilipczuk, 2010)	$O(3.619^k \cdot n^4)$	Optimal
Inclusion-Exclusion DP	Uses inclusion-exclusion principle with DP for counting; fast for very small graphs ($n \leq 25$)	$O(2^n \cdot n)$	Optimal

Key Insight: FPT algorithms practical for $k \leq 50$; exponential in n feasible only for $n \leq 20$

Category 2: Approximation Algorithms

Algorithm	Description	Complexity	Solution Quality
2-Approximation (VC-based)	Reduce FVS to Vertex Cover; iteratively find cycles and remove both endpoints of any edge (Bafna et al., 1999)	$O(n^2)$	2-approx
Log-Approximation	For tournament graphs using hitting set techniques; specific to directed complete graphs	$O(n^2 \log n)$	$O(\log n)$ -approx
LP Rounding	Formulate as ILP, solve LP relaxation, then round fractional solution (deterministic or randomized)	$O(n^{3.5})$	2-approx
Primal-Dual	Maintain primal and dual solutions simultaneously; combinatorial approach without LP solver	$O(n^2)$	2-approx
Local Ratio	Decompose weight function and apply local decisions; works well with weighted vertices	$O(n^2)$	2-approx

Open Question: Does $(2 - \varepsilon)$ -approximation exist? Under UGC, 2 might be optimal.

Category 3: Randomized Algorithms

Algorithm	Description	Complexity	Solution Quality
Random Sampling	Randomly sample vertices in random order; if vertex in cycle, include it in FVS; Monte Carlo approach	$O(n^2)$ per trial	Expected $O(\log n)$ -approx
Randomized Rounding	Solve LP relaxation, then randomly include vertex v with probability x_v^* ; LP-based randomization	$O(n^3)$	Expected 2-approx
Color Coding	Randomly color vertices and use DP to find colorful solutions; for bounded treewidth graphs	$O(2^{O(k)} \cdot n)$	Optimal w.h.p.

Key Advantages

- Probabilistic guarantees with high probability (w.h.p.)
- Can be derandomized using method of conditional expectations
- Excellent for sparse graphs and bounded treewidth structures

Category 4: Heuristic Algorithms

Algorithm	Description	Complexity	Solution Quality
Greedy Vertex Selection	Repeatedly remove vertex with maximum degree; simple and fast; uses priority queue	$O(n^2 \log n)$	No guarantee
Cycle-Based Greedy	Find cycles using DFS/BFS and select vertex appearing in most cycles; iterative improvement	$O(n^3)$	No guarantee
Maximum Degree Heuristic	Like max degree but with tie-breaking: clustering coefficient, betweenness centrality	$O(n^2 \log n)$	No guarantee
Core-Periphery Decomposition	Compute k -core decomposition; focus on highly connected core vertices	$O(n + m)$	No guarantee
Reduction Rules + Greedy	Apply polynomial-time reduction rules first (degree 0,1,2 vertices, self-loops) then greedy	$O(n^2)$	No guarantee

Practical Value: Often reduce graph size by 50-90% before greedy phase; excellent performance on real-world networks

Category 5: Metaheuristic Algorithms

Algorithm	Description	Complexity	Solution Quality
Genetic Algorithm	Evolve population using selection, crossover, mutation; binary encoding or permutation-based	$O(g \cdot p \cdot n^2)$	No guarantee
Simulated Annealing	Probabilistic technique accepting worse solutions with decreasing probability; geometric cooling schedule	$O(i \cdot n^2)$	No guarantee
Ant Colony Optimization	Simulate ant foraging using pheromone trails; balance exploration vs exploitation	$O(\text{ants} \cdot i \cdot n^2)$	No guarantee
Tabu Search	Local search with memory (tabu list) to avoid cycling; aspiration criterion for best solutions	$O(i \cdot n^2)$	No guarantee
Particle Swarm Optimization	Swarm intelligence inspired by bird flocking; particles explore solution space collaboratively	$O(\text{particles} \cdot i \cdot n^2)$	No guarantee

Legend: g = generations, p = population size, i = iterations

Implementation Plan

Overview

- Describe selected algorithms to implement (Iterative Compression, Genetic Algorithm).
- Outline implementation details, complexity, and engineering considerations.
- State expected deliverables and milestones for development.

Algorithm Selection Criteria

Essential Criteria

1. Implementability

- Feasible in 6-week timeframe
- Well-documented in literature
- Reasonable debugging complexity

2. Research Potential

- Novel comparisons possible
- Room for improvements
- Publishable results

3. Complementary Nature

- Different problem sizes
- Different paradigms
- Interesting comparisons

Additional Criteria

4. Practical Relevance

- Real-world applications
- Industry interest
- Addresses practical needs

5. Educational Value

- Learn important techniques
- Transferable skills
- Deep algorithmic insights

Goal

Select algorithms that maximize research impact while ensuring feasibility

Selected Algorithms for Implementation

Three-Algorithm Approach (Maximum Research Impact)

We will implement three complementary algorithms covering the entire solution spectrum:

① **Iterative Compression** (Exact FPT Algorithm)

- Guarantees optimal solution for small-medium k
- Time: $O(5^k \cdot kn^2)$ — FPT breakthrough (2004)
- Research: Hybrid approaches, parallelization, adaptive branching

② **Kernelization + Bounded Search Tree** (Enhanced Exact)

- Preprocessing with reduction rules + exact search
- Kernel reduction: 50-90% for many graph types
- Research: New reduction rules, smart branching strategies

③ **Memetic Algorithm** (Advanced GA + Local Search)

- Handles large instances ($n > 1000$)
- Combines population evolution with local optimization
- Research: Problem-specific operators, ML integration, hybrid exact-metaheuristic

Algorithm 1: Iterative Compression (IC)

Core Concept

Given FVS of size $k + 1$, compress it to size k through smart enumeration

Theoretical Significance:

- Most important FPT technique
- Published in STOC/FOCS
- Demonstrates advanced understanding

Implementation:

- Complexity: Medium
- Expected range: $k \leq 30$
- Validation on small instances

Research Directions:

- 1 **Hybrid Kernelization + IC**
 - Apply reduction rules before IC
 - Potential 2-5x speedup
- 2 **Adaptive Branching**
 - Learn which vertices to branch first
 - Use graph structure metrics
- 3 **Parallelization**
 - Independent branches in parallel
 - Multi-core speedup potential
- 4 **Improved Compression**
 - Smart partition enumeration
 - Structure-based pruning

Algorithm 2: Kernelization + Bounded Search Tree

Core Concept

Reduce graph size via preprocessing rules, then apply exact search on smaller kernel

Reduction Rules:

- Degree 0, 1, 2 vertices
- Self-loops, duplicate edges
- Crown decomposition
- Flower rule

Search Strategy:

- Smart vertex selection
- Bounded depth: k
- Branching factor: ≤ 4

Research Directions:

- 1 **New Reduction Rules**
 - Graph-specific rules
 - Theoretical contribution
- 2 **Rule Application Order**
 - Optimize ordering
 - ML-based prediction
- 3 **Kernelization Bounds**
 - Tighter bounds for special classes
 - Experimental validation
- 4 **Smart Branching**
 - Centrality-based selection
 - ML-guided search

Algorithm 3: Memetic Algorithm (GA + Local Search)

Core Concept

Population evolution + local optimization for large-scale instances

Components:

- Smart initialization (greedy + random)
- FVS-aware crossover operators
- Centrality-based mutation
- Problem-specific local search

Practical Relevance:

- Industry standard
- Handles $n > 1000$ vertices
- Near-optimal (5-10% gap)

Research Directions:

1 Cycle-Preserving Crossover

- Preserve cycle-breaking structures
- Novel contribution

2 Hybrid Exact-Metaheuristic

- Use IC for small components
- GA for large core

3 ML Integration

- Predict promising vertices
- Learn operator selection

4 Multi-Objective

- Minimize size + maximize robustness
- Pareto frontier

Why This Three-Algorithm Combination?

Aspect	Iter. Compression	Kernel + BST	Memetic GA
Size Range	Small-Medium ($k \leq 30$)	Medium (after kernel)	Large ($n > 1000$)
Paradigm	FPT Dynamic	FPT + Preprocess	Evolutionary
Guarantee	Optimal	Optimal	Approximate
Speed	Medium	Slow (small kernel)	Fast
Research	FPT techniques	Reduction rules	EA design
Practice	Moderate k	Preprocessing in-sight	Industry standard

Complementary Research

- **Standalone:** Each algorithm offers unique research directions
- **Pairwise:** IC vs K+BST (exact methods), IC vs GA (quality-time tradeoff)
- **Hybrid:** Kernelize + IC (best exact), Kernelize + GA (best approx)

Implementation Timeline (6 Weeks)

Week	Phase	Tasks
1	Foundation	Project setup, graph data structures, basic utilities (cycle detection), testing framework, greedy baseline
2	Iterative Compression	Core IC algorithm, compression subroutine, reduction rules integration, testing & validation
3	Kernel + BST	Reduction rules (degree-based, crown, flower), bounded search tree, smart vertex selection, integration
4	Memetic Algorithm	Basic GA structure, FVS-specific operators (crossover, mutation), local search, parameter tuning
5	Experimentation	Dataset generation (synthetic + real-world), run all experiments, multiple runs for randomized, data collection
6	Analysis	Statistical analysis, visualization, code documentation, final presentation preparation

Risk Mitigation

If behind schedule: Drop K+BST (keep IC + GA for max contrast), simplify GA features, reduce experiment scope

Expected Research Contributions

Potential Publications (3-5 Papers)

1. Comprehensive Benchmark Study

- Venue: SEA (Symposium on Experimental Algorithms) or ACM JEA
- Contribution: Largest benchmark (1,200+ instances), systematic comparison
- Impact: Medium-High (experimental paper)

2. Hybrid Exact-Metaheuristic Algorithms

- Venue: GECCO or EvoCOP
- Contribution: Novel IC-GA hybrid, kernelization as preprocessing
- Impact: High (novel approach)

3. Problem-Specific Genetic Operators

- Venue: PPSN or IEEE CEC
- Contribution: Cycle-aware crossover, theoretical analysis
- Impact: Medium-High (EA contribution)

4. New Reduction Rules (if discovered)

Success Metrics and Deliverables

Technical Metrics:

- **Correctness:** 100% valid solutions
- **IC Performance:** Solve $k \leq 25$ in $< 60s$
- **GA Performance:** Within 10% optimal for $n = 1000$
- **Kernel Reduction:** 50%+ on average

Research Metrics:

- Novel insights discovered
- Paper draft quality
- Comparison comprehensiveness
- Unique contributions

Deliverables:

- 1 Three working implementations
- 2 Comprehensive test suite
- 3 1,200+ benchmark instances
- 4 Experimental results & analysis
- 5 Statistical validation
- 6 Code documentation
- 7 Final presentation
- 8 1+ paper draft (optional)

Minimum Success

2 algorithms + basic experiments = Pass
3 algorithms + comprehensive = High Grade
3 optimized + novel contributions = Publication

Overview

- Define datasets (synthetic + real-world) and instance sizes.
- Specify performance metrics: solution quality, runtime, robustness.
- Describe protocol: runs per instance, timeouts, reproducibility.

Dataset Design

Graph Type	Sizes	Instances	Purpose
Random (Erdős-Rényi)	$n \in \{10, 20, 50, 100, 200, 500, 1000\}$ $p \in \{0.1, 0.3, 0.5, 0.7, 0.9\}$	350	General performance across densities
Scale-Free (BA)	$n \in \{10, 20, 50, 100, 200, 500, 1000\}$ $m \in \{2, 3, 5\}$	210	Realistic networks (power-law degree)
Grid	$\{3 \times 3, 5 \times 5, 10 \times 10, 20 \times 20, 30 \times 30\}$	25	Structured graphs with known properties
Small-World (WS)	$n \in \{20, 50, 100, 200, 500\}$ $k \in \{4, 6, 8\}, \beta \in \{0.1, 0.3, 0.5\}$	450	High clustering, short paths
Cycle-Heavy	4 base cycle counts 3 interconnection levels	120	Stress test (many cycles)
Trees	$n \in \{10, 20, 50, 100, 200\}$ Random, Balanced, Star	75	Baseline (optimal = 0)
Real-World	Karate, Dolphins, Email, Political blogs, Power grid	15-20	Validation on real networks

Total: $\sim 1,250$ synthetic + 20 real-world instances

Performance Metrics

Solution Quality:

- ① **FVS Size:** $|S|$ (smaller is better)
- ② **Approximation Ratio:**

$$\text{Ratio} = \frac{|S_{\text{alg}}|}{|S_{\text{opt}}|}$$

- ③ **Relative Gap:**

$$\text{Gap} = \frac{|S_{\text{alg}}| - |S_{\text{best}}|}{|S_{\text{best}}|} \times 100\%$$

- ④ **Validity:** $G - S$ acyclic? (must be 100%)

Runtime Performance:

- ① **Wall-Clock Time** (seconds)
- ② **CPU Time** (process time)
- ③ **Iterations/Generations**
- ④ **Function Evaluations**

Robustness:

- ① **Coefficient of Variation:**

$$CV = \frac{\sigma}{\mu} \times 100\%$$

- ② **Success Rate** (solved within timeout)

Experimental Protocol

Implementation Environment

- **Language:** Python 3.x
- **Libraries:** NetworkX, NumPy, Matplotlib, Pandas
- **Hardware:** [Specify: CPU, RAM, OS]

Execution Details

- **Runs per instance:** 10 for randomized algorithms, 1 for deterministic
- **Timeout limits:**
 - Small ($n \leq 50$): 60 seconds
 - Medium ($50 < n \leq 200$): 300 seconds
 - Large ($n > 200$): 600 seconds
- **Random seeds:** Fixed for reproducibility
- **Data collection:** CSV format with all metrics

Key Experiments

① Correctness Verification

- Verify all solutions are valid FVS (100% required)

② Solution Quality Comparison

- Compare FVS sizes across algorithms
- Box plots, statistical tests

③ Runtime Performance

- Runtime vs. graph size (scalability)
- Log-scale plots

④ Quality-Runtime Trade-off

- Pareto frontier analysis
- Best algorithm for given time budget

⑤ Graph Type Sensitivity

- Performance heatmap across graph types
- Identify algorithm strengths

Key Experiments (continued)

6 Parameter Sensitivity (GA)

- Population size: $\{20, 50, 100, 200, 500\}$
- Mutation rate: $\{0.01, 0.05, 0.1, 0.2\}$
- Crossover rate: $\{0.5, 0.7, 0.8, 0.9\}$

7 Convergence Behavior

- Track best solution over iterations/time
- Convergence curves


8 Optimality Gap (small instances)

- For $n \leq 20$: compute optimal with exact algorithm
- Measure gap: $(\text{approx} - \text{optimal}) / \text{optimal}$

9 Real-World Performance

- Validate on realistic networks
- Compare to synthetic results

Expected Results Visualization



Overview

- Survey theoretical and practical applications of FVS.
- Provide domain examples: OS deadlocks, VLSI testing, biology, social networks, finance.
- Discuss impact and real-world relevance of solutions.

Application 1 : Deadlock Detection in Operating Systems

Problem

- Processes compete for shared resources
- Circular waiting leads to deadlock
- Goal: resolve deadlock with minimal impact


Graph Model

- Vertices represent processes
- Directed edges represent wait-for relations
- Cycles correspond to deadlocks

Role of FVS

- FVS models processes whose removal breaks all cycles

$$\text{FVS} = \{P1\}$$



Deadlock cycle in a wait-for graph

Application 2: VLSI Circuit Testing

Challenge

- Modern chips contain millions of logic gates
- Feedback loops make testing computationally hard
- Acyclic circuits are testable in linear time

FVS-Based Solution

- Model circuit as a graph
- Compute a small FVS to break all cycles
- Fix FVS gates and test remaining acyclic circuit
- Test FVS gates separately

Example

- 32-bit ALU circuit
- 5,000 gates total
- 200 feedback paths
- FVS size: 50 gates

Fixing 50 gates $\Rightarrow$ 4,950 acyclic gates

Benefits

- Reduced test time
- Lower power consumption
- Smaller hardware overhead

Application 3: Gene Regulatory Networks

Biological Motivation

- Genes regulate each other via feedback loops
- Cycles control cell behavior and disease states

Graph Model

- Vertices: genes
- Edges: regulatory interactions
- Cycles: feedback regulation

Role of FVS

- Small set of FVS genes controls all feedback : Interpreted as **master regulators**

Cancer Study Example

- Breast cancer regulatory network
- 500 genes analyzed
- FVS: 12 key genes
- 10 known and 2 novel drug targets

Applications

- Drug target discovery
- Gene knockout analysis
- Personalized medicine

Social and Financial Networks

Social Network Analysis

- Feedback loops amplify influence and information spread
- FVS nodes correspond to key influencers or superspreaders
- Targeting FVS improves marketing efficiency
- Disrupting FVS reduces misinformation propagation

Financial Systemic Risk

- Financial institutions form highly interconnected networks
- Cycles represent circular dependencies and systemic risk
- FVS identifies systemically important institutions
- Used for regulation, monitoring, and crisis prevention

Theoretical Applications

- **Complexity Theory**

- Used in NP-completeness reductions
- Benchmark problem for cycle-breaking hardness

- **Algorithm Design**

- Testbed for FPT(Fixed Parameter Tractable) techniques
- Motivates iterative compression and branching methods

- **Approximation Theory**

- Used to study approximation limits
- Reference problem for constant-factor approximations

- **Graph Structure Analysis**

- Tool for analyzing treewidth and feedback structure
- Applied in kernelization and graph decompositions

Potential Research Directions

Overview

- Highlight open theoretical problems (approximation gap, faster FPT, kernels).
- Point out practical directions: ML integration, dynamic and distributed algorithms.