TAS MOCK · HYPOTHETICAL · NOT OFFICIAL
NOT A FIRST® PUBLICATION — DO NOT CITE AT ANY EVENT

TAS Mock Game & Season Manual

FIRST® POWER UP℠ (2018 field)

Volume I — 2018 Game · Volume II — 2026 Robot Construction · Volume III — 2027 Preview

---

Prepared for: Trident Robotics, Taipei American School (TAS)
Audience: TAS students and mentors — mock kickoff drill
Document: **TAS-MOCK-2018-PU** · Version **V0** · 2026-11-09
Format: print / PDF, US Letter

*This is a TAS mock / hypothetical training document. It is **not** an official FIRST® Robotics Competition Game Manual, it is not endorsed by FIRST®, and it carries no authority at any event. Rule text is paraphrased or quoted in short extracts only, with rule IDs and links to the official manuals. FIRST®, FIRST® Robotics Competition, FIRST® POWER UP℠ and REBUILT are marks of FIRST (For Inspiration and Recognition of Science and Technology). The AprilTag layout in Appendix B is fiction. If anything here disagrees with an official FIRST document, the FIRST document is right and this one is wrong.*

> **TAS MOCK · HYPOTHETICAL · NOT OFFICIAL.** Every page of this document carries this header. Nothing in this manual is a FIRST rule. It is a classroom drill that pretends the 2018 game is being kicked off today, with robots built to current rules.

Contents

- **Front matter**
  - FM.1 About this mock manual
  - FM.2 Which rules apply (the one-page answer)
  - FM.3 This document and its conventions
  - FM.4 Sources, links and legal notice
- **VOLUME I — THE 2018 GAME (FIRST POWER UP)**
  - Section 1 Introduction and kickoff
    - 1.1 The kickoff story · 1.2 Official game animation · 1.3 How to use Volume I
  - Section 2 FIRST POWER UP overview
  - Section 3 ARCADE
    - 3.1 Zones and markings · 3.2 FIELD · 3.3 SCALE · 3.4 SWITCH · 3.5 PLATE lighting · 3.6 ALLIANCE WALL, EXCHANGE and VAULT · 3.7 PORTAL · 3.8 POWER CUBE · 3.9 Vision targets · 3.10 FIELD Management System
  - Section 4 MATCH play
    - 4.1 Stages and setup · 4.2 Scoring (Table 4-1) · 4.3 POWER UPS (Table 4-2) · 4.4 Rule violations (Table 4-3) · 4.5 DRIVE TEAM (Table 4-4) · 4.6 Logistics
  - Section 5 ROBOT match envelope (2018 R03, R04, R05, G05)
  - Section 6 Game rules (curated)
    - 6.1 Before the MATCH · 6.2 ROBOT restrictions · 6.3 ROBOT-to-ROBOT interaction · 6.4 FIELD and POWER CUBE interaction · 6.5 AUTO rules
- **VOLUME II — ROBOT CONSTRUCTION (2026 REBUILT RULES)**
  - Section 7 Construction overview and precedence
  - Section 8 ROBOT construction rules (selected)
    - 8.1 Weight (R103) · 8.4 BUMPERS · 8.5 Motors and actuators (R501–R503) · 8.6 Power distribution (R601) · 8.7 Control, command and signals (R701–R717) · 8.8 Pneumatics · 8.9 OPERATOR CONSOLE
- **VOLUME III — 2027 PREVIEW**
  - Section 9 2027 Event & Robot Rule Preview, Part 1
- **APPENDICES**
  - Appendix A Rule cross-reference and precedence table
  - Appendix B TAS AprilTag retrofit, IDs 1–32 (FICTION)

◦ Appendix C Glossary (excerpt)
◦ Appendix D Study and review sheets
◦ Appendix E Revision history

Front Matter

TAS MOCK · HYPOTHETICAL · NOT OFFICIAL — FRONT MATTER

FM.1 About this mock manual

Every January, FIRST® Robotics Competition teams receive a Game Manual that runs to well over a hundred pages. Learning to read that document fast, accurately and as a team is one of the most valuable skills a new member can build. This mock manual exists so that TAS students can practise that skill in November, months before a real kickoff, on a game whose answers are already known.

The drill is simple to state. It is **2018 on the field and 2026 in the pit.** Students play the 2018 game, FIRST POWER UP, with its Switches, Scale, Exchange, Vault, Portals, Platform and Rungs. They size the robot for that game using the 2018 match envelope. They build the robot itself — bumpers, motors, wiring, control system, pneumatics, operator console — to the 2026 construction rules they would meet at a real event today. And they keep one eye on 2027, because FIRST has already published the first part of its 2027 rule preview and some of those changes affect what we should buy this winter.

This manual is deliberately shaped like a real FRC Game Manual: volumes and numbered sections, rule IDs in boxes, numbered tables and figures, a glossary, and blue-box-style notes. It is also deliberately *not* a copy of any FIRST manual. Rules are paraphrased in our own words, with short quotes only where the exact wording matters, and every rule carries its official ID so students can (and should) look it up in the source.

What this manual is not:

- It is not a FIRST document and has no authority at any event, inspection or Q&A.
- It is not a complete rulebook. Volume I covers the parts of the 2018 manual a strategy and design discussion needs; Volume II covers the 2026 construction rules most likely to change a design; Volume III covers one blog post.
- It does not depend on any website, simulator or software tool. Everything here works on paper.

FM.2 Which rules apply (the one-page answer)

If students remember one page, it should be this one. Table FM-1 is the precedence rule for the whole mock. Appendix A repeats it with every rule ID cross-referenced.

Table FM-1: Rule layers in this mock

Question	Governing source in this mock	Where in this manual
What is the game, how is it scored, what are the penalties?	**2018** Game Manual, Sections 3, 4 and 7	Vol I, Sec 3, 4, 6
How big may the robot start? How far may it reach during a MATCH? What may it weigh at inspection?	**2018** R03, R04, R05 and G05	Vol I, Sec 5
How are bumpers, motors, electrical, control system, pneumatics and the operator console built?	**2026** Game Manual (REBUILT), Section 8	Vol II, Sec 7–8
What is likely to change for 2027?	**2027** Part 1 preview blog — a watch list, not a rule	Vol III, Sec 9
Where do the AprilTags go?	Nowhere on a real 2018 field. Appendix B is **fiction** for TAS vision discussion	Appendix B

Three sentences to say out loud at the start of the kickoff:

1. *"Game, scoring and penalties come from 2018."*
2. *"Starting size, reach and inspection weight come from 2018: 33 × 28 × 55 in. at the start, 16 in. of reach past the frame, 120 lb."*
3. *"Everything about how we build it comes from the 2026 manual, and we read the 2027 preview as a shopping list."*

> **Design target note.** The mock inspection weight is 2018 R05 (120 lb). TAS still recommends designing to the 2026 limit in R103 (115 lb, see Sec 8.1) so that the robot you sketch would also pass a current inspection. A robot that meets R103 automatically meets R05.

FM.3 This document and its conventions

This manual follows the conventions of a real FRC Game Manual so that reading it is practice for reading the real thing.

Volumes and sections. Volume I (Sections 1–6) is the 2018 game. Volume II (Sections 7–8) is construction under 2026 rules; its subsection numbers (8.1, 8.4, 8.5 …) deliberately match the 2026 manual's Section 8 numbering so students can jump straight to the source. Volume III (Section 9) is the 2027 preview. Appendices are lettered.

Rule boxes. Each rule we discuss appears in a box like this:

> ### X00 — Rule title (mock example)
>
> A plain-language paraphrase of the rule, with the key numbers in bold.
>
> ---
>
> **Violation:** the penalty, paraphrased from the source.
>
> *Source: manual and rule ID, with page or section reference.*

The ID in the box is always the **official** FIRST rule ID from the cited year. A 2018 rule is written as it appears in 2018 (for example **G05**, **R03**); a 2026 rule is written as it appears in 2026 (for example **R501**, **R717**). The two numbering schemes do not overlap, so an ID tells you which year it came from: two-digit IDs (R03, G14) are 2018; three-digit IDs (R103, R601) are 2026.

Rule-ID prefixes. As in the real manuals: **S** = safety, **C** = conduct, **G** = game, **A** = AUTO-period game rules (2018), **H** = human/drive-team rules (2018), **R** = robot construction, **I** = inspection.

Notes. Text in a shaded call-out (like the “Design target note” above) is a TAS teaching note. Like the blue boxes in a real manual, a note helps you understand a rule but never overrides it. If a note and a rule box disagree, the rule box wins — and if this manual and an official FIRST manual disagree, FIRST wins.

Defined terms. Words with a special meaning in the game appear in ALL CAPS (for example SCALE, OWNERSHIP, FRAME PERIMETER), as in the official manuals. Appendix C defines them.

Units. The 2018 and 2026 manuals both use imperial units first. We follow that, and give metric in parentheses where a number is likely to be used in a design calculation.

Figures. This mock does not reproduce FIRST artwork. Where a real manual would show a drawing, you will see a dashed placeholder box with the figure number from the official manual, so you can look the real drawing up:

Figure FM-1 (placeholder): this is what a figure placeholder looks like. Open the cited official manual page to see the real drawing.

Fiction. Anything that did not exist in the real 2018 game — chiefly the AprilTag layout in Appendix B — is marked **FICTION** in a grey call-out.

Running headers. Every printed page carries *TAS MOCK · NOT OFFICIAL* in the top-left corner and the current section title in the top-right. If a page you are holding does not have that header, it did not come from this manual.

FM.4 Sources, links and legal notice

Table FM-2: Primary sources

Layer	Document	Link
Game (2018)	2018 FRC Game and Season Manual — FIRST POWER UP	https://firstfrc.blob.core.windows.net/frc2018/Manual/2018FRCGameSeasonManual.pdf
Construction (2026)	2026 Game Manual — REBUILT (Team Update 22 version)	https://firstfrc.blob.core.windows.net/frc2026/Manual/2026GameManual.pdf
Preview (2027)	FIRST community blog: “2026 Event & Robot Rule Preview for 2027 Season — Part 1” (31 August 2026)	https://www.firstinspires.org/community-blog/2026-event-robot-rule-preview-for-2027-season-part-1
Animation (2018)	Official FIRST YouTube: *2018 FIRST Robotics Competition — FIRST POWER UP Game Animation*	https://www.youtube.com/watch?v=HZbdwYiCY74

Legal notice. This manual paraphrases FIRST documents for non-commercial classroom use and quotes them only in short extracts (rule titles and key phrases). It does not reproduce any FIRST manual, drawing or table in full; read the linked originals for the authoritative text. FIRST®, FIRST® Robotics Competition, FIRST® POWER UP℠, REBUILT and related marks belong to FIRST. Vendor and product names (roboRIO, CANivore, Talon, Victor, NEO, Kraken, etc.) belong to their owners and appear only because the rules name them. TAS internal use only; do not post publicly.

Accuracy. Numbers in Volumes I and II were checked against text extracts of the linked manuals on 2026-11-09. Dimensions are nominal, exactly as the real manuals say: real fields vary slightly from event to event, and the official drawings are the reference.

VOLUME I — THE 2018 GAME · FIRST POWER UP · TAS MOCK · NOT OFFICIAL

Vol I · Section 1 Introduction and Kickoff

1.1 The kickoff story

On **6 January 2018**, FIRST revealed FIRST POWER UP, the FRC game for the 2018 season. The theme was a retro arcade: two alliances of video-game characters and their human operators are trapped inside an arcade game and must defeat "the boss" to escape. Each alliance has three ways to prepare for the boss fight:

1. **Control the SWITCHES and the SCALE.** Robots collect POWER CUBES and place them on PLATES. When an alliance's PLATE is tipped down far enough, the alliance has OWNERSHIP and earns points for every second it holds it.
2. **Earn POWER UPS.** Robots deliver cubes through the EXCHANGE to their HUMAN PLAYERS, who load them into the VAULT. Three POWER UPS — FORCE, BOOST and LEVITATE — give a temporary or end-of-match advantage.
3. **Climb the SCALE.** In the last thirty seconds, robots climb a RUNG on the SCALE tower to "Face the Boss", or at least park on the PLATFORM.

The game is unusual among FRC games because its main scoring is **continuous**: points accrue per second of OWNERSHIP rather than per object scored. A team that tips the SCALE early and keeps it tipped can win even if it places fewer cubes than its opponent. That single idea drives almost every strategy conversation in this manual.

For the TAS mock, imagine that this is the game we have just been handed, but that our pit is in 2026: we build with today's motors, today's control system and today's bumper rules.

1.2 Official game animation

Watch the official animation once, as a group, before reading further. It is about three minutes long and shows every field element in motion.

> **VIDEO — 2018 FIRST POWER UP Game Animation (official FIRST channel)**
> Watch: https://www.youtube.com/watch?v=HZbdwYiCY74
> Embed (slides / web): `https://www.youtube.com/embed/HZbdwYiCY74`
> Video ID: `HZbdwYiCY74`
> *Published by FIRST on its official YouTube channel. Link only; the video is not reproduced here.*

While watching, each student writes down:

- the three things a POWER CUBE can be used for;
- which field element is the same for both alliances and which elements belong to one alliance;
- what happens at the 30-seconds-left mark;
- one question about the rules that the animation does not answer.

Keep the questions. Most of them are answered in Sections 3–6, and the rest are good material for the “Q&A drill” in Appendix D.

1.3 How to use Volume I

Volume I follows the structure of the real 2018 manual so that its section numbers line up with the source:

This manual	Real 2018 manual	Content
Section 2	Section 2 Overview	The game in one page
Section 3	Section 3 ARCADE	Field elements and dimensions
Section 4	Section 4 MATCH Play	Periods, scoring, POWER UPS, penalties, drive team
Section 5	Section 8 (R03–R05) and Section 7 (G05)	Robot starting size, reach and weight — the “match envelope”
Section 6	Section 7 Game Rules	Curated G-rules and A-rules

A first read should take about forty minutes. Read Sections 2 and 4.2 first (what scores), then Section 3 (where things are), then Sections 5–6 (what you may not do).

Vol I · Section 2 FIRST POWER UP Overview

Each MATCH is played by two ALLIANCES (Red and Blue) of three robots each. A MATCH lasts **2 minutes 30 seconds**: a **15-second AUTO** period in which robots run only on pre-programmed instructions, then a **2 minute 15 second TELEOP** period with student drivers. The last **30 seconds** of TELEOP is the **ENDGAME**.

Just before AUTO, the Field Management System (FMS) randomly assigns which PLATE of each SWITCH and of the SCALE is red and which is blue, and sends that assignment to each team's driver station. Robot code has to read that assignment and choose an autonomous routine accordingly — a real software requirement, and a good mock exercise.

What scores, in one table. Values are from the 2018 manual's overview tables (Tables 2-1 and 2-2) and Table 4-1; Section 4.2 gives the full criteria.

Table 2-1: Point values at a glance

Action	AUTO	TELEOP
Cross the AUTO LINE (AUTO-RUN), per robot	5	—
SWITCH OWNERSHIP	2 + 2 per second	1 + 1 per second
SCALE OWNERSHIP	2 + 2 per second	1 + 1 per second
POWER CUBE placed in the VAULT	—	5
BOOST bonus	—	doubles the boosted OWNERSHIP points for 10 s
PARKING on the PLATFORM, per robot	—	5
Successful CLIMB, per robot	—	30

Ranking points (Qualification MATCHES only). Win = 2 RP, tie = 1 RP. One extra RP for **FACE THE BOSS** (three robots CLIMBED, or two CLIMBED plus LEVITATE played). One extra RP for the **AUTO QUEST** (all three robots completed an AUTO-RUN *and* the alliance owns its SWITCH at the end of AUTO). An alliance can therefore earn up to **4 RP** per Qualification MATCH.

The three questions every strategy must answer:

1. *Who holds the SCALE?* The SCALE is shared and worth the same per second as your SWITCH, but you are fighting for it.
2. *How many cubes go to the VAULT, and when?* Each Vault cube is 5 points, and POWER UPS can swing OWNERSHIP points for ten seconds at a time.
3. *How many robots climb?* Three climbs is 90 points plus a ranking point. LEVITATE can stand in for one of them.

Vol I · Section 3 ARCADE

The ARCADE is everything needed to play the game: the FIELD, the SWITCHES, the SCALE, the VAULTS, the carpet, the POWER CUBES and the field electronics. The real manual stresses that its dimensions are **nominal**: fields are assembled by different crews in different venues, and good robots are designed to tolerate small variations. The official 2018 field drawings and CAD are the reference for exact values.

Figure 3-1 (placeholder): FIRST POWER UP playing area, isometric view. See 2018 manual Section 3, Figure 3-1.

3.1 Zones and markings

Zones are volumes on the FIELD, usually bounded by 2 in. gaffer tape, and are mostly “infinitely tall”: a robot is in a zone if any part of it breaks the plane of the boundary, unless a rule says “fully” or “completely”.

Table 3-1: Zones and markings (2018 §3.1, paraphrased)

Zone / marking	Size and location	Why it matters
ALLIANCE STATION	22 ft wide × 10 ft deep × 10 ft tall, behind the ALLIANCE WALL	Where drivers, coach and one or more human players stand
AUTO LINE	Black tape across the field, 10 ft from each ALLIANCE WALL	Crossing it with a BUMPER in AUTO = AUTO-RUN, 5 points
EXCHANGE ZONE	4 ft wide × 3 ft deep in front of the EXCHANGE wall	Protected delivery area; G15 limits opponent blocking
NULL TERRITORY	Two areas, 7 ft 11¼ in. wide × 6 ft deep, at each end of the SCALE, against the guardrails	The alliance whose SCALE PLATE is on that side is protected there (G16)
PLATFORM ZONE	11 ft 1½ in. wide × 9 ft 11¾ in. deep, between the SWITCH and the SCALE	ENDGAME protection (G18); G05 reach limit is lifted inside it during ENDGAME
PORTAL	4 ft × 12 ft 11 in., at the field corners next to each alliance	Human players feed cubes onto the field
POWER CUBE ZONE	3 ft 9 in. wide × 3 ft 6 in. deep, in front of each SWITCH on the alliance-wall side	Holds the alliance’s cube pile; opponents may not remove cubes from it (G23)
STARTING LINE	White tape 2 ft 6 in. behind the ALLIANCE WALL diamond plate	Drive team positions before and during AUTO

Figure 3-2 (placeholder): zones and markings, top view. See 2018 manual Figure 3-2.

3.2 FIELD

The FIELD is a **27 ft × 54 ft** (about 8.2 m × 16.5 m) carpeted area bounded by the GUARDRAILS, the PORTALS, the EXCHANGE walls and the ALLIANCE WALLS. The GUARDRAIL is clear polycarbonate on aluminium extrusion. Four gates, each 3 ft 2 in. wide, let teams carry robots on and off; they are closed during a MATCH.

Design note. A robot that must fit through a 3 ft 2 in. gate on its cart, and through school doorways on the way to the venue, is one more reason the starting-size rule (R03, Section 5) matters.

3.3 SCALE

There is **one SCALE**, in the centre of the field, with its arm parallel to the ALLIANCE WALLS. It consists of an arm with two PLATES, a central TOWER, OUTRIGGERS, two RUNGS and two PLATFORMS. Black cable protectors (about ⅞ in. tall once fastened) run from the centre of each PLATFORM side to the guardrails and the SWITCHES — a small bump every drivetrain must cross.

SCALE PLATES. Each PLATE is **3 ft wide × 4 ft deep**. The outside edges of the two PLATES are **15 ft apart**. Each PLATE has four polycarbonate walls with LED strips; the wall nearest the field centre stands **1 ft 3 in.** above the PLATE surface, the others **3½ in.**

At the start of a MATCH the PLATES are level, with their outside edges **5 ft (60 in.) ± 1 in.** above the carpet. The SCALE tips according to the weight *and position* of the cubes on each PLATE. It is always in one of three states:

Table 3-2: SCALE states (2018 §3.3)

Outside edge of an alliance's PLATE, above carpet	State
4 ft 0 in. to 4 ft 8 in. (48–56 in.)	That alliance has OWNERSHIP
4 ft 8 in. to 5 ft 4 in. (56–64 in.)	Neither alliance has OWNERSHIP (balanced band)
5 ft 4 in. to 6 ft 0 in. (64–72 in.)	The opposing alliance has OWNERSHIP

The manual warns that equal cube counts do not guarantee balance: where cubes sit on a PLATE changes the torque. A cube placed at the outer end of a PLATE is worth more tilt than a cube near the tower.

Figures 3-4 to 3-8 (placeholders): SCALE overview, BRICKS, range of motion, PLATE and wall dimensions. See 2018 manual §3.3.

RUNGS. At the top of the SCALE are two RUNGS, one per alliance, each reaching into that alliance's PLATFORM ZONE. A RUNG is a **1 ft 1 in. (13 in.) long, 1¼ in. Schedule 40 aluminium pipe**, extending **8¼ in.** from the vertical face of the SCALE supports. The **top of the RUNG is 7 ft (84 in.)** above the carpet.

BRICKS. Gold-and-black brick graphics cover the base of the TOWER and OUTRIGGERS up to **12 in. above the PLATFORM** surface. They matter for scoring: a robot only counts as CLIMBED if its BUMPERS are fully above the BRICKS at the end of the MATCH (Section 4.2).

TOWER and OUTRIGGERS. The TOWER is the central structure supporting the RUNGS and PLATES; it is **17 in. wide** and stands **2 in.** proud of the OUTRIGGER faces. All frame surfaces are covered in polycarbonate.

PLATFORM. At the base of the SCALE, on each alliance's side, is a PLATFORM covered in alliance-coloured HDPE. Its top is **8 ft 8 in. wide × 3 ft 5¼ in. deep** and **3½ in. tall**, with ramps **1 ft 1 in.** long at **15.35°**. The alliance-coloured tape that abuts the ramps counts as part of the PLATFORM.

Figures 3-9 to 3-12 (placeholders): RUNGS, TOWER dimensions, PLATFORM top and ramp. See 2018 manual §3.3.

3.4 SWITCH

There are **two SWITCHES**, one per alliance, each centred across the field width with its centre **14 ft** from the alliance's ALLIANCE STATION. *Your* SWITCH is the one nearest your ALLIANCE STATION. Any robot may place cubes on either SWITCH, but only the owning alliance scores from it.

SWITCH PLATES. Each SWITCH has two PLATES, **3 ft × 4 ft**, whose outside edges are **12 ft apart**. Walls and lighting match the SCALE PLATES (1 ft 3 in. centre-facing wall, 3½ in. elsewhere). When the SWITCH is level, the PLATES sit **9 in.** above the carpet.

Table 3-3: SWITCH states (2018 §3.4)

Outside edge of an alliance's PLATE, above carpet	State
3 in. to 6 in.	That alliance has OWNERSHIP of its SWITCH
6 in. to 15 in.	Neither alliance has OWNERSHIP

FENCE. Each SWITCH is surrounded by a FENCE **12 ft 9½ in. wide × 4 ft 8 in. deep × 1 ft 6¾ in. (18.75 in.) tall**. The gap between the FENCE and the sides of the PLATES is about 1½ in.; between the FENCE and the outer ends of a level PLATE, about 2¼ in.

> **Teaching trap — 9 in. vs 18.75 in.** The PLATE is 9 in. off the carpet, but the FENCE around it is 18.75 in. tall. The height your mechanism actually has to clear is the **fence**, plus the 13 ×

13 × 11 in. cube you are holding. Students who design to “9 in.” build robots that can’t score on the SWITCH.

Figures 3-13 to 3-16 (placeholders): SWITCH, PLATE dimensions, range of motion, FENCE. See 2018 manual §3.4.

3.5 PLATE lighting

Each PLATE is outlined with LED strings that show the alliance colour of the PLATE and the state of play: pulsing when that colour owns the element, dim (about 25%) when the other colour owns it, a chase pattern while that alliance’s BOOST is active, and pulsing with corners in the opposite colour while FORCE is active. After the MATCH, **purple** means “safe for field staff only” and **green** means “safe for everyone” — drive teams wait for green before stepping onto the field (S02). The 2018 manual notes that, during the season, events were told to move the SCALE light strings to the cavity under the OUTRIGGERS.

3.6 ALLIANCE WALL, EXCHANGE and VAULT

The ALLIANCE WALL separates the robots from the drive teams. It holds three PLAYER STATIONS and one EXCHANGE.

PLAYER STATION. Each has a 3 ft diamond-plate base with a 3 ft 6 in. clear panel above it and a shelf **5 ft 9 in. wide × 1 ft deep** for the OPERATOR CONSOLE, with a **4 ft 6 in.** strip of hook-and-loop tape. Each station provides an Ethernet cable to the FMS, a 120 VAC outlet on its own 2 A breaker, an E-Stop button, a team sign and a team LED (solid = connected and enabled; blinking = waiting for the match, or lost connection during it).

EXCHANGE. A polycarbonate wall **6 ft 5¾ in. tall × 4 ft wide** between PLAYER STATIONS 1 and 2.

- **Lower opening** (robot → human): **1 ft 4¼ in. (16.25 in.) tall × 1 ft 9 in. wide**, with a small 1¾ in. ramp up to conveyor rollers that the HUMAN PLAYER spins to pull the cube through a tunnel about 2 ft deep.
- **RETURN** (human → robot): a **1 ft 2 in. (14 in.) square** opening centred above the lower opening, **1 ft 8 in. (20 in.)** above the carpet, with a chute and a swinging wall that pushes the cube onto the field.

VAULT. Behind the EXCHANGE, inside the ALLIANCE STATION. Three columns, each about **13½ in. wide × 39¼ in. tall**, bottom **15½ in.** off the floor. Facing the open columns from the ALLIANCE STATION: **FORCE** on the left, **LEVITATE** in the centre, **BOOST** on the right. Each column holds up to three cubes; a row of lights counts them, and a button plays the POWER UP. The manual advises placing cubes logo-side-down so three always fit and are sensed reliably.

Figures 3-18 to 3-20 (placeholders): ALLIANCE STATION, EXCHANGE, VAULT. See 2018 manual §3.6.

3.7 PORTAL

Each alliance has two PORTALS, one at each corner of its end of the field. A HUMAN PLAYER standing in a PORTAL can push cubes onto the field through a **14 in. square opening, 20 in. above the carpet**, using a chute with a swinging wall — the same geometry as the EXCHANGE RETURN. A robot that can take a cube from a 20 in. chute can therefore be fed from three places.

3.8 POWER CUBE

A POWER CUBE is a **13 in. × 13 in. × 11 in. tall** HDPE milk crate in a yellow nylon cover, with the FIRST logo over the open face. It weighs about **3¼ lb (1.5 kg)**. Cubes are soft-sided enough to squash slightly in a roller intake and stiff enough to stack.

Figure 3-22 (placeholder): POWER CUBE. See 2018 manual §3.8.

3.9 Vision targets

The real 2018 field had **retro-reflective tape**, not AprilTags. Each SWITCH FENCE carried targets on its faces toward the ALLIANCE WALLS, one per PLATE: two vertical 2 in. strips, 16 in. tall, 4 in. apart, with about 15.3 in. visible when viewed straight on, centred **51⅞ in.** from the centre of the SWITCH.

> **FICTION reminder.** AprilTags did not exist on any 2018 field. Appendix B gives a TAS-invented 32-tag layout so vision students share a vocabulary. It is never used at a real event and is not a hint about any future game.

3.10 The FIELD Management System

The FMS runs the field: computers, referee tablets, the wireless access point, sensors, stack lights and E-Stops. When a team plugs its OPERATOR CONSOLE into the PLAYER STATION Ethernet, the Driver Station software talks to the FMS, and only listed network ports are open. Robot code cannot be deployed while connected to the FMS.

The software requirement that matters most in this game: **the FMS sends each team the PLATE colour assignment just before AUTO.** The manual is explicit that teams must write the robot code to use it. A robot that ignores it is guessing which side of the SCALE is its own.

Audio cues mark the MATCH (for example, three bells at the start of TELEOP and a train whistle at 30 seconds left), but the field timers, not the sounds, are official.

Vol I · Section 4 MATCH Play

4.1 Stages and setup

Stages. AUTO is the first **0:15**: robots act only on pre-loaded code, with no drive-team input. TELEOP is the remaining **2:15**: drivers control the robots. The last **0:30** of TELEOP is the ENDGAME. Before and after each MATCH, crews reset the field and the next drive teams load in.

Figure 4-1 (placeholder): the four possible PLATE colour assignments. See 2018 manual §4.1.

Cube staging (per alliance side, 2018 §4.1).

- **7** cubes in each PORTAL, minus any preloads (at least **5** must remain in each PORTAL);
- **6** cubes along the SCALE-facing side of each SWITCH FENCE, evenly spaced;
- **10** cubes in each alliance's POWER CUBE ZONE pile, a 6-3-1 pyramid against the SWITCH.

Each robot may **preload one cube**, held entirely by the robot.

Placement order. If either alliance asks, robots are placed alternately (in Qualifications: Red 1, Blue 1, Red 2, Blue 2, Red 3, Blue 3; in Playoffs the higher seed places last).

4.2 Scoring

The main way to score is OWNERSHIP of your SWITCH or of the SCALE.

SWITCH OWNERSHIP. An alliance owns its SWITCH when, for at least one second, its PLATE's outside edge is **at or below 6 in.**, *or* it has played FORCE at level 1 or 3.

SCALE OWNERSHIP. An alliance owns the SCALE when, for at least one second, its PLATE's outside edge is **at or below 4 ft 8 in. (56 in.)** and the opponent does not have an active level 2 or 3 FORCE, *or* it has played FORCE at level 2 or 3.

OWNERSHIP pays an entry bonus when it is established, plus points for every further second. Points already earned are never taken away; when OWNERSHIP changes, accumulation stops (if balanced) or switches to the other alliance.

Table 4-1: FIRST POWER UP rewards (paraphrase of 2018 Table 4-1)

Action	Criteria (paraphrased)	AUTO pts	TELEOP pts	RP
AUTO-RUN	Per robot whose BUMPER breaks the plane of its AUTO LINE at any time in AUTO	5	—	—
OWNERSHIP — SCALE	Per Section 4.2 above	2 + 2/s	1 + 1/s	—
OWNERSHIP — own SWITCH	Per Section 4.2 above	2 + 2/s	1 + 1/s	—
VAULT	Per cube placed in the VAULT	—	5	—
PARKING	Per robot fully supported by the SCALE (directly or through another robot), not in the opponent's PLATFORM ZONE, and not CLIMBED	—	5	—
CLIMBING	Per robot fully supported by the SCALE, BUMPERS fully above the BRICKS at T=0, not touching its PLATFORM, not in the opponent's PLATFORM ZONE	—	30	—
FACE THE BOSS	Three robots CLIMBED, or two CLIMBED and LEVITATE played	—	—	1
AUTO QUEST	Three AUTO-RUNS and OWNERSHIP of own SWITCH at the end of AUTO	—	—	1
Win / Tie	Final score higher / equal	—	—	2 / 1

Worked example (from the manual's own example). An alliance takes its SWITCH 3 seconds into AUTO and holds it for 5 seconds: 2 points for establishing OWNERSHIP + 5 × 2 = 10 points for the seconds held = **12 points**.

Note — PARKING. "Fully supported by the SCALE" includes standing on the PLATFORM, since the PLATFORM is part of the SCALE.

Note — referees. AUTO-RUN and CLIMBING are judged by human referees, not sensors. The manual tells teams to make both obvious. A climb that ends with a bumper an inch from the BRICK line invites a "no".

Cubes delivered through the EXCHANGE. The HUMAN PLAYER may (1) put the cube in the VAULT for 5 points and progress toward a POWER UP, (2) send it back through the RETURN, or (3) keep it in the ALLIANCE STATION for later.

4.3 POWER UPS

POWER UPS are earned by filling VAULT columns and played by pressing that column's button during TELEOP.

Table 4-2: POWER UPS (paraphrase of 2018 Table 4-2)

Name	Cubes in column	Effect	Duration
LEVITATE	3	One extra CLIMBING robot is credited to the alliance at the end of the MATCH (maximum three CLIMBS total)	N/A
FORCE	1	Alliance earns OWNERSHIP points for its SWITCH regardless of PLATE position	10 s
FORCE	2	… for the SCALE	10 s
FORCE	3	… for both its SWITCH and the SCALE	10 s
BOOST	1	Doubles the OWNERSHIP points the alliance is earning from its SWITCH	10 s
BOOST	2	… from the SCALE	10 s
BOOST	3	… from both its SWITCH and the SCALE	10 s

Rules of play for POWER UPS (2018 §4.3, paraphrased):

- **Only one FORCE or BOOST can be active on the field at a time.** If one is running and the *other* alliance plays FORCE or BOOST, theirs is **queued** and starts the moment the current one ends. If an alliance presses FORCE or BOOST while its own other FORCE/BOOST is active, the press is ignored.
- Each POWER UP can be played **once per MATCH**. Once played it cannot be cancelled. FORCE and BOOST can be played with 1, 2 or 3 cubes in their column; the level is the number of cubes at the moment of the press.
- Cubes added to a column *after* its POWER UP has been played still score 5 VAULT points.
- **LEVITATE** can be played at any time in TELEOP and is not queued. At the end of the MATCH the climb is credited to a robot that is neither PARKING nor CLIMBING; if every robot is PARKING or CLIMBING, a PARKING robot is upgraded to CLIMBING.

Figure 4-3 (placeholder): POWER UP timeline example — Red FORCE at 0:60 runs to 0:50; Blue BOOST pressed at 0:55 is queued until 0:50; Red BOOST pressed at 0:48 is queued until Blue's ends at 0:40; Blue LEVITATE at 0:35 is immediate. See 2018 manual §4.3.

Strategy note. The queue makes timing a weapon: playing a POWER UP early in a period when your opponent wants to play theirs pushes theirs later. Because LEVITATE costs three cubes and only ever replaces *one* climb, it is most valuable to an alliance with two reliable climbers — it turns them into FACE THE BOSS.

4.4 Rule violations

Table 4-3: Penalties (2018 Table 4-3, paraphrased)

Penalty	Effect
FOUL	5 points added to the opponent's score
TECH FOUL	25 points added to the opponent's score
YELLOW CARD	A warning from the Head Referee for egregious behaviour or violations; a second YELLOW in the same tournament phase becomes a RED
RED CARD	The team is DISQUALIFIED for that MATCH
DISABLED	The robot is commanded to turn off all outputs for the rest of the MATCH
DISQUALIFIED	Zero MATCH points for the team in Qualifications; zero for the whole alliance in Playoffs

4.5 DRIVE TEAM

A DRIVE TEAM is up to **five** people from one team.

Table 4-4: DRIVE TEAM roles (2018 Table 4-4, paraphrased)

Role	What they do	Max	Who
COACH	Guide / advisor	1	Student or adult mentor
DRIVER and HUMAN PLAYER	Operate the robot; manage POWER CUBES at the EXCHANGE, VAULT and PORTALS	3 combined	Pre-college students
TECHNICIAN	Robot set-up, connectivity, console troubleshooting, removal from the field	1	Pre-college student

The TECHNICIAN was new in 2018. They stand outside the ALLIANCE STATION (usually with the robot cart) and should know the radio, roboRIO lights, console login, battery change and pneumatic charging. The manual also expects every drive-team member to know where the main breaker is and how to release the robot from the SCALE after a climb.

4.6 Logistics

- A cube that leaves the FIELD is out of play for the rest of the MATCH (one that bounces straight back in is fair game). Robots may not deliberately send cubes out of the field except through the EXCHANGE lower opening (G21).
- A MATCH is not replayed because cubes were missing, misplaced or damaged at the start; tell field staff *before* the MATCH.
- After the MATCH, wait for **green** PLATE lights before entering the field.

Vol I · Section 5 ROBOT Match Envelope (2018)

MOCK PRECEDENCE: THESE FOUR 2018 RULES SET THE ROBOT'S SIZE, REACH AND INSPECTION WEIGHT FOR THIS GAME.

In this mock, the robot's **match envelope** — how big it may be at the start, how far it may reach during play, and how much it may weigh at inspection — comes from the **2018** manual, because these rules were written for this field. Four rules do the work: R03, R04 and R05 from 2018 Section 8, and G05 from 2018 Section 7, which restates R04 as a game rule with a penalty.

Citation for this whole section: 2018 FRC Game and Season Manual, §8.2 (R01–R05) and §7.2 (G05).

5.1 FRAME PERIMETER — the reference for everything

Both size rules are measured from the **FRAME PERIMETER**. In 2018 (R01) it is found by wrapping a string around the robot, *excluding bumpers*, at bumper height and pulling it taut; the string outlines the FRAME PERIMETER. It must be made of fixed, non-articulated structure. Bolt heads, rivets and similar protrusions up to ¼ in. are ignored.

Mock note. The 2026 manual calls the same idea the ROBOT PERIMETER (2026 R101) and finds it with the same taut-string method. For this mock, treat the 2026 ROBOT PERIMETER of a TAS robot as its 2018 FRAME PERIMETER. Everything in this section is then measured from that string line.

5.2 Starting size — R03

R03 — Starting configuration size (2018)

In its STARTING CONFIGURATION, the robot **excluding BUMPERS** must fit inside a box **33 in. × 28 in. × 55 in. tall** (about 83 × 71 × 139 cm). Minor protrusions of less than ¼ in. are exempt from the 33 in. and 28 in. limits.

Enforced at: inspection. Teams should expect to demonstrate that the robot can constrain itself to this box; the constraint may be hardware or software.

Source: 2018 Game Manual §8.2, R03. See also R02 (nothing outside the vertical projection of the FRAME PERIMETER at the start, except bumpers and minor protrusions).

What it means for POWER UP. A **55 in.** starting height lets an elevator robot start with its first stage already tall, so it can reach the SCALE quickly in AUTO. The 33 × 28 in. footprint is a box, not a perimeter limit: a long, thin chassis that might be legal under a perimeter-length rule can fail R03. Common 26–27½ in. square swerve frames fit comfortably.

Read R02 with R03. At the start, nothing may stick out past the vertical projection of the FRAME PERIMETER. Intakes, arms and climbers must therefore start folded *inside* the frame outline, as well as inside the 55 in. height.

5.3 Reach during the MATCH — R04 and G05

R04 — Extension limit (2018)

Robots may not extend more than **16 in. (~40 cm) beyond their FRAME PERIMETER**, except during the ENDGAME (see G05).

Source: 2018 Game Manual §8.2, R04, Figure 8-1.

G05 — “Don’t overextend yourself.” (2018)

Robots may not extend more than **16 in. (41 cm) beyond their FRAME PERIMETER**. The limit does **not** apply to a robot that is **fully within its own PLATFORM ZONE during the ENDGAME**.

Violation: FOUL. If strategic (for example, the over-extension results in scoring a POWER CUBE), RED CARD.

Source: 2018 Game Manual §7.2, G05, Figure 7-1. Blue box: teams should also think about venue height, camera poles and lighting trusses.

How to read R04 and G05 together. R04 is the construction rule and mentions the ENDGAME; G05 is the game rule referees enforce, and it is more specific: the exemption needs the robot to be **fully inside its own PLATFORM ZONE** *and* the MATCH to be in the ENDGAME. A robot that unfolds a climber in the last 30 seconds while still half outside the PLATFORM ZONE is not exempt.

The 16 in. is horizontal. In 2018 the extension limit is measured outward from the FRAME PERIMETER, as Figure 7-1 of the 2018 manual shows with bars drawn in the same orientation as the frame. **The 2018 rules have no general cap on robot height during a MATCH.** That is how 2018 elevators reached the SCALE. The real limits on height were physical: venue ceilings, the 84 in. RUNG, and the robot’s own centre of gravity.

What it means for POWER UP.

- **SWITCH:** the PLATE ends sit about 2¼ in. inside the FENCE. 16 in. of reach is plenty to put a cube over the FENCE and onto the PLATE.
- **SCALE:** scoring is a *height* problem (PLATE edges 48–72 in.), not a reach problem. An elevator or a pivoting arm that stays within 16 in. horizontally is legal at any height.
- **Floor intake:** a 13 in. cube can be grabbed by an intake that reaches less than 16 in. out.
- **Climbing:** a deployable hook or buddy-climb platform may exceed 16 in. once the robot is fully in its PLATFORM ZONE in the ENDGAME.

Figure 5-1 (placeholder, after 2018 Figures 7-1 and 8-1): extension measured from the FRAME PERIMETER — robot A over the limit, robots B and C within it.

5.4 Weight — R05

R05 — Weight limit (2018)

The robot may weigh no more than **120 lb**. All mechanisms that might be used in different configurations are weighed together. **Excluded** from the weight: (A) the robot's BUMPERS, and (B) the robot battery with its half of the Anderson connector pair (including no more than 12 in. of cable per leg, lugs, bolts and insulation).

Enforced at: inspection (2018 I03).

Source: 2018 Game Manual §8.2, R05.

Mock rule of thumb. R05 (120 lb) is the mock inspection limit. Design to the 2026 limit in R103 (**115 lb**, Volume II Sec 8.1) and you pass both. A full 2018-style robot with an elevator, intake and climber is buildable inside 115 lb.

5.5 Envelope summary

Table 5-1: The 2018 match envelope used in this mock

Topic	Rule	Limit	Exceptions / notes
Starting size	R03 (with R02)	33 × 28 × 55 in. tall, bumpers excluded	Protrusions < ¼ in. exempt from 33/28 in.
Reach during MATCH	R04, G05	≤ 16 in. beyond the FRAME PERIMETER	Lifted when fully inside own PLATFORM ZONE during ENDGAME
Height during MATCH	—	No general 2018 rule	Bounded in practice by venue, RUNG at 84 in., stability
Inspection weight	R05	≤ 120 lb, bumpers and battery excluded	Design target 115 lb (2026 R103)

Vol I · Section 6 Game Rules (curated)

This section collects the 2018 game rules most likely to change a design or a strategy. It is **not** the full rule set: the 2018 manual also has safety rules (S01–S06), conduct rules (C), human rules (H01–H09) and further A-rules. Each box gives the rule's own short title in quotes, a paraphrase and the violation. Citations are to 2018 Game Manual §7.

6.1 Before the MATCH

G01 — "Know your ROBOT setup."

When placed on the field, each robot must: have passed inspection; be the only item the drive team leaves on the field; be in its STARTING CONFIGURATION; sit on the carpet; touch its ALLIANCE WALL diamond plate; not touch the EXCHANGE wall or break the plane of the EXCHANGE ZONE; and hold no more than one POWER CUBE.

Violation: the MATCH waits for a quick fix; otherwise the robot is DISABLED and may need re-inspection.

2018 §7.1

G03 — "Know your DRIVE TEAM positions."

Before the MATCH, drivers and coach stand in their ALLIANCE STATION behind the STARTING LINE; HUMAN PLAYERS stand behind the STARTING LINE in the ALLIANCE STATION or a PORTAL; the TECHNICIAN stands in the designated area outside both.

Violation: the MATCH does not start until corrected.

2018 §7.1

G04 — "Leave the POWER CUBES alone."

Before the MATCH, drive teams may not rearrange cubes in a PORTAL or on the field (other than one preloaded in their robot), or move cubes from one PORTAL to another.

Violation: the MATCH does not start until corrected.

2018 §7.1

6.2 ROBOT restrictions

G05 — "Don't overextend yourself."

No more than **16 in.** beyond the FRAME PERIMETER, except a robot fully within its own PLATFORM ZONE during the ENDGAME. Full treatment in Section 5.3.

Violation: FOUL; RED CARD if strategic.

2018 §7.2

G06 — “Keep it together.”

Robots may not *intentionally* detach parts or leave them on the field. Accidental breakage is not penalised under this rule.

Violation: RED CARD.

2018 §7.2

G07 — “Keep your BUMPERS together.”

Robots must meet the bumper rules for the whole MATCH.

Violation: FOUL. DISABLED if a bumper segment comes completely off, a whole side of the robot is exposed, or the team number or alliance colour can no longer be determined.

2018 §7.2. In this mock, bumpers are built to 2026 rules (Sec 8.4), and G07 is how the game enforces them on the field.

G08 — Robots are removed by hand.

After the MATCH, robots are carried off unpowered. They are not re-enabled, and teams may not tether to them (wired or wireless) on the field except in special circumstances with the FTA’s or a referee’s permission.

Violation: YELLOW CARD.

2018 §7.2. Design consequence: a climber must be releasable by hand, unpowered, without dropping the robot.

G09 — “Launching POWER CUBES is okay, but keep it short.”

A robot may launch a cube only when (A) its bumpers are in its own NULL TERRITORY and it is placing on the SCALE PLATE in that territory; (B) its bumpers touch a SWITCH FENCE, or part of it is inside the vertical planes of the FENCE, and it is placing on the nearest PLATE of that SWITCH; or (C) its bumpers are in its own EXCHANGE ZONE and it is placing into its EXCHANGE.

Violation: TECH FOUL per cube; repeated violations escalate quickly to cards.

2018 §7.2, Figure 7-2

6.3 ROBOT-to-ROBOT interaction

G10 — “Don’t tear others down to lift yourself up.”

No strategies aimed at destroying or disabling other robots through attachment, damage, tipping or entanglement (a wedge to tip robots is the manual’s example).

Violation: FOUL and YELLOW CARD; RED CARD if harm or incapacitation results.

2018 §7.3

G11 — “Stay out of other ROBOTS.”

No deliberate or damaging contact with an opponent on or inside the vertical extension of its FRAME PERIMETER, including through a POWER CUBE. High-speed accidental collisions happen; robots extend mechanisms outside their frame at their own risk.

Violation: FOUL and YELLOW CARD.

2018 §7.3

G12 — No collusion to shut down major parts of the game.

Two or more robots may not close off a major part of play — blocking the EXCHANGE, blocking both PORTALS, cutting off all cubes, or boxing opponents into a small area. One robot blocking one area is not a violation; two robots each defending one opponent is not a violation.

Violation: YELLOW CARD for the alliance.

2018 §7.3

G13 — “If an opponent’s down, back off.”

A tipped robot trying to right itself (alone or with a partner’s help) gets one grace period of **10 seconds**, or until it is upright, during which opponents may not touch it.

Violation: FOUL; YELLOW CARD if intentional.

2018 §7.3

G14 — “There’s a 5-count on pins.”

No pinning an opponent for more than **5 seconds**. A pin lasts until the robots are at least **6 ft** apart; the pinning robot must then wait at least **3 seconds** before pinning the same robot again. Pinning can be transitive through other objects, and contact is not required (trapping a robot against a wall counts). If the pinned robot chases the retreating robot, the pin is over and not penalised.

Violation: FOUL, plus another FOUL every 5 seconds until corrected; RED CARD if extended (generally more than 15 seconds).

2018 §7.3

G15 — “Opponent’s EXCHANGE ZONE: no camping.”

A robot may not block the opponent’s EXCHANGE ZONE (any part breaking its plane) for more than **5 seconds**; the block lasts until the robot has moved at least **6 ft** away. A pinned robot is exempt until the pin ends.

Violation: FOUL, plus another every 5 seconds; YELLOW CARD if extended and egregious (generally more than 15 seconds).

2018 §7.3

G16 — “The NULL TERRITORY is safe.”

A robot whose bumpers are in its own NULL TERRITORY (and not in the opponent’s PLATFORM ZONE) may not be contacted by an opponent, directly or through a cube, **no matter who starts the contact**. A robot shoved into the opponent’s NULL TERRITORY and wedged under the SCALE is not a violation.

Violation: TECH FOUL.

2018 §7.3

G17 — “Don’t climb on each other until the end.”

Except during the ENDGAME, or while righting a tipped partner, robots may not strategically support a partner’s weight.

Violation: TECH FOUL.

2018 §7.3

G18 — “Don’t mess with opponents in their PLATFORM ZONE.”

During the ENDGAME, robots may not contact an opponent that is completely inside that opponent’s own PLATFORM ZONE, directly or through a cube, regardless of who starts it.

Violation: the contacted robot, and every partner it is fully supporting, is counted as CLIMBED at the end of the MATCH.

2018 §7.3. The manual also points teams to conduct rule C07 about trying to draw this violation.

Contact summary for drivers. Three places are safe for your robot: your NULL TERRITORY (G16, any time), your PLATFORM ZONE (G18, ENDGAME only), and — for five seconds — your EXCHANGE ZONE against a camper (G15). Two clocks run in your head: the 5-second pin count (G14) and the 5-second EXCHANGE count (G15).

6.4 FIELD and POWER CUBE interaction

G19 — “Be careful about what you interact with.”

Drive teams, robots and consoles may not grab, grasp, attach to, hang from, deform, become entangled with, or damage field elements. Grabbing, grasping, attaching and hanging are allowed on **RUNGS and POWER CUBES** (that is how robots climb and carry cubes). Normal cube wear is expected; gouging or tearing cubes is not.

Violation: FOUL during a MATCH; YELLOW CARD if extended or repeated; DISABLED if further damage is likely.

2018 §7.4

G20 — “POWER CUBES: use as directed.”

Apart from placing them on PLATES, robots may not use cubes to make field elements easier or harder — for example, stacking cubes under a PLATE, climbing on cubes, using cubes to block opponents, or (egregiously) placing a cube on top of the SCALE to block the opponent’s RUNG.

Violation: TECH FOUL per cube; escalates quickly to cards.

2018 §7.4

G21 — “Keep POWER CUBES in bounds.”

Except through the EXCHANGE lower opening, robots may not intentionally eject cubes from the field.

Violation: FOUL per cube.

2018 §7.4

G22 — “One POWER CUBE per ROBOT.”

A robot may control at most **one** cube. “Control” includes carrying, herding (deliberately pushing a cube somewhere), trapping it against a field element, and launching. Not control: bulldozing (incidental contact while driving), deflecting, briefly plowing through a pile, and nudging a cube already on a PLATE while placing another. A cube lodged in or on a robot counts as controlled.

Violation: FOUL per extra cube; escalates to cards.

2018 §7.4. Design consequence: an intake must be physically unable to swallow a second cube.

G23 — Opponent’s POWER CUBE ZONE is off limits.

Robots may not remove cubes from, or cause cubes to be removed from, the opponent’s POWER CUBE ZONE — including by pushing one cube with another.

Violation: FOUL per cube.

2018 §7.4

G24 — “POWER CUBES stay on PLATES.”

No strategies aimed at removing cubes from PLATES (sweeping them off with an arm, launching at a stack to knock it over).

Violation: TECH FOUL per cube removed.

2018 §7.4

G25 — “PLATES are moved by POWER CUBES, not ROBOTS.”

Apart from the weight of placed cubes, robots may not cause or prevent PLATE movement, directly or through a cube. Momentary contact with minimal movement (the blue box says roughly under 1 second and under 3 in.) is not a violation; neither is a robot shoved under the SCALE by an opponent.

Violation: FOUL per instance, plus a TECH FOUL for every 5 seconds not corrected; escalates to cards.

2018 §7.4. Examples in the manual: holding the SCALE level; holding a PLATE up.

6.5 AUTO rules (selected)

A01–A03 — Hands off during AUTO.

During AUTO, drive-team members may not touch anything in front of the STARTING LINE (A01), may not interact with their robot or console except for safety or an E-Stop (A02 — adjusting the console after PLATE colours are assigned is a violation), and must disconnect any controllers they are holding or wearing (A03).

Violation: A01 FOUL per item; A02 FOUL and YELLOW CARD; A03 FOUL.

2018 §7.5

A04 — “Stay out of your opponent’s side of the FIELD.”

During AUTO, no part of a robot’s bumpers may cross from the NULL TERRITORY into the opponent’s side of the field.

Violation: FOUL; TECH FOUL if contact is made with an opponent on its side; escalates to cards.

2018 §7.5

Design consequences of Volume I, in one list. (1) Clear an 18.75 in. FENCE with a cube. (2) Reach 48–72 in. SCALE PLATE edges without exceeding 16 in. horizontally. (3) Fit a cube through a 16.25 in. EXCHANGE opening and take cubes from 20 in. chutes. (4) Hold exactly one cube. (5) Climb an 84 in. RUNG, finishing with bumpers above the 12 in. BRICKS, and be removable unpowered. (6) Start inside 33 × 28 × 55 in. (7) Read the FMS PLATE colours in AUTO.

VOLUME II — ROBOT CONSTRUCTION · 2026 REBUILT RULES · TAS MOCK · NOT OFFICIAL

Vol II · Section 7 Construction Overview and Precedence

Volume II answers the question *"How do we build it?"* In this mock, the answer is: **to the 2026 Game Manual (REBUILT), Section 8**, the construction rules a TAS robot would meet at an event today. Volume I's 2018 rules still decide the game, the scoring and the match envelope; Volume II decides what the robot is made of.

Citation for this whole volume: 2026 Game Manual, TU22 version, Section 8 *ROBOT Construction Rules*. Subsection numbers below (8.1, 8.4, 8.5 …) match that manual so you can turn straight to the source.

2026 match-size rules (starting size, reach and in-match size limits) are not used in this mock; Volume I Section 5 governs the envelope.

Table 7-1: What Volume II covers

This manual	2026 manual	Topic	Rules summarised
8.1	8.1 General ROBOT Design	Weight	R103
8.4	8.4 BUMPER Rules	Bumpers	R401–R412 (summary)
8.5	8.5 Motors & Actuators	Motors	R501, R502, R503 (and R504–R505 for context)
8.6	8.6 Power Distribution	Battery and main power	R601 (and R602, R605, R609 for context)
8.7	8.7 Control, Command & Signals	Control system	R701–R717
8.8	8.8 Pneumatic System	Pneumatics	R801–R811 (summary)
8.9	8.9 OPERATOR CONSOLE	Driver station hardware	R901–R907 (pointer)

Sections 8.2 (safety and damage prevention) and 8.3 (budget and fabrication schedule) of the 2026 manual also apply to a real build, but they rarely change a concept design, so this mock only points to them. Read them before you buy or cut anything.

> **Why 2026 for construction?** Motors, motor controllers, radios and the control system have changed completely since 2018. A design exercise that used the 2018 parts list would teach students to plan around devices they cannot buy. Using 2026 construction rules keeps the mock honest about what is in our cabinets.

Vol II · Section 8 ROBOT Construction Rules (2026, selected)

An asterisk (*) before a rule title in the 2026 manual marks rules that apply at all times at an event, not only on the field. All rules in this section carry that mark in the source.

8.1 Weight — R103

> **R103 — “ROBOT weight limit.” (2026)**
>
> The robot may weigh no more than **115.0 lb (52.16 kg)**. Everything that might be used in a single configuration is weighed together. **Excluded:** (A) BUMPERS; (B) the robot battery with its half of the Anderson connector pair, including wire, lugs, bolts and insulation; (C) location-detection tags if the event provides them.
>
> *Source: 2026 Game Manual §8.1, R103. Related: R408 caps robot plus bumpers at 135.0 lb.*

In this mock: inspection uses 2018 R05 (120 lb, Section 5.4); R103’s 115 lb is the TAS **design target**. Track weight in a spreadsheet from the first CAD sketch: a 2018-style elevator robot typically spends its budget on drivetrain, elevator stages and the climber, in that order.

8.4 BUMPERS (summary of R401–R412)

Bumpers protect robots from each other and from the field. The 2026 manual measures bumper dimensions at inspection with a **0.25 in. tolerance** (maximums +0.25 in., minimums −0.25 in.) and asks teams to design to nominal values.

Table 8-A: 2026 bumper rules at a glance (paraphrased)

Rule	Title (2026)	Requirement, paraphrased
R401	BUMPERS almost all around	Bumpers protect the whole ROBOT PERIMETER. Gaps under 1.25 in. are allowed if corners are filled; one larger gap is allowed if at least 5.0 in. of perimeter each side of every corner is covered. Arcs count as “infinite corners”.
R402	BUMPER construction	Every vertical cross-section has: **padding** ≥ 2.25 in. deep and ≥ 4.5 in. tall (pool noodles/backer rod, or polyethylene, EVA or floor-tile foam within stated densities); **backing** ≥ 4.5 in. tall supporting the padding; a cloth **cover**; and a rigid **fastening system**.
R403	Extension limit	Bumpers extend no more than **4.0 in.** from the ROBOT PERIMETER.
R404	Must be soft	Hard parts no more than 1.25 in. out from the perimeter; padding extends at least 2.0 in. past any hard part.
R405	BUMPERS interact with BUMPERS	While driving normally, padding and backing fill the **BUMPER ZONE: 2.5 in. to 5.75 in. above the floor** (relative to whatever surface the robot is on).
R406	Fill corners	Corners filled with uncompressed padding at least 2.25 in. from the corner; two mitred segments do not count as filled.
R407	Not wedges	No profiles that act as wedges (soft-on-top foam, semicircles, tapered padding).
R408	Weight with bumpers	Robot (as weighed for R103) plus bumpers ≤ **135.0 lb**.
R409	Passive	Bumpers are fixed to the perimeter, with no moving or electrical parts.
R410	Must come off	Designed for removal for inspection and weighing

Rule	Title (2026)	Requirement, paraphrased
		(guideline: two people, under five minutes).
R411	Show your alliance	Red or blue covers as scheduled; only listed markings allowed (team numbers, fasteners, white FIRST logos 4.75–5.25 in. wide, exposed seams).
R412	Team numbers	White numerals ≥ 3.75 in. tall, ≥ 0.5 in. stroke, in at least 3 locations about 90° apart, readable from about 60 ft; not wrapped round sharp corners or split ambiguously.

Fit with the 2018 game. 2018 R03 *excludes* bumpers from the 33 × 28 in. starting box, so the bumpers' up-to-4 in. thickness does not count against the footprint. The 2.5–5.75 in. bumper zone keeps a 2026 bumper low enough to cross the ⅞ in. cable protectors and climb the 3½ in. PLATFORM ramp — but check ground clearance at the ramp transition on your drivetrain.

G07 on the field. Built to 2026, enforced in-game by 2018 G07 (Section 6.2): a detached segment or an exposed side gets the robot DISABLED.

8.5 Motors and actuators — R501, R502, R503

R501 — "Allowable motors." (2026)

Only the motors and actuators on the list in 2026 Table 8-1 are allowed, **in any quantity** (subject to R502). The list includes the CIM family, AndyMark and Banebots brushed motors, the Falcon 500, REV NEO, NEO 550 and NEO Vortex, the WCP Kraken X44 and X60, the CTRE Minion, the REV HD Hex, the ThriftyBot Pulsar 775, the WCP RS775 Pro, the VEX BAG and Mini-CIM, several KOP automotive motors (window, seat, etc.) and the Playing With Fusion Venom. Also allowed: small fans (≤ 120 mm, ≤ 10 W), motors inside COTS computing devices and sensors, PWM servos within stated stall-current and power limits, one compressor per R806, and **any COTS 12 V brushed motor, linear actuator, solenoid or electromagnet wired through an approved controller downstream of a breaker of 20 A or less**.

Source: 2026 §8.5, R501 and Table 8-1. Read the table itself for part numbers. A blue box warns that many motors drawing current at once can sag battery voltage, trip the main breaker or brown out the roboRIO.

R502 — “Only 4 propulsion motors.” (2026)

A robot may have **no more than 4 propulsion motors** — motors that move the robot across the carpet. **Not** counted as propulsion: swerve steering motors; mechanism motors whose wheels occasionally touch the carpet without significant thrust; gear-shifting motors; and motors that move the robot by contact with non-carpet field surfaces.

Source: 2026 §8.5, R502.

R503 — “Don’t modify motors (mostly).” (2026)

The integral mechanical and electrical system of a motor must not be modified. Allowed: modifying mounting brackets and output shafts; trimming leads and adding connectors; removing window-motor locking pins; modifying KOP automotive connector housings; manufacturer-sanctioned servo changes; minimal labelling; removing #10-32 plug screws from Falcon 500 / Kraken X60; insulating terminals; like-for-like repairs; and manufacturer-recommended maintenance.

Source: 2026 §8.5, R503. Intent (blue box): allow mounting changes, not weight-saving that weakens the motor.

Context: controllers (R504–R505). Every actuator except servos, fans and device-internal motors must be driven by an approved power-regulating device. In 2026 that list includes the Spark MAX, Spark Flex, Spark, Talon SRX, Talon FXS, Talon FX (for its integrated motors only), Victor SPX, original Talon, Victor SP, Thrifty Nova, Koors40 and Venom, plus relay modules, pneumatics controllers and the REV Servo Hub. R505’s Table 8-2 says which loads each device may drive and how many (generally one motor per controller; certain small motors two). Volume III notes that the original Talon and the Victor SP are on their way out.

Motor budget for a POWER UP robot (TAS estimate).

Subsystem	Typical motors	Propulsion?
Drivetrain (tank) or swerve drive	4	yes — 4
Swerve steering (if swerve)	4	no
Elevator	2	no
Intake rollers	2	no
Arm / wrist	1–2	no
Climber	2	no
Total	**11–16**	**4 (R502 limit)**

A 2018-era six-CIM tank drive would break R502; four brushless drive motors give more power than six 2018 CIMs. The 11–16 total also fits under the 2027 preview’s 18-motor cap (Volume III).

8.6 Power distribution — R601

R601 — “Battery limit – everyone has the same power.” (2026)

The only legal source of electrical energy on the robot is **one** non-spillable sealed lead-acid battery: nominal **12 V**; **17–18.2 Ah** at the 20-hour rate; rectangular, about **7.1 × 3.0 × 6.6 in.** (± 0.1 in.); **11.0–14.5 lb**; nut-and-bolt terminals; vents not obstructed while charging.

Source: 2026 §8.6, R601. The manual lists a dozen example part numbers (e.g. Enersys NP18-12).

Neighbouring rules students should know (2026 §8.6, paraphrased):

- **R602** — besides the robot battery, only COTS USB packs of **≤ 100 Wh** (27,000 mAh at 3.7 V) with stated 5 V/12 V, 5 A per-port output limits, batteries built into COTS computers or self-contained cameras, and CMOS/RTC cells may power COTS computing devices and their peripherals — securely mounted, with unmodified COTS cables. (Volume III: 2027 drops the voltage/current condition.)
- **R605** — no other batteries on the robot, even as ballast.
- **R606 / R607** — the battery must stay put even if the robot flips, and every terminal on the battery and main breaker must be fully insulated.
- **R609** — main power is one battery → one pair of Anderson SB connectors → one **120 A** main breaker → one power distribution device (PDP, PDP 2.0, REV PDH or AndyMark AMPD), all with **6 AWG** copper wire or larger.

8.7 Control, command and signals — R701 to R717

Table 8-B: 2026 control-system rules (paraphrased)

Rule	Short title (2026)	What it requires
R701	Control the ROBOT with a roboRIO	Exactly one roboRIO or roboRIO 2.0, imaged 2026_v1.2 or later. Co-processors are allowed if the roboRIO enables and disables every power-regulating device.
R702	Specified radio	One Vivid Hosting VH-109 wireless bridge, configured with the event's team key, is the only robot communication device in a MATCH (events in China use an OpenMesh radio).
R703	roboRIO Ethernet port	The roboRIO connects to the radio's "RIO" port, directly or via an allowed pigtail / passive PoE adapter, as specified per radio version.
R704	Allowed ports and bandwidth	Robot–console traffic only on the listed FMS ports, at most 7.0 Mbit/s on Vivid Hosting radios (4.0 on OpenMesh).
R705	Team number	roboRIO, Driver Station and radio configured for your team number.
R706	Don't bypass the ARENA network	All control signals come from the OPERATOR CONSOLE over the arena Ethernet network.
R707	Limited wireless	Only the radio link, event-provided location tags, and RFID/NFC entirely inside the robot. Cameras and non-RF sensors are not "wireless communication".
R708	Bridge visible	Radio mounted so field staff can see its lights; keep it away from noisy devices.
R709	Signal light	One or two approved Robot Signal Lights, visible from 36 in. away on at least one side, wired to the roboRIO RSL terminals.
R710	Only specified modifications	No tampering with control-system devices (roboRIO, PD, controllers, radio, breakers, battery …) except listed exceptions.
R711		

Rule	Short title (2026)	What it requires
	Don’t feed outputs to the roboRIO	No 12 V or motor/relay outputs into the roboRIO except its 12 V input.
R712	PWM from the roboRIO	Relays, servos and PWM controllers connect to roboRIO ports (or via a Spartan Sensor Board / legal MXP), and nothing else drives them.
R713	Approved MXP devices	Motors driven via the MXP use direct PWM pins, passive conductors, or one listed active board (navX MXP, navX2, RIOduino, etc.).
R714	CAN controllers from the roboRIO	CAN motor controllers are enabled/disabled by the roboRIO over CAN or PWM — not both at once. Closed-loop features are fine while the heartbeat is maintained.
R715	PCM, PH, Servo Hub from the roboRIO	Controlled over CAN from the roboRIO’s built-in CAN bus (directly or daisy-chained).
R716	Don’t alter the CAN bus	Nothing may block or alter CAN traffic between the roboRIO and its devices; one wire per Weidmuller terminal.
R717	USB-to-CAN adapter permitted	Extra CAN buses may be added with the CTRE **CANivore** USB-to-CAN adapter; motor controllers on that bus satisfy R714.

Figure 8-C (placeholder): control-system block diagram — battery → main breaker → PD → controllers; roboRIO ↔ radio ↔ field; CAN chain with optional CANivore. See the 2026 manual §8.6–8.7 and FIRST’s “How to Wire an FRC ROBOT”.

POWER UP software requirement. The 2018 FMS sends the PLATE colour assignment to the Driver Station just before AUTO (Section 3.10). Your autonomous code must read it and pick a routine. Practise that in the mock with a simple three-letter string such as “LRL” (left/right for near SWITCH, SCALE, far SWITCH, from your alliance’s point of view) — the format described in the 2018 control-system documentation.

8.8 Pneumatics (summary of R801–R811)

Table 8-C: 2026 pneumatic rules at a glance (paraphrased)

Rule	Requirement
R801	Only pneumatic parts explicitly permitted in §8.8.
R802	COTS only; rated ≥ 125 psi, or ≥ 70 psi if downstream of the primary relieving regulator.
R803	No modifications except cutting tubing, rewiring for control, assembling with existing threads/ fittings, removing a cylinder mounting pin, and labelling.
R804	Permitted items: vent plug, relief valve (125 psi, ≥ 1 scfm), solenoid valves (≤ ⅛ in. ports or ¼ in. push-to-connect), ≤ ¼ in. OD tubing, gauges and transducers, needle valves, manifolds, check and quick-exhaust valves, exhausting shut-off valves, regulators set ≤ 60 psi, cylinders and rotary actuators, tanks (except white Clippard AVT-PP-41), one compressor, filters, Venturi valves. Vacuum generators, gas shocks and air-filled wheels are not “pneumatic devices”.
R805	If you use pneumatics you must have: one legal compressor, a calibrated relief valve, a Nason pressure switch and/or REV analog pressure sensor, at least one vent plug, stored and working pressure gauges, and one primary working regulator.
R806	All air comes from the one onboard compressor (≤ 1.1 cfm nominal at 12 V).
R807	Stored pressure ≤ **120 psi**; no off-board storage.
R808	Working pressure ≤ **60 psi**, through one primary adjustable relieving regulator.
R809–R811	Only listed parts on the high-pressure side; gauges visible upstream and downstream of the regulator; relief valve attached at the compressor and set to release at 125 psi.

For POWER UP. Pneumatics were popular in 2018 for cube grabbers and two-position wrists. Remember that the battery powers the compressor, and that the mock design-weight budget includes the compressor, tanks and valves.

8.9 OPERATOR CONSOLE (pointer)

The OPERATOR CONSOLE rules are 2026 **R901–R907**. In short: use the official Driver Station software (version 26.0 or newer) on a device of your choice; show the Driver Station display where inspectors and the team can see it; plug the field Ethernet cable directly into that device (a pigtail is recommended); keep the console no longer than **60.0 in.**, no deeper than **16.0 in.** and no taller than **78.0 in.** above the floor; attach to the shelf only with its

hook-and-loop strip or a non-damaging clamp; no wireless of any kind; nothing unsafe; and no AC inverters. Consoles over about 30 lb invite scrutiny. Read the source before building one.

2018 vs 2026 shelf. The 2018 PLAYER STATION shelf was 5 ft 9 in. wide with a 4 ft 6 in. hook-and-loop strip (Section 3.6); the 2026 rules expect a 54 in. strip. A console that meets R904 fits either.

VOLUME III — 2027 PREVIEW · WATCH LIST, NOT RULES · TAS MOCK · NOT OFFICIAL

Vol III · Section 9 2027 Event & Robot Rule Preview — Part 1

On **31 August 2026** FIRST posted the first part of its rule preview for the 2027 season on the FIRST community blog. The post says its purpose is to help teams make purchasing decisions before kickoff, that the rules are not yet final, and that a part two may follow. **Nothing in a preview blog is a rule.** The 2027 Game Manual and Team Update 00 will be the authority.

Source: 2026 Event & Robot Rule Preview for 2027 Season — Part 1. This mock uses Part 1 only.

9.1 The seven bullets (paraphrased)

Table 9-1: 2027 Part 1 preview, paraphrased

#	Topic	What Part 1 says	2026 rule it touches
1	**Motor cap**	A maximum of **18 motors** per robot. FIRST says the cap would have affected about 10% of 2026 teams, and expects it to cut motor and controller cost and the need for secondary power distribution.	New limit on top of R501 (“any quantity”) and R502 (4 propulsion)
2	**No heating or cooling**	A new rule similar to FIRST Tech Challenge **E510**, “Don’t heat or cool ROBOT components to gain an advantage” — for example, breakers or batteries.	New
3	**Pneumatics**	**No significant changes** for 2027. FIRST is still considering changes for 2028 or later and aims to announce them early.	R801–R811 unchanged (per Part 1)
4	**CANivore**	Legal in 2027 to add extra CAN buses to **Systemcore**, the 2027 control system, as an interim measure (the equivalent of 2026 R717). For 2028 that allowance is planned to be removed; CANivore would stay legal as a node on a Systemcore-native bus.	R717
5			R504-A

#	Topic	What Part 1 says	2026 rule it touches
	Controllers removed	The original **Talon** and the **Victor SP** will no longer be legal motor controllers (each used by under 0.5% of teams).	
6	**BAG and Mini-CIM**	The VEX **BAG** and **Mini-CIM** leave the explicit motor list. They remain usable under the “any brushed motor downstream of a 20 A breaker” allowance, but no longer on larger breakers.	R501 / Table 8-1
7	**USB batteries**	The USB battery rule drops its voltage/current condition: any COTS USB battery of **≤ 100 Wh** (27,000 mAh at 3.7 V) is permitted.	R602

9.2 What Part 1 does not say

Part 1 does not address robot weight, size, reach, bumpers, the battery, the radio, or the operator console. Do not infer changes in those areas from silence. It does mention Systemcore by name, and describes broader ongoing discussion about robot power, component cost and actuator limits, but announces no decisions on them beyond the seven bullets above.

9.3 What it means for TAS this winter

- **Count motors, not just propulsion motors.** Every design sketch in this mock should include a motor count against 18. The Section 8.5 POWER UP estimate (11–16) fits; a swerve robot with a two-motor elevator, two-motor climber, intake and a two-motor wrist is close to the line.
- **Don’t buy original Talons or Victor SPs**, and treat any we own as practice-bot parts.
- **BAG and Mini-CIM** stay useful on 20 A circuits only — fine for small mechanisms, not for drivetrains.
- **Plan CAN topology for Systemcore.** CANivore is a bridge for 2027, not a permanent architecture.

- **Pneumatics investments are safe for 2027.**
- **Coprocessor power banks** become simpler to source: any COTS USB battery ≤ 100 Wh.
- **Never heat or cool parts for advantage** — no freezing breakers, no warming batteries — even before the 2027 rule exists. It is already a safety issue.

Table 9-2: Rule snapshot across the three layers

Topic	2018 (game layer)	2026 (construction layer)	2027 Part 1
Inspection weight	120 lb (R05)	115 lb design target (R103)	not addressed
Starting size	33 × 28 × 55 in., bumpers excluded (R03)	—	not addressed
Reach during MATCH	16 in. past FRAME PERIMETER; lifted in own PLATFORM ZONE in ENDGAME (R04, G05)	—	not addressed
Motor count	not the governing layer	≤ 4 propulsion (R502); others any quantity (R501)	**≤ 18 total**
Motor controllers	not the governing layer	R504 list	original Talon and Victor SP removed
CAN expansion	not the governing layer	CANivore (R717)	CANivore on Systemcore, 2027 only
USB batteries	not the governing layer	≤ 100 Wh with output limits (R602)	any COTS ≤ 100 Wh
Pneumatics	not the governing layer	R801–R811	no significant change
Heating/cooling parts	—	—	new prohibition (E510-like)

APPENDICES · TAS MOCK · NOT OFFICIAL

Appendix A Rule Cross-Reference and Precedence

Use this table when two layers seem to disagree. The left column is the question; the middle column is the rule that answers it *in this mock*.

Table A-1: Precedence by topic

Topic	Governing rule(s) in this mock	Layer	Manual section here
Field elements and dimensions	2018 §3	2018 game	Vol I Sec 3
MATCH stages, timing, setup	2018 §4.1	2018 game	Vol I Sec 4.1
Scoring, ranking points	2018 §4.2, Table 4-1	2018 game	Vol I Sec 4.2
POWER UPS	2018 §4.3, Table 4-2	2018 game	Vol I Sec 4.3
Penalty values	2018 §4.4, Table 4-3	2018 game	Vol I Sec 4.4
DRIVE TEAM roles	2018 §4.5, Table 4-4	2018 game	Vol I Sec 4.5
FRAME PERIMETER definition	2018 R01 (measured on the 2026 ROBOT PERIMETER, R101)	2018 envelope	Vol I Sec 5.1
Starting size	2018 R02, R03	2018 envelope	Vol I Sec 5.2
Reach during MATCH	2018 R04, G05	2018 envelope	Vol I Sec 5.3
Inspection weight	2018 R05 (design target 2026 R103)	2018 envelope	Vol I Sec 5.4, Vol II Sec 8.1
Game play, contact, cubes, AUTO	2018 G01–G25, A01–A05	2018 game	Vol I Sec 6
Bumpers — construction	2026 R401–R412	2026 construction	Vol II Sec 8.4
Bumpers — on the field	2018 G07	2018 game	Vol I Sec 6.2
Motors and actuators	2026 R501–R503 (R504–R506)	2026 construction	Vol II Sec 8.5
Battery and main power	2026 R601–R609	2026 construction	Vol II Sec 8.6
Control system and CAN	2026 R701–R717	2026 construction	Vol II Sec 8.7
Pneumatics	2026 R801–R811	2026 construction	Vol II Sec 8.8
OPERATOR CONSOLE	2026 R901–R907	2026 construction	Vol II Sec 8.9
Purchasing for next season	2027 Part 1 preview	watch list only	Vol III Sec 9
AprilTags	none — Appendix B is fiction	fiction	Appendix B

Table A-2: Rule IDs used in this manual

ID	Year	Short title / topic	Where
G01	2018	Know your ROBOT setup	6.1
G03	2018	Know your DRIVE TEAM positions	6.1
G04	2018	Leave the POWER CUBES alone	6.1
G05	2018	Don’t overextend yourself (16 in.)	5.3, 6.2
G06	2018	Keep it together	6.2
G07	2018	Keep your BUMPERS together	6.2
G08	2018	Remove robots by hand, no tethering	6.2
G09	2018	Launching POWER CUBES — limited	6.2
G10–G13	2018	Robot-to-robot conduct, fallen robots	6.3
G14	2018	5-count on pins	6.3
G15	2018	No camping in opponent EXCHANGE ZONE	6.3
G16	2018	NULL TERRITORY is safe	6.3
G17	2018	No climbing on partners until ENDGAME	6.3
G18	2018	PLATFORM ZONE protection in ENDGAME	6.3
G19–G25	2018	Field and POWER CUBE interaction	6.4
A01–A04	2018	AUTO rules	6.5
R01–R05	2018	FRAME PERIMETER, start size, reach, weight	5
R101	2026	ROBOT PERIMETER	5.1
R103	2026	Weight 115.0 lb	8.1
R401–R412	2026	Bumpers	8.4
R501–R506	2026	Motors, controllers, servos	8.5
R601–R609	2026	Battery and main power	8.6
R701–R717	2026	Control, command and signals	8.7
R801–R811	2026	Pneumatics	8.8
R901–R907	2026	OPERATOR CONSOLE	8.9

Appendix B TAS AprilTag Retrofit — IDs 1–32 (FICTION)

> **FICTION — READ THIS FIRST.** No 2018 FIRST POWER UP field ever carried AprilTags. The real field used retro-reflective tape on the SWITCH FENCES (Vol I Sec 3.9). The layout below was invented by TAS as a shared vocabulary for vision discussions, so that “tag 17” means the same thing to everyone. No FIRST rule, inspection, event or future game uses it, and it is not a prediction of anything. Mount positions are described in words only and are not surveyed.

Tag family: 36h11 (the family used in current WPILib field layouts). **Size:** 6.5 in. tag (8.125 in. with the recommended border). Stay consistent within one layout.

Table B-1: Allocation summary (fiction)

Group	Count	IDs	Moves with the game?
Blue SWITCH	8	1–8	Plate tags (1–4) tilt; fence tags (5–8) fixed
Red SWITCH	8	9–16	Plate tags (9–12) tilt; fence tags (13–16) fixed
SCALE plates	8	17–24	**Moving** — rigid to the plates
SCALE tower	4	25–28	**Fixed** — world-frame anchors
EXCHANGE feeders	4	29–32	Fixed; 29–30 Blue, 31–32 Red
Total	**32**	**1–32**	

Double-tag pairs. Each pair is two IDs on the same rigid element facing opposite directions, so a robot sees one of them from either side. The EXCHANGE pairs are the exception: both tags face the field, one each side of the RETURN. Treat each pair as one rigid body. **Never average a moving tag into your robot’s field pose**; use fixed tags (5–8, 13–16, 25–32) for localisation and moving tags only to *measure the game state*.

B.1 Blue SWITCH — IDs 1–8 (fiction)

ID	Location	Pair	Notes
1	Low-y PLATE, faces Blue ALLIANCE WALL	1 ↔ 2	Tilts with PLATE
2	Low-y PLATE, faces field centre	1 ↔ 2	Same panel as 1
3	High-y PLATE, faces Blue ALLIANCE WALL	3 ↔ 4	Tilts with PLATE
4	High-y PLATE, faces field centre	3 ↔ 4	
5	FENCE, low-y end, alliance-wall face	5 ↔ 6	Near the real 2018 retro-tape location
6	FENCE, low-y end, centre face	5 ↔ 6	
7	FENCE, high-y end, alliance-wall face	7 ↔ 8	
8	FENCE, high-y end, centre face	7 ↔ 8	

B.2 Red SWITCH — IDs 9–16 (fiction)

ID	Location	Pair	Notes
9	Low-y PLATE, faces Red ALLIANCE WALL	9 ↔ 10	Mirror of 1
10	Low-y PLATE, faces field centre	9 ↔ 10	
11	High-y PLATE, faces Red ALLIANCE WALL	11 ↔ 12	
12	High-y PLATE, faces field centre	11 ↔ 12	
13	FENCE, low-y end, alliance-wall face	13 ↔ 14	
14	FENCE, low-y end, centre face	13 ↔ 14	
15	FENCE, high-y end, alliance-wall face	15 ↔ 16	
16	FENCE, high-y end, centre face	15 ↔ 16	

B.3 SCALE — moving 17–24, fixed 25–28 (fiction)

Moving tags hang on panels rigid to each SCALE PLATE, so their pose encodes plate tilt: two PLATES × two ends (inner = toward the TOWER, outer) × two faces = 8 IDs.

ID	Location	Pair	Notes
17	Low-y PLATE, inner end, faces Blue	17 ↔ 18	Moves little (near pivot)
18	Low-y PLATE, inner end, faces Red	17 ↔ 18	
19	Low-y PLATE, outer end, faces Blue	19 ↔ 20	Best ownership signal
20	Low-y PLATE, outer end, faces Red	19 ↔ 20	
21	High-y PLATE, inner end, faces Blue	21 ↔ 22	Moves little
22	High-y PLATE, inner end, faces Red	21 ↔ 22	
23	High-y PLATE, outer end, faces Blue	23 ↔ 24	Best ownership signal
24	High-y PLATE, outer end, faces Red	23 ↔ 24	
25	TOWER face toward Blue, lower	25 ↔ 26	Fixed anchor
26	TOWER face toward Red, lower	25 ↔ 26	Fixed anchor
27	TOWER face toward Blue, upper	27 ↔ 28	Fixed anchor
28	TOWER face toward Red, upper	27 ↔ 28	Fixed anchor

Reading the SCALE with tags (concept only). Level outer edge is 60 in.; your alliance owns at 48–56 in.; the opponent owns at 64–72 in. (Vol I Table 3-2). An outer-end tag therefore moves several inches between bands, which a camera can distinguish; inner-end tags move much less.

B.4 EXCHANGE feeders — IDs 29–32 (fiction)

ID	Feeder	Pair	Notes
29	Blue EXCHANGE, left of RETURN	29 ↔ 30	Faces the field
30	Blue EXCHANGE, right of RETURN	29 ↔ 30	Faces the field
31	Red EXCHANGE, left of RETURN	31 ↔ 32	Faces the field
32	Red EXCHANGE, right of RETURN	31 ↔ 32	Faces the field

B.5 Known limitations of this fiction

These are deliberate discussion points, not errors to fix before the kickoff.

1. **SWITCH plate tags are partly hidden.** The PLATES sit 9 in. up inside an 18.75 in. FENCE, so a plate-mounted tag is mostly below the fence line from a robot camera. Discussion: move them onto the PLATE’s 1 ft 3 in. tall wall, or drop them and rely on the fence tags.
2. **PORTALS have no tags.** The 32-ID budget covers only the two EXCHANGES as feeders. Tagging all four PORTALS would need 8 more IDs or a rebalanced allocation.
3. **Inner SCALE tags carry little signal.** 17, 18, 21 and 22 sit near the pivot.
4. **No coordinates.** Anyone building a layout file must survey positions from the official 2018 field drawings.

Figure B-1 (placeholder): top-down sketch of tag IDs 1–32 — students draw this themselves on a printed field outline. FICTION.

Appendix C Glossary (excerpt)

Definitions are TAS paraphrases. The official glossaries are 2018 Section 11 and the 2026 manual’s glossary.

Table C-1: Game terms (2018)

Term	Meaning in this manual
ALLIANCE	A cooperative of three robots/teams (Red or Blue) in a MATCH.
ALLIANCE STATION	The 22 ft × 10 ft area behind the ALLIANCE WALL where the drive team stands.
ALLIANCE WALL	Three PLAYER STATIONS plus the EXCHANGE; separates robots from people.
ARCADE	Everything needed to play: field, elements, cubes, electronics.
AUTO	The first 15 seconds; robots run pre-programmed code only.
AUTO LINE / AUTO-RUN	Tape 10 ft from the ALLIANCE WALL; crossing it with a bumper in AUTO scores 5.
AUTO QUEST	Ranking point for three AUTO-RUNS plus SWITCH OWNERSHIP at the end of AUTO.
BOOST	POWER UP that doubles OWNERSHIP points for 10 s.
BRICKS	Graphics at the base of the SCALE to 12 in. above the PLATFORM; CLIMBED robots' bumpers must be above them.
CLIMB / CLIMBED	Fully supported by the SCALE, bumpers above the BRICKS, not touching the PLATFORM at T=0; 30 points.
ENDGAME	The last 30 seconds of TELEOP.
EXCHANGE	Alliance-wall opening (16.25 in. tall) where robots pass cubes to HUMAN PLAYERS; includes the RETURN.
EXCHANGE ZONE	4 ft × 3 ft area in front of the EXCHANGE.
FACE THE BOSS	Ranking point for three CLIMBS (or two plus LEVITATE).
FENCE	18.75 in. tall barrier around each SWITCH.
FORCE	POWER UP that awards OWNERSHIP points regardless of PLATE position for 10 s.
FRAME PERIMETER	Taut-string outline of the robot frame at bumper height, bumpers excluded (2018 R01).
LEVITATE	POWER UP (3 cubes) that credits one extra CLIMB.
MATCH	One 2:30 game between two alliances.
NULL TERRITORY	Areas at each end of the SCALE; the matching alliance's robots there are protected (G16).
OWNERSHIP	

Term	Meaning in this manual
	State in which a SWITCH or the SCALE is tilted toward an alliance's PLATE (or forced by FORCE); scores per second.
PARKING	Fully supported by the SCALE (e.g. on the PLATFORM) at the end without CLIMBING; 5 points.
PIN	Preventing an opponent from moving; limited to 5 s (G14).
PLATE	One of the two tilting trays on each SWITCH and on the SCALE.
PLATFORM / PLATFORM ZONE	Raised alliance-coloured base of the SCALE (3½ in.) / the taped zone around it.
PORTAL	Corner station where HUMAN PLAYERS feed cubes through a 14 in. opening 20 in. up.
POWER CUBE	13 × 13 × 11 in. yellow-covered crate, about 3¼ lb.
POWER CUBE ZONE	Area by each SWITCH holding the alliance's 10-cube pile.
POWER UP	FORCE, BOOST or LEVITATE, bought with cubes in the VAULT.
RETURN	Opening above the EXCHANGE through which humans send cubes back to the field.
RUNG	13 in. pipe on the SCALE, top 84 in. above the carpet, for climbing.
SCALE	Central tilting element with two PLATES; shared by both alliances.
STARTING CONFIGURATION	The robot's physical configuration at the start of a MATCH.
SWITCH	Tilting element near each alliance; only its own alliance can own it.
TECHNICIAN	Drive-team member (new in 2018) responsible for robot setup and connectivity.
TELEOP	The 2:15 driver-controlled period.
VAULT	Three-column structure where HUMAN PLAYERS place cubes for POWER UPS and points.

Table C-2: Construction and control terms (2026)

Term	Meaning in this manual
BUMPER	Required padded assembly around the ROBOT PERIMETER (R401–R412).
BUMPER ZONE	2.5–5.75 in. above the floor; bumper padding must fill it (R405).
CAN / CANivore	Controller Area Network bus for motor controllers and hubs / CTRE USB-to-CAN adapter (R717).
COTS	Commercial off-the-shelf.
Driver Station	The official software that sets robot mode and enable state (R901).
FMS	Field Management System.
OPERATOR CONSOLE	Everything drivers use to command the robot, including the Driver Station device (R901–R907).
PD	The robot’s main power distribution device (PDP, PDP 2.0, PDH, AMPD).
Propulsion motor	A motor that moves the robot across the carpet (R502 limit: 4).
roboRIO	The 2026 robot controller (R701).
ROBOT PERIMETER	2026 name for the taut-string frame outline (R101).
RSL	Robot Signal Light (R709).
Systemcore	The robot control system named in the 2027 preview.
Wireless bridge	The robot radio (Vivid Hosting VH-109 in 2026, R702).

Appendix D Study and Review Sheets

These sheets are designed to be photocopied. Answers to D.2 are on the last page of the appendix.

D.1 Scoring worksheet

Work each match out on paper using Vol I Table 4-1 and Table 4-2.

Match A. In AUTO, all three Red robots cross the AUTO LINE. Red takes its SWITCH at 0:04 into AUTO and holds it to the end of AUTO. Red also takes the SCALE at 0:09 into AUTO and holds it to the end of AUTO.

Item	Working	Points
AUTO-RUNS	3 × 5	
SWITCH OWNERSHIP in AUTO	2 + 2 × (seconds held)	
SCALE OWNERSHIP in AUTO	2 + 2 × (seconds held)	
AUTO QUEST?	yes / no	RP:

Match B (TELEOP). Blue holds the SCALE for 40 seconds and its SWITCH for 70 seconds (one continuous period each), places 6 cubes in the VAULT, PARKS one robot and CLIMBS two. Blue plays LEVITATE. Compute Blue's TELEOP points and say whether Blue earns FACE THE BOSS.

Item	Working	Points
SCALE	1 + 1 × 40	
SWITCH	1 + 1 × 70	
VAULT	6 × 5	
PARK / CLIMB / LEVITATE		
FACE THE BOSS?		RP:

Match C (POWER UP queue). Red plays FORCE (level 2) at 1:20 remaining. Blue plays BOOST (level 3) at 1:15 remaining. When does Blue's BOOST start and end? What happens if Red presses BOOST at 1:12 remaining?

D.2 Rules quiz (20 questions)

1. How long are AUTO, TELEOP and the ENDGAME?
2. At what outside-edge height does an alliance own its SWITCH? The SCALE?
3. Why is "9 in." the wrong number to design your SWITCH mechanism around?
4. What is the starting-size limit in this mock, and which rule sets it? Are bumpers included?
5. How far may a robot extend past its FRAME PERIMETER during a MATCH, and when does that limit not apply?
6. Is there a general robot height limit during a 2018 MATCH?

7. What is the mock inspection weight limit, and what design target does TAS recommend?
8. What is the penalty for scoring a cube *because* your robot was over-extended?
9. How many cubes may a robot control at once? Name two actions that count as “control”.
10. You are pinning an opponent against a PORTAL wall. How long until it is a FOUL, and how far must you back off?
11. Where is your robot protected from contact regardless of who starts it?
12. What happens if an opponent touches your robot while it is fully in your PLATFORM ZONE during the ENDGAME?
13. Can you launch a cube at the SCALE from anywhere on the field?
14. How many propulsion motors does 2026 R502 allow? Does a swerve steering motor count?
15. What does the 2027 Part 1 preview say about total motor count?
16. Name the two motor controllers Part 1 says will be removed for 2027.
17. Under Part 1, can a VEX BAG motor still be used in 2027? On what breaker?
18. What are the 2026 BUMPER ZONE heights?
19. What is the maximum stored and working air pressure under 2026 rules?
20. Is the Appendix B AprilTag layout used at any real event?

D.3 Design constraint checklist

Tick each item for your concept sketch.

- [ ] Starts inside 33 × 28 × 55 in., bumpers excluded (R03), nothing outside the frame outline (R02)
- [ ] Never more than 16 in. past the FRAME PERIMETER except fully in own PLATFORM ZONE in ENDGAME (G05)
- [ ] Places a cube over an 18.75 in. FENCE onto a SWITCH PLATE
- [ ] Places a cube on a SCALE PLATE whose edge may be anywhere from 48 to 72 in.
- [ ] Delivers through a 16.25 in. EXCHANGE opening; accepts cubes from 20 in. chutes
- [ ] Physically cannot hold two cubes (G22)
- [ ] Climbs an 84 in. RUNG with bumpers ending above the 12 in. BRICKS, or parks on the PLATFORM
- [ ] Releases from the RUNG by hand, unpowered (G08)
- [ ]

Weighs ≤ 115 lb design target (R103); ≤ 120 lb mock limit (R05); ≤ 135 lb with bumpers (R408)

☐ Bumpers fill 2.5–5.75 in., ≤ 4.0 in. thick from the perimeter (R403, R405)

☐ ≤ 4 propulsion motors (R502); ≤ 18 motors total (2027 preview)

☐ All controllers on the 2026 list, none of the 2027-removed ones

☐ One SLA battery (R601); 120 A main breaker; one PD (R609)

☐ roboRIO + VH-109 radio + RSL, CAN plan with or without CANivore (R701–R717)

☐ Pneumatics (if any) at ≤ 120 psi stored, ≤ 60 psi working (R807, R808)

☐ Autonomous code reads the FMS PLATE assignment

D.4 Motor budget worksheet

Subsystem	Motor type	Qty	Propulsion? (R502)	Controller	Breaker
Drive					
Steering					
Elevator					
Intake					
Arm / wrist					
Climber					
Other					
Totals		**/ 18**	**/ 4**		

D.5 AUTO planner

For each of the four PLATE assignments the FMS can send (the near SWITCH and SCALE plates each left or right), write the routine your robot will run from each of the three starting positions. Fill in all twelve cells before arguing about which one is best.

FMS assignment (SWITCH / SCALE)	Left start	Centre start	Right start
L / L			
L / R			
R / L			
R / R			

D.6 Rule-lookup drill

Pairs of students race to find each item **in the official PDFs** (not in this mock) and write the page number:

1. 2018 Figure 7-1 (G05 examples) — page: ____
2. 2018 Table 4-2 (POWER UPS) — page: ____
3. 2018 §3.3 SCALE state heights — page: ____
4. 2026 R502 — page: ____
5. 2026 R717 — page: ____
6. 2026 Table 8-2 (controller allotments) — page: ____
7. 2027 Part 1: the sentence about the 18-motor cap — paragraph: ____

D.7 Mentor checklist

- [ ] Show the animation (`HZbdwYiCY74`) once, with the “watch for” list from Sec 1.2.
- [ ] Read FM.2 aloud: game and envelope from 2018, construction from 2026, 2027 as a watch list.
- [ ] Assign squads: SWITCH cycle, SCALE, EXCHANGE/VAULT, ENDGAME.
- [ ] Everyone does D.1 and D.2; designers do D.3 and D.4; programmers do D.5.
- [ ] Vision students only: Appendix B, framed as fiction.
- [ ] Collect one alliance strategy page per squad.

D.8 Answer key for D.2

1. AUTO 0:15; TELEOP 2:15; ENDGAME the last 0:30 of TELEOP. (4.1)
2. SWITCH: outside edge ≤ 6 in. for at least 1 s. SCALE: ≤ 4 ft 8 in. (56 in.) for at least 1 s, with no active opposing level 2/3 FORCE. (4.2)
3. The PLATE is 9 in. up, but the FENCE is 18.75 in. — the mechanism must clear the fence with a cube. (3.4)
4. 33 × 28 × 55 in. tall, from 2018 R03; bumpers are excluded. (5.2)
5. 16 in. (R04, G05); not applicable to a robot fully inside its own PLATFORM ZONE during the ENDGAME. (5.3)
6. No; the 2018 rules have no general in-match height cap. (5.3)
7. 120 lb (2018 R05), bumpers and battery excluded; design target 115 lb (2026 R103). (5.4, 8.1)
8. RED CARD (G05: strategic violation).
9. One (G22). Carrying, herding, trapping, launching.

10. More than 5 s is a FOUL; separate by at least 6 ft, then wait 3 s before pinning the same robot. (G14)
11. Your own NULL TERRITORY (G16), unless also in the opponent's PLATFORM ZONE.
12. Your robot, and any partner it fully supports, is counted as CLIMBED. (G18)
13. No — only from your NULL TERRITORY (to that SCALE PLATE), at a SWITCH FENCE (to its nearest PLATE), or in your EXCHANGE ZONE (into your EXCHANGE). (G09)
14. Four; swerve steering motors do not count. (R502)
15. A maximum of 18 motors per robot. (9.1)
16. The original Talon and the Victor SP. (9.1)
17. Yes, under the "any brushed motor downstream of a 20 A breaker" allowance — 20 A or less only. (9.1)
18. 2.5 in. to 5.75 in. above the floor. (R405)
19. 120 psi stored (R807); 60 psi working (R808).
20. No. It is TAS fiction. (Appendix B)

Answers to D.1. Match A: AUTO-RUNS 15; SWITCH 2 + 2 × 11 = 24; SCALE 2 + 2 × 6 = 14 (taking AUTO as 15 s and counting whole seconds held); AUTO QUEST yes (+1 RP). Match B: SCALE 41; SWITCH 71; VAULT 30; every robot is PARKING or CLIMBING, so LEVITATE upgrades the parked robot to CLIMBING — 3 × 30 = 90 instead of 60 + 5; FACE THE BOSS yes (two climbs + LEVITATE) — Blue TELEOP total 41 + 71 + 30 + 90 = 232. Match C: Blue's BOOST is queued until Red's FORCE ends at 1:10 remaining, then runs from 1:10 to 1:00. Red's BOOST press at 1:12 is **ignored**, because Red's own FORCE is still active (2018 §4.3); Red has not used its BOOST and may press it again later.

Appendix E Revision History

Version	Date	Change
V0	2026-11-09	First full mock manual. Replaces the earlier eight-section kickoff handout. Volume I (2018 game and match envelope), Volume II (2026 construction), Volume III (2027 Part 1 preview), Appendices A–E. Numbers checked against text extracts of the 2018 manual, the 2026 manual (TU22) and the 2027 Part 1 blog.

TAS MOCK · HYPOTHETICAL · NOT OFFICIAL. Not a FIRST® publication. For TAS classroom use only; do not post publicly. Official sources: 2018 Game Manual · 2026 Game Manual · 2027 Preview Part 1.

TAS-MOCK-2018-PU · Document version V0 · 2026-11-09 · End of document