

Tutorial on: Digital Topology, Geometry and Applications

1st talk: Distance Transforms

Gunilla Borgefors


Centre for Image Analysis
Uppsala University

Gunilla.Borgefors@it.uu.se



Distance into shape


2



Each pixel gets a value that is the distance to the nearest background pixel in the used metric.

Distance from shape

3



ICPR tutorial 2014

A distance transform imposes a structure on an object / background that can be used for manipulating, recognizing, and analysing the image

4

ICPR tutorial 2014

5

Contents

1. The optimal weighted 3x3 DT
2. Other 2D DTs
3. DT properties
4. Computing DTs
3. 3D DTs
6. Extended DTs

ICPR tutorial 2014

6


The distance between two points in Z^n is defined as the length of the shortest path connecting them in an appropriate graph.

Depends on:

1. Neighbourhood relation
2. Definition of path length

ICPR tutorial 2014

7



edge-neighbour steps
point-neighbour steps
knight-neighbour steps

ICPR tutorial 2014

8

3 x 3 neighbourhood mask

+b	+a	+b
+a	+0	+a
+b	+a	+b


3x3 weighted DT

the weights **a** and **b** are the local distances between the pixels

ICPR tutorial 2014

9

Path between two pixels




ICPR tutorial 2014

10


Path – alternative order, same distance

It's not about
simulating a
straight line – it is
about measuring
a distance!




ICPR tutorial 2014

11



$$2a < 2b$$



$$1b < 2a$$


A 3 x 3 weighted DT is

REGULAR if $a < b < 2a$

SEMI-REGULAR if $a \leq b \leq 2a$

ICPR tutorial 2014

12



$$\begin{aligned} \text{path length} &= \\ b y + a (x-y) &= \\ x a + y (b - a) \end{aligned}$$

What are the
optimal a and b ?

ICPR tutorial 2014

(13)

Assume $x \leq y$ and an $M \times M$ image. Minimize rotation dependence.

Difference from Euclidean for max $x = M$ is

$$\text{Diff}(y) = y(b-a) + aM - \sqrt{x^2 + y^2}, \quad 0 \leq y \leq M$$

Max of $\text{Diff}(y)$ occurs for

$$y=0 \quad E1 = (a-1) M$$

$$y : \text{Diff}'(y) = 0 \quad E2 = (a - \sqrt{1 - (b-a)^2}) M$$

$$y = M \quad E3 = (b - \sqrt{2}) M$$

$\min\{E1, E2, E3\}$ occurs for $-E1 = E2 = -E3$, so solve

$$1-a = a - \sqrt{1 - (b-a)^2} = \sqrt{2} - b$$

ICPR tutorial 2014

(14)

Optimal weights

$$a_{\text{opt}} = \frac{1}{2} + \frac{1}{2} \sqrt{2\sqrt{2}-2} \approx 0.955$$

$$b_{\text{opt}} = \sqrt{2} - \frac{1}{2} + \frac{1}{2} \sqrt{2\sqrt{2}-2} \approx 1.369$$

$$\text{maxdiff} = \frac{1}{2} - \frac{1}{2} \sqrt{2\sqrt{2}-2} \approx 0.045 M$$

ICPR tutorial 2014

(15)

Optimal weights

$$a_{\text{opt}} = \frac{1}{2} + \frac{1}{2} \sqrt{2\sqrt{2}-2} \approx 0.955$$

$$b_{\text{opt}} = \sqrt{2} - \frac{1}{2} + \frac{1}{2} \sqrt{2\sqrt{2}-2} \approx 1.369$$

$$\text{maxdiff} = \frac{1}{2} - \frac{1}{2} \sqrt{2\sqrt{2}-2} \approx 0.045 \text{ M}$$

Note that $a = 1$, $b = \sqrt{2}$ give $\text{maxdiff} = 0.090 \text{ M}$

ICPR tutorial 2014

(16)


Integer approximations

a	b	maxdiff
opt	opt	0.064
2	3	0.134
3	4	0.081
8	11	0.073


Multiply the optimal **a**, **b** by a number and then round to the nearest integer.

ICPR tutorial 2014

17



optimal $\langle a, b \rangle$ weights disc




$\langle 3, 4 \rangle$ disc


ICPR tutorial 2014

18

Path-generated distance transforms




City block / Manhattan DT
 D^4




Chessboard DT
 D^8

ICPR tutorial 2014

19



City block disc




Chessboard disc

ICPR tutorial 2014

20

5 x 5 neighbourhood mask



adding **knight**-neighbour step **c**

ICPR tutorial 2014

(21)

Optimal a , b , c are complex expressions, approximately

$$\mathbf{a}_{\text{opt}} \approx 0.986$$

$$\mathbf{b}_{\text{opt}} \approx [1.400, 1.422]$$

$$\mathbf{c}_{\text{opt}} \approx 2.208$$

$$\text{maxdiff} \approx 0.014 \text{ M}$$

ICPR tutorial 2014


(22)

Integer approximation

a	b	c	maxdiff
opt	opt	opt	0.0141
5	7	11	0.0202

ICPR tutorial 2014

23





$\langle 5, 7, 11 \rangle$ disc

ICPR tutorial 2014

24

Path-generated Knight-distance



this generates a (strange) metric

ICPR tutorial 2014

(25)

Euclidean distance transform

+(1,1)	+(0,1)	+(1,1)
+(1,0)	+(0,0)	+(1,0)
+(1,1)	+(0,1)	+(1,1)

A vector in each pixel, counting
x-steps and y-steps separately.

Distance value = $\sqrt{x^2 + y^2}$,
but usually $(x^2 + y^2)$ is used

ICPR tutorial 2014

(26)

Useful 2D distance transforms


	a	b	c	maxdiff
City block	1	-	-	58.6 %
3 - 4	3	4	-	8.1 %
5-7-11	5	7	11	2.0 %
Euclidean	(1,0)	(1,1)	-	0* %

* If computed correctly (which is not trivial!)

ICPR tutorial 2014

27

Useful 2D distance transforms



city block

<3,4>


<5, 7, 11>

EDT

Distance transform from single point

ICPR tutorial 2014


28



R^2 circle, radius = 10

ICPR tutorial 2014


29





Z^2 circle, radius = 10



ICPR tutorial 2014

30



ICPR tutorial 2014






<3,4> computation by chamfering

35

Initialisation



■ = 0


■ = infinity

ICPR tutorial 2014


<3,4> computation by chamfering

36

Forward pass – first change



Forward mask




ICPR tutorial 2014

<3,4> computation by chamfering

(37)

Forward pass – ongoing




ICPR tutorial 2014

<3,4> computation by chamfering

(38)

Forward pass – finished




Distances are now measured from left and from above.

ICPR tutorial 2014

39


Backward mask



ICPR tutorial 2014

40


Backward mask



ICPR tutorial 2014

<3,4> computation by chamfering


Backward pass – finished



Distances are now measured also from right and from bottom.

ICPR tutorial 2014

Chamfering: 5x5 masks



Backward


Only two passes necessary also in this case.

ICPR tutorial 2014

43

Chamfering: Euclidean distance

...can be computed by three raster scans...




...but the result is not quite correct in all pixels and the result is not a metric. Use more complex, but correct algorithms!

ICPR tutorial 2014

44

3D distance transforms




area neighbours (6) + edge neighbours (18) + point neighbours (26)

ICPR tutorial 2014


(45)

3D distance transforms - path-generates spheres




area neighbours

D^6



+ edge neighbours

D^{18}



+ point neighbours

D^{26}

Do not use D^{18} – it has some weird properties.

ICPR tutorial 2014

(46)

3 x 3 x 3 neighbourhood

+c	+b	+c
+b	+a	+b
+c	+b	+c

+b	+a	+b
+a	+0	+a
+b	+a	+b

+c	+b	+c
+b	+a	+b
+c	+b	+c

A weighted DT is semiregular if

$$\begin{aligned} a &\leq b \leq 2a \\ b &\leq c \leq 3b/2 \end{aligned}$$

ICPR tutorial 2014

(47)


Useful 3D distance transforms

	a	b	c	maxdiff
D^6	1	-	-	126.8 %
3-4-5	3	4	5	11.8 %
optimal	0.926	1.341	1.658	7.4 %
Euclidean	(1,0,0)	(1,1,0)	(1,1,1)	0* %

* If computed correctly (which is not trivial!)

ICPR tutorial 2014

(48)



<3, 4, 5> sphere = icositetrahedron



Natural garnet crystal

ICPR tutorial 2014

Reverse distance transform

Start from seed points with radius values.


Subtract local distance from neighbours in mask

Maximize the values

works for city block and weighted distances.

Computing the reverse Euclidean DT is quite complex.


Reverse distance transform



Reverse <3,4> from seed points **17** and **10**.

(51)

Reverse distance transform



Reverse <3,4> from seed point 17.

DT values are not the same. But the **shape** is the correct one.


ICPR tutorial 2014

(52)

Constrained distance transform

● start

■ constraint




Compute DT from start using parallel algorithm

ICPR tutorial 2014

(53)


Constrained distance transform



ICPR tutorial 2014

(54)

Constrained distance transform



Shortest path: follow gradient from goal to start

ICPR tutorial 2014


(55)

Geodesic distance transform

2D: Consider a grey-level image as a landscape and find the shortest path through it.
Problem: How high is a grey-level step?

<3-4> DT
4 grey-levels of height 2

● start



ICPR tutorial 2014

(56)


Geodesic distance transform

Shortest path(s) in the geodesic DT

<3-4> DT
4 grey-levels of height 2

● start

● goal




ICPR tutorial 2014

(57)


Saliency distance transform

Spread other information than grey-level together with the distance:


Edge strength – Edge length – Curvature – etc.



Gradient map



DT map from thresholded edges



Saliency DT map

Stolen from Paul Rosin
and Geoff West

ICPR tutorial 2014

(58)

A few key references

Borgefors, G. (1986). Distance Transformations in Digital Images, *Computer Vision, Graphics and Image Processing* 34, pp. 344–371.

Borgefors, G. (1996). On Digital Distance Transforms in Three Dimensions, *Computer Vision and Image Understanding* 64, pp. 368–376.

Borgefors, G. (2003). Weighted Digital Distance Transforms in Four Dimensions, *Discrete Applied Mathematics* 125, pp. 161–176.

Coeurjolly, D. (2003). *d*-Dimensional Reverse Euclidean Distance Transformation and Euclidean Medial Axis Extraction in Optimal Time, *LNCS 2886*, Springer-Verlag, pp. 327–337.

Das, P.P. and Chatterji, B.N. (1988). Knight's Distance in Digital Geometry, *Pattern Recognition Letters* 7, pp. 215–226.

Ikonen, L. and Toivanen, P. (2007). Distance and nearest neighbour transforms on grey-level surfaces, *Pattern Recognition Letters* 28, pp. 604–612.

ICPR tutorial 2014

A few more key references

Piper, J. and Granum, E. (1987). Computing Distance Transformations in Convex and Non-Convex Domains, *Pattern Recognition* 20, pp. 599–615.

Rosenfeld, A. and Pfaltz, J.L. (1968). Distance Functions on Digital Pictures, *Pattern Recognition* 1, pp. 33–61.

Ragnemalm, I. (1993). The Euclidean Distance Transform in Arbitrary Dimensions, *Pattern Recognition Letters* 14, pp. 883–888.

Rosin, P.R. and West, G.A.W. (1995). Saliency Distance Transforms, *Graphical Models and Image Processing* 57, pp. 483–521.

Sintorn, I.M. and Borgefors, G. (2004). Weighted Distance Transforms for Volume Images Digitized in Elongated Voxel Grids, *Pattern Recognition Letters* 25, pp. 571–580.

Ye, Q.Z. (1988). The Signed Euclidean Distance Transform and Its Applications, In: *Proc. 9th ICPR*, Rome, Italy, pp. 495–499.

THE END