

# Discrete Circle Recognition

David Cœurjolly

Laboratoire LIRIS  
Université Claude Bernard Lyon 1  
43 Bd du 11 Novembre 1918  
69622 Villeurbanne CEDEX  
France  
`david.cœurjolly@liris.cnrs.fr`

January - 2005

# Plan

- 1 Definitions
- 2 Discrete circle recognition in  $LP_3$
- 3 Discrete circle recognition in  $LP_2$
- 4 Efficient discrete algorithm
  - Optimizations
    - Computational cost analysis
    - On-line recognition and Discrete arc segmentation
- 5 Conclusion

- 1 Definitions
- 2 Discrete circle recognition in  $LP_3$
- 3 Discrete circle recognition in  $LP_2$
- 4 Efficient discrete algorithm
  - Optimizations
  - Computational cost analysis
  - On-line recognition and Discrete arc segmentation
- 5 Conclusion

- 1 Definitions
- 2 Discrete circle recognition in  $LP_3$
- 3 Discrete circle recognition in  $LP_2$
- 4 Efficient discrete algorithm
  - Optimizations
  - Computational cost analysis
  - On-line recognition and Discrete arc segmentation
- 5 Conclusion

## Definitions

Discrete  
circle  
recognition in  
 $LP_3$

Discrete  
circle  
recognition in  
 $LP_2$

Efficient  
discrete  
algorithm

Optimizations  
Computational  
cost  
analysis  
On-line  
recognition  
and  
Discrete arc  
segmentation

## Conclusion

# Table of contents

## 1 Definitions

## 2 Discrete circle recognition in $LP_3$

## 3 Discrete circle recognition in $LP_2$

## 4 Efficient discrete algorithm

- Optimizations
- Computational cost analysis
- On-line recognition and Discrete arc segmentation

## 5 Conclusion

# Introduction

## *Why the discrete circle recognition ?*

- Important elementary object in the discrete geometry paradigm
- Order 2 object  $\rightarrow$  curvature estimation

## Definitions

Discrete  
circle  
recognition  
in  
 $LP_3$

Discrete  
circle  
recognition  
in  
 $LP_2$


Efficient  
discrete  
algorithm

Optimizations  
Computational  
cost  
analysis  
On-line  
recognition  
and  
Discrete arc  
segmentation

Conclusion

Definition of a discrete disk with center  $(0, 0)$


$$D : x^2 + y^2 < \left(R + \frac{1}{2}\right)^2, \quad x, y \in \mathbb{Z} \text{ and } R \in \mathbb{R}$$



# Discrete circle

Definition of an arithmetical discrete circle with center  $(x_0, x_0)$  and radius  $R$

$$\left(R - \frac{1}{2}\right)^2 \leq (x - x_0)^2 + (y - y_0)^2 < \left(R + \frac{1}{2}\right)^2, \quad x, y \in \mathbb{Z}$$





# Recognition based on circular separability


## Property

A set  $D$  of pixels is a digital disk if there exists an Euclidean circle that encloses the pixels of  $D$  but excludes its complement

## Circular separability in Computational Geometry

- $\Rightarrow$  Linear programming in dimension 3
- $\Rightarrow$  Linear programming in dimension 2

## Notations



# Recognition based on circular separability


## Property

A set  $D$  of pixels is a digital disk if there exists an Euclidean circle that encloses the pixels of  $D$  but excludes its complement

## Circular separability in Computational Geometry

- $\Rightarrow$  Linear programming in dimension 3
- $\Rightarrow$  Linear programming in dimension 2

## Notations



# Preimage of discrete circle and *arc center domain*

## Definition

Given a set of pixels  $S$ , its preimage must contain the set of discrete disks enclosing  $S$  and excluding its complement

- 3 parameters:  $(x_0, y_0)$  and  $R$ 
  - The problem is not linear
  - Can be reduced to a 2-D domain representing the centers  $(x_0, y_0)$  (*arc center domain*) from which we can deduce a set of radii  $R$  according to  $S$

$acd$  is empty  $\Leftrightarrow$  the preimage is empty  $\Leftrightarrow S$  is not a discrete disk

## Preimage of discrete circle and *arc center domain*

### Definition

Given a set of pixels  $S$ , its preimage must contain the set of discrete disks enclosing  $S$  and excluding its complement

- 3 parameters:  $(x_0, y_0)$  and  $R$
- The problem is not linear
- Can be reduced to a 2-D domain representing the centers  $(x_0, y_0)$  (*arc center domain*) from which we can deduce a set of radii  $R$  according to  $S$

$acd$  is empty  $\Leftrightarrow$  the preimage is empty  $\Leftrightarrow S$  is not a discrete disk

## Preimage of discrete circle and *arc center domain*

### Definition

Given a set of pixels  $S$ , its preimage must contain the set of discrete disks enclosing  $S$  and excluding its complement

- 3 parameters:  $(x_0, y_0)$  and  $R$
- The problem is not linear
- Can be reduced to a 2-D domain representing the centers  $(x_0, y_0)$  (*arc center domain*) from which we can deduce a set of radii  $R$  according to  $S$

$acd$  is empty  $\Leftrightarrow$  the preimage is empty  $\Leftrightarrow S$  is not a discrete disk

## Preimage of discrete circle and *arc center domain*

### Definition

Given a set of pixels  $S$ , its preimage must contain the set of discrete disks enclosing  $S$  and excluding its complement

- 3 parameters:  $(x_0, y_0)$  and  $R$
- The problem is not linear
- Can be reduced to a 2-D domain representing the centers  $(x_0, y_0)$  (*arc center domain*) from which we can deduce a set of radii  $R$  according to  $S$

$acd$  is empty  $\Leftrightarrow$  the preimage is empty  $\Leftrightarrow S$  is not a discrete disk

## Preimage of discrete circle and *arc center domain*

### Definition

Given a set of pixels  $S$ , its preimage must contain the set of discrete disks enclosing  $S$  and excluding its complement

- 3 parameters:  $(x_0, y_0)$  and  $R$
- The problem is not linear
- Can be reduced to a 2-D domain representing the centers  $(x_0, y_0)$  (*arc center domain*) from which we can deduce a set of radii  $R$  according to  $S$

$acd$  is empty  $\Leftrightarrow$  the preimage is empty  $\Leftrightarrow S$  is not a discrete disk

# Table of contents

## 1 Definitions

## 2 Discrete circle recognition in $LP_3$

## 3 Discrete circle recognition in $LP_2$

## 4 Efficient discrete algorithm

- Optimizations
- Computational cost analysis
- On-line recognition and Discrete arc segmentation

## 5 Conclusion



## Circular separability as a LP in dimension 3

[OKM86]

### Paraboloid projection

$$(x, y) \rightarrow (x, y, x^2 + y^2)$$

i.e. projection onto the paraboloid  $z = x^2 + y^2$

In this transformed space, a plane  $ax + by + (x^2 + y^2) = c$  can be rewritten as:

$$(x + \frac{1}{2}a)^2 + (y - \frac{1}{2}b)^2 = c + \frac{1}{4}(a^2 + b^2)$$

Hence, assuming  $c + \frac{1}{4}(a^2 + b^2) > 0$ , a plane in the transformed space is a circle in  $\mathbb{R}^2$ .

Conversely, a circle  $(x - A)^2 + (y - B)^2 = R^2$  is transformed into:

$$-2Ax - 2By + (x^2 + y^2) = R^2 - (A^2 + B^2)$$

## Circular separability as a LP in dimension 3

[OKM86]

### Paraboloid projection

$$(x, y) \rightarrow (x, y, x^2 + y^2)$$

i.e. projection onto the paraboloid  $z = x^2 + y^2$

In this transformed space, a plane  $ax + by + (x^2 + y^2) = c$  can be rewritten as:

$$(x + \frac{1}{2}a)^2 + (y - \frac{1}{2}b)^2 = c + \frac{1}{4}(a^2 + b^2)$$

Hence, assuming  $c + \frac{1}{4}(a^2 + b^2) > 0$ , a plane in the transformed space is a circle in  $\mathbb{R}^2$ .

Conversely, a circle  $(x - A)^2 + (y - B)^2 = R^2$  is transformed into:

$$-2Ax - 2By + (x^2 + y^2) = R^2 - (A^2 + B^2)$$

## Circular separability as a LP in dimension 3

[OKM86]

### Paraboloid projection

$$(x, y) \rightarrow (x, y, x^2 + y^2)$$

i.e. projection onto the paraboloid  $z = x^2 + y^2$

In this transformed space, a plane  $ax + by + (x^2 + y^2) = c$  can be rewritten as:

$$(x + \frac{1}{2}a)^2 + (y - \frac{1}{2}b)^2 = c + \frac{1}{4}(a^2 + b^2)$$

Hence, assuming  $c + \frac{1}{4}(a^2 + b^2) > 0$ , a plane in the transformed space is a circle in  $\mathbb{R}^2$ .

Conversely, a circle  $(x - A)^2 + (y - B)^2 = R^2$  is transformed into:

$$-2Ax - 2By + (x^2 + y^2) = R^2 - (A^2 + B^2)$$

## Circular separability as a LP in dimension 3

### LP system

$S$  can be separated from  $T$  by a circle if the feasible region of the system:

$$\begin{cases} ax + by + (x^2 + y^2) \leq c & \text{if } (x, y) \in S \\ ax + by + (x^2 + y^2) \geq c + d & \text{if } (x, y) \in T \end{cases}$$

is not empty.

### Rem.

The parameter  $d$  can be defined by  $a$ ,  $b$  and  $c$ , hence we obtain a linear system in dimension 3

# Simple Discrete Circle recognition in $LP_3$

## Definitions

### Discrete circle recognition in $LP_3$

### Discrete circle recognition in $LP_2$

### Efficient discrete algorithm

### Optimizations

### Computational cost analysis On-line recognition and Discrete arc segmentation

### Conclusion

## Algorithm

- For each pixel  $s \in S$  and  $t \in T$ 
  - Construction of the two linear constraints  $s \rightarrow ax + by + (x^2 + y^2) \leq c$  and  $t \rightarrow ax + by + (x^2 + y^2) \geq c + d$
- Solve the global linear inequality system
- If the feasible region is empty,  $S$  is not a discrete disk
- Otherwise, return the preimage

## Computational cost

- $|S| + |T|$  linear constraints
- To detect if the feasible is empty or not :  $O(|S| + |T|)$  [Meg83, Meg84]
- To construct the preimage :  $O((|S| + |T|) \cdot \log(|S| + |T|))$  [PS85] (not on-line)

# Simple Discrete Circle recognition in $LP_3$

## Definitions

### Discrete circle recognition in $LP_3$

### Discrete circle recognition in $LP_2$

### Efficient discrete algorithm

### Optimizations Computational cost analysis On-line recognition and Discrete arc segmentation

## Conclusion

## Algorithm

- For each pixel  $s \in S$  and  $t \in T$ 
  - Construction of the two linear constraints  $s \rightarrow ax + by + (x^2 + y^2) \leq c$  and  $t \rightarrow ax + by + (x^2 + y^2) \geq c + d$
- Solve the global linear inequality system
- If the feasible region is empty,  $S$  is not a discrete disk
- Otherwise, return the preimage

## Computational cost

- $|S| + |T|$  linear constraints
- To detect if the feasible is empty or not :  $O(|S| + |T|)$  [Meg83, Meg84]
- To construct the preimage :  $O((|S| + |T|) \cdot \log(|S| + |T|))$  [PS85] (not on-line)

# Table of contents

## 1 Definitions

## 2 Discrete circle recognition in $LP_3$

## 3 Discrete circle recognition in $LP_2$

## 4 Efficient discrete algorithm

- Optimizations
- Computational cost analysis
- On-line recognition and Discrete arc segmentation

## 5 Conclusion

## Solutions in $LP_2$

### Lemma

If a circle  $C(\omega, R)$  encloses  $S$  but excludes  $T$ , its center  $\omega$  necessarily satisfies the following inequality:

$$\forall s \in S, \forall t \in T, \text{dist}(\omega, s) < \text{dist}(\omega, t)$$

### Definition

Let  $s \in S$  and  $t \in T$ ,  $H(s, t)$  denotes the half-plane bounded by the perpendicular bisector of  $s$  and  $t$ , and containing  $s$


$C(\omega, R)$  is valid for  $(s, t) \Leftrightarrow \omega \in H(s, t)$  and  $\text{dist}(\omega, s) \leq R < \text{dist}(\omega, t)$



## Arc Center Domain

acd

$$acd(S, T) = \bigcap_{s \in S, t \in T} H(s, t)$$




- $|S| \cdot |T|$  linear constraints
- $acd$  is a 2-D convex region (maybe unbounded)
- it corresponds to the *Generalized Voronoi cell* in Computational Geometry

## Arc Center Domain

acd

$$acd(S, T) = \bigcap_{s \in S, t \in T} H(s, t)$$




- $|S| \cdot |T|$  linear constraints
- $acd$  is a 2-D convex region (maybe unbounded)
- it corresponds to the *Generalized Voronoi cell* in Computational Geometry

## Arc Center Domain

acd

$$acd(S, T) = \bigcap_{s \in S, t \in T} H(s, t)$$




- $|S| \cdot |T|$  linear constraints
- $acd$  is a 2-D convex region (maybe unbounded)
- it corresponds to the *Generalized Voronoi cell* in Computational Geometry

## Arc Center Domain

acd

$$acd(S, T) = \bigcap_{s \in S, t \in T} H(s, t)$$



- $|S| \cdot |T|$  linear constraints
- $acd$  is a 2-D convex region (maybe unbounded)
- it corresponds to the *Generalized Voronoi cell* in Computational Geometry

## Computational cost

### Intersection of $|S| \cdot |T|$ linear constraints in 2-D

- Detect if the *acd* is empty or not :  $O(|S| \cdot |T|)$  [Meg83, Meg84]
- Construct the *acd* :  $O((|S| \cdot |T|) \cdot \log(|S| \cdot |T|))$  [PS85] (on-line algorithms)

# Summary

## $LP_2$

- $O(|S| \cdot |T|)$  or  
 $O((|S| \cdot |T|) \cdot \log(|S| \cdot |T|))$
- Elementary 2-D on-line algorithms

## $LP_3$

- $O(|S| + |T|)$  or  
 $O((|S| + |T|) \cdot \log(|S| + |T|))$
- LP solvers exist but optimal algorithms are quite complex

Discrete case:  $S$  = set of pixels and  $T$  = background pixels

$\Rightarrow$  Inefficient algorithms

# Summary

## $LP_2$

- $O(|S| \cdot |T|)$  or  
 $O((|S| \cdot |T|) \cdot \log(|S| \cdot |T|))$
- Elementary 2-D on-line algorithms

## $LP_3$

- $O(|S| + |T|)$  or  
 $O((|S| + |T|) \cdot \log(|S| + |T|))$
- LP solvers exist but optimal algorithms are quite complex

Discrete case:  $S$  = set of pixels and  $T$  = background pixels

⇒ Inefficient algorithms

# Table of contents

- 1 Definitions
- 2 Discrete circle recognition in  $LP_3$
- 3 Discrete circle recognition in  $LP_2$
- 4 **Efficient discrete algorithm**
  - Optimizations
  - Computational cost analysis
  - On-line recognition and Discrete arc segmentation
- 5 Conclusion



# Table of contents

## 1 Definitions

## 2 Discrete circle recognition in $LP_3$

## 3 Discrete circle recognition in $LP_2$

## 4 Efficient discrete algorithm

### • Optimizations

### • Computational cost analysis


### • On-line recognition and Discrete arc segmentation

## 5 Conclusion

## Filtering of $S$

Prop 1: [CGRT04]

$S$  can be reduced to its convex hull




Computational cost

Discrete Convex hull of the border  $\mathcal{B}$  of the object :  $O(|\mathcal{B}|)$

## Filtering of $T$

### Prop 2: Triangular inclusion


If a point  $t' \in T$  belongs to the triangle  $(s, s', t)$  with  $s, s' \in S$  and  $t \in T$ , then the point  $t$  can be removed from  $T$  without changing the  $acd$



# Filtering of $T$ in the discrete case

## Prop 3

We can independently process the edges of  $\text{Conv}(\mathcal{B})$



## Filtering of $T$ and Bezout's points


[CGRT04]

### Definition: Bezout's point

A point  $\mathcal{P}$  is a Bezout point of a straight segment  $[mn]$  defined by an arithmetical directional vector  $\vec{u}$  if and only if:

$$\overrightarrow{m\mathcal{P}} = \vec{v} + k\vec{u} \quad \text{with } k \in \mathbb{Z} \quad \text{and} \quad \text{det}(\vec{u}, \vec{v}) = \pm 1$$

and  $\mathcal{P}$  is the closest point to the middle of  $[mn]$ .



### Uni-modular parallelogram

Let  $O, P, Q, R \in \mathbb{Z}^2$  be a parallelogram. There is no discrete point inside  $(OPQR) \Leftrightarrow \text{det}(\vec{OP}, \vec{OQ}) = \pm 1$

## Filtering of $T$ and Bezout's points



[CGRT04]

### Definition: Bezout's point

A point  $\mathcal{P}$  is a Bezout point of a straight segment  $[mn]$  defined by an arithmetical directional vector  $\vec{u}$  if and only if:

$$\overrightarrow{m\mathcal{P}} = \vec{v} + k\vec{u} \quad \text{with } k \in \mathbb{Z} \quad \text{and} \quad \text{det}(\vec{u}, \vec{v}) = \pm 1$$




and  $\mathcal{P}$  is the closest point to the middle of  $[mn]$ .



### Theorem

Let us consider the oriented edge  $e = [mn]$  with  $m, n \in \mathbb{Z}$  and  $T_e$  the set of grid points in  $\vec{O}$  belonging to the half-space defined by  $e$ . Then, all triangles  $(m, n, t)$  contain another point  $t' \in T$  except for Bezout points

## Conclusion on the optimizations




- $S = \text{Conv}(\mathcal{B})$
- $T = \text{one Bezout's point per edge of the } \text{Conv}(\mathcal{B})$

Objective

Bound on the number of edges of the discrete convex hull

## Conclusion on the optimizations



- $S = \text{Conv}(\mathcal{B})$
- $T = \text{one Bezout's point per edge of the } \text{Conv}(\mathcal{B})$

### Objective

Bound on the number of edges of the discrete convex hull



# Table of contents

## 1 Definitions

## 2 Discrete circle recognition in $LP_3$

## 3 Discrete circle recognition in $LP_2$

## 4 Efficient discrete algorithm

- Optimizations
- Computational cost analysis
- On-line recognition and Discrete arc segmentation

## 5 Conclusion

## Discrete convex hull in a $m \times m$ -grid

[BB91, AŽ95]

Let  $e(m)$  be the number of edges of a convex polygon whose vertices belong to a  $m \times m$  grid:

$$e(m) = \frac{12}{(4\pi^2)^{1/3}} m^{2/3} + O(m^{1/3} \log(m))$$

Given a convex object  $\mathcal{O}$  in a  $m \times m$ -grid

- $|S| = O(m^{2/3})$
- $|T| = O(m^{2/3})$

## Discrete convex hull in a $m \times m$ -grid

[BB91, AŽ95]

Let  $e(m)$  be the number of edges of a convex polygon whose vertices belong to a  $m \times m$  grid:

$$e(m) = \frac{12}{(4\pi^2)^{1/3}} m^{2/3} + O(m^{1/3} \log(m))$$

Given a convex object  $\mathcal{O}$  in a  $m \times m$ -grid

- $|S| = O(m^{2/3})$
- $|T| = O(m^{2/3})$

## Overall algorithm

### Alg

- 1 Compute the convex hull of  $\mathcal{O}$   $O(m)$
- 2 For each edge of  $\text{Conv}(\mathcal{B})$   $O(m^{2/3})$  edges
  - Compute Bezout's point and append it to  $T$   $O(\log(m))$
- 3 Solve the Separability problem using either  $LP_2$  or  $LP_3$

### $LP_2$

- $O(|S| \cdot |T|)$  or  
 $O((|S| \cdot |T|) \cdot \log(|S| \cdot |T|))$
- $O(m^{4/3})$  or  $O(m^{4/3} \log(m))$

### $LP_3$

- $O(|S| + |T|)$  or  
 $O((|S| + |T|) \cdot \log(|S| + |T|))$
- $O(m^{2/3})$  or  $O(m^{2/3} \log(m))$

# Table of contents

- 1 Definitions
- 2 Discrete circle recognition in  $LP_3$
- 3 Discrete circle recognition in  $LP_2$
- 4 **Efficient discrete algorithm**
  - Optimizations
  - Computational cost analysis
  - On-line recognition and Discrete arc segmentation
- 5 Conclusion

# On-line recognition and Discrete arc segmentation

## Specific problems

- The LP solver must be on-line to update the *acd*
- If the input is an 8-arc, we need to estimate the local orientation (kind of *local convex hull*)



⇒ *greedy process*

A possible solution:

- 1 Use an on-line DSS segmentation to extract *Strictly convex or concave part* (SCoC) from the 8-arc
- 2 On-line construction of the convex hull and Bezout's points
- 3 On-line solver in  $LP_2$  [PS85] ( $O(m^{4/3} \log(m))$ )

# Some results

## SCoC and the *local convex hull* in $S$



[CGRT04]

## Definitions

Discrete  
circle  
recognition in  
 $LP_3$


Discrete  
circle  
recognition in  
 $LP_2$

Efficient  
discrete  
algorithm

Optimizations  
Computational  
cost  
analysis


On-line  
recognition  
and  
Discrete arc  
segmentation

## Conclusion





# Final result of the segmentation




# Table of contents

- 1 Definitions
- 2 Discrete circle recognition in  $LP_3$
- 3 Discrete circle recognition in  $LP_2$
- 4 Efficient discrete algorithm
  - Optimizations
  - Computational cost analysis
  - On-line recognition and Discrete arc segmentation
- 5 Conclusion


## Conclusion

### Importance of the arithmetic in geometrical problems

Without Bezout's points [Kov90]:



With Bezout's points:



Recognition in  $LP_2$ :

#### Brute-force algorithm

- $O(n^2 \log n)$
- update  $O(\log n)$
- memory  $O(n^2)$

#### With the arithmetical properties

- $O(n^{4/3} \log n)$
- update  $O(\log n)$
- memory  $O(n^{4/3})$

## Other references...

[NA84, Fis86, Sau93, WS95, Dam95, TC89, Kim84, KA84]



D.M. Acketa and J.D. Žunić.

On the maximal number of edges of convex digital polygons included into a  $m \times m$ -grid.  
*Journal of Combinatorial Theory, Serie A*(69):358–368, 1995.



A. Balog and I. Bárány.

On the convex hull of the integer points in a disc.

In ACM-SIGACT ACM-SIGGRAPH, editor, *Proceedings of the 7th Annual Symposium on Computational Geometry (SCG '91)*, pages 162–165, North Conway, NH, USA, June 1991. ACM Press.



D. Coeurjolly, Y. Gerard, J.-P. Reveillès, and L. Tougne.

An elementary algorithm for digital arc segmentation.

*Discrete Applied Mathematics*, 139(1-3):31–50, 2004.



P. Damaschke.

The linear time recognition of digital arcs.

*Pattern Recognition Letters*, 16(5):543–548, May 1995.



S. Fisk.

Separating points sets by circles, and the recognition of digital disks.

*IEEE Transaction on Pattern Analysis and Machine Intelligence*, 8(4):554–556, 1986.



C. E. Kim and T. A. Anderson.

Digital disks and a digital compactness measure.

In *Seventh International Conference on Pattern Recognition (Montreal, Canada, July 30-August 2, 1984)*, IEEE Publ. 84CH2046-1, pages 254–257. IEEE, 1984.



C. E. Kim.

Digital disks.

*IEEE Transactions on Pattern Analysis and Machine Intelligence*, 6:372–374, 1984.



V. A. Kovalevsky.

New definition and fast recognition of digital straight segments and arcs.

*Proceedings of the tenth international conference on Pattern Analysis and Machine Intelligence*, pages 31–34, June 1990.



N. Megiddo.

Linear-time algorithms for linear programming in  $\mathbb{R}^3$  and related problems.

*SIAM Journal of Computing*, 12(4):759–776, November 1983.



N. Megiddo.

Linear programming in linear time when the dimension is fixed.  
*Journal of the ACM*, 31(1):114–127, January 1984.



A. Nakamura and K. Aizawa.

Digital circles.

*Computer Vision, Graphics, and Image Processing*, 26(2):242–255, May 1984.



Joseph O'Rourke, S. R. Kosaraju, and N. Megiddo.

Computing circular separability.

*Discrete and Computational Geometry*, 1(1):105–113, 1986.



F. P. Preparata and M. I. Shamos.

*Computational Geometry : An Introduction*.

Springer-Verlag, 1985.



P. Sauer.

On the recognition of digital circles in linear time.

*Computational Geometry: Theory and Application 2*, pages 287–302, 1993.



S. M. Thomas and Y. T. Chan.

A simple approach for the estimation of circular arc center and its radius.

*Computer Vision, Graphics and Image Processing*, 45:362–370, 1989.



M. Worring and W.M. Smeulders.

Digitized circular arcs: characterization and parameter estimation.

*IEEE Transactions on Pattern Analysis and Machine Intelligence*, 17(6):587–598, jun 1995.