

Tutorial on Digital Topology, Geometry and Application

2nd talk: Minimal path-costs *Computation and applications*

Robin Strand

Centre for Image Analysis
Division of Visual Information and Interaction
Division of Radiology
Uppsala University



Outline

- What is a path cost?
- Methods
 - Geodesic distance
 - Fuzzy connectedness
 - Fuzzy distance
 - Minimum barrier distance
- Algorithms for efficient computation
- Application - segmentation




Digital images, paths



210	212	204	198
210	208	208	197
207	180	175	176
162	167	157	154


4-connected paths



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014




Topographic representation




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Path cost



Intensity profile




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014




Path cost

Intensity profile




Cost function: curve length



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014




Path cost



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014





Path cost



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014





Path cost



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014




Path cost



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Optimal/minimal cost paths



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Methods

- Curve length - Geodesic distance
- Max/min value - Fuzzy connectedness
- Curve integral - Fuzzy distance
- Minimum barrier distance


ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Methods

$n_{1,1}$	$n_{2,1}$	$n_{3,1}$
$n_{1,2}$	$n_{2,2}$	$n_{3,2}$
$n_{1,3}$	$n_{2,3}$	$n_{3,3}$

Image, intensity values




Graph representation


ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Methods



Node weighted graph




Edge weighted graph

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Curve length - Geodesic distance


- Geodesic distance – Curve length on topographic image representation



- Cost: Sum of edge weights
- Simple $f(m, n) = |m - n| + 1$
(or $f(m, n) = \sqrt{(m - n)^2 + 1}$)

- Example path cost:

$$f(n_{1,1}, n_{2,1}) + f(n_{2,1}, n_{2,2}) + f(n_{2,2}, n_{2,3}) = 3 + |n_{1,1} - n_{2,1}| + |n_{2,1} - n_{2,2}| + |n_{2,2} - n_{2,3}|$$



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Geodesic distance

Extensions of the simple cost function:

- Distance Transform on Curved Spaces (DTOCS)
 - Approximation of local cost
- Weighted DTOCS (WDTOCS)
 - Approximation of local distances

P.J. Toivanen "New geodesic distance transforms for gray-scale images". Pattern Recognition Letters 17(5) (1996) 437–450

L. Ikonen "Distance transforms on gray-level surfaces." Acta Universitatis Lappeenrantaensis (2006).

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Fuzzy Connectedness

Fuzzy set, fuzzy membership functions:

A fuzzy set S in a fuzzy space X (here $X \subset \mathbb{Z}^2$) is a set of ordered pairs $S = \{(x, \mu_S(x)) | x \in X\}$, where the membership function $\mu_S: X \rightarrow [0, 1]$ represents the grade of membership of x in S .


ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Max/min value - Fuzzy Connectedness

- f defined by fuzzy affinity
- Cost: minimum of edge weights
- Simple $f(m, n) = 1 - |m - n|$
- Example path cost:

$$\min(f(n_{1,1}, n_{2,1}), f(n_{2,1}, n_{2,2}), f(n_{2,2}, n_{2,3})) = 1 - \max(|n_{1,1} - n_{2,1}|, |n_{2,1} - n_{2,2}|, |n_{2,2} - n_{2,3}|)$$
- Gives fuzzy membership values



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Fuzzy Connectedness

Extension of the simple cost: support for prior information:

- Homogeneity-based component: The degree of local hanging-togetherness due to the similarity in intensity
- Object-feature based component: The degree of local hanging-togetherness with respect to some given feature

A. Rosenfeld, "The fuzzy geometry of image subsets", Pattern Recognition Letters, 2(5), 1984

J. K. Udupa and S. Samarasekera, "Fuzzy connectedness and object definition: theory, algorithms, and applications in image segmentation," *Graphical Models and Image Processing*, vol 58, 1996.

J. K. Udupa and P. K. Saha, "Fuzzy connectedness and image segmentation," *Proceedings of the IEEE*, vol. 9, 2003.



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Fuzzy Connectedness

Extensions/variants

- Local scale
- Vectorial fuzzy connectedness
- Relative fuzzy connectedness
- Iterative relative fuzzy connectedness
- ...



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Curve integral



- Cost: Sum of edge weights

- Simple $f(m, n) = \frac{|m+n|}{2}$

- Example path cost:

$$f(n_{1,1}, n_{2,1}) + f(n_{2,1}, n_{2,2}) + f(n_{2,2}, n_{2,3}) =$$

$$\frac{n_{1,1} + 2n_{2,1} + 2n_{2,2} + n_{2,3}}{2}$$



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Curve integral

- Stability to noise and blur
- Generalization of path costs (chessboard/city block distances) for binary images
- Fuzzy distance - Curve integral typically applied to, for example, (inverted) fuzzy membership values or edge magnitude images


G. Levi, U. Montanari, "A grey-weighted skeleton", Information and Control, Volume 17(1), 1970
 D. Rutovitz "Data structures for operations on digital images" Pictorial Pattern Recognition, Washington, Thompson 1968
 Saha, P., Wehrli, F.W., Gomberg, B.R.: "Fuzzy distance transform: Theory, algorithms, and applications" Computer Vision and Image Understanding 86(3) (2002)

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum Barrier Distance

- f vector valued function
- Cost: minimum interval
- $f(m, n) = (\min(m, n), \max(m, n))$



- Example path cost:

$$|\min(f_1(n_{1,1}, n_{2,1}), f_1(n_{2,1}, n_{2,2}), f_1(n_{2,2}, n_{2,3})) - \max(f_2(n_{1,1}, n_{2,1}), f_2(n_{2,1}, n_{2,2}), f_2(n_{2,2}, n_{2,3}))| = \max(n_{1,1}, n_{2,1}, n_{2,2}, n_{2,3}) - \min(n_{1,1}, n_{2,1}, n_{2,2}, n_{2,3})$$

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier distance

- Efficient algorithms
- Metricity
- Convergence properties
- Vectorial minimum barrier distance

R. Strand, K.C. Ciesielski, F. Malmberg, P.K. Saha. "The Minimum Barrier Distance" Computer Vision and Image Understanding 117 (4), 2013

K.C. Ciesielski, R. Strand, F. Malmberg, P.K. Saha. "Efficient algorithms for finding the exact minimum barrier distance" Computer Vision and Image Understanding vol 123, 2014

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier distance property

Let Π be the set of all paths between two points p and q in \mathbb{Z}^n and $I: \mathbb{Z}^n \rightarrow \mathbb{R}$ (the *image*).

The minimum barrier distance between the points is

$$\min_{\pi \in \Pi} \left(\max_t I(\pi(t)) - \min_t I(\pi(t)) \right)$$

Let Π' be the set of all paths between points p and q in \mathbb{R}^n and $I: \mathbb{R}^n \rightarrow \mathbb{R}$, then

$$\inf_{\pi \in \Pi'} \left(\max_t I(\pi(t)) - \min_t I(\pi(t)) \right) = \inf_{\pi \in \Pi'} \max_t I(\pi(t)) - \sup_{\pi \in \Pi'} \min_t I(\pi(t))$$

for bounded, continuous I !

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Properties

- Geodesic distance
 - Gradient based (noise, blur sensitive)
 - A parameter gives spatial and intensity distance trade-off
- Fuzzy distance
 - Favors high/low intensity values
 - ⇒ suited for gradient magnitude image (noise sensitive)
 - Developed for fuzzy membership values
- Fuzzy connectedness
 - Gradient based (noise, blur sensitive)
 - No spatial distance term
 - Support for apriori information
- Minimum barrier distance
 - Noise and blur stability
 - No spatial distance term
 - Interval weighted graph

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

- Efficient algorithms needed in order to
 - process large amount of information and
 - minimize execution time

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014




Algorithms

Repeated raster scan until convergence.

Drawback: Highly image content dependent

Slow convergence in some cases




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.

Scan 1, forward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.

Scan 1, forward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.

Scan 1, forward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.

Scan 1, forward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.

After scan 1, forward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.

After scan 1, backward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.
After scan 2, forward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Repeated raster scan until convergence.
After scan 2, backward pass




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Dijkstra's algorithm / wavefront propagation



Sufficient for *monotonic incremental* path cost functions

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Dijkstra's algorithm / wavefront propagation

A path cost function is *monotonic incremental* if

- $f(\pi \cdot \langle s, t \rangle) = f(\pi) \circ (s, t)$, where \circ satisfies
 - $x' \geq x \Rightarrow x' \circ (s, t) \geq x \circ (s, t)$
 - $x \circ (s, t) \geq x$

In other words:

- Adding the same element to two paths preserves the order of the cost of the paths.
- The path cost function is non-decreasing (adding an element to a path gives higher or equal cost).

A. Frieze, "Minimum Paths in Directed Graphs," Operational Research Quarterly 28(2), 1977.

A. X. Falcão, J. Stolfi, R. Lotufo, "The Image Foresting Transform: Theory, Algorithms, and Applications", TPAMI 26(1), 2004

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Algorithms

Dijkstra's algorithm / wavefront propagation

Monotonic incremental:

- Curve length
- Curve integral (if non-negative)
- Max/min

Not monotonic incremental:

- Minimum barrier distance


ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier

5	7	3
4	5	1
9	8	5

Image, intensity values




Graph representation

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier Dijkstra approximation

Interval weighted Dijkstra




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier Dijkstra approximation


Interval weighted Dijkstra



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier Dijkstra approximation




Result from interval
weighted Dijkstra

The cost of this path is 3!

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum barrier Dijkstra approximation




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Another approximation: min max - max min

i) minimize max




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Another approximation: min max - max min

ii) maximize min



Graph representation


Weighted graph

Result

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Another approximation: min max - max min



Min max


Max min

Difference

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Another approximation: min max - max min



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum path cost/Distance transform

Seed point




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum path cost transform

1) Geodesic distance, $f(m, n) = \sqrt{(m - n)^2 + 1}$




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum path cost transform

2) Curve integral/Fuzzy distance, $f(m, n) = \frac{|m+n|}{2}$




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum path cost transform

3) Gradient magnitude ('inverted fuzzy connectedness')

$$f(m, n) = |m - n|$$



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Minimum path cost transform

4) Minimum barrier, $f(m, n) = (\min(m, n), \max(m, n))$




ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Interactive (semi-automatic) image processing


Human

Complex patterns
Interpret based on experience



Computer



quantitative analysis
objective
fast



ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Segmentation





MR image

Interactive segmentation: The user adds background and object seed points. Labels are propagated together with cost values.

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Segmentation




MR image

Interactive segmentation: The user adds seed points and the segmentation is updated locally.

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Segmentation of volume images




MR, volume image


ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Segmentation of volume images



Seed points



Segmentation result

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014



Summary

Minimum path cost methods

- Geodesic distance
- Fuzzy connectedness.
- Fuzzy distance
- Minimum barrier distance

Efficient computation by wave-front propagation

Some applications in segmentation

ICPR 2014 Tutorial – Stockholm, Sweden 24 August 2014

