

**Tutorial on:
Digital Topology, Geometry and Applications**

**4th talk:
Skeleton computation and use for shape
analysis**

Gabriella Sanniti di Baja
Istituto di Cibernetica "E.Caianiello", CNR
Pozzuoli, Naples, Italy

g.sannitidibaja@cib.na.cnr.it

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Outline

- Notions
- Object representation: the skeleton
- Shape analysis via object decomposition

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Notions


- Paths and path-based distance
- Distance transform
- Balls and Centers of Maximal Balls

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Paths and path-based distance

A path of length n from a voxel p to a voxel q is a sequence of voxels $p = p_0, p_1, \dots, p_n = q$, such that p_i is a (face, edge, vertex) neighbor of p_{i-1} for $1 \leq i \leq n$

6-, 18- and 26-path



The distance between a voxel p and a voxel q is the length of a minimal 6-, 18-, or 26-path linking p to q .

The distance can be measured by weighting the unit moves along the path with weights that take into account the different Euclidean length of the different moves. A good selection is $w_f = 3$ $w_e = 4$ $w_v = 5$

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Distance transform

- The distance transform is a replica of the image where all object elements are labeled with their distance from the background.
- The distance can be computed by using any distance function (including the Euclidean distance).

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Balls, maximal balls and centers of maximal balls

- Each voxel v in the distance transform of an object can be interpreted as the center of a ball whose radius is given by the distance of v from the background.
- A ball is maximal if it is not included by any other single ball in the object. The centers of the maximal balls of the object, CMBs, have a key role. In fact, the object can be recovered by the union of its maximal balls.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Centers of maximal balls

Since distance values of voxels in DT correspond to the radii of the associated balls, to check whether the ball centered on p is maximal it is enough to compare the radius of that ball with the radii of the balls centered on the voxels that are neighbors of p .

If a weighted distance is used, the weights should be taken into account while performing the radii comparison.

A CMB is a voxel p for which the following condition holds for each of its neighbors n_i

$$n_i < p + w_i$$

where w_i is 3, 4 or 5 depending on whether n_i is face-, edge- or vertex-neighbor of p .

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Object representation: the skeleton

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

The skeleton

provides rich geometric information, giving simultaneously locational, orientational, and metric (size) description of an object;

provides a basis for description at multiple spatial scales;

provides descriptions of objects that are intuitive to non-mathematical users.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Desired features

- Stability and robustness;
- Dimensionality reduction;
- Resemblance to the object;
- Correspondence to the object;
- Centrality;
- Level of detail;
- Reversibility;
- Topological equivalence.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Skeletonization approaches

Medial Axis Transform (MAT);
Grassfire;
Voronoi Diagrams;
Topological Thinning.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

MAT

The medial axis transform, MAT, defined by Blum is the locus of the symmetry points, i.e., the object points placed midway between two sections of the object boundary. Each point of the MAT is center of a ball touching the object boundary in at least two different points and is associated with the radius of the ball.


ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

The grassfire paradigm

Suppose that all points on the boundary of a dry grass field are set on fire at the same instant of time. In the absence of wind, the fire propagates at constant speed in every direction toward the innermost part of the field. Fire dies out at the quenching points, i.e., the points reached at the same instant of time by fire fronts originated at different parts of the boundary of the field. Of course, the quenching points are symmetrically placed within the field and the instant of time at which they are reached depends on their distance from the boundary of the field. Thus, the grassfire transform has the same properties as the MAT.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014



Voronoi Diagram



In the continuous plane/space, given a finite set of points S , the Voronoi cell associated to a point p of S is defined as the subset of the plane/space with the points closer to p than to any other point q in S . For each point in the plane/space there exist at least one point of S to which it is closer. A point can have the same distance from more than one point of S and, if this is the case, the point belongs to a Voronoi edge separating two or more Voronoi cells. The union of Voronoi cells of all points in S is a partition of the plane/space called Voronoi Diagram of the set S .

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Voronoi Diagram & MAT



- Main problems:
- 1. Boundary sampling (if the density of the boundary points constituting S goes to infinity, the Voronoi diagram of S converges to the continuous medial locus)
- 2. Pruning (when the density increases, the number of Voronoi edges also increases).

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Topological Thinning: the peeling scheme



Reduction of dimensionality can be achieved by sequentially removing, border after border, all border pixels/voxels whose presence is not necessary to preserve topology of both the object and the background

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Topological Thinning

Repeat

remove “deletable” boundary points
from the current object

Until no points are removed

} One
Iteration
step

Which points can be regarded as “deletable”?

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014


Simple point

Topology preserving local removal operations
(based on the notion of “simple point”) can be
used, since it has been proved that:

if removal of a voxel p does not alter topology in
the $3 \times 3 \times 3$ neighborhood of p, then sequential
removal does not alter topology globally.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Shape preservation



End points

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014


MAT & Distance Transform

A discrete approximation of the MAT is given by the *centers of maximal balls* (CMB) in the *distance transform* (DT) of the object.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

MAT & Distance Transform

Drawback 1: the discrete MAT and the represented object may have different topology.



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

drawback 1

Other object elements are necessary, besides the CMB, to obtain a topologically correct skeleton.

The skeleton can be computed by applying topology preserving removal operations to object elements that are not CMB.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014


Simple Voxels

- A voxel v is **simple** if its removal does not change the topology
- Consider only voxels v having at least a face-neighbor in the background
- Count 26-connected object components in the 26-neighbourhood of v , N^{26}
- Count 6-connected background components that are face-adjacent to v in its 18-neighbourhood, N_f^{18}
- A simple voxel has $N^{26} = 1$ and $N_f^{18} = 1$

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

MAT & Distance Transform

Drawback 2: the structure of the discrete MAT depends on the metric used to compute the DT, which may originate a MAT that is not invariant under object rotation.



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

drawback 2


The skeleton may change under object rotation.

A distance function providing a good approximation of the Euclidean distance has to be used to originate a skeleton stable under object rotation.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

MAT & Distance Transform

Drawback 3: whichever distance is used the CMB are generally very many, especially for natural shapes.



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

drawback 3

The structure of the skeleton would be too complex to effectively use it for shape analysis.

Only a suitable subset of CMB has to be taken into account, so as to obtain a skeleton with a structure easy to manage and still adequately representing the object.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Skeletonization algorithm: phase 1

From the object P to a subset PS, consisting of surfaces and curves

- <3,4,5>DT of P
- Anchor point selection (subset of CMB)
- Voxel removal

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Skeletonization algorithm: phase 2

From PS to the skeleton S, consisting exclusively of curves


- Classification of the voxels of PS
- $<3,4,5>$ DT of PS
- Anchor point selection
- Voxel removal

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

phase 1 – DT computation

We use the $<3,4,5>$ weighted path-based distance, where the unit moves from a voxel to any face-neighbor, edge-neighbor, and vertex-neighbor are weighted 3, 4 and 5 respectively.

This choice allows us to combine the simplicity of path-based distances with a good approximation to the Euclidean distance.



The standard 2-raster scan DT algorithm is used.


ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

phase 1 – CMB computation

A CMB is a voxel p for which the following condition holds for each of its neighbors n_i ,

$$n_i < p + w_i$$

where w_i is 3, 4 or 5 depending on whether n_i is face-, edge- or vertex-neighbor of p .



		3
3	3	4
3	6	7
3	4	7
3	(6)	8
3	6	9
		12

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

phase 1 –Anchor point selection



Due to the CMB rule ($n_i < p + w_i$), a CMB p may have neighbors with distance values larger than p .

If the neighbors of p are *small*, p is a stronger CMB.

Thus, we select as anchor points only the CMB satisfying, for each n_i , the stricter condition:

$$n_i - p < w_i - 1$$

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

phase 1 – Voxel removal



Voxels in DT are accessed in increasing distance order and are sequentially removed provided that they are simple points and are not anchor points.


The obtained PS is likely to be 2-voxel thick at parts. Standard final thinning is used to make PS unit wide.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

phase 2 – Voxel classification

By using local checks, the voxels of PS are classified as *curve* voxels (light blue), *junction* voxels (dark green), *internal* voxels (brown) and *edge* voxels (light green).

Voxel classification allows us to compute the DT of the set of internal voxels with respect to the set of the edge voxels.



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

phase 2 –getting the skeleton

CMB and voxels classified as curve or junction voxels are taken as anchor points.




Voxels are accessed in increasing distance order and are sequentially removed if are simple points and are not anchor points.

The obtained set is likely to be 2-voxel thick. Standard final thinning is accomplished to obtain the unit wide skeleton S.

Pruning completes skeletonization.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Pruning



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Some examples


ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Infra-renal aortic aneurysms

Trachealstenosis

Colonoscopy


ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014



Why decompose?

object recognition as a hierarchical process

- decompose into parts
- analyze the parts
- describe the object by a graph
 - nodes: parts
 - edges: adjacency between parts



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Two main approaches

- pre-defined shape primitives
- irregularities in the boundary

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Recognition-by-components

- theory of human understanding
- decomposition into shape primitives
 - generalized-cone components (geons)
 - small number



I. Biederman, *Recognition-by-Components: A Theory of Human Image Understanding*, Psychological Review, 94(2):115-147, 1987

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014


Skeleton decomposition method

- Skeleton partition
- 4D polygonal approximation
- Reconstruction of the object's parts
- Region merging

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014




Partial reconstruction



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Complete reconstruction



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Curvature changes along the boundary


ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Thickness changes

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

4D polygonal approximation

Split type Ramer algorithm



$$d^2 = ||AC||^2 - P_{ABC} * P_{ABC} / ||AB||^2$$


$||AB||$ is the norm of the vector AB

P_{ABC} is the scalar product between vectors AB and AC.

U.Ramer, 1972. An Iterative procedure for the polygonal approximation of plane curves,
CGIP, 1, 244-256.


ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Basic regions



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014


Approximating the simple curves



The image shows four separate green dashed curves. Each curve is composed of small segments, representing a piecewise linear approximation of a more complex, irregular shape. The curves are arranged in a cluster, with one prominent one at the top left and others below it.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Decomposition into kernels and simple regions, possibly split into basic regions




The image displays a complex object, likely a silhouette or a boundary, divided into several distinct regions. These regions are filled with different colors: purple, green, yellow, blue, and red. The boundaries between these colored regions represent the decomposition into kernels and basic regions, as described in the title. The overall shape is irregular and organic in form.

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Merging


Consider for merging only simple-regions in between kernels

Use the "visibility criterion" to merge scarcely elongated simple-regions, i.e., regions whose "visible" boundary part is smaller than the non-visible boundary part



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Merging





ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014



Some results

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014


More results

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014





Results with polygonal approximation



ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Questions?

Thank you!

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014

Some references

- Arcelli C., Sanniti di Baja G. and Serino L., "A parallel algorithm to skeletonize the distance transform of 3D objects", *Image and Vision Computing* **27**, 666-672 (2009).
- Arcelli C., Sanniti di Baja G. and Serino L., "The <3,4,5> curvilinear skeleton", *DGCI 2009: Lecture Notes in Computer Science*, Springer Publ. **Vol. 5810**, Briek S., Reutenauer C., Provencal X. Eds., p.409-420 (2009).
- Serino L., Sanniti di Baja G. and Arcelli C., "Object decomposition via curvilinear skeleton partition", 20th International Conference on Pattern Recognition ICPR 2010- August 23-26, 2010, Istanbul (Turkey), Proceedings, 4081-4084, IEEE CS Press
- Arcelli C., Sanniti di Baja G. and Serino L., "Distance driven skeletonization in voxel images", *IEEE Transactions on Pattern Analysis and Machine Intelligence* **33 (4)**, 709-720 (2011).
- Serino L., Arcelli C., and Sanniti di Baja G., "On the computation of the <3,4,5> curve skeleton of 3D objects", *Pattern Recognition Letters* **32 (9)**, 1406-1414 (2011).
- Serino L., Sanniti di Baja G., and Arcelli C., "Using the skeleton for 3D object decomposition", *SCIA 2011: Lecture Notes in Computer Science*, Springer Publ. **Vol.6688**, Heyden A. and Kahl F. Eds., p. 447-456 (2011)
- Sanniti di Baja G., Serino L., Arcelli C., "From linear representations to object parts", *MCP2012: Lecture Notes in Computer Science*, Springer Publ. **Vol. 7329**, Carrasco-Ochoa J.A. et al. Eds., p. 1-12 (2012)
- Serino L., Arcelli C., and Sanniti di Baja G., "From the zones of influence of skeleton branch points to meaningful object parts", *DGC2013: Lecture Notes in Computer Science*, Springer Publ. **Vol. 7749**, R. Gonzalez-Diaz et al. Eds., p. 131-142 (2013).
- Sanniti di Baja G., Serino L., and Arcelli C., "3D curve skeleton computation and use for discrete shape analysis", *Innovations for Shape Analysis: Models and Algorithms*, Springer, Breuss M., Bruckstein A., Maragos P. Eds., p. 117-136, (2013)
- Serino L., Arcelli C. and Sanniti di Baja G., "4D polygonal approximation of the skeleton for 3D object decomposition", *ICPRAM 2013: SCITEPRESS Science and Technology Publications* (ISBN: 978-989-8565-41-9), De Marsico M., Fred A. Eds, p. 467-472 (2013)
- Serino L., Arcelli C. and Sanniti di Baja G., "Approximating the skeleton for fine-to-coarse shape representation", *ICIAP 2013, Part I, Lecture Notes in Computer Science*, Springer Publ. **Vol. 8156**, A. Petrosino, Ed. p. 111-120 (2013)
- Serino L., Arcelli C. and Sanniti di Baja G., "Decomposing and sketching 3D objects by curve skeleton processing", *CIARP 2013, Part I, Vol. 8258*, J. Ruiz-Shulcloper and G. Sanniti di Baja Eds, p. 25-32, (2013).
- Serino L. and Sanniti di Baja G., "Pruning the 3D curve skeleton", *22th International Conference on Pattern Recognition ICPR 2014- August 24-29, 2014, Stockholm (Sweden), Proceedings*, 1051-4651/14 \$31.00, ©2014IEEE, 2269-2274, (2'14).

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014



Gabriella Sanniti di Baja
Institute of Cybernetics "E.Caianiello" (ICIB),
Italian National Research Council,
Pozzuoli, Naples, Italy
<gsdb@cib.na.cnr.it>



Education:

- "laurea cum laude" in Physics, University of Naples, Italy, 1973
- PhD Honoris Causa, Uppsala University, Sweden, 2002.

Professional experience:

- Director of Research at ICIB-CNR 1990 -
- Co-Editor-in-Chief of Pattern Recognition Letters 2000 -
- International Association for Pattern Recognition (IAPR) Executive Committee member 1994-2002
- IAPR Governing Board member 2008 - 2012
- GIRPR (Group of Italian Researchers in Pattern Recognition) President 2008 – 2012
- Organization of international conferences

Professional achievements: IAPR Fellow; Foreign Member of the Royal Society of Sciences at Uppsala, Sweden.

Main research interests:

Pattern Recognition, Computer Vision, Digital Geometry and Topology, Distance Transformation and applications, Representation Systems, Shape Decomposition and Description in 2D and 3D images, Multiresolution, Segmentation.

Publications: ≈ 200 papers

ICPR 2014 Tutorials – Stockholm, Sweden, 24 August 2014