



Product Data Sheet

AWS32

DESCRIPTION

Premium anti-wear hydraulic oil made from highly refined base oils and zinc- based additives. It provides excellent protection against wear, oxidation, and corrosion. The formulation ensures reliable performance and long service life, even in demanding hydraulic systems.

APPLICATION

hydraulic oil is used in industrial and mobile hydraulic systems, including forklifts, excavators, injection molding machines, compressors, and factory machinery. It provides smooth operation, reduces wear, prevents corrosion, and ensures stable performance under high pressure

FEATURES AND ADVANTAGES

- Excellent wear protection for longer equipment life
- High oxidation stability keeps systems clean
- Good rust and corrosion resistance
- Stable viscosity and reliable performance under pressure

PRODUCT PERFORMANCE CLAIM

ISO VG 32 (viscosity grade), DIN 51524 Part II (HLP anti-wear hydraulic fluids) and AW / AWS (Anti-Wear Hydraulic Oil Standards)

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	AWS32
Colour	VISUAL	-	Visual
Density @ 15°C	ASTM D4052	kg/m3	861.8
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	32.12
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	5.9071
Viscosity Index	ASTM D2270	-	112.4
Pour Point, °C	ASTM D97	°C	-33
Flash Point, °C	IP 523	°C	210

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the