



Product Data Sheet

AWS68

DESCRIPTION

AWS68 is a premium anti-wear hydraulic oil made from highly refined Group II base oils and zinc-based additives. It provides excellent protection against wear, oxidation, and corrosion. The clean “white oil” formulation ensures reliable performance and long service life, even in demanding hydraulic systems.

APPLICATION

Recommended for use in automotive gearboxes, final drives, and differentials where API GL-4 or GL-5 performance is required. Suitable for use in trucks, buses, tractors, and off-road equipment operating under severe or high-temperature conditions.

FEATURES AND ADVANTAGES

- Excellent wear protection for longer equipment life
- High oxidation stability keeps systems clean
- Good rust and corrosion resistance
- Fast water separation and easy filtration
- Stable viscosity and reliable performance under pressure

PRODUCT PERFORMANCE CLAIM

ISO VG 68 (viscosity grade), DIN 51524 Part II (HLP anti-wear hydraulic fluids) and AW / AWS (Anti-Wear Hydraulic Oil Standards)

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	AWS68
Colour	VISUAL	-	Visual
Density @ 15°C	ASTM D4052	kg/m ³	863.6
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	64.694
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	9.1529
Viscosity Index	ASTM D2270	-	126.46
Pour Point, °C	ASTM D97	°C	-18
Flash Point, °C	IP 523	°C	220

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the