



Product Data Sheet

CUTTING FLUID COOLANT

DESCRIPTION

Cutting Fluid provides superior cooling and lubrication during metal cutting and machining operations. It reduces friction, prevents tool wear, and ensures smooth surface finishes. Formulated for excellent rust protection and long fluid life, it enhances productivity and precision in various industrial and workshop applications.

APPLICATION

Cutting Fluid is suitable for use in drilling, milling, turning, grinding, and tapping operations on ferrous and non-ferrous metals. Ideal for CNC machines, lathes, and general machining tools to ensure smoother cuts, extended tool life, and improved surface quality.

FEATURES AND ADVANTAGES

- Excellent cooling and lubrication performance
- Reduces friction and tool wear
- Improves surface finish and machining accuracy
- Provides strong rust and corrosion protection
- Extends tool and fluid life for higher productivity

PARAMETER	METHOD
Appearance Neat	Yellow Color Liquid
Appearanceafter dilution	WhiteTranslucent
Odour	Mild
Density(@15 degree C)	1.02
pHvalue (5.0% Emulsion)	9.6
Solubility	Water
Synthetic Oil/ Mineral Oil	15 to 30 %
Fatty Oil(Vegetable type)	1.0 to 5.0%
Anti corrosionadditives	2.0 to 5.0 %
Brix reading factor	1.11

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the