



Product Data Sheet

10W30 SL/CF Mineral

DESCRIPTION

10W30 SL/CF Mineral is a high-quality mineral engine oil formulated with refined base oils and a balanced additive system. It provides reliable lubrication, wear protection, and thermal stability for gasoline and light-duty diesel engines. The formulation helps minimize deposits, reduce friction, and support smooth engine operation under various driving conditions.

APPLICATION

10W30 SL/CF Mineral is suitable for gasoline and light-duty diesel engines in passenger cars, light trucks, small commercial vehicles, and general-purpose equipment. It is recommended for engines operating in moderate climates, mixed driving conditions, and daily commuting where consistent lubrication and dependable mineral-based protection are required.

FEATURES AND ADVANTAGES

- Strong protection against wear, sludge, and deposits
- Stable viscosity and good lubrication at operating temperatures
- Reduced friction for smoother and more efficient engine performance
- Suitable for gasoline (SL) and older diesel engines (CF)
- Reliable performance for urban, highway, and light commercial use

PRODUCT PERFORMANCE CLAIM

API SL/SJ/CF
ACEA: A3/B3 or A3/B4

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m3	867.3
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	88.01
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	10.229
Viscosity Index	ASTM D2270	None	119.01
Pour Point, °C	ASTM D97	°C	-11
Flash Point, °C	IP 523	°C	240

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the