

Product Data Sheet

10W40 SQ/CF Semi

DESCRIPTION

A high-quality semi-synthetic engine oil designed to provide excellent protection and performance for a wide range of gasoline and diesel engines. Formulated to ensure superior lubrication under high temperature and heavy load conditions, reducing wear and extending engine life.

APPLICATION

Suitable for modern passenger cars, light commercial vehicles, and motorcycles. Recommended for engines operating in city traffic or long-distance driving conditions, ensuring stable performance and fuel efficiency.

FEATURES AND ADVANTAGES

- Excellent high-temperature protection and oxidation stability
- Reduces engine wear and deposits
- Enhances fuel efficiency
- Compatible with a wide range of engine types
- Meets API SQ/CF performance standards

PRODUCT PERFORMANCE CLAIM

API SQ/CF-4

BMW Longlife-01, Chrysler MS-6395, Fiat 9.55535-G2,

Mercedes-Benz MB 229.1 / 229.3, PSA B71 2294, Renault RN 0700 / RN 0710

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m3	870.6
Kinematic Viscosity @ 40°C	ASTM D7042	mm²/s	148.36
Kinematic Viscosity @ 100°C	ASTM D7042	mm²/s	16.21
Viscosity Index	ASTM D2270	-	143.91
Pour Point, °C	ASTM D97	°C	-26
Flash Point, °C	IP 523	°C	220

*VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the