



Product Data Sheet

15W40 FULLY

DESCRIPTION

15W-40 Fully Synthetic Engine Oil is engineered to deliver superior engine protection and consistent performance under extreme temperatures and heavy-duty conditions. Its advanced synthetic formulation ensures excellent thermal stability, strong wear protection, and reduced engine deposits

APPLICATION

Designed for both diesel and petrol engines, it helps extend engine life, maintain cleanliness, and provide reliable lubrication during long drain intervals. Ideal for commercial vehicles, trucks, and high-load applications requiring dependable performance.

FEATURES AND ADVANTAGES

- Strong wear protection
- Excellent thermal stability
- Cleaner engine performance
- Longer engine life
- Reliable heavy-duty performance

PRODUCT PERFORMANCE CLAIM

API CK-4/SL

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	15W40
Colour	VISUAL	-	Visual
Density @ 15°C	ASTM D4052	kg/m ³	850.7
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	142.55
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	16.53
Viscosity Index	ASTM D2270	-	160
Pour Point, °C	ASTM D97	°C	-30
Flash Point, °C	IP 523	°C	220

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the