



Product Data Sheet

15W40 SM/CF Mineral

DESCRIPTION

15W40 SM/CF Mineral is a high-quality mineral engine oil formulated with refined base oils and a robust additive package. It provides strong lubrication, wear protection, and oxidation stability for both gasoline and light-duty diesel engines. The formulation helps reduce deposits, minimize friction, and maintain smooth and reliable engine performance under various driving conditions.

APPLICATION

15W40 SM/CF Mineral is suitable for gasoline and light-duty diesel engines used in passenger cars, light trucks, commercial vehicles, generators, and small industrial equipment. It is recommended for engines operating in mixed driving conditions such as high-temperature environments, frequent stop-and-go traffic, long-distance travel, and moderate load applications where dependable mineral-based protection is required.

FEATURES AND ADVANTAGES

- Excellent protection against wear, deposits, and sludge
- Strong high-temperature stability and oxidation resistance
- Smooth engine operation with reduced friction
- Suitable for gasoline (SM) and older diesel engines (CF)
- Reliable performance in urban, highway, and light commercial use

PRODUCT PERFORMANCE CLAIM

API SM/SL/SJ/CF
ACEA: A3/B3 or A3/B4

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m ³	866.8
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	137.92
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	15.796
Viscosity Index	ASTM D2270	-	128.59
Pour Point, °C	ASTM D97	°C	-11
Flash Point, °C	IP 523	°C	240

*VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the