



Product Data Sheet

15W40 SQ/CF Semi

DESCRIPTION

A high-performance semi-synthetic engine oil engineered for reliable protection and durability. Provides excellent lubrication under high temperature and heavy load conditions, helping reduce engine wear and extend engine life.

APPLICATION

Suitable for a wide range of gasoline and diesel engines in passenger cars, light trucks, and commercial vehicles. Recommended for engines operating in mixed driving conditions, including city traffic and long-distance journeys.

FEATURES AND ADVANTAGES

- Superior wear and deposit protection
- Excellent oxidation stability at high temperatures
- Enhances engine performance and fuel efficiency
- Meets API SQ/CF performance standards
- Suitable for engines requiring semi-synthetic lubrication

PRODUCT PERFORMANCE CLAIM

API SQ/CF-4

ACEA A3/B4

Cummins CES 20076/77, Mack EO-M Plus

Mercedes-Benz MB 228.3, MAN M3275, Volvo VDS-2

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m ³	875.6
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	135.17
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	15.938
Viscosity Index	ASTM D2270	None	141.62
Pour Point, °C	ASTM D97	°C	-20
Flash Point, °C	IP 523	°C	240

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the