



Product Data Sheet

20W50 SL/CF Mineral

DESCRIPTION

20W50 SL/CF Mineral is a high-quality mineral engine oil formulated with refined base oils and a balanced additive system. It provides excellent lubrication, wear protection, and high-temperature stability for reliable engine performance. The formulation helps reduce deposits, minimize friction, and maintain smooth operation under demanding conditions.

APPLICATION

20W50 SL/CF Mineral is suitable for gasoline and light-duty diesel engines used in passenger cars, light trucks, motorcycles, generators, and commercial equipment. It is recommended for engines operating in high-temperature environments, heavy-load driving, or long-distance travel where stable viscosity and dependable mineral-based protection are required.

FEATURES AND ADVANTAGES

- Excellent wear and deposit protection
- Stable viscosity and strong lubrication at high temperatures
- Reduced friction for smoother engine performance
- Suitable for gasoline (SL) and older diesel engines (CF)
- Reliable performance in city, highway, and heavy-load driving

PRODUCT PERFORMANCE CLAIM

API SL/SJ/CF
ACEA: A3/B3 or A3/B4

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m ³	868.1
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	188.07
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	19.996
Viscosity Index	ASTM D2270	-	125.62
Pour Point, °C	ASTM D97	°C	-11
Flash Point, °C	IP 523	°C	240

*VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the