



Product Data Sheet

ATF DEXRON-III

DESCRIPTION

A premium automatic transmission fluid specially formulated for smooth shifting and reliable performance. Provides excellent oxidation stability, wear protection, and friction characteristics to extend transmission life.

APPLICATION

Suitable for automatic transmissions, power steering systems, and hydraulic systems requiring DEXRON-III specification. Ideal for cars, trucks, and other vehicles operating under normal or severe driving conditions.

FEATURES AND ADVANTAGES

- Smooth gear shifting and reduced noise
- Protects against wear, corrosion, and foaming
- Maintains performance under high temperatures
- Compatible with systems requiring DEXRON-III, DEXRON-IIIE, and II specifications
- Enhances transmission life and reliability

PRODUCT PERFORMANCE CLAIM

Toyota : D-III, GM Dexron III F / Dexron III G , GM Type A Suffix A, Allison TES-389, Allison C-4, Mercedes Benz MB 236.1/ 236.9, Man 339 Type V1 / V2, 339 Type Z1/ Z2, Ford Mercon IV, Ford M2C-138CJ, Voith H55.6335xx, Volvo STD 1273.41(97341) Subaru ATF/ ATF HP , Mazda M III FluidM III Fluid

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m3	857.2
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	37.078
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	7.580
Viscosity Index	ASTM D2270	None	178.53
Pour Point, °C	ASTM D97	°C	-31
Flash Point, °C	IP 523	°C	210

*VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the