



Product Data Sheet

HD 40

DESCRIPTION

HD40 is a high-quality monograde diesel engine oil made from refined mineral base oils and selected additives. It provides effective protection against wear, deposits, rust, and oxidation, ensuring reliable lubrication and extended engine life. The oil maintains good film strength and stability even under high operating temperatures.

APPLICATION

Recommended for use in naturally aspirated and light turbocharged diesel engines used in trucks, buses, construction, and agricultural equipment. Suitable for engines where SAE 40 monograde oil meeting API CF or SF/ MIL-L performance levels is specified.

FEATURES AND ADVANTAGES

- Excellent wear protection for longer engine life
- High oxidation and thermal stability
- Protects against rust, corrosion, and sludge formation
- Maintains good oil film strength under high temperature
- Ensures smooth and reliable engine performance

PRODUCT PERFORMANCE CLAIM

API CF / SF, MIL-L-2104C, CCMC D2

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	g/ml	0.876
Kinematic Viscosity @ 40°C	ASTM D445	mm ² /s	101
Kinematic Viscosity @ 100°C	ASTM D445	mm ² /s	12.6
Viscosity Index	ASTM D2270	None	120
Pour Point, °C	ASTM D97	°C	-10
Flash Point, °C	ASTM D93	°C	249

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the