

TPC-H DATABASE SCHEMA

Create the following tables with their corresponding schema:

- **region** (
 - r_regionkey integer,
 - r_name string,
 - r_comment string)

- **nation** (
 - n_nationkey integer,
 - n_name string,
 - n_regionkey integer,
 - n_comment string)

- **part** (
 - p_partkey integer,
 - p_name string,
 - p_mfgr string,
 - p_brand string,
 - p_type string,
 - p_size integer,
 - p_container string,
 - p_retailprice float,
 - p_comment string)

- **supplier** (
 - s_suppkey integer,
 - s_name string,
 - s_address string,
 - s_nationkey integer,
 - s_phone string,
 - s_acctbal float,
 - s_comment string)

- **partsupp** (
 - ps_partkey integer,)

- ps_suppkey integer,
- ps_availqty integer,
- ps_supplycost float,
- ps_comment string

)

- **customer** (
 - c_custkey integer,
 - c_name string,
 - c_address string,
 - c_nationkey integer,
 - c_phone string,
 - c_acctbal float,
 - c_mktsegment string,
 - c_comment string
)
- **orders** (
 - o_orderkey integer,
 - o_custkey integer,
 - o_orderstatus string,
 - o_totalprice float,
 - o_orderdate string,
 - o_orderpriority string,
 - o_clerk string,
 - o_shippriority integer,
 - o_comment string
)
- **lineitem** (
 - l_orderkey integer,
 - l_partkey integer,
 - l_suppkey integer,
 - l_linenummer integer,
 - l_quantity integer,
 - l_extendedprice float,
 - l_discount float,
 - l_tax float,
 - l_returnflag string,
 - l_linestatus string,

- l_shipdate string,
- l_commitdate string,
- l_receiptdate string,
- l_shipinstruct string,
- l_shipmode string,
- l_comment string

)