

POTENTIAL WAYS OF REDUCING COST OF THE QUADRUPEL SPOT DEVELOPED BY BOSTON DYNAMICS

Tanishq Harish Duhan

Birla Institute of Technology and Sciences, Pilani

ABSTRACT

The aim of this paper is to list down the potential ways that can reduce the cost of the Quadruped-ed robot- "Spot" that is developed and maintained by Boston Dynamics. The paper Focuses on different aspects of Spot, technologies that it currently uses and potential changes that can bring down its cost. It also compares it to its competitors in the market and ways Spot could use their innovations to achieve similar, if not better performance at a lower cost.

1. INTRODUCTION

Spot is a Quadruped robot developed by Boston Dynamics and is currently one of the most famous in the market. It is highly customizable - both with respect to hardware and software. Recently we saw that the Spot robot came with a manipulator on top of it. It can operate in temperature ranges from -20 to 45-degree C. Due to these reasons, Spot currently has applications in various industries and is further used by different research institutes and helping them conduct breakthrough research in the field of robotics. As discussed above, Spot has very few to no limitations, and Boston Dynamics is working effortlessly to improve the already near perfect Robot-dog. Hence the only big limitation Spot has is its price. Spot's current price is of an enormous 75,000 dollars. Our aim is to discuss various methods of reducing the price of Spot without significantly decreasing its performance capabilities by suggesting replacements of current parts and comparing Spot to its competitors like Cheetah or Anymal.

2. SENSORS

SPOT features a mapping, localization, and autonomous traverse system collectively known as GraphNav. GraphNav uses sensor data to create waypoints, which are places in the real world it can travel to. Each waypoint has an associated snapshot of feature data from its location. This data allows the robot to track its position as it moves from waypoint to waypoint and correct its path. SPOT uses 5 Intel Realsense cameras' 360-degree perception to map surrounding terrain and avoid obstacles dynamically. Robots like, Anymal on the other hand, use a lidar and a

monocular camera mounted on a 2dof arm to achieve a similar performance. The lidar is used for mapping and gathering 3d point cloud data whereas the camera is used for object detection whereas Cheetah, developed by MIT only uses a forward-facing stereo camera for obstacle detection and avoidance. Based on the use of sensor data from by GraphNav, we could potentially replace the 5 Intel Realsense cameras with a system like Anymal. The lidar can be used to create maps and a stereo camera can be mounted on a 2dof arm instead of a monocular camera. At every way-point, the stereo camera can be rotated to capture multiple images at different orientations to cover its complete surroundings. Using this system, the quadruped would be able to achieve similar performance while reducing the cost of sensors to half.

Also, the Intel Realsense cameras are not optimum for working in outdoor environments, while a zed camera does not have such a limitation.

Hence using a lidar with a zed camera mounted on a gimbal or a 2dof arm can provide similar if not better performance at a lower price.

3. ACTUATORS

SPOT has 2 actuators in each hip, and one actuator in each knee. This creates the following degrees of freedom and limits on each axis: 12 DOFs: Hip Joint X-axis: +/- 45 degrees from vertical (45 degrees of internal and external rotation from vertical) Hip Joint Y-axis: +/- 91 degrees with 50-degree bias from vertical (flexion/extension) Knee: +/- 14-160 degrees from straight (flexion/extension range from 14 to 160 degrees)

SPOT Mini quadruped robots are driven by battery-motor. For the hip and shoulder joint, SPOT Mini uses Brushless DC Motors with harmonic gear, cycloidal, and or planetary gear reduction. The speed from the BLDC gets turned into torque with almost no back drive. The leg has a linear actuator to act on the cantilever knee. Since the range of motion of the knee joint is pretty small, it can be torque, fast, and low inertia. In contrast, the prototype of SPOT used a battery-motor-hydraulic pump-electric servo hydraulic cylinder.

Laikago, a Chinese quadruped robot also has a model like SPOT and uses Unitree brushless DC motors for actuation. MIT cheetah uses custom modular, low-gear ratio, backdriveable actuators with integrated electronics and high-bandwidth torque control. Anymal uses 12 electric series elastic actuators and hollow-shaft for

maximal range of motion. Mjbots quad uses 12 qdd100 quasi direct drive actuators for its motion. These are the alternates for the actuators that SPOT currently uses. The qdd100 actuators used by MJBots Quad is cheaper than most of the competition on the market but commenting exactly on the price will not be possible as the exact cost of the custom actuators of SPOT is not known.

4. MATERIALS AND MANUFACTURING

The exact materials used in SPOT are not currently known to us but looking at other quadrupeds, SPOT is either made of aluminum 6061 series, titanium-based alloys, carbon fiber, fiberglass or a combination of these. Looking at the competition, Unitree Laikago is made of Carbon fiber, aluminum and 3D-printed parts. MIT Cheetah is made using Aluminium with plastic protectors used wherever needed. Anymal is has a carbon fiber and aluminum body with foam protectors and some custom 3D-printed parts. SPOT has a very efficient design through which wastage of materials is minimised. Therefore, the cost due to materials doesn't significantly change irrespective of the materials used. Still, there are two ways to reduce cost. One is using cheaper materials like Steel or Iron which is not viable as these are optimal due to their weight and inability to handle high stress. The second and more practical approach is using Recycled Aluminium. Recycled Aluminium is almost as good as normal high-grade Aluminium and comes at a lower price and this price difference will become more noticeable when SPOT starts getting mass produced. Hence, the best way of reducing the cost materials used in SPOT is using Recycled Aluminium instead of normal Aluminium.

5. COMPUTATION

SPOT uses a custom control and computing system developed by Boston Dynamics as it on board computer. Additional compute module can be mounted on top using SPOT's 2 payload ports and the additional compute module developed by Boston Dynamics costs \$4,000. Assuming the cost of the on-board computer to be close to the additional compute module, the price of the on-board computer can be estimated to about \$4000, which is enormous and holds the greatest potential for cost-reducing. As the major use of SPOT is industrial, it can make do with a processing power which is sufficient to run GraphNav. GraphNav is the system SPOT features for mapping, localization, and autonomous traversal.

As for its competition, only Anymal uses algorithms with complexity close to GraphNav and it uses three Intel i7 dual-core processors. One processor for real-time locomotion control, one processor for navigation, and one processor for task-specific application software (e.g., inspection). Other quadrupeds like Cheetah or MJBots quad don't use complex algorithms and only need computation for basic obstacle avoidance or motion control, and hence, their on-board computers cannot potentially replace the existing ones on SPOT.

Another way to Reduce the reduce the cost of on board computers is to use computationally simpler algorithms

that can perform similar to GraphNav and could run on NVIDIA Jetson TX2 or Xavier NX.

Hence using multiple processors like Anymal is still extremely cheaper than using a custom \$4,000 computer system. The total cost of buying 3 Intel, top of the line, 11th gen i7 processors is still less than \$2,000 and hence this can enormously reduce the cost of SPOT. At the same time, if algorithms are made simple enough to run on a Nvidia Jetson TX2, the costs will further drop to less than \$1000.

6. CITATIONS

Boston Dynamics, official Website:

<https://www.bostondynamics.com/>

Spot official SDF

Robots IEEE Web-site:

<https://robots.ieee.org/robots/laikago/>

<https://robots.ieee.org/robots/anymal/>

<https://robots.ieee.org/robots/spotmini/>

<https://robots.ieee.org/robots/hyq/>.

Hack-day.io: <https://hackaday.io/project/167845/logs>

https://en.wikipedia.org/wiki/Boston_Dynamics<https://www.anybotics.com/anymal> – autonomous –

legged – robot/