- **Supply Current . . . 300 μA Max**
- **High Unity-Gain Bandwidth . . . 2 MHz Typ**
- **High Slew Rate . . . 0.45 V/μs Min**
- **Supply-Current Change Over Military Temp Range . . . 10 μA Typ at $V_{CC\pm} = \pm 15$ V**
- **Specified for Both 5-V Single-Supply and ±15-V Operation**
- **Phase-Reversal Protection**
- **High Open-Loop Gain . . . 6.5 V/μV (136 dB) Typ**
- **Low Offset Voltage . . . 100 μV Max**
- **Offset Voltage Drift With Time 0.005 μV/mo Typ**
- **Low Input Bias Current . . . 50 nA Max**
- **Low Noise Voltage . . . 19 nV/$\sqrt{Hz}$ Typ**

## description

The TLE202x, TLE202xA, and TLE202xB devices are precision, high-speed, low-power operational amplifiers using a new Texas Instruments Excalibur process. These devices combine the best features of the OP21 with highly improved slew rate and unity-gain bandwidth.

The complementary bipolar Excalibur process utilizes isolated vertical pnp transistors that yield dramatic improvement in unity-gain bandwidth and slew rate over similar devices.

The addition of a bias circuit in conjunction with this process results in extremely stable parameters with both time and temperature. This means that a precision device remains a precision device even with changes in temperature and over years of use.

This combination of excellent dc performance with a common-mode input voltage range that includes the negative rail makes these devices the ideal choice for low-level signal conditioning applications in either single-supply or split-supply configurations. In addition, these devices offer phase-reversal protection circuitry that eliminates an unexpected change in output states when one of the inputs goes below the negative supply rail.

A variety of available options includes small-outline and chip-carrier versions for high-density systems applications.

The C-suffix devices are characterized for operation from 0°C to 70°C. The I-suffix devices are characterized for operation from –40°C to 85°C. The M-suffix devices are characterized for operation over the full military temperature range of –55°C to 125°C.

**TLE2021 AVAILABLE OPTIONS**

| $T_A$ | $V_{IO}$max AT 25°C | PACKAGED DEVICES | | | | | | CHIP FORM§ (Y) |
|---|---|---|---|---|---|---|---|---|
| | | SMALL OUTLINE† (D) | SSOP‡ (DB) | CHIP CARRIER (FK) | CERAMIC DIP (JG) | PLASTIC DIP (P) | TSSOP‡ (PW) | |
| 0°C to 70°C | 200 µV<br>500 µV | TLE2021ACD<br>TLE2021CD | TLE2021CDBLE | — | — | TLE2021ACP<br>TLE2021CP | —<br>TLE2021CPWLE | —<br>TLE2021Y |
| –40°C to 85°C | 200 µV<br>500 µV | TLE2021AID<br>TLE2021ID | — | — | — | TLE2021AIP<br>TLE2021IP | — | — |
| –55°C to 125°C | 100 µV<br>200 µV<br>500 µV | —<br>TLE2021AMD<br>TLE2021MD | — | TLE2021BMFK<br>TLE2021AMFK<br>TLE2021MFK | TLE2021BMJG<br>TLE2021AMJG<br>TLE2021MJG | —<br>TLE2021AMP<br>TLE2021MP | — | — |

† The D packages are available taped and reeled. To order a taped and reeled part, add the suffix R (e.g., TLE2021CDR).
‡ The DB and PW packages are only available left-end taped and reeled.
§ Chip forms are tested at 25°C only.

**TLE2022 AVAILABLE OPTIONS**

| $T_A$ | $V_{IO}$max AT 25°C | PACKAGED DEVICES | | | | | | CHIP FORM§ (Y) |
|---|---|---|---|---|---|---|---|---|
| | | SMALL OUTLINE† (D) | SSOP‡ (DB) | CHIP CARRIER (FK) | CERAMIC DIP (JG) | PLASTIC DIP (P) | TSSOP‡ (PW) | |
| 0°C to 70°C | 150 µV<br>300 µV<br>500 µV | TLE2022BCD<br>TLE2022ACD<br>TLE2022CD | —<br>—<br>TLE2022CDBLE | — | — | —<br>TLE2022ACP<br>TLE2022CP | —<br>—<br>TLE2022CPWLE | —<br>—<br>TLE2022Y |
| –40°C to 85°C | 150 µV<br>300 µV<br>500 µV | TLE2022BID<br>TLE2022AID<br>TLE2022ID | — | — | — | —<br>TLE2022AIP<br>TLE2022IP | — | — |
| –55°C to 125°C | 150 µV<br>300 µV<br>500 µV | —<br>TLE2022AMD<br>TLE2022MD | — | —<br>TLE2022AMFK<br>TLE2022MFK | TLE2022BMJG<br>TLE2022AMJG<br>TLE2022MJG | —<br>TLE2022AMP<br>TLE2022MP | — | — |

† The D packages are available taped and reeled. To order a taped and reeled part, add the suffix R (e.g., TLE2022CDR).
‡ The DB and PW packages are only available left-end taped and reeled.
§ Chip forms are tested at 25°C only.

**TLE2024 AVAILABLE OPTIONS**

| $T_A$ | $V_{IO}$max AT 25°C | PACKAGED DEVICES | | | | CHIP FORM§ (Y) |
|---|---|---|---|---|---|---|
| | | SMALL OUTLINE (DW) | CHIP CARRIER (FK) | CERAMIC DIP (J) | PLASTIC DIP (N) | |
| 0°C to 70°C | 500 µV<br>750 µV<br>1000 µV | TLE2024BCDW<br>TLE2024ACDW<br>TLE2024CDW | — | — | TLE2024BCN<br>TLE2024ACN<br>TLE2024CN | —<br>—<br>TLE2024Y |
| –40°C to 85°C | 500 µV<br>750 µV<br>1000 µV | TLE2024BIDW<br>TLE2024AIDW<br>TLE2024IDW | — | — | TLE2024BIN<br>TLE2024AIN<br>TLE2024IN | — |
| –55°C to 125°C | 500 µV<br>750 µV<br>1000 µV | TLE2024BMDW<br>TLE2024AMDW<br>TLE2024MDW | TLE2024BMFK<br>TLE2024AMFK<br>TLE2024MFK | TLE2024BMJ<br>TLE2024AMJ<br>TLE2024MJ | TLE2024BMN<br>TLE2024AMN<br>TLE2024MN | — |

§ Chip forms are tested at 25°C only.

**TLE2021**
**D, DB, JG, P, OR PW PACKAGE**
**(TOP VIEW)**




**TLE2021**
**FK PACKAGE**
**(TOP VIEW)**




NC – No internal connection

**D, DB, JG, P, OR PW PACKAGE**
**(TOP VIEW)**




**FK PACKAGE**
**(TOP VIEW)**




NC – No internal connection

**DW PACKAGE**
**(TOP VIEW)**




**FK PACKAGE**
**(TOP VIEW)**




**J OR N PACKAGE**
**(TOP VIEW)**




NC – No internal connection

## TLE2021Y chip information

This chip, when properly assembled, display characteristics similar to the TLE2021. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. This chip may be mounted with conductive epoxy or a gold-silicon preform.

**BONDING PAD ASSIGNMENTS**







**CHIP THICKNESS: 15 MILS TYPICAL**

**BONDING PADS: 4 × 4 MILS MINIMUM**

**$T_{Jmax}$ = 150°C**

**TOLERANCES ARE ±10%.**

**ALL DIMENSIONS ARE IN MILS.**

**PIN (4) IS INTERNALLY CONNECTED TO BACKSIDE OF CHIP.**

## TLE2022Y chip information

This chip, when properly assembled, displays characteristics similar to TLE2022. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. This chip may be mounted with conductive epoxy or a gold-silicon preform.

**BONDING PAD ASSIGNMENTS**







**CHIP THICKNESS: 15 MILS TYPICAL**

**BONDING PADS: 4 × 4 MILS MINIMUM**

**$T_J$max = 150°C**

**TOLERANCES ARE ±10%.**

**ALL DIMENSIONS ARE IN MILS.**

**PIN (4) IS INTERNALLY CONNECTED TO BACKSIDE OF CHIP.**

## TLE2024Y chip information

This chip, when properly assembled, displays characteristics similar to the TLE2024. Thermal compression or ultrasonic bonding may be used on the doped aluminum-bonding pads. This chip may be mounted with conductive epoxy or a gold-silicon preform.

**BONDING PAD ASSIGNMENTS**







**CHIP THICKNESS: 15 MILS TYPICAL**

**BONDING PADS: 4 × 4 MILS MINIMUM**

**$T_J$max = 150°C**

**TOLERANCES ARE ±10%.**

**ALL DIMENSIONS ARE IN MILS.**

**PIN (11) IS INTERNALLY CONNECTED TO BACKSIDE OF CHIP.**

## equivalent schematic (each amplifier)




| ACTUAL DEVICE COMPONENT COUNT | | | |
|---|---|---|---|
| COMPONENT | TLE2021 | TLE2022 | TLE2024 |
| Transistors | 40 | 80 | 160 |
| Resistors | 7 | 14 | 28 |
| Diodes | 4 | 8 | 16 |
| Capacitors | 4 | 8 | 16 |

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, $V_{CC+}$ (see Note 1) . . . 20 V
Supply voltage, $V_{CC-}$ (see Note 1) . . . –20 V
Differential input voltage, $V_{ID}$ (see Note 2) . . . ±0.6 V
Input voltage range, $V_I$ (any input, see Note 1) . . . $\pm V_{CC}$
Input current, $I_I$ (each input) . . . ±1 mA
Output current, $I_O$ (each output): TLE2021 . . . ±20 mA
TLE2022 . . . ±30 mA
TLE2024 . . . ±40 mA
Total current into $V_{CC+}$ . . . 80 mA
Total current out of $V_{CC-}$ . . . 80 mA
Duration of short-circuit current at (or below) 25°C (see Note 3) . . . unlimited
Continuous total power dissipation . . . See Dissipation Rating Table
Operating free-air temperature range, $T_A$: C suffix . . . 0°C to 70°C
I suffix . . . –40°C to 85°C
M suffix . . . –55°C to 125°C
Storage temperature range, $T_{stg}$ . . . –65°C to 150°C
Case temperature for 60 seconds, $T_C$: FK package . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D, DP, P, or PW package . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG package . . . 300°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values, except differential voltages, are with respect to the midpoint between $V_{CC+}$, and $V_{CC-}$.
2. Differential voltages are at IN+ with respect to IN–. Excessive current flows if a differential input voltage in excess of approximately ±600 mV is applied between the inputs unless some limiting resistance is used.
3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

**DISSIPATION RATING TABLE**

| PACKAGE | $T_A \le 25°C$ POWER RATING | DERATING FACTOR ABOVE $T_A$ = 25°C | $T_A$ = 70°C POWER RATING | $T_A$ = 85°C POWER RATING | $T_A$ = 125°C POWER RATING |
|---|---|---|---|---|---|
| D–8 | 725 mW | 5.8 mW/°C | 464 mW | 377 mW | 145 mW |
| DB–8 | 525 mW | 4.2 mW/°C | 336 mW | — | — |
| DW–16 | 1025 mW | 8.2 mW/°C | 656 mW | 533 mW | 205 mW |
| FK | 1375 mW | 11.0 mW/°C | 880 mW | 715 mW | 275 mW |
| J–14 | 1375 mW | 11.0 mW/°C | 880 mW | 715 mW | 275 mW |
| JG–8 | 1050 mW | 8.4 mW/°C | 672 mW | 546 mW | 210 mW |
| N–14 | 1150 mW | 9.2 mW/°C | 736 mW | 598 mW | 230 mW |
| P–8 | 1000 mW | 8.0 mW/°C | 640 mW | 520 mW | 200 mW |
| PW–8 | 525 mW | 4.2 mW/°C | 336 mW | — | — |

## recommended operating conditions

| | | C SUFFIX | | I SUFFIX | | M SUFFIX | | UNIT |
|---|---|---|---|---|---|---|---|---|
| | | MIN | MAX | MIN | MAX | MIN | MAX | |
| Supply voltage, $V_{CC}$ | | ±2 | ±20 | ±2 | ±20 | ±2 | ±20 | V |
| Common-mode input voltage, $V_{IC}$ | $V_{CC}$ = ± 5 V | 0 | 3.5 | 0 | 3.2 | 0 | 3.2 | V |
| | $V_{CC\pm}$ = ±15 V | –15 | 13.5 | –15 | 13.2 | –15 | 13.2 | |
| Operating free-air temperature, $T_A$ | | 0 | 70 | –40 | 85 | –55 | 125 | °C |

## TLE2021 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2021C | | | TLE2021AC | | | TLE2021BC | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | 120 | 600 | | 100 | 300 | | 80 | 200 | μV |
| | | | Full range | | | 850 | | | 600 | | | 300 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.2 | 6 | | 0.2 | 6 | | 0.2 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 25 | 70 | | 25 | 70 | | 25 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | – 0.3 to 4 | | 0 to 3.5 | – 0.3 to 4 | | 0 to 3.5 | – 0.3 to 4 | | V |
| | | | Full range | 0 to 3.5 | | | 0 to 3.5 | | | 0 to 3.5 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | 25°C | 4 | 4.3 | | 4 | 4.3 | | 4 | 4.3 | | V |
| | | | Full range | 3.9 | | | 3.9 | | | 3.9 | | | |
| $V_{OL}$ | Low-level output voltage | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.85 | | | 0.85 | | | 0.85 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.3 | 1.5 | | 0.3 | 1.5 | | 0.3 | 1.5 | | V/μV |
| | | | Full range | 0.3 | | | 0.3 | | | 0.3 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 85 | 110 | | 85 | 110 | | 85 | 110 | | dB |
| | | | Full range | 80 | | | 80 | | | 80 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | 25°C | 105 | 120 | | 105 | 120 | | 105 | 120 | | dB |
| | | | Full range | 100 | | | 100 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, No load | 25°C | | 200 | 300 | | 200 | 300 | | 200 | 300 | μA |
| | | | Full range | | | 300 | | | 300 | | | 300 | |
| $\Delta I_{CC}$ | Supply-current change over operating temperature range | | Full range | | 5 | | | 5 | | | 5 | | μA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2021 electrical characteristics at specified free-air temperature, $V_{CC}$ = ±15 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2021C | | | TLE2021AC | | | TLE2021BC | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | 120 | 500 | | 80 | 200 | | 40 | 100 | μV |
| | | | Full range | | | 750 | | | 500 | | | 200 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.2 | 6 | | 0.2 | 6 | | 0.2 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 25 | 70 | | 25 | 70 | | 25 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.5 | | | –15 to 13.5 | | | –15 to 13.5 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L$ = 10 kΩ | 25°C | 14 | 14.3 | | 14 | 14.3 | | 14 | 14.3 | | V |
| | | | Full range | 13.9 | | | 13.9 | | | 13.9 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.7 | | | –13.7 | | | –13.7 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = ± 10 V, $R_L$ = 10 kΩ | 25°C | 1 | 6.5 | | 1 | 6.5 | | 1 | 6.5 | | V/μV |
| | | | Full range | 1 | | | 1 | | | 1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC}$ = $V_{ICR}$ min, $R_S$ = 50 Ω | 25°C | 100 | 115 | | 100 | 115 | | 100 | 115 | | dB |
| | | | Full range | 96 | | | 96 | | | 96 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$) | $V_{CC\pm}$ = ± 2.5 V to ± 15 V | 25°C | 105 | 120 | | 105 | 120 | | 105 | 120 | | dB |
| | | | Full range | 100 | | | 100 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 0, No load | 25°C | | 240 | 350 | | 240 | 350 | | 240 | 350 | μA |
| | | | Full range | | | 350 | | | 350 | | | 350 | |
| $\Delta I_{CC}$ | Supply-current change over operating temperature range | | Full range | | 6 | | | 6 | | | 6 | | μA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2022 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2022C | | | TLE2022AC | | | TLE2022BC | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | | 600 | | | 400 | | | 250 | μV |
| | | | Full range | | | 800 | | | 550 | | | 400 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.5 | 6 | | 0.4 | 6 | | 0.3 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 35 | 70 | | 33 | 70 | | 30 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | V |
| | | | Full range | 0 to 3.5 | | | 0 to 3.5 | | | 0 to 3.5 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | 25°C | 4 | 4.3 | | 4 | 4.3 | | 4 | 4.3 | | V |
| | | | Full range | 3.9 | | | 3.9 | | | 3.9 | | | |
| $V_{OL}$ | Low-level output voltage | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.85 | | | 0.85 | | | 0.85 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.3 | 1.5 | | 0.4 | 1.5 | | 0.5 | 1.5 | | V/μV |
| | | | Full range | 0.3 | | | 0.4 | | | 0.5 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 85 | 100 | | 87 | 102 | | 90 | 105 | | dB |
| | | | Full range | 80 | | | 82 | | | 85 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | 25°C | 100 | 115 | | 103 | 118 | | 105 | 120 | | dB |
| | | | Full range | 95 | | | 98 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, No load | 25°C | | 450 | 600 | | 450 | 600 | | 450 | 600 | μA |
| | | | Full range | | | 600 | | | 600 | | | 600 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 7 | | | 7 | | | 7 | | μA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2022 electrical characteristics at specified free-air temperature, $V_{CC} = \pm 15$ V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2022C | | | TLE2022AC | | | TLE2022BC | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC} = 0$, $R_S = 50\ \Omega$ | 25°C | | 150 | 500 | | 120 | 300 | | 70 | 150 | μV |
| | | | Full range | | | 700 | | | 450 | | | 300 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.5 | 6 | | 0.4 | 6 | | 0.3 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 35 | 70 | | 33 | 70 | | 30 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S = 50\ \Omega$ | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.5 | | | –15 to 13.5 | | | –15 to 13.5 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L = 10\ k\Omega$ | 25°C | 14 | 14.3 | | 14 | 14.3 | | 14 | 14.3 | | V |
| | | | Full range | 13.9 | | | 13.9 | | | 13.9 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.7 | | | –13.7 | | | –13.7 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O = \pm 10$ V, $R_L = 10\ k\Omega$ | 25°C | 0.8 | 4 | | 1 | 7 | | 1.5 | 10 | | V/μV |
| | | | Full range | 0.8 | | | 1 | | | 1.5 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S = 50\ \Omega$ | 25°C | 95 | 106 | | 97 | 109 | | 100 | 112 | | dB |
| | | | Full range | 91 | | | 93 | | | 96 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm} = \pm 2.5$ V to $\pm 15$ V | 25°C | 100 | 115 | | 103 | 118 | | 105 | 120 | | dB |
| | | | Full range | 95 | | | 98 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O = 0$, No load | 25°C | | 550 | 700 | | 550 | 700 | | 550 | 700 | μA |
| | | | Full range | | | 700 | | | 700 | | | 700 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 9 | | | 9 | | | 9 | | μA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A = 150°C$ extrapolated to $T_A = 25°C$ using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2024 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2024C | | | TLE2024AC | | | TLE2024BC | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | | 1100 | | | 850 | | | 600 | µV |
| | | | Full range | | | 1300 | | | 1050 | | | 800 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.6 | 6 | | 0.5 | 6 | | 0.4 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 45 | 70 | | 40 | 70 | | 35 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | V |
| | | | Full range | 0 to 3.5 | | | 0 to 3.5 | | | 0 to 3.5 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | 25°C | 3.9 | 4.2 | | 3.9 | 4.2 | | 4 | 4.3 | | V |
| | | | Full range | 3.7 | | | 3.7 | | | 3.8 | | | |
| $V_{OL}$ | Low-level output voltage | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.95 | | | 0.95 | | | 0.95 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.2 | 1.5 | | 0.3 | 1.5 | | 0.4 | 1.5 | | V/µV |
| | | | Full range | 0.1 | | | 0.1 | | | 0.1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 80 | 90 | | 82 | 92 | | 85 | 95 | | dB |
| | | | Full range | 80 | | | 82 | | | 85 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | 25°C | 98 | 112 | | 100 | 115 | | 103 | 117 | | dB |
| | | | Full range | 93 | | | 95 | | | 98 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, No load | 25°C | | 800 | 1200 | | 800 | 1200 | | 800 | 1200 | µA |
| | | | Full range | | | 1200 | | | 1200 | | | 1200 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 15 | | | 15 | | | 15 | | µA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2024 electrical characteristics at specified free-air temperature, $V_{CC} = \pm15$ V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2024C | | | TLE2024AC | | | TLE2024BC | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC} = 0$, $R_S = 50\ \Omega$ | 25°C | | | 1000 | | | 750 | | | 500 | μV |
| | | | Full range | | | 1200 | | | 950 | | | 700 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.6 | 6 | | 0.5 | 6 | | 0.4 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 50 | 70 | | 45 | 70 | | 40 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S = 50\ \Omega$ | 25°C | −15 to 13.5 | −15.3 to 14 | | −15 to 13.5 | −15.3 to 14 | | −15 to 13.5 | −15.3 to 14 | | V |
| | | | Full range | −15 to 13.5 | | | −15 to 13.5 | | | −15 to 13.5 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L = 10\ k\Omega$ | 25°C | 13.8 | 14.1 | | 13.9 | 14.2 | | 14 | 14.3 | | V |
| | | | Full range | 13.7 | | | 13.8 | | | 13.9 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | −13.7 | −14.1 | | −13.7 | −14.1 | | −13.7 | −14.1 | | V |
| | | | Full range | −13.6 | | | −13.6 | | | −13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O = \pm10$ V, $R_L = 10\ k\Omega$ | 25°C | 0.4 | 2 | | 0.8 | 4 | | 1 | 7 | | V/μV |
| | | | Full range | 0.4 | | | 0.8 | | | 1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S = 50\ \Omega$ | 25°C | 92 | 102 | | 94 | 105 | | 97 | 108 | | dB |
| | | | Full range | 88 | | | 90 | | | 93 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm} = \pm2.5$ V to $\pm15$ V | 25°C | 98 | 112 | | 100 | 115 | | 103 | 117 | | dB |
| | | | Full range | 93 | | | 95 | | | 98 | | | |
| $I_{CC}$ | Supply current | $V_O = 0$, No load | 25°C | | 1050 | 1400 | | 1050 | 1400 | | 1050 | 1400 | μA |
| | | | Full range | | | 1400 | | | 1400 | | | 1400 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 20 | | | 20 | | | 20 | | μA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A = 150°C$ extrapolated to $T_A = 25°C$ using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2021 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2021I | | | TLE2021AI | | | TLE2021BI | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | 120 | 600 | | 100 | 300 | | 80 | 200 | μV |
| | | | Full range | | | 950 | | | 600 | | | 300 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.2 | 6 | | 0.2 | 6 | | 0.2 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 25 | 70 | | 25 | 70 | | 25 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | –0.3 to 4 | | 0 to 3.5 | –0.3 to 4 | | 0 to 3.5 | –0.3 to 4 | | V |
| | | | Full range | 0 to 3.2 | | | 0 to 3.2 | | | 0 to 3.2 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | 25°C | 4 | 4.3 | | 4 | 4.3 | | 4 | 4.3 | | V |
| | | | Full range | 3.9 | | | 3.9 | | | 3.9 | | | |
| $V_{OL}$ | Low-level output voltage | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.9 | | | 0.9 | | | 0.9 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.3 | 1.5 | | 0.3 | 1.5 | | 0.3 | 1.5 | | V/μV |
| | | | Full range | 0.25 | | | 0.25 | | | 0.25 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$ min, $R_S$ = 50 Ω | 25°C | 85 | 110 | | 85 | 110 | | 85 | 110 | | dB |
| | | | Full range | 80 | | | 80 | | | 80 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | 25°C | 105 | 120 | | 105 | 120 | | 105 | 120 | | dB |
| | | | Full range | 100 | | | 100 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, No load | 25°C | | 200 | 300 | | 200 | 300 | | 200 | 300 | μA |
| | | | Full range | | | 300 | | | 300 | | | 300 | |
| $\Delta I_{CC}$ | Supply-current change over operating temperature range | | Full range | | 6 | | | 6 | | | 6 | | μA |

† Full range is – 40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2021 electrical characteristics at specified free-air temperature, $V_{CC}$ = ± 15 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2021I | | | TLE2021AI | | | TLE2021BI | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | 120 | 500 | | 80 | 200 | | 40 | 100 | µV |
| | | | Full range | | | 850 | | | 500 | | | 200 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.2 | 6 | | 0.2 | 6 | | 0.2 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 25 | 70 | | 25 | 70 | | 25 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.2 | | | –15 to 13.2 | | | –15 to 13.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L$ = 10 kΩ | 25°C | 14 | 14.3 | | 14 | 14.3 | | 14 | 14.3 | | V |
| | | | Full range | 13.9 | | | 13.9 | | | 13.9 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.6 | | | –13.6 | | | –13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 10 V, $R_L$ = 10 kΩ | 25°C | 1 | 6.5 | | 1 | 6.5 | | 1 | 6.5 | | V/µV |
| | | | Full range | 0.75 | | | 0.75 | | | 0.75 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC}$ = $V_{ICR}$ min, $R_S$ = 50 Ω | 25°C | 100 | 115 | | 100 | 115 | | 100 | 115 | | dB |
| | | | Full range | 96 | | | 96 | | | 96 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$) | $V_{CC\pm}$ = ± 2. 5 V to ± 15 V | 25°C | 105 | 120 | | 105 | 120 | | 105 | 120 | | dB |
| | | | Full range | 100 | | | 100 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 0 V, No load | 25°C | | 240 | 350 | | 240 | 350 | | 240 | 350 | µA |
| | | | Full range | | | 350 | | | 350 | | | 350 | |
| $\Delta I_{CC}$ | Supply-current change over operating temperature range | | Full range | | 7 | | | 7 | | | 7 | | µA |

† Full range is – 40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2022 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2022I | | | TLE2022AI | | | TLE2022BI | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | | 600 | | | 400 | | | 250 | µV |
| | | | Full range | | | 800 | | | 550 | | | 400 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.5 | 6 | | 0.4 | 6 | | 0.3 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 35 | 70 | | 33 | 70 | | 30 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | –0.3 to 4 | | 0 to 3.5 | –0.3 to 4 | | 0 to 3.5 | –0.3 to 4 | | V |
| | | | Full range | 0 to 3.2 | | | 0 to 3.2 | | | 0 to 3.2 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | 25°C | 4 | 4.3 | | 4 | 4.3 | | 4 | 4.3 | | V |
| | | | Full range | 3.9 | | | 3.9 | | | 3.9 | | | |
| $V_{OL}$ | Low-level output voltage | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.9 | | | 0.9 | | | 0.9 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.3 | 1.5 | | 0.4 | 1.5 | | 0.5 | 1.5 | | V/µV |
| | | | Full range | 0.2 | | | 0.2 | | | 0.2 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 85 | 100 | | 87 | 102 | | 90 | 105 | | dB |
| | | | Full range | 80 | | | 82 | | | 85 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | 25°C | 100 | 115 | | 103 | 118 | | 105 | 120 | | dB |
| | | | Full range | 95 | | | 98 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, No load | 25°C | | 450 | 600 | | 450 | 600 | | 450 | 600 | µA |
| | | | Full range | | | 600 | | | 600 | | | 600 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 15 | | | 15 | | | 15 | | µA |

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2022 electrical characteristics at specified free-air temperature, $V_{CC}$ = ± 15 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2022I | | | TLE2022AI | | | TLE2022BI | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | 150 | 500 | | 120 | 300 | | 70 | 150 | µV |
| | | | Full range | | | 700 | | | 450 | | | 300 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.5 | 6 | | 0.4 | 6 | | 0.3 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 35 | 70 | | 33 | 70 | | 30 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | – 15 to 13.5 | –15.3 to 14 | | – 15 to 13.5 | –15.3 to 14 | | – 15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | – 15 to 13.2 | | | – 15 to 13.2 | | | – 15 to 13.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L$ = 10 kΩ | 25°C | 14 | 14.3 | | 14 | 14.3 | | 14 | 14.3 | | V |
| | | | Full range | 13.9 | | | 13.9 | | | 13.9 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | – 13.7 | – 14.1 | | – 13.7 | – 14.1 | | – 13.7 | – 14.1 | | V |
| | | | Full range | – 13.6 | | | – 13.6 | | | – 13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = ± 10 V, $R_L$ = 10 kΩ | 25°C | 0.8 | 4 | | 1 | 7 | | 1.5 | 10 | | V/µV |
| | | | Full range | 0.8 | | | 1 | | | 1.5 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC}$ = $V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 95 | 106 | | 97 | 109 | | 100 | 112 | | dB |
| | | | Full range | 91 | | | 93 | | | 96 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = ±2.5 V to ±15 V | 25°C | 100 | 115 | | 103 | 118 | | 105 | 120 | | dB |
| | | | Full range | 95 | | | 98 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 0, No load | 25°C | | 550 | 700 | | 550 | 700 | | 550 | 700 | µA |
| | | | Full range | | | 700 | | | 700 | | | 700 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 30 | | | 30 | | | 30 | | µA |

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2024 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2024I | | | TLE2024AI | | | TLE2024BI | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | | 1100 | | | 850 | | | 600 | µV |
| | | | Full range | | | 1300 | | | 1050 | | | 800 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.6 | 6 | | 0.5 | 6 | | 0.4 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 45 | 70 | | 40 | 70 | | 35 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | V |
| | | | Full range | 0 to 3.2 | | | 0 to 3.2 | | | 0 to 3.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L$ = 10 kΩ | 25°C | 3.9 | 4.2 | | 3.9 | 4.2 | | 4 | 4.3 | | V |
| | | | Full range | 3.7 | | | 3.7 | | | 3.8 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.95 | | | 0.95 | | | 0.95 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.2 | 1.5 | | 0.3 | 1.5 | | 0.4 | 1.5 | | V/µV |
| | | | Full range | 0.1 | | | 0.1 | | | 0.1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 80 | 90 | | 82 | 92 | | 85 | 95 | | dB |
| | | | Full range | 80 | | | 82 | | | 85 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm}$ = ±2.5 V to ±15 V | 25°C | 98 | 112 | | 100 | 115 | | 103 | 117 | | dB |
| | | | Full range | 93 | | | 95 | | | 98 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 0, No load | 25°C | | 800 | 1200 | | 800 | 1200 | | 800 | 1200 | µA |
| | | | Full range | | | 1200 | | | 1200 | | | 1200 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 30 | | | 30 | | | 30 | | µA |

† Full range is −40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2024 electrical characteristics at specified free-air temperature, $V_{CC} = \pm 15$ V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2024I | | | TLE2024AI | | | TLE2024BI | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC} = 0$, $R_S = 50\ \Omega$ | 25°C | | | 1000 | | | 750 | | | 500 | μV |
| | | | Full range | | | 1200 | | | 950 | | | 700 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.6 | 6 | | 0.5 | 6 | | 0.4 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 50 | 70 | | 45 | 70 | | 40 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S = 50\ \Omega$ | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.2 | | | –15 to 13.2 | | | –15 to 13.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L = 10\ k\Omega$ | 25°C | 13.8 | 14.1 | | 13.9 | 14.2 | | 14 | 14.3 | | V |
| | | | Full range | 13.7 | | | 13.7 | | | 13.8 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.6 | | | –13.6 | | | –13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O = \pm 10$ V, $R_L = 10\ k\Omega$ | 25°C | 0.4 | 2 | | 0.8 | 4 | | 1 | 7 | | V/μV |
| | | | Full range | 0.4 | | | 0.8 | | | 1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S = 50\ \Omega$ | 25°C | 92 | 102 | | 94 | 105 | | 97 | 108 | | dB |
| | | | Full range | 88 | | | 90 | | | 93 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm} = \pm 2.5$ V to $\pm 15$ V | 25°C | 98 | 112 | | 100 | 115 | | 103 | 117 | | dB |
| | | | Full range | 93 | | | 95 | | | 98 | | | |
| $I_{CC}$ | Supply current | $V_O = 0$, No load | 25°C | | 1050 | 1400 | | 1050 | 1400 | | 1050 | 1400 | μA |
| | | | Full range | | | 1400 | | | 1400 | | | 1400 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 50 | | | 50 | | | 50 | | μA |

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A = 150°C$ extrapolated to $T_A = 25°C$ using the Arrhenius equation and assuming an activation energy of 0.96 eV.

### TLE2021 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2021M | | | TLE2021AM | | | TLE2021BM | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | 120 | 600 | | 100 | 300 | | 80 | 200 | µV |
| | | | Full range | | | 1100 | | | 600 | | | 300 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.2 | 6 | | 0.2 | 6 | | 0.2 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 25 | 70 | | 25 | 70 | | 25 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | –0.3 to 4 | | 0 to 3.5 | –0.3 to 4 | | 0 to 3.5 | –0.3 to 4 | | V |
| | | | Full range | 0 to 3.2 | | | 0 to 3.2 | | | 0 to 3.2 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | 25°C | 4 | 4.3 | | 4 | 4.3 | | 4 | 4.3 | | V |
| | | | Full range | 3.8 | | | 3.8 | | | 3.8 | | | |
| $V_{OL}$ | Low-level output voltage | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.95 | | | 0.95 | | | 0.95 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.3 | 1.5 | | 0.3 | 1.5 | | 0.3 | 1.5 | | V/µV |
| | | | Full range | 0.1 | | | 0.1 | | | 0.1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 85 | 110 | | 85 | 110 | | 85 | 110 | | dB |
| | | | Full range | 80 | | | 80 | | | 80 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | 25°C | 105 | 120 | | 105 | 120 | | 105 | 120 | | dB |
| | | | Full range | 100 | | | 100 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, No load | 25°C | | 170 | 230 | | 170 | 230 | | 170 | 230 | µA |
| | | | Full range | | | 230 | | | 230 | | | 230 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 9 | | | 9 | | | 9 | | µA |

† Full range is –55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2021 electrical characteristics at specified free-air temperature, $V_{CC} = \pm 15$ V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2021M | | | TLE2021AM | | | TLE2021BM | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC} = 0$, $R_S = 50\ \Omega$ | 25°C | | 120 | 500 | | 80 | 200 | | 40 | 100 | μV |
| | | | Full range | | | 1000 | | | 500 | | | 200 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.2 | 6 | | 0.2 | 6 | | 0.2 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 25 | 70 | | 25 | 70 | | 25 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S = 50\ \Omega$ | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.2 | | | –15 to 13.2 | | | –15 to 13.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L = 10\ k\Omega$ | 25°C | 14 | 14.3 | | 14 | 14.3 | | 14 | 14.3 | | V |
| | | | Full range | 13.8 | | | 13.8 | | | 13.8 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.6 | | | –13.6 | | | –13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O = \pm 10$ V, $R_L = 10\ k\Omega$ | 25°C | 1 | 6.5 | | 1 | 6.5 | | 1 | 6.5 | | V/μV |
| | | | Full range | 0.5 | | | 0.5 | | | 0.5 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}min$, $R_S = 50\ \Omega$ | 25°C | 100 | 115 | | 100 | 115 | | 100 | 115 | | dB |
| | | | Full range | 96 | | | 96 | | | 96 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm} = \pm 2.5$ V to $\pm 15$ V | 25°C | 105 | 120 | | 105 | 120 | | 105 | 120 | | dB |
| | | | Full range | 100 | | | 100 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O = 0$, No load | 25°C | | 200 | 300 | | 200 | 300 | | 200 | 300 | μA |
| | | | Full range | | | 300 | | | 300 | | | 300 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 10 | | | 10 | | | 10 | | μA |

† Full range is –55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A = 150°C$ extrapolated to $T_A = 25°C$ using the Arrhenius equation and assuming an activation energy of 0.96 eV.

### TLE2022 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | $T_A$† | TLE2022M | | | TLE2022AM | | | TLE2022BM | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, | $R_S$ = 50 Ω | 25°C | | | 600 | | | 400 | | | 250 | μV |
| | | | | Full range | | | 800 | | | 550 | | | 400 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | μV/mo |
| $I_{IO}$ | Input offset current | | | 25°C | | 0.5 | 6 | | 0.4 | 6 | | 0.3 | 6 | nA |
| | | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | | 25°C | | 35 | 70 | | 33 | 70 | | 30 | 70 | nA |
| | | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | | 25°C | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | V |
| | | | | Full range | 0 to 3.2 | | | 0 to 3.2 | | | 0 to 3.2 | | | |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | | 25°C | 4 | 4.3 | | 4 | 4.3 | | 4 | 4.3 | | V |
| | | | | Full range | 3.8 | | | 3.8 | | | 3.8 | | | |
| $V_{OL}$ | Low-level output voltage | | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | | Full range | | | 0.95 | | | 0.95 | | | 0.95 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, | $R_L$ = 10 kΩ | 25°C | 0.3 | 1.5 | | 0.4 | 1.5 | | 0.5 | 1.5 | | V/μV |
| | | | | Full range | 0.1 | | | 0.1 | | | 0.1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, | $R_S$ = 50 Ω | 25°C | 85 | 100 | | 87 | 102 | | 90 | 105 | | dB |
| | | | | Full range | 80 | | | 82 | | | 85 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | | 25°C | 100 | 115 | | 103 | 118 | | 105 | 120 | | dB |
| | | | | Full range | 95 | | | 98 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, | No load | 25°C | | 450 | 600 | | 450 | 600 | | 450 | 600 | μA |
| | | | | Full range | | | 600 | | | 600 | | | 600 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | | Full range | | 37 | | | 37 | | | 37 | | μA |

† Full range is −55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2022 electrical characteristics at specified free-air temperature, $V_{CC} = \pm 15$ V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2022M | | | TLE2022AM | | | TLE2022BM | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC} = 0$, $R_S = 50\ \Omega$ | 25°C | | 150 | 500 | | 120 | 300 | | 70 | 150 | µV |
| | | | Full range | | | 700 | | | 450 | | | 300 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.5 | 6 | | 0.4 | 6 | | 0.3 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 35 | 70 | | 33 | 70 | | 30 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S = 50\ \Omega$ | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.2 | | | –15 to 13.2 | | | –15 to 13.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L = 10\ k\Omega$ | 25°C | 14 | 14.3 | | 14 | 14.3 | | 14 | 14.3 | | V |
| | | | Full range | 13.9 | | | 13.9 | | | 13.9 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.6 | | | –13.6 | | | –13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O = \pm 10$ V, $R_L = 10\ k\Omega$ | 25°C | 0.8 | 4 | | 1 | 7 | | 1.5 | 10 | | V/µV |
| | | | Full range | 0.8 | | | 1 | | | 1.5 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S = 50\ \Omega$ | 25°C | 95 | 106 | | 97 | 109 | | 100 | 112 | | dB |
| | | | Full range | 91 | | | 93 | | | 96 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$) | $V_{CC\pm} = \pm 2.5$ V to $\pm 15$ V | 25°C | 100 | 115 | | 103 | 118 | | 105 | 120 | | dB |
| | | | Full range | 95 | | | 98 | | | 100 | | | |
| $I_{CC}$ | Supply current | $V_O = 0$, No load | 25°C | | 550 | 700 | | 550 | 700 | | 550 | 700 | µA |
| | | | Full range | | | 700 | | | 700 | | | 700 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 60 | | | 60 | | | 60 | | µA |

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A = 150°C$ extrapolated to $T_A = 25°C$ using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2024 electrical characteristics at specified free-air temperature, $V_{CC}$ = 5 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2024M | | | TLE2024AM | | | TLE2024BM | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, $R_S$ = 50 Ω | 25°C | | | 1100 | | | 850 | | | 600 | µV |
| | | | Full range | | | 1300 | | | 1050 | | | 800 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | µV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.005 | | | 0.005 | | | 0.005 | | µV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.6 | 6 | | 0.5 | 6 | | 0.4 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 45 | 70 | | 40 | 70 | | 35 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | 25°C | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | 0 to 3.5 | −0.3 to 4 | | V |
| | | | Full range | 0 to 3.2 | | | 0 to 3.2 | | | 0 to 3.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L$ = 10 kΩ | 25°C | 3.9 | 4.2 | | 3.9 | 4.2 | | 4 | 4.3 | | V |
| | | | Full range | 3.7 | | | 3.7 | | | 3.8 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | | 0.7 | 0.8 | | 0.7 | 0.8 | | 0.7 | 0.8 | V |
| | | | Full range | | | 0.95 | | | 0.95 | | | 0.95 | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, $R_L$ = 10 kΩ | 25°C | 0.2 | 1.5 | | 0.3 | 1.5 | | 0.4 | 1.5 | | V/µV |
| | | | Full range | 0.1 | | | 0.1 | | | 0.1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S$ = 50 Ω | 25°C | 80 | 90 | | 82 | 92 | | 85 | 95 | | dB |
| | | | Full range | 80 | | | 82 | | | 85 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm}$ = ±2.5 V to ±15 V | 25°C | 98 | 112 | | 100 | 115 | | 103 | 117 | | dB |
| | | | Full range | 93 | | | 95 | | | 98 | | | |
| $I_{CC}$ | Supply current | $V_O$ = 0, No load | 25°C | | 800 | 1200 | | 800 | 1200 | | 800 | 1200 | µA |
| | | | Full range | | | 1200 | | | 1200 | | | 1200 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 50 | | | 50 | | | 50 | | µA |

† Full range is −55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2024 electrical characteristics at specified free-air temperature, $V_{CC} = \pm 15$ V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | TLE2024M MIN | TLE2024M TYP | TLE2024M MAX | TLE2024AM MIN | TLE2024AM TYP | TLE2024AM MAX | TLE2024BM MIN | TLE2024BM TYP | TLE2024BM MAX | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| $V_{IO}$ | Input offset voltage | $V_{IC} = 0$, $R_S = 50\ \Omega$ | 25°C | | | 1000 | | | 750 | | | 500 | μV |
| | | | Full range | | | 1200 | | | 950 | | | 700 | |
| $\alpha_{VIO}$ | Temperature coefficient of input offset voltage | | Full range | | 2 | | | 2 | | | 2 | | μV/°C |
| | Input offset voltage long-term drift (see Note 4) | | 25°C | | 0.006 | | | 0.006 | | | 0.006 | | μV/mo |
| $I_{IO}$ | Input offset current | | 25°C | | 0.6 | 6 | | 0.5 | 6 | | 0.4 | 6 | nA |
| | | | Full range | | | 10 | | | 10 | | | 10 | |
| $I_{IB}$ | Input bias current | | 25°C | | 50 | 70 | | 45 | 70 | | 40 | 70 | nA |
| | | | Full range | | | 90 | | | 90 | | | 90 | |
| $V_{ICR}$ | Common-mode input voltage range | $R_S = 50\ \Omega$ | 25°C | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | –15 to 13.5 | –15.3 to 14 | | V |
| | | | Full range | –15 to 13.2 | | | –15 to 13.2 | | | –15 to 13.2 | | | |
| $V_{OM+}$ | Maximum positive peak output voltage swing | $R_L = 10\ k\Omega$ | 25°C | 13.8 | 14.1 | | 13.9 | 14.2 | | 14 | 14.3 | | V |
| | | | Full range | 13.7 | | | 13.7 | | | 13.8 | | | |
| $V_{OM-}$ | Maximum negative peak output voltage swing | | 25°C | –13.7 | –14.1 | | –13.7 | –14.1 | | –13.7 | –14.1 | | V |
| | | | Full range | –13.6 | | | –13.6 | | | –13.6 | | | |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O = \pm 10$ V, $R_L = 10\ k\Omega$ | 25°C | 0.4 | 2 | | 0.8 | 4 | | 1 | 7 | | V/μV |
| | | | Full range | 0.4 | | | 0.8 | | | 1 | | | |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, $R_S = 50\ \Omega$ | 25°C | 92 | 102 | | 94 | 105 | | 97 | 108 | | dB |
| | | | Full range | 88 | | | 90 | | | 93 | | | |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC\pm} = \pm 2.5$ V to $\pm 15$ V | 25°C | 98 | 112 | | 100 | 115 | | 103 | 117 | | dB |
| | | | Full range | 93 | | | 95 | | | 98 | | | |
| $I_{CC}$ | Supply current | $V_O = 0$, No load | 25°C | | 1050 | 1400 | | 1050 | 1400 | | 1050 | 1400 | μA |
| | | | Full range | | | 1400 | | | 1400 | | | 1400 | |
| $\Delta I_{CC}$ | Supply current change over operating temperature range | | Full range | | 85 | | | 85 | | | 85 | | μA |

† Full range is –55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A = 150$°C extrapolated to $T_A = 25$°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2021 operating characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | $T_A$ | C SUFFIX | | | I SUFFIX | | | M SUFFIX | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = 1 V to 3 V, See Figure 1 | 25°C | | 0.5 | | | 0.5 | | | 0.5 | | V/μs |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | 25°C | | 21 | 50 | | 21 | 50 | | 21 | | nV/Hz |
| | | f = 1 kHz | 25°C | | 17 | 30 | | 17 | 30 | | 17 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | 25°C | | 0.16 | | | 0.16 | | | 0.16 | | μV |
| | | f = 0.1 to 10 Hz | 25°C | | 0.47 | | | 0.47 | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | 25°C | | 0.09 | | | 0.09 | | | 0.9 | | pA/Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | 25°C | | 1.2 | | | 1.2 | | | 1.2 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | 25°C | | 42° | | | 42° | | | 42° | | |

## TLE2021 operating characteristics at specified free-air temperature, $V_{CC}$ = ±15 V

| PARAMETER | | TEST CONDITIONS | $T_A$† | C SUFFIX | | | I SUFFIX | | | M SUFFIX | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = 1V to 3 V, See Figure 1 | 25°C | 0.45 | 0.65 | | 0.45 | 0.65 | | 0.45 | 0.65 | | V/μs |
| | | | Full range | 0.45 | | | 0.42 | | | 0.45 | | | |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | 25°C | | 19 | 50 | | 19 | 50 | | 19 | | nV/Hz |
| | | f = 1 kHz | 25°C | | 15 | 30 | | 15 | 30 | | 15 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | 25°C | | 0.16 | | | 0.16 | | | 0.16 | | μV |
| | | f = 0.1 to 10 Hz | 25°C | | 0.47 | | | 0.47 | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | 25°C | | 0.09 | | | 0.09 | | | 0.09 | | pA/Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | 25°C | | 2 | | | 2 | | | 2 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | 25°C | | 46° | | | 46° | | | 46° | | |

† Full range is 0°C to 70°C for the C-suffix devices, –40°C to 85°C for the I-suffix devices, and –55°C to 125°C for the M-suffix devices.

### TLE2022 operating characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | C SUFFIX | | | I SUFFIX | | | M SUFFIX | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = 1 V to 3 V, See Figure 1 | | 0.5 | | | 0.5 | | | 0.5 | | V/µs |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | | 21 | 50 | | 21 | 50 | | 21 | | nV/√Hz |
| | | f = 1 kHz | | 17 | 30 | | 17 | 30 | | 17 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | | 0.16 | | | 0.16 | | | 0.16 | | µV |
| | | f = 0.1 to 10 Hz | | 0.47 | | | 0.47 | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | | 0.1 | | | 0.1 | | | 0.1 | | pA/√Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | | 1.7 | | | 1.7 | | | 1.7 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | | 47° | | | 47° | | | 47° | | |

### TLE2022 operating characteristics at specified free-air temperature, $V_{CC}$ = ±15 V

| PARAMETER | | TEST CONDITIONS | $T_A$† | C SUFFIX | | | I SUFFIX | | | M SUFFIX | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = ±10 V, See Figure 1 | 25°C | 0.45 | 0.65 | | 0.45 | 0.65 | | 0.45 | 0.65 | | V/µs |
| | | | Full range | 0.45 | | | 0.42 | | | 0.4 | | | |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | 25°C | | 19 | 50 | | 19 | 50 | | 19 | | nV/√Hz |
| | | f = 1 kHz | 25°C | | 15 | 30 | | 15 | 30 | | 15 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | 25°C | | 0.16 | | | 0.16 | | | 0.16 | | µV |
| | | f = 0.1 to 10 Hz | 25°C | | 0.47 | | | 0.47 | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | 25°C | | 0.1 | | | 0.1 | | | 0.1 | | pA/√Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | 25°C | | 2.8 | | | 2.8 | | | 2.8 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | 25°C | | 52° | | | 52° | | | 52° | | |

† Full range is 0°C to 70°C.

## TLE2024 operating characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | C SUFFIX | | | I SUFFIX | | | M SUFFIX | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = 1 V to 3 V, See Figure 1 | | 0.5 | | | 0.5 | | | 0.5 | | V/µs |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | | 21 | 50 | | 21 | 50 | | 21 | | nV/√Hz |
| | | f = 1 kHz | | 17 | 30 | | 17 | 30 | | 17 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | | 0.16 | | | 0.16 | | | 0.16 | | µV |
| | | f = 0.1 to 10 Hz | | 0.47 | | | 0.47 | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | | 0.1 | | | 0.1 | | | 0.1 | | pA/√Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | | 1.7 | | | 1.7 | | | 1.7 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | | 47° | | | 47° | | | 47° | | |

## TLE2024 operating characteristics at specified free-air temperature, $V_{CC}$ = ±15 V (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | $T_A$† | C SUFFIX | | | I SUFFIX | | | M SUFFIX | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = ±10 V, See Figure 1 | 25°C | 0.45 | 0.7 | | 0.45 | 0.7 | | 0.45 | 0.7 | | V/µs |
| | | | Full range | 0.45 | | | 0.42 | | | 0.4 | | | |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | 25°C | | 19 | 50 | | 19 | 50 | | 19 | | nV/√Hz |
| | | f = 1 kHz | 25°C | | 15 | 30 | | 15 | 30 | | 15 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | 25°C | | 0.16 | | | 0.16 | | | 0.16 | | µV |
| | | f = 0.1 to 10 Hz | 25°C | | 0.47 | | | 0.47 | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | 25°C | | 0.1 | | | 0.1 | | | 0.1 | | pA/√Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | 25°C | | 2.8 | | | 2.8 | | | 2.8 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | 25°C | | 52° | | | 52° | | | 52° | | |

† Full range is 0°C to 70°C.

## TLE2021Y electrical characteristics at $V_{CC}$ = 5 V, $T_A$ = 25°C (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | TLE2021Y | | | UNIT |
|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 150 | | μV |
| | Input offset voltage long-term drift (see Note 4) | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 0.005 | | μV/mo |
| $I_{IO}$ | Input offset current | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 0.5 | | nA |
| $I_{IB}$ | Input bias current | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 35 | | nA |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | | | – 0.3 to 4 | | V |
| $V_{OH}$ | Maximum high-level output voltage | $R_L$ = 10 kΩ | | | 4.3 | | V |
| $V_{OL}$ | Maximum low-level output voltage | $R_L$ = 10 kΩ | | | 0.7 | | V |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 to 4 V, | $R_L$ = 10 kΩ | | 1.5 | | V/μV |
| CMRR | Common-mode rejection ratio | $V_{IC}$ = $V_{ICR}$ min, | $R_S$ = 50 Ω | | 100 | | dB |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | | | 115 | | dB |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, | No load | | 400 | | μA |

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2021Y operating characteristics at $V_{CC}$ = 5 V, $T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | TLE2021Y | | | UNIT |
|---|---|---|---|---|---|---|
| | | | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = 1 V to 3 V | | 0.5 | | V/μs |
| $V_n$ | Equivalent input noise voltage | f = 10 Hz | | 21 | | nV/√Hz |
| | | f = 1 kHz | | 17 | | nV/√Hz |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | | 0.16 | | μV |
| | | f = 0.1 to 10 Hz | | 0.47 | | μV |
| $I_n$ | Equivalent input noise current | | | 0.1 | | pA/√Hz |
| $B_1$ | Unity-gain bandwidth | | | 1.7 | | MHz |
| $\phi_m$ | Phase margin at unity gain | | | 47° | | |

## TLE2022Y electrical characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | TLE2022Y | | | UNIT |
|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | |
| $V_{IO}$ | Input offset voltage | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 150 | 600 | µV |
| | Input offset voltage long-term drift (see Note 4) | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 0.005 | | µV/mo |
| $I_{IO}$ | Input offset current | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 0.5 | | nA |
| $I_{IB}$ | Input bias current | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 35 | | nA |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | | | – 0.3 to 4 | | V |
| $V_{OH}$ | Maximum high-level output voltage | $R_L$ = 10 kΩ | | | 4.3 | | V |
| $V_{OL}$ | Maximum low-level output voltage | $R_L$ = 10 kΩ | | | 0.7 | | V |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 to 4 V, | $R_L$= 10 kΩ | | 1.5 | | V/µV |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$ min, | $R_S$ = 50 Ω | | 100 | | dB |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | | | 115 | | dB |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, | No load | | 450 | | µA |

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

## TLE2022Y operating characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | | TLE2022Y | | | UNIT |
|---|---|---|---|---|---|---|---|
| | | | | MIN | TYP | MAX | |
| SR | Slew rate at unity gain | $V_O$ = 1 V to 3 V, | See Figure 1 | | 0.5 | | V/µs |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | | | 21 | | nV/√Hz |
| | | f = 1 kHz | | | 17 | | nV/√Hz |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | | | 0.16 | | µV |
| | | f = 0.1 to 10 Hz | | | 0.47 | | µV |
| $I_n$ | Equivalent input noise current | | | | 0.1 | | pA/√Hz |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | | | 1.7 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | | | 47° | | |

### TLE2024Y electrical characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | TLE2024Y MIN | TLE2024Y TYP | TLE2024Y MAX | UNIT |
|---|---|---|---|---|---|---|---|
| | Input offset voltage long-term drift (see Note 4) | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 0.005 | | μV/mo |
| $I_{IO}$ | Input offset current | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 0.6 | | nA |
| $I_{IB}$ | Input bias current | $V_{IC}$ = 0, | $R_S$ = 50 Ω | | 45 | | nA |
| $V_{ICR}$ | Common-mode input voltage range | $R_S$ = 50 Ω | | | –0.3 to 4 | | V |
| $V_{OH}$ | High-level output voltage | $R_L$ = 10 kΩ | | | 4.2 | | V |
| $V_{OL}$ | Low-level output voltage | $R_L$ = 10 kΩ | | | 0.7 | | V |
| $A_{VD}$ | Large-signal differential voltage amplification | $V_O$ = 1.4 V to 4 V, | $R_L$ = 10 kΩ | | 1.5 | | V/μV |
| CMRR | Common-mode rejection ratio | $V_{IC} = V_{ICR}$min, | $R_S$ = 50 Ω | | 90 | | dB |
| $k_{SVR}$ | Supply-voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$) | $V_{CC}$ = 5 V to 30 V | | | 112 | | dB |
| $I_{CC}$ | Supply current | $V_O$ = 2.5 V, | No load | | 800 | | μA |

NOTE 4. Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at $T_A$ = 150°C extrapolated to $T_A$ = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

### TLE2024Y operating characteristics, $V_{CC}$ = 5 V, $T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | | TLE2024Y MIN | TLE2024Y TYP | TLE2024Y MAX | UNIT |
|---|---|---|---|---|---|---|---|
| SR | Slew rate at unity gain | $V_O$ = 1 V to 3 V, | See Figure 1 | | 0.5 | | V/μs |
| $V_n$ | Equivalent input noise voltage (see Figure 2) | f = 10 Hz | | | 21 | | $nV/\sqrt{Hz}$ |
| | | f = 1 kHz | | | 17 | | |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | f = 0.1 to 1 Hz | | | 0.16 | | μV |
| | | f = 0.1 to 10 Hz | | | 0.47 | | |
| $I_n$ | Equivalent input noise current | | | | 0.1 | | $pA/\sqrt{Hz}$ |
| $B_1$ | Unity-gain bandwidth | See Figure 3 | | | 1.7 | | MHz |
| $\phi_m$ | Phase margin at unity gain | See Figure 3 | | | 47° | | |

## PARAMETER MEASUREMENT INFORMATION




(a) SINGLE SUPPLY

(b) SPLIT SUPPLY

NOTE A: $C_L$ includes fixture capacitance.

**Figure 1. Slew-Rate Test Circuit**




(a) SINGLE SUPPLY

(b) SPLIT SUPPLY

**Figure 2. Noise-Voltage Test Circuit**




(a) SINGLE SUPPLY

(b) SPLIT SUPPLY

NOTE A: $C_L$ includes fixture capacitance.

**Figure 3. Unity-Gain Bandwidth and Phase-Margin Test Circuit**

## PARAMETER MEASUREMENT INFORMATION




(a) SINGLE SUPPLY




(b) SPLIT SUPPLY

NOTE A: $C_L$ includes fixture capacitance.

**Figure 4. Small-Signal Pulse-Response Test Circuit**

### typical values

Typical values presented in this data sheet represent the median (50% point) of device parametric performance.

## TYPICAL CHARACTERISTICS

### Table of Graphs

| | | | FIGURE |
|---|---|---|---|
| $V_{IO}$ | Input offset voltage | Distribution | 5, 6, 7 |
| $I_{IB}$ | Input bias current | vs Common-mode input voltage<br>vs Free-air temperature | 8, 9, 10<br>11, 12, 13 |
| $I_I$ | Input current | vs Differential input voltage | 14 |
| $V_{OM}$ | Maximum peak output voltage | vs Output current<br>vs Free-air temperature | 15, 16, 17<br>18 |
| $V_{OH}$ | High-level output voltage | vs High-level output current<br>vs Free-air temperature | 19, 20<br>21 |
| $V_{OL}$ | Low-level output voltage | vs Low-level output current<br>vs Free-air temperature | 22<br>23 |
| $V_{O(PP)}$ | Maximum peak-to-peak output voltage | vs Frequency | 24, 25 |
| $A_{VD}$ | Large-signal differential voltage amplification | vs Frequency<br>vs Free-air temperature | 26<br>27, 28, 29 |
| $I_{OS}$ | Short-circuit output current | vs Supply voltage<br>vs Free-air temperature | 30 – 33<br>34 – 37 |
| $I_{CC}$ | Supply current | vs Supply voltage<br>vs Free-air temperature | 38, 39, 40<br>41, 42, 43 |
| CMRR | Common-mode rejection ratio | vs Frequency | 44, 45, 46 |
| SR | Slew rate | vs Free-air temperature | 47, 48, 49 |
| | Voltage-follower small-signal pulse response | | 50, 51 |
| | Voltage-follower large-signal pulse response | | 52 – 57 |
| $V_{N(PP)}$ | Peak-to-peak equivalent input noise voltage | 0.1 to 1 Hz<br>0.1 to 10 Hz | 58<br>59 |
| $V_n$ | Equivalent input noise voltage | vs Frequency | 60 |
| $B_1$ | Unity-gain bandwidth | vs Supply voltage<br>vs Free-air temperature | 61, 62<br>63, 64 |
| $\phi_m$ | Phase margin | vs Supply voltage<br>vs Load capacitance<br>vs Free-air temperature | 65, 66<br>67, 68<br>69, 70 |
| | Phase shift | vs Frequency | 26 |

## TYPICAL CHARACTERISTICS




Figure 5




Figure 6




Figure 7




Figure 8

## TYPICAL CHARACTERISTICS

**TLE2022**
**INPUT BIAS CURRENT**
**vs**
**COMMON-MODE INPUT VOLTAGE**




**Figure 9**

**TLE2024**
**INPUT BIAS CURRENT**
**vs**
**COMMON-MODE INPUT VOLTAGE**




**Figure 10**

**TLE2021**
**INPUT BIAS CURRENT†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 11**

**TLE2022**
**INPUT BIAS CURRENT†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 12**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS




Figure 13




Figure 14




Figure 15




Figure 16

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

TLE2024
MAXIMUM PEAK OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 17

MAXIMUM PEAK OUTPUT VOLTAGE†
vs
FREE-AIR TEMPERATURE




Figure 18

TLE2021
HIGH-LEVEL OUTPUT VOLTAGE
vs
HIGH-LEVEL OUTPUT CURRENT




Figure 19

TLE2022 AND TLE2024
HIGH-LEVEL OUTPUT VOLTAGE
vs
HIGH-LEVEL OUTPUT CURRENT




Figure 20

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS




Figure 21




Figure 22




Figure 23




Figure 24

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

### MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE vs FREQUENCY




Figure 25

### LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY




Figure 26

## TYPICAL CHARACTERISTICS

**TLE2021**
**LARGE-SCALE DIFFERENTIAL VOLTAGE AMPLIFICATION†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 27**

**TLE2022**
**LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 28**

**TLE2024**
**LARGE-SCALE DIFFERENTIAL VOLTAGE AMPLIFICATION†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 29**

**TLE2021**
**SHORT-CIRCUIT OUTPUT CURRENT**
**vs**
**SUPPLY VOLTAGE**




**Figure 30**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

**TLE2022 AND TLE2024
SHORT-CIRCUIT OUTPUT CURRENT
vs
SUPPLY VOLTAGE**




**Figure 31**

**TLE2021
SHORT-CIRCUIT OUTPUT CURRENT
vs
SUPPLY VOLTAGE**




**Figure 32**

**TLE2022 AND TLE2024
SHORT-CIRCUIT OUTPUT CURRENT
vs
SUPPLY VOLTAGE**




**Figure 33**

**TLE2021
SHORT-CIRCUIT OUTPUT CURRENT†
vs
FREE-AIR TEMPERATURE**




**Figure 34**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

**TLE2022 AND TLE2024**
**SHORT-CIRCUIT OUTPUT CURRENT†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 35**

**TLE2021**
**SHORT-CIRCUIT OUTPUT CURRENT†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 36**

**TLE2022 AND TLE2024**
**SHORT-CIRCUIT OUTPUT CURRENT†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 37**

**TLE2021**
**SUPPLY CURRENT**
**vs**
**SUPPLY VOLTAGE**




**Figure 38**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

TLE2022
SUPPLY CURRENT
vs
SUPPLY VOLTAGE




Figure 39

TLE2024
SUPPLY CURRENT
vs
SUPPLY VOLTAGE




Figure 40

TLE2021
SUPPLY CURRENT†
vs
FREE-AIR TEMPERATURE




Figure 41

TLE2022
SUPPLY CURRENT†
vs
FREE-AIR TEMPERATURE




Figure 42

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

**TLE2024**
**SUPPLY CURRENT†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 43**

**TLE2021**
**COMMON-MODE REJECTION RATIO**
**vs**
**FREQUENCY**




**Figure 44**

**TLE2022**
**COMMON-MODE REJECTION RATIO**
**vs**
**FREQUENCY**




**Figure 45**

**TLE2024**
**COMMON-MODE REJECTION RATIO**
**vs**
**FREQUENCY**




**Figure 46**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

**TLE2021**
**SLEW RATE†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 47**

**TLE2022**
**SLEW RATE†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 48**

**TLE2024**
**SLEW RATE†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 49**

**VOLTAGE-FOLLOWER**
**SMALL-SIGNAL**
**PULSE RESPONSE**




**Figure 50**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

VOLTAGE-FOLLOWER
SMALL-SIGNAL
PULSE RESPONSE




Figure 51

TLE2021
VOLTAGE-FOLLOWER LARGE-SIGNAL
PULSE RESPONSE




Figure 52

TLE2022
VOLTAGE-FOLLOWER LARGE-SIGNAL
PULSE RESPONSE




Figure 53

TLE2024
VOLTAGE-FOLLOWER LARGE-SCALE
PULSE RESPONSE




Figure 54

## TYPICAL CHARACTERISTICS

**TLE2021**
**VOLTAGE-FOLLOWER LARGE-SIGNAL PULSE RESPONSE**




**Figure 55**

**TLE2022**
**VOLTAGE-FOLLOWER LARGE-SIGNAL PULSE RESPONSE**




**Figure 56**

**TLE2024**
**VOLTAGE-FOLLOWER LARGE-SIGNAL PULSE RESPONSE**




**Figure 57**

**PEAK-TO-PEAK EQUIVALENT INPUT NOISE VOLTAGE**
**0.1 TO 1 Hz**




**Figure 58**

## TYPICAL CHARACTERISTICS

**PEAK-TO-PEAK EQUIVALENT INPUT NOISE VOLTAGE 0.1 TO 10 Hz**




**Figure 59**

**EQUIVALENT INPUT NOISE VOLTAGE vs FREQUENCY**




**Figure 60**

**TLE2021 UNITY-GAIN BANDWIDTH vs SUPPLY VOLTAGE**




**Figure 61**

**TLE2022 AND TLE2024 UNITY-GAIN BANDWIDTH vs SUPPLY VOLTAGE**




**Figure 62**

## TYPICAL CHARACTERISTICS

**TLE2021**
**UNITY-GAIN BANDWIDTH†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 63**

**TLE2022 AND TLE2024**
**UNITY-GAIN BANDWIDTH†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 64**

**TLE2021**
**PHASE MARGIN**
**vs**
**SUPPLY VOLTAGE**




**Figure 65**

**TLE2022 AND TLE2024**
**PHASE MARGIN**
**vs**
**SUPPLY VOLTAGE**




**Figure 66**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS

**TLE2021**
**PHASE MARGIN**
**vs**
**LOAD CAPACITANCE**




**Figure 67**

**TLE2022 AND TLE2024**
**PHASE MARGIN**
**vs**
**LOAD CAPACITANCE**




**Figure 68**

**TLE2021**
**PHASE MARGIN†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 69**

**TLE2022 AND TLE2024**
**PHASE MARGIN†**
**vs**
**FREE-AIR TEMPERATURE**




**Figure 70**

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## APPLICATION INFORMATION

### voltage-follower applications

The TLE202x circuitry includes input-protection diodes to limit the voltage across the input transistors; however, no provision is made in the circuit to limit the current if these diodes are forward biased. This condition can occur when the device is operated in the voltage-follower configuration and driven with a fast, large-signal pulse. It is recommended that a feedback resistor be used to limit the current to a maximum of 1 mA to prevent degradation of the device. This feedback resistor forms a pole with the input capacitance of the device. For feedback resistor values greater than 10 kΩ, this pole degrades the amplifier phase margin. This problem can be alleviated by adding a capacitor (20 pF to 50 pF) in parallel with the feedback resistor (see Figure 71).




**Figure 71. Voltage Follower**

### Input offset voltage nulling

The TLE202x series offers external null pins that further reduce the input offset voltage. The circuit in Figure 72 can be connected as shown if this feature is desired. When external nulling is not needed, the null pins may be left disconnected.




**Figure 72. Input Offset Voltage Null Circuit**

## APPLICATION INFORMATION

### macromodel information

Macromodel information provided was derived using Microsim *Parts*™, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 5) and subcircuit in Figure 73, Figure 74, and Figure 75 were generated using the TLE202x typical electrical and operating characteristics at 25°C. Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Unity-gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 5: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, “Macromodeling of Integrated Circuit Operational Amplifiers”**,** *IEEE Journal of Solid-State Circuits*, SC-9, 353 (1974).




Figure 73. Boyle Subcircuit

*PSpice* and *Parts* are trademarks of MicroSim Corporation.

```
.SUBCKT TLE2021  1 2 3 4 5
*
  c1     11   12 6.244E–12
  c2     6    7  13.4E–12
  c3     87   0  10.64E–9
  cpsr   85   86 15.9E–9
  dcm+   81   82 dx
  dcm–   83   81 dx
  dc     5    53 dx
  de     54   5  dx
  dlp    90   91 dx
  dln    92   90 dx
  dp     4    3  dx
  ecmr   84   99 (2 99) 1
  egnd   99   0  poly(2) (3,0) (4,0) 0 .5 .5
  epsr   85   0  poly(1) (3,4) –60E–6  2.0E–6
  ense   89   2  poly(1) (88,0) 120E–6  1
  fb     7    99 poly(6) vb vc ve vlp vln vpsr 0 547.3E6
  + –50E7 50E7 50E7 –50E7 547E6
  ga     6    0  11 12 188.5E–6
  gcm    0    6  10 99 335.2E–12
  gpsr   85   86 (85,86) 100E–6
  grc1   4    11 (4,11) 1.885E–4
  grc2   4    12 (4,12) 1.885E–4
  gre1   13   10 (13,10) 6.82E–4
  gre2   14   10 (14,10) 6.82E–4
  hlim   90   0  vlim 1k
  hcmr   80   1  poly(2) vcm+ vcm– 0 1E2 1E2
  irp    3    4  185E–6
  iee    3    10 dc 15.67E–6
  iio    2    0  2E–9
  i1     88   0  1E–21
  q1     11   89 13 qx
  q2     12   80 14 qx
  R2     6    9  100.0E3
  rcm    84   81 1K
  ree    10   99 14.76E6
  rn1    87   0  2.55E8
  rn2    87   88 11.67E3
  ro1    8    5  62
  ro2    7    99 63
  vcm+   82   99 13.3
  vcm–   83   99 –14.6
  vb     9    0  dc 0
  vc     3    53 dc 1.300
  ve     54   4  dc 1.500
  vlim   7    8  dc 0
  vlp    91   0  dc 3.600
  vln    0    92 dc 3.600
  vpsr   0    86 dc 0
.model dx d(is=800.0E–18)
.model qx pnp(is=800.0E–18 bf=270)
.ends
```

**Figure 74. Boyle Macromodel for the TLE2021**

```
.SUBCKT TLE2022  1 2 3 4 5
*
  c1    11  12 6.814E–12
  c2    6   7  20.00E–12
  dc    5   53 dx
  de    54  5 dx
  dlp   90  91 dx
  dln   92  90 dx
  dp    4   3 dx
  egnd 99   0  poly(2) (3,0) (4,0) 0 .5 .5
  fb    7   99 poly(5) vb vc ve vlp vln 0
+ 45.47E6 –50E6 50E6 50E6 –50E6
  ga 6  0   11 12 377.9E–6
  gcm 0 6   10 99 7.84E–10
  iee   3   10 DC 18.07E–6
  hlim 90   0 vlim 1k
  q1    11  2 13 qx
  q2    12  1 14 qx
  r2    6   9 100.0E3
  rc1  4   11 2.842E3
  rc2  4   12 2.842E3
  ge1  13  10 (10,13) 31.299E–3
  ge2  14  10 (10,14) 31.299E–3
  ree  10  99 11.07E6
  ro1  8   5 250
  ro2  7   99 250
  rp   3   4 137.2E3
  vb   9   0 dc 0
  vc   3   53 dc 1.300
  ve   54  4 dc 1.500
  vlim 7   8 dc 0
  vlp  91  0 dc 3
  vln  0   92 dc 3
.model dx  d(is=800.0E–18)
.model qx  pnp(is=800.0E–18 bf=257.1)
.ends
```

**Figure 75. Boyle Macromodel for the TLE2022**

## MECHANICAL INFORMATION

**D (R-PDSO-G**)** **PLASTIC SMALL-OUTLINE PACKAGE**

**14 PIN SHOWN**

| DIM \ PINS ** | 8 | 14 | 16 |
|---|---|---|---|
| A MAX | 0.197 (5,00) | 0.344 (8,75) | 0.394 (10,00) |
| A MIN | 0.189 (4,80) | 0.337 (8,55) | 0.386 (9,80) |




NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion, not to exceed 0.006 (0,15).
D. Four center pins are connected to die mount pad.
E. Falls within JEDEC MS-012

## MECHANICAL INFORMATION

**DB (R-PDSO-G**)** **PLASTIC SMALL-OUTLINE PACKAGE**

**28 PIN SHOWN**




| PINS ** / DIM | 8 | 14 | 16 | 20 | 24 | 28 | 30 | 38 |
|---|---|---|---|---|---|---|---|---|
| A MAX | 3,30 | 6,50 | 6,50 | 7,50 | 8,50 | 10,50 | 10,50 | 12,90 |
| A MIN | 2,70 | 5,90 | 5,90 | 6,90 | 7,90 | 9,90 | 9,90 | 12,30 |

4040065 / C 10/95

NOTES: A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.
D. Falls within JEDEC MO-150

## MECHANICAL INFORMATION

**DW (R-PDSO-G**)** **PLASTIC SMALL-OUTLINE PACKAGE**

**16 PIN SHOWN**




| PINS ** / DIM | 16 | 20 | 24 | 28 |
|---|---|---|---|---|
| A MAX | 0.410 (10,41) | 0.510 (12,95) | 0.610 (15,49) | 0.710 (18,03) |
| A MIN | 0.400 (10,16) | 0.500 (12,70) | 0.600 (15,24) | 0.700 (17,78) |

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
D. Falls within JEDEC MS-013

## MECHANICAL INFORMATION

**FK (S-CQCC-N**)** **LEADLESS CERAMIC CHIP CARRIER**

**28 TERMINAL SHOWN**




| NO. OF TERMINALS ** | A | | B | |
|---|---|---|---|---|
| | MIN | MAX | MIN | MAX |
| 20 | 0.342 (8,69) | 0.358 (9,09) | 0.307 (7,80) | 0.358 (9,09) |
| 28 | 0.442 (11,23) | 0.458 (11,63) | 0.406 (10,31) | 0.458 (11,63) |
| 44 | 0.640 (16,26) | 0.660 (16,76) | 0.495 (12,58) | 0.560 (14,22) |
| 52 | 0.739 (18,78) | 0.761 (19,32) | 0.495 (12,58) | 0.560 (14,22) |
| 68 | 0.938 (23,83) | 0.962 (24,43) | 0.850 (21,6) | 0.858 (21,8) |
| 84 | 1.141 (28,99) | 1.165 (29,59) | 1.047 (26,6) | 1.063 (27,0) |




4040140 / D 10/96

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a metal lid.
D. The terminals are gold plated.
E. Falls within JEDEC MS-004

## MECHANICAL INFORMATION

**J (R-GDIP-T**)** **CERAMIC DUAL-IN-LINE PACKAGE**

**14 PIN SHOWN**




| DIM \ PINS ** | 14 | 16 | 18 | 20 | 22 |
|---|---|---|---|---|---|
| A MAX | 0.310 (7,87) | 0.310 (7,87) | 0.310 (7,87) | 0.310 (7,87) | 0.410 (10,41) |
| A MIN | 0.290 (7,37) | 0.290 (7,37) | 0.290 (7,37) | 0.290 (7,37) | 0.390 (9,91) |
| B MAX | 0.785 (19,94) | 0.785 (19,94) | 0.910 (23,10) | 0.975 (24,77) | 1.100 (28,00) |
| B MIN | 0.755 (19,18) | 0.755 (19,18) | — | 0.930 (23,62) | — |
| C MAX | 0.280 (7,11) | 0.300 (7,62) | 0.300 (7,62) | 0.300 (7,62) | 0.388 (9,65) |
| C MIN | 0.245 (6,22) | 0.245 (6,22) | 0.245 (6,22) | 0.245 (6,22) | — |




4040083/B 04/95

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
E. Falls within MIL-STD-1835 GDIP1-T14, GDIP1-T16, GDIP1-T18, GDIP1-T20, and GDIP1-T22

## MECHANICAL INFORMATION

**JG (R-GDIP-T8)** **CERAMIC DUAL-IN-LINE PACKAGE**




NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only
E. Falls within MIL-STD-1835 GDIP1-T8

## MECHANICAL INFORMATION

**N (R-PDIP-T**)** **PLASTIC DUAL-IN-LINE PACKAGE**

**16 PIN SHOWN**

| PINS ** / DIM | 14 | 16 | 18 | 20 |
|---|---|---|---|---|
| A MAX | 0.775 (19,69) | 0.775 (19,69) | 0.920 (23.37) | 0.975 (24,77) |
| A MIN | 0.745 (18,92) | 0.745 (18,92) | 0.850 (21.59) | 0.940 (23,88) |




NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-001 (20 pin package is shorter then MS-001.)

## MECHANICAL INFORMATION

**P (R-PDIP-T8)** **PLASTIC DUAL-IN-LINE PACKAGE**




NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-001

## MECHANICAL INFORMATION

**PW (R-PDSO-G**)** **PLASTIC SMALL-OUTLINE PACKAGE**

**14 PIN SHOWN**




| PINS ** / DIM | 8 | 14 | 16 | 20 | 24 | 28 |
|---|---|---|---|---|---|---|
| A MAX | 3,10 | 5,10 | 5,10 | 6,60 | 7,90 | 9,80 |
| A MIN | 2,90 | 4,90 | 4,90 | 6,40 | 7,70 | 9,60 |

4040064/D 10/95

NOTES: A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.
D. Falls within JEDEC MO-153

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third–party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments
Post Office Box 655303
Dallas, Texas 75265