

## index.html

```
<form action="DBTemplate">
  Example input: <input type="number" name="example_input">
  <!--Add as many input you can with the name-->
  <input type="submit" value="This is submit button">
</form>
```

## DBTemplate.java

```
protected void processRequest(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
    response.setContentType("text/html;charset=UTF-8");
    PrintWriter out = response.getWriter();

    try {
        //Load mysql driver
        Class.forName("com.mysql.jdbc.Driver");

        //Create Connection object
        Connection
con=DriverManager.getConnection("jdbc:mysql://localhost:3099/javadb","root",""
);

        //Create preparedStatement object
        PreparedStatement stmt=con.prepareStatement("Insert into TableName
values(?)");

        //Access the data from frontEnd
        //same name as front end
        int data=Integer.parseInt(request.getParameter("example_input"));

        //set this value to query
        stmt.setInt(1, data);

        //execute this query
        int r=stmt.executeUpdate();
        if(r>0)
            out.print("Success");
        else
            out.print("Failed");

        //For fetching
        stmt=con.prepareStatement("Select * from TableName where id=?");
        stmt.setInt(1, data);
```

```

//execute query
ResultSet res=stmt.executeQuery();

//display all the record in tabular format
out.print("<table border=1>"
        + "<tr>"
        + "<th>Id</th>"
        + "<th>Name</th>"
        + "<th>Average</th>"
        + "</tr>");
while(res.next()){
    out.println("<tr>"
        + "<td>" + res.getInt(1) + "</td>"
        + "<td>" + res.getString(2) + "</td>"
        + "<td>" + res.getFloat(3) + "</td>"
        + "</tr>");
}
out.print("</table>");
}catch(Exception e){
    System.out.println(e);
}
}

```